

National Aeronautics and
Space Administration

CASE FILE
COPY

[illegible]

ACCESSION NUMBER RANGES

Accession numbers cited in this Supplement fall within the following ranges.

STAR (N-10000 Series)

N82-18119 - N82-20138

IAA (A-10000 Series)

A82-22251 - A82-25538

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by PRC Government Information Systems.

NASA SP-7037(149)

AERONAUTICAL ENGINEERING

**A CONTINUING BIBLIOGRAPHY
WITH INDEXES**

(Supplement 149)

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in May 1982 in

- *Scientific and Technical Aerospace Reports (STAR)*
- *International Aerospace Abstracts (IAA)*

This supplement is available as NTISUB 141'093 from the National Technical Information Service (NTIS), Springfield, Virginia 22161 at the price of \$5.00 domestic \$10.00 foreign

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering. The first issue of this bibliography was published in September 1970 and the first supplement in January 1971

This supplement to *Aeronautical Engineering -- A Continuing Bibliography* (NASA SP-7037) lists 418 reports, journal articles, and other documents originally announced in May 1982 in *Scientific and Technical Aerospace Reports (STAR)* or in *International Aerospace Abstracts (IAA)*.

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied in most cases by an abstract. The listing of the entries is arranged in two major sections, *IAA Entries* and *STAR Entries*, in that order. The citations, and abstracts when available, are reproduced exactly as they appeared originally in *IAA* and *STAR*, including the original accession numbers from the respective announcement journals. This procedure, which saves time and money, accounts for the slight variation in citation appearances.

Three indexes -- subject, personal author, and contract number -- are included.

An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A82-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc (AIAA), as follows. Paper copies of accessions are available at \$8.00 per document. Microfiche⁽¹⁾ of documents announced in *IAA* are available at the rate of \$4.00 per microfiche on demand, and at the rate of \$1.35 per microfiche for standing orders for all *IAA* microfiche.

Minimum air-mail postage to foreign countries is \$2.50 and all foreign orders are shipped on payment of pro-forma invoices.

All inquiries and requests should be addressed to AIAA Technical Information Service. Please refer to the accession number when requesting publications.

STAR ENTRIES (N82-10000 Series)

One or more sources from which a document announced in *STAR* is available to the public is ordinarily given on the last line of the citation. The most commonly indicated sources and their acronyms or abbreviations are listed below. If the publication is available from a source other than those listed, the publisher and his address will be displayed on the availability line or in combination with the corporate source line.

Avail NTIS Sold by the National Technical Information Service. Prices for hard copy (HC) and microfiche (MF) are indicated by a price code preceded by the letters HC or MF in the *STAR* citation. Current values for the price codes are given in the tables on page vii.

Documents on microfiche are designated by a pound sign (#) following the accession number. The pound sign is used without regard to the source or quality of the microfiche.

Initially distributed microfiche under the NTIS SRIM (Selected Research in Microfiche) is available at greatly reduced unit prices. For this service and for information concerning subscription to NASA printed reports, consult the NTIS Subscription Section, Springfield, Va. 22161.

NOTE ON ORDERING DOCUMENTS When ordering NASA publications (those followed by the * symbol), use the N accession number. NASA patent applications (only the specifications are offered) should be ordered by the US-Patent-Appl-SN number. Non-NASA publications (no asterisk) should be ordered by the AD, PB, or other *report* number shown on the last line of the citation, not by the N accession number. It is also advisable to cite the title and other bibliographic identification.

Avail SOD (or GPO) Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The current price and order number are given following the availability line. (NTIS will fill microfiche requests, at the standard \$4.00 price, for those documents identified by a # symbol.)

Avail NASA Public Document Rooms Documents so indicated may be examined at or purchased from the National Aeronautics and Space Administration, Public Document Room (Room 126), 600 Independence Ave., S.W., Washington, D.C. 20546, or public document rooms located at each of the NASA research centers, the NASA Space Technology Laboratories, and the NASA Pasadena Office at the Jet Propulsion Laboratory.

(1) A microfiche is a transparent sheet of film 105 by 148 mm in size containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 26:1 reduction).

- Avail DOE Depository Libraries Organizations in U S cities and abroad that maintain collections of Department of Energy reports, usually in microfiche form, are listed in *Energy Research Abstracts* Services available from the DOE and its depositories are described in a booklet, *DOE Technical Information Center - Its Functions and Services* (TID-4660), which may be obtained without charge from the DOE Technical Information Center
- Avail Univ Microfilms Documents so indicated are dissertations selected from *Dissertation Abstracts* and are sold by University Microfilms as xerographic copy (HC) and microfilm All requests should cite the author and the Order Number as they appear in the citation
- Avail USGS Originals of many reports from the U S Geological Survey, which may contain color illustrations, or otherwise may not have the quality of illustrations preserved in the microfiche or facsimile reproduction, may be examined by the public at the libraries of the USGS field offices whose addresses are listed in this introduction The libraries may be queried concerning the availability of specific documents and the possible utilization of local copying services, such as color reproduction
- Avail HMSO Publications of Her Majesty's Stationery Office are sold in the U S by Pendragon House, Inc (PHI), Redwood City, California The U S price (including a service and mailing charge) is given, or a conversion table may be obtained from PHI
- Avail BLL (formerly NLL) British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England Photocopies available from this organization at the price shown (If none is given, inquiry should be addressed to the BLL)
- Avail Fachinformationszentrum, Karlsruhe Sold by the Fachinformationszentrum Energie, Physik, Mathematik GMBH, Eggenstein Leopoldshafen, Federal Republic of Germany, at the price shown in deutschmarks (DM)
- Avail Issuing Activity, or Corporate Author, or no indication of availability Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document
- Avail U S Patent and Trademark Office Sold by Commissioner of Patents and Trademarks, U S Patent and Trademark Office, at the standard price of 50 cents each, postage free
- Other availabilities If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA A listing of public collections of NASA documents is included on the inside back cover

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics and
Astronautics
Technical Information Service
555 West 57th Street, 12th Floor
New York, New York 10019

British Library Lending Division,
Boston Spa, Wetherby, Yorkshire,
England

Commissioner of Patents and
Trademarks
U S Patent and Trademark Office
Washington, D C 20231

Department of Energy
Technical Information Center
P O Box 62
Oak Ridge, Tennessee 37830

ESA-Information Retrieval Service
ESRIN
Via Galileo Galilei
00044 Frascati (Rome) Italy

Fachinformationszentrum Energie, Physik,
Mathematik GMBH
7514 Eggenstein Leopoldshafen
Federal Republic of Germany

Her Majesty's Stationery Office
P O Box 569, S E 1
London, England

NASA Scientific and Technical Information
Facility
P O Box 8757
B W I Airport, Maryland 21240

National Aeronautics and Space
Administration
Scientific and Technical Information
Branch (NST-41)
Washington, D C 20546

National Technical Information Service
5285 Port Royal Road
Springfield, Virginia 22161

Pendragon House, Inc
899 Broadway Avenue
Redwood City, California 94063

Superintendent of Documents
U S Government Printing Office
Washington, D C 20402

University Microfilms
A Xerox Company
300 North Zeeb Road
Ann Arbor, Michigan 48106

University Microfilms, Ltd
Tylers Green
London, England

U S Geological Survey
1033 General Services Administration
Building
Washington, D C 20242

U S Geological Survey
601 E Cedar Avenue
Flagstaff, Arizona 86002

U S Geological Survey
345 Middlefield Road
Menlo Park, California 94025

U S Geological Survey
Bldg 25, Denver Federal Center
Denver, Colorado 80225

NTIS PRICE SCHEDULES

Schedule A STANDARD PAPER COPY PRICE SCHEDULE

(Effective January 1, 1982)

Price Code	Page Range	North American Price	Foreign Price
A01	Microfiche	\$ 4 00	\$ 8 00
A02	001-025	6 00	12 00
A03	026-050	7 50	15 00
A04	051-075	9 00	18 00
A05	076-100	10 50	21 00
A06	101-125	12 00	24 00
A07	126-150	13 50	27 00
A08	151-175	15 00	30 00
A09	176-200	16 50	33 00
A10	201-225	18 00	36 00
A11	226-250	19 50	39 00
A12	251-275	21 00	42 00
A13	276-300	22 50	45 00
A14	301-325	24 00	48 00
A15	326-350	25 50	51 00
A16	351-375	27 00	54 00
A17	376-400	28 50	57 00
A18	401-425	30 00	60 00
A19	426-450	31 50	63 00
A20	451-475	33 00	66 00
A21	476-500	34 50	69 00
A22	501-525	36 00	72 00
A23	526-550	37 50	75 00
A24	551-575	39 00	78 00
A25	576-600	40 50	81 00
	601-up	-- 1/	-- 2/

A99 - Write for quote

- 1/ Add \$1 50 for each additional 25 page increment or portion thereof for 601 pages up
 2/ Add \$3 00 for each additional 25 page increment or portion thereof for 601 pages and more


Schedule E EXCEPTION PRICE SCHEDULE Paper Copy & Microfiche

Price Code	North American Price	Foreign Price
E01	\$ 6 50	\$ 13 50
E02	7 50	15 50
E03	9 50	19 50
E04	11 50	23 50
E05	13 50	27 50
E06	15 50	31 50
E07	17 50	35 50
E08	19 50	39 50
E09	21 50	43 50
E10	23 50	47 50
E11	25 50	51 50
E12	28 50	57 50
E13	31 50	63 50
E14	34 50	69 50
E15	37 50	75 50
E16	40 50	81 50
E17	43 50	88 50
E18	46 50	93 50
E19	51 50	102 50
E20	61 50	123 50
E-99 - Write for quote		
N01	30 00 ¹	45 00


TABLE OF CONTENTS

	Page
IAA ENTRIES (A82-10000)	217
STAR ENTRIES (N82-10000)	245
Subject Index	A-1
Personal Author Index	B-1
Contract Number Index	C-1

TYPICAL CITATION AND ABSTRACT FROM STAR



TYPICAL CITATION AND ABSTRACT FROM IAA



AERONAUTICAL ENGINEERING

A Continuing Bibliography (Suppl. 149)

JUNE 1982

IAA ENTRIES

A82-22398 † Analysis and optimization of control systems in piloted flight vehicles (Analiz i optimizatsia sistem upravleniia pilotiruemykh letatel'nykh apparatov) G I Ryl'skii. Moscow, Izdatel'stvo Mashinostroenie, 1981 200 p. 156 refs. In Russian

An analysis is given of the activity of a human operator in the control systems of piloted flight vehicles and of the possibility of describing this activity mathematically. A classification is suggested, and an analysis made, of recent mathematical models describing human activity in these systems. Attention is given to the advantages of the models that use queuing theory, and these models are used in elaborating techniques for determining characteristics of the operator's work. C R.

A82-22407 † Utilization of radio equipment at airports and on airways (Ekspluatatsiia radiooborudovaniia aerodromov i trass) A A. Kuznetsov and V I Dubrovskii. Moscow, Izdatel'stvo Transport, 1981 224 p. 26 refs. In Russian

The organization of navigation aids and air traffic control in civil aviation is briefly considered. Problems of technical and economic planning, the organization of support and maintenance, and the collection and processing of reliability data pertaining to air navigation and ATC equipment are also considered. Specific attention is given to the utilization characteristics of radio navigation and ATC systems, ATC radar stations, automated ATC, display equipment, and methods and models for the utilization of radio navigation and ATC systems. B J.

A82-22880 Complete guide to Rutan homebuilt aircraft. D. Downie and J. Downie. Blue Ridge Summit, PA, Tab Books, Inc., 1981 288 p. \$8.95.

The development history of a group of home-built sport aircraft characterized by canard configurations and non-metallic construction is presented, from the time that the designer, Burt Rutan, who won an AIAA award for his thesis on roll-yaw coupling started the project to the flight testing of the four-passenger, push/pull propeller Defiant aircraft. Incorporating the canard in order to exploit both its inherent stall-limiting function and its direct-lift generation at low incidence during short takeoffs and landings, the two designs featured are (1) the plywood-structure VariViggen, and (2) the more highly developed VariEze/Long-EZ, whose structure is of fiberglass cloth-reinforced self-curing epoxy layups over pre-shaped styrofoam. Additional material on aircraft construction and performance at the hands of the designer and dozens of his hobbyist-clients is also presented. O C.

A82-22881 Computer-generated images for simulators - The cost of technology. G C. Larson. *Air Force Magazine*, vol. 65, Feb 1982, p. 54-59.

The effectiveness, capabilities, and prospects for computer-controlled flight simulators suitable for combat flight training are examined. Current devices offer a wraparound imagery, multiple crewmember interface, and separate cockpit coordinated displays suitable for developing teamwork among pilots of different aircraft. The simulators are equipped with realistic cockpits, an instructor's station with full control and recording equipment, a data base with simulator dynamics and ability to translate actions into real-time responses, and a visual system which displays a scene that could be expected in the real world. Mechanical limitations are defined by the

cost of memory and processing speed necessary for edge generation, the formation of geometric shapes and solids closely resembling real world objects, and texturing has shown promise for defining recognizable areas by rectangular areas which overlap in a fashion acceptable to a human field of vision. M S K.

A82-22896 # Lineup of the IM-series aircraft-derivative gas turbines. K. Takeo (Ishikawajima-Harima Heavy Industries Co., Ltd., Tokyo, Japan). *IHI Engineering Review*, vol. 14, Oct 1981, p. 36-42. 5 refs.

The development of the IM-series of aircraft derivative gas turbines is reviewed. The discussion begins with the IM1500 GL engine, having an output at turbine coupling of 11,100 kW and a thermal efficiency of 26.8%, first used as an industrial gas generator in 1968. Principal characteristics of the IM2000 and IM2500 are then discussed. The output and thermal efficiency of these two models are given as 12,800 kW and 33.5% and 19,300 kW and 35.1%, respectively. Fundamental specifications of the power turbines are described, and the flowpath design is presented. The construction and mechanical design of the engines are described, and results of creep-rupture, high temperature fatigue, and vibratory stress tests are given. Finally, the IM5000 power turbine, with an output of 38,000 kW and an efficiency of 38.4% is described. It is also shown how heat in the high-temperature exhaust gases from the turbines can be used in waste heat recovery systems to improve the total plant efficiency. J F.

A82-22898 # History of the sweptback wing (Geschichte des Pfeilflügels). H. Ludwig (Aerodynamische Versuchsanstalt, Institut für experimentelle Stromungsmechanik, Göttingen, West Germany). *Deutsche Gesellschaft für Luft- und Raumfahrt, Jahrestagung, Aachen, West Germany, May 11-14, 1981, Paper 81-070*. 15 p. 10 refs. In German.

The history of sweptback wings which make use of the sweepback to alter the effective Mach number is reviewed. Principles of the sweptback wing and its effects are discussed for subsonic flight with high Mach numbers, supersonic flight with a subsonic leading edge, and supersonic flight with a supersonic leading edge. The historical development is traced from the first sweptback wing model in 1939 for the Göttingen high speed wind tunnel to various fighter aircraft including the Messerschmitt 262 and Heinkel designs. Results of wind tunnel tests for various angles of sweepback are presented. D L G.

A82-22902 The use of dynamic mock-ups in the design of advanced systems. M L. Gravely (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, OH) and L. Hitchcock (US Naval Material Command, Naval Air Development Center, Warminster, PA). In: *Human Factors Society, Annual Meeting, 24th, Los Angeles, CA, October 13-17, 1980, Proceedings*. Santa Monica, CA, Human Factors Society, Inc., 1980, p. 5-8.

The advantages of using dynamic mock-ups in advanced system design are discussed in terms of the USAF's Digital Avionic Information System (DAIS) Program and the Navy's Advanced Integrated Display System (AIDS) Cockpit Development Program. Experienced pilots are employed to judge the acceptability of slide projector displays for radar, low-light level television, and alpha-numeric and vector graphic formats. Cost effectiveness is achieved by lowering software costs, minimizing time in constructing the mock-up, and high reliability-low maintenance features. The cockpit layout is set up once the required tasks and the number of multifunction

A82-22905

controls are known, and variations on the instrumentation set-up are tested repeatedly. The AIDS concept allows remote location of a slide projector for closed circuit television display of various instrument configurations in different situations, and selected displays are chosen for full scale simulation. M S K

A82-22905 Combined multisensor displays A J Josefowitz, R A North (Honeywell Systems and Research Center, Minneapolis, MN), and J Trimble (U S Navy, Office of Naval Research, Arlington, VA) In Human Factors Society, Annual Meeting, 24th, Los Angeles, CA, October 13-17, 1980, Proceedings Santa Monica, CA, Human Factors Society, Inc., 1980, p 17-21 Contract No N00014-77-C-0684

The use of combined multisensor displays which result from preprocessing of various sensor data for shape coding in a display is discussed in terms of lowering the pilot's workload. A Forward Looking Infrared (FLIR) radar display was selected as the background for combinations with other sensor displays in trials of suitability, with color coded close, intermediate, and far range conditions. Test subjects were 32 right-handed males who performed point of impact, target detection, and tracking tasks. The variables were processed in univariate and multivariate analyses of combined and uncombined display types, and individual display comparisons by pairs. The combined displays were found to enhance the time-sharing of tasks with other crewmembers and the accurate detection of targets. Color coding is recommended to be of secondary value, with some results showing that colors actually slow response times. M S K

A82-22974 Direct comparison of community response to road traffic noise and to aircraft noise F L Hall, S E Birnie, S M Taylor, and J E Palmer (McMaster University, Hamilton, Ontario, Canada). *Acoustical Society of America, Journal*, vol 70, Dec 1981, p 1690-1698 23 refs. Research supported by the Transport Canada and Natural Sciences and Engineering Research Council of Canada.

Previous efforts to synthesize information on community responses to various noise sources have been forced to rely on a variety of surveys conducted in different countries over a number of years. Data collected recently around Toronto International Airport provide a direct comparison of response to two sources, based on 673 interviews of persons exposed to a variety of levels of both aircraft and road traffic noise. The results of that analysis do not support the assumption that response to these two noise sources is the same. For the same value of the 24-h energy-averaging metric, a greater percentage of the sample is highly annoyed by aircraft noise than by road traffic noise. Possible reasons for this contradiction of the results of a previous synthesis of noise surveys are discussed. (Author)

A82-23027 GTD terrain reflection model applied to ILS glide scope R Luebbers, V Ungvichian, and L Mitchell (Ohio University, Athens, OH) *IEEE Transactions on Aerospace and Electronic Systems*, vol 18, Jan 1982, p 11-20 20 refs. USAF-supported research, U.S. Department of Transportation Contract No. FA7WA-3549.

A terrain reflection model based on the geometrical theory of diffraction is described which (1) can accommodate any piecewise linear terrain profile, (2) requires less computer time than physical optics models, (3) is capable of including transverse terrain effects, and (4) determines the reflected fields with all important diffraction and blockage effects included. The model's approach to the calculation of the reflected magnetic fields consists of a geometrical process by which the existence and the reflection and/or diffraction points of the rays are determined, and a mathematical process by which the magnitude and phase of the corresponding electric field at the receiver location are evaluated. O C

A82-23029 Sensitivity reduction by double perfect model following. T. Okada, M. Kihara, and K. Motoyama (Defense Academy, Yokosuka, Kanagawa, Japan). *IEEE Transactions on Aerospace and Electronic Systems*, vol 18, Jan 1982, p 29-38 12 refs.

A double perfect model following (DPMF) system is proposed which uses two models: one is used to define the desirable response and the other is used to reduce sensitivity to parameter perturbation.

The concept is shown and methods of model selection and controller synthesis are discussed, followed by numerical examples and an aircraft control example which demonstrate performance of the DPMF concept. It is shown that the DPMF system can be less sensitive than a nominally equivalent single perfect model following (SPMF) system and that sensitivity reduction is enhanced by proper selection of the model. It is also shown that the sensitivity of multi-input systems can be reduced componentwise or blockwise by using a decoupled type model. (Author)

A82-23031 # Stereographic projection in the National Air-space System. R G Mulholland and D W Stout (FAA, Technical Center, Atlantic City, NJ) *IEEE Transactions on Aerospace and Electronic Systems*, vol 18, Jan 1982, p 48-57 10 refs.

Consideration is given to the calculation of stereographic representations of airborne targets from observations of slant range, azimuth, and altitude in a multiple radar tracking system. Emphasis is placed upon the translation of the accuracy of the surveillance information into the stereographic plane. Applications include air traffic control operations in which calculations must be performed repeatedly in real time for numerous targets without overtaxing available computational resources. (Author)

A82-23037 * Methodology for multi-aircraft minimum noise impact landing trajectories G Cook, I D Jacobson, R Chang, and R. Melton (Virginia University, Charlottesville, VA) *IEEE Transactions on Aerospace and Electronic Systems*, vol 18, Jan 1982, p 131-146 14 refs. Grant No. Nsg-1509.

The problem of optimizing landing trajectories with respect to noise impact index is addressed. In contrast with previous work, multilandings are considered. In order to make the problem tractable the trajectories are specified in functional form with certain parameters left free for selection by the optimization methods. Constraint of aircraft dynamic behavior, trajectory separation, pilot workload, passenger comfort, and maximum noise intensity all enter into the determination of what is an allowable trajectory. A version of the quasi-Newton iterative procedure is used to determine the optimum parameter values. The results show improvement in noise impact to the airport considered and the potential for even greater improvement at many airports. (Author)

A82-23225 Linear alpha-ray altimeter (Lineinyi alpha radiatsionnyi vysotomer) P S Kamenov, D N Vasilev, and E N Vapirev (Sofiyski Universitet, Sofia, Bulgaria) *Iadrena Energiia*, no 15, 1981, p 24-28 8 refs. In Russian.

The paper describes an alpha-ray altimeter which employs scintillation detection and achieves linearity between the number of counts per unit time and the altitude. The design of the altimeter is described, and experimental results are presented. Causes of errors and nonlinearities are analyzed, and ways to reduce them are discussed. B J

A82-23227 # Aircraft parameter identification in the presence of atmospheric turbulence H Okubo (Osaka Prefecture University, Sakai, Japan), T Kanou (Kawasaki Heavy Industries, Ltd., Akashi, Japan), and M Kobayakawa (Kyoto University, Kyoto, Japan) *Kyoto University, Faculty of Engineering, Memoirs*, vol 43, July 1981, p 364-375 7 refs.

The paper investigates a method for the identification of unknown parameters in the dynamics of an aircraft, using flight data which are affected by random disturbances due to wind gusts. Two general algorithms, the maximum likelihood (ML) method and the extended Kalman filter (EKF) technique, along with a combination of the algorithms are examined for capability by numerical simulations. The ML algorithm requires no a priori information on the initial parameter estimates, while the EKF algorithm computes an on-line estimate of the parameter in real time, has a smaller program size, and requires less computational time and memory than the former. The combined use of the two algorithms gives a useful method for an on-line parameter estimation, using the ML algorithm as a start-up procedure, and processing the remaining data sequentially with the EKF technique. D L G.

A82-23250 † Improving the accuracy of the estimates of surfactant content in jet fuels (Povyshenie tochnosti otsenki soder-

zhaniia pav v reaktivnykh toplivakh). A F Gorenkov, V S Stepanenko, and V A Saleev *Khimiia i Tekhnologiya Topliva Masel*, no 2, 1982, p 36-39 In Russian

Surface processes associated with the interaction between jet fuels and water are investigated with a view to increasing the accuracy of the estimates of surfactant content in jet fuels. It is shown that when analyzing water-fuel interaction, it is essential that the meniscus condition and the presence of drops on the test cylinder walls be taken into account. In view of this, modifications to the standard jet fuel quality control procedure are proposed. V L

A82-23309 **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980 204 p

Developments towards higher levels of ATC automation are considered along with the requirements for reduced IFR separations on final approach, an analysis of system problems using aviation safety reporting system data, and specification issues and problems in connection with air traffic control computer replacement. Attention is given to maintenance concepts for the 1980's, approaches for reducing reflections on the front surface of air traffic control displays, the price of safety, general aviation in the future ATC system, the utilization of the helicopter's versatility to improve the ATC system, the human element, international plans concerning ATC-related developments, and challenges and issues for the future. Technological developments are discussed, taking into account distributed data processing modeling for future ATC systems, lightweight ATC systems, the Discrete Address Beacon System, voice communications, and a Microwave Landing System simulation. G.R

A82-23311 **The requirements for reduced IFR separations on final approach** W J Swedish (MITRE Corp., Metrek Div., McLean, VA) In **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980, p 39-43 US Department of Transportation Contract No. FA80WA-4370

This paper examines the factors which affect the feasibility of reducing IFR standards from a minimum of 3.0 nmi to 2.5 or 2.0 nmi. For those aircraft pairs which are not restricted by wake vortices, separation reduction is likely to be limited by the rate at which aircraft must go around to avoid simultaneous runway occupancy. The runway occupancy performance required to avoid an unacceptable increase in the go-around rate is determined. The impacts of ATC improvements such as metering and spacing on the runway occupancy requirements and on the controller's decision making workload are then presented. Alternating arrivals to close-spaced parallel runways are discussed as one means to avoid the constraints of runway occupancy and, possibly, wake vortices. Lastly, it is proposed that further research on reduced separations should address a single specific airport, in order to narrow the range of variables and thereby facilitate the identification of problems and solutions. (Author)

A82-23312 **Analysis of system problems using aviation safety reporting system data.** R L Grayson (Battelle Columbus Laboratories, Mountain View, CA) In **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980, p 45-48

The Aviation Safety Reporting System (ASRS) was inaugurated in 1976 as the result of an interagency agreement between the FAA and NASA. It was designed as a confidential, voluntary reporting system to enable individual users or observers of the National Aviation System to record hazardous occurrences or to report conditions which might adversely affect aviation safety. A description is presented of the system operation, the characteristics of the data base compiled by the system as the principal information source, and the ways in which the system has helped in defining and clarifying various aviation system problems. G.R

A82-23313 **Air Traffic Control computer replacement - Specification issues and problems** T L Hannan and M E. Perre (FAA, Washington, DC). In **Air Traffic Control Association, Annual**

Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 51-56

The foundation of today's Air Traffic Control (ATC) system is the ATC specialist, who is supported by ATC automation systems and automated radar terminal systems. According to many ATC experts, however, the computer will become the foundation of the future ATC system. The transition to the future ATC system will be gradual. The extent to which decision-making processes will be accomplished automatically will increase until significant elements of the ATC process are controlled by the computer. Attention is given to an ATC Computer Replacement System which is suited for the evolutionary transition process. In the form of its initial implementation, the new system must be compatible with the ongoing ATC system. But it must also be capable of meeting future ATC functional requirements as it evolves toward automated decision-making. The considered requirements are examined in an attempt to define the scope of the ATC computer replacement acquisition. G.R

A82-23314 **Reducing reflections on the front surface of air traffic control displays** J W Aschenbach (FAA, Technical Center, Atlantic City, NJ) In **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980, p 65-71 5 refs

Problems related to the occurrence of surface reflections on the FAA's en route air traffic control displays have become more serious in connection with the installation of the near vertical stroke-writing display in the air route traffic control centers. New investigations were initiated to see if it was feasible to raise the display background level, in order to mask reflections and to further reduce the sources of plan view display screen reflections through more modifications to the lighting. A study was conducted with the objective to find a method of decreasing the reflectivity of the front surfaces of the display itself. By eliminating the extra panel on the front of the display and by etching and coating the outside surface of the CRT with a multilayer dielectric thin film, it was possible to produce a display with very little glare. G.R

A82-23315 **NAS system load - Utilization of the DARC system** E P Schmidt (FAA, Hampton, GA) In **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980, p 73-78

In connection with an unexpectedly large increase in air traffic volume, there is a growing threat that ATS requirements might exceed the processing capacity of the NAS En Route 9020 computer systems. An investigation is conducted concerning the feasibility of providing an interim solution to the problem by means of an approach based on the utilization of existing hardware allocations. The approach would employ the Direct Access Radar Channel (DARC) system as an associative processor to the NAS 9020 system. DARC is specified to provide a parallel radar data path for use in the event of catastrophic failure of the prime channel, and during planned down time of the NAS 9020 system. G.R

A82-23316 **Utilizing the helicopter's versatility to improve the ATC system** A G B DeLucien and F D Smith (Pacer Systems, Inc., Arlington, VA) In **Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings** Arlington, VA, Air Traffic Control Association, 1980, p 89-96 14 refs

This paper presents an overview of certain operating environments of civilian helicopters, and summarizes selected performance-manuever envelopes of those models certified for operation under instrument flight rules (IFR). It discusses how the capabilities and limitations which are unique to these vehicles can be used to improve the capability, and expand the capacity, of the Air Traffic Control (ATC) system. Helicopter-oriented technical issues which will impact future changes to the system are identified. The paper concludes that as controllers become increasingly aware of related helicopter characteristics and operating environments, and take advantage of them, the effect would be to reduce controller workload, and to increase the capacity, expand the functional capabilities, and enhance the overall versatility of the ATC system. (Author)

A82-23317

A82-23317 International plans for civil and military co-ordination P J Gray (RAF, National Air Traffic Services, London, England) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 105-108

Attention is given to a review of the common aims of the civil and military controller, certain conflicts of interest inherent in the function of civil and military air traffic control, and the resolution of conflicts related to the existence of national boundaries in Western Europe. In connection with the finite nature of air space, it is found to be important that, in an allocation of the utilization of this space, the needs and characteristics of all users, civil and military, must be taken into consideration. In the UK, integrated civil and military staffs at HQ and field levels are used to ensure that no one user interest is permitted to unfairly predominate. In the wider European context civil and military coordination and cooperation prevails within Eurocontrol, and perhaps most successfully, at NATO CEAC (Committee for European Airspace Coordination) G R

A82-23318 Operational air traffic in the Federal Republic of Germany F-W von Schlichtkrull (Bundeswehr, Frankfurt am Main, West Germany) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 111-117

Aspects of traffic volume are considered, taking into account the number of civil and military aircraft flights for 1979. For an appropriate evolution of the performance involved in controlling the total number of flights reported (3,950,000), the geographic size of the Federal Republic of Germany must be taken into account, giving attention also to regulations which exclude military aircraft from an area near the iron curtain border. Military operational air traffic can be divided into three categories, including uncontrolled military flights, military air traffic under the control of air defense units, and military air traffic handled by Air Traffic Services. The high air traffic density leads to special problems which are partly related to midair collision hazards. Approaches for solving these problems are discussed, taking into account a separation in space for flights of different traffic categories, and an employment of advanced control methods G R

A82-23319 Distributed data processing modeling for future ATC systems R R Jones (Hughes Aircraft Co., Fullerton, CA) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 125-131

The use of distributed processing procedures makes it feasible to reduce the processor cost, and to increase, at the same time, maintainability and reliability. Other advantages are related to the convenience of system expansion by means of added capabilities. The utilization of distributed data processing benefits for air traffic control systems (ATC) is considered, taking into account the use of a rigorous analytic technique for a determination of optimal operational configurations. The analytic technique selected is simulation modeling. This approach makes use of a Distributed Data Processing Model (DDPM) coupled with a Design Analysis System (DAS). The considered approach has been employed extensively to design many complex systems similar in scope and nature to ATC systems. A description is presented of the DDPM and the DAS, giving attention to the use of these techniques in an application involving an ATC system G R

A82-23320 ATC automation - A look forward Technology/architecture L M Reppert (Texas Instruments, Inc., Dallas, TX) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 133-136

It is pointed out that ATC automation is going through a revolutionary evolution due to major technological advances in such areas as microprocessors and memories. A reasonable projection prediction for the 80's and 90's would specify a high utilization of distributive computer architecture implemented with simple/high technology hardware. The considered evolution will require a system

which is functional-task oriented, repartitionable, and modular. Using distributed computer architecture and available microprocessor and memory technologies, ATC system designers can perform all the required functions and implement the system in a highly efficient and cost effective manner which inherently provides the desired characteristics, taking into account modularity, recoverability, high data integrity, ultra-high reliability, and computer-aided maintainability G R

A82-23321 Lightweight ATC systems R Bonitch (Eaton Corp., AJL Div., Farmingdale, NY) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 139-144

The problem of tactical ATC system implementation has been considered, taking into account the generation of light-weight and low-cost equipment which can provide advanced ATC capabilities for forward command posts, tactical command centers, and low traffic density applications, such as remote airfields and oil rigs. The considered systems are based on microprocessor technology. This technology makes it possible to utilize recent advances related to signal processing, antenna development, and plasma displays. Attention is given to the development of the Small Plasma Automated Radar Terminal Area Navigation System (SPARTAN) and its military version, the Very Lightweight Air Traffic Management Equipment (VLATME). The advantages of the employed ac plasma displays are related to light weight, low operating voltage (200 volts), and sustained memory G R

A82-23322 Discrete Address Beacon System /DABS/ P D Hodgkins (FAA, Washington, DC) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 147-155

In connection with the results of a study conducted in 1969, recommendations had been made to upgrade the Air Traffic Control System. These recommendations became the basic system requirements for DABS. The recommendations had been concerned with the development of three new systems, including an improved surveillance system for the eventual replacement of the present Secondary Surveillance Radar (SSR), a digital air/ground data link communication system, and a ground-based collision avoidance system. Probably the most significant characteristic of the DABS is that it is a direct extension of and fully compatible with the SSR or the ATC Radar Beacon System (ATCRBS), as it is referred to in the US. Although primarily a surveillance system, DABS is also a communications and ground-based collision avoidance system designed with sufficient capacity to accommodate expected air traffic growth well into the next century G R

A82-23323 A Microwave Landing System simulation. R P Spengler and R W Zoladz (Computer Sciences Corp., Pomona, NJ) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings Arlington, VA, Air Traffic Control Association, 1980, p 157-162

Computer software is being developed for a series of experiments involving the simulation of Microwave Landing System (MLS) operations. The purpose of these experiments is to identify, or at least obtain advanced warning of, potential problem areas in an MLS implementation. The MLS simulation model is divided into three phases. Each phase represents a different level of avionics and thus provides capabilities for different approach paths. Emphasis is placed on the ATC communications and the various approach geometries. The MLS is an air derived system in which ground based equipment transmits accurate approach information to a receiver on board the aircraft. Azimuth, elevation, and ranging elements comprise the system operating in the microwave band (approximately 5000 megahertz). With MLS, aircraft can enter the approach area from various directions and speeds and fly toward separate approach gates G R

A82-23324 Voice communications - The vital link. R E Husted (Littton Industries, Amecom Div., College Park, MD) In Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings

Arlington, VA, Air Traffic Control Association, 1980, p 165-168

Voice communications provides the vital link among controllers and between controllers and aircrews. Communications systems presently in use provide voice communications via three links, including intercom (between different air traffic controllers), interphone (between different sites), and radio (between the air traffic controller and the pilots). It is pointed out that current communications systems at most air traffic control facilities are generally outdated, inflexible, and difficult to maintain. Attention is given to needs for a new voice communication system which is able to handle the peak loads of air traffic that the facility will encounter. Amecom's Integrated Voice Communications Systems satisfies these needs and is available now. The system has been designed specifically for the Air Traffic Control environment. Aspects of system operation are discussed in some detail. G R

A82-23368 **Fighters - Tomorrow's terminology.** G. Warwick. *Flight International*, vol 121, Feb 6, 1982, p 291, 292, 301, 302

Consideration is given to the technological features under study for integration into fighter aircraft designs over the course of the 1990s. These features include (1) fly-by-wire and fly-by-light active electronic controls, which will permit the modification of flight characteristics through reprogramming of software control laws, (2) the use of primary, directional-reinforced composite structures that will aeroelastically deform in flight to increase aerodynamic efficiency, (3) the improvement of wing aerodynamics through the downstream effect of canards, (4) the use of conformal stores carriages to reduce drag by as much as 60%, (5) the generation of direct lift force control by means of coordinated wing/canard control surface actuation, and (6) the vectoring of engine exhaust nozzles to increase lift and maneuverability. O.C

A82-23369 **Boeing's big, quiet 737-300** B Sweetman. *Flight International*, vol 121, Feb 13, 1982, p 353-356

A description is given of the modifications made on the precursor 737-200 commercial aircraft design to yield the 737-300, which include (1) greater wing and horizontal stabilizer spans, (2) fuselage extensions totalling 104 in, (3) leading edge slat airfoil redesign, (4) the incorporation of adhesive bonding construction techniques and more advanced aluminum alloys for longer service life, and most importantly, (5) a new engine installation that will accommodate either CFM 56-3 or RJ-500 turbofans. The modified aircraft is expected to meet FAR 36 Stage 3 noise limits, and to be more fuel-efficient than its predecessor. In the context of the present commercial aircraft market, the 737-300 represents a transitional design which will be replaced by a novel, 150-passenger short-haul aircraft. O C

A82-23426 **Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers.** Conference supported by the Technion - Israel Institute of Technology, Israel Ministry of Defence, Ministry of Transport, et al. Haifa, Israel, Technion - Israel Institute of Technology, 1981 251 p

Topics significant to modern aircraft design and performance, design and efficiency, and to control logic were examined. Flow past an airfoil in a supersonic stream was discussed, as were drag reduction by means of an active boundary layer thickening, the aerodynamic characteristics of an axisymmetric configuration with transverse jets in the base plane, and coherent structure of the turbulent boundary layer in the lateral direction. A general similarity solution of the transonic equation in the physical plane was presented, and perturbations to unidirectional turbulent flow due to small lateral mean velocity gradients were studied. Discussions were devoted to the evaluation of stiffened shell characteristics from imperfection measurements, to fixed gain controller design for aircraft, and to a time finite element discretization of Hamilton's law. M.S.K

A82-23439 # **Low grade fuels for turbo and jet engines.** B. Gal-Or, E. Zahavi, and A. Burcat (Technion - Israel Institute of Technology, Haifa, Israel). In *Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12,*

1981, Collection of Papers. Haifa, Israel, Technion - Israel Institute of Technology, 1981, p 170-180

In connection with the energy crisis, a program has been initiated to reexamine the design methodologies and the expected performance characteristics of turbo and jet engines in the light of the higher temperatures and reduced durability that would result from the increasing use of low-grade, high-aromatic aircraft fuels. The discussion focuses on the first phase of the program which includes simulated computer studies of the maximum flame temperatures expected in jet engine combustors with different fuels under various operating conditions such as takeoff, cruise, and idle performance at various altitudes and Mach numbers. General parameters are proposed for the comparison of alternative fuels in terms of the maximum flame temperatures and the combustion products distributions. V L.

A82-23441 # **Fixed gain controller design for aircraft** Y Baram and D Eidelman (Tel Aviv University, Tel Aviv, Israel). In *Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers, Haifa, Israel, Technion - Israel Institute of Technology, 1981, p 211-216* 6 refs. Grant No AF-AFOSR-80-0178

A method for designing fixed-gain controllers for systems with large parameter variation is presented, with particular attention to the problem of designing non-adaptive back-up control systems for high performance aircraft. The approach, based on minmax information criteria, is used to design a fixed-gain controller and a state estimator for a given aircraft, and is shown to provide good performance qualities. (Author)

A82-23444 **YF-16 design concept and philosophy** H J Hillaker (General Dynamics Corp., Fort Worth, TX). *(Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, Feb 11, 12, 1981)* *Israel Journal of Technology*, vol 19, no 1-2, 1981, p 3-18

The design objective of the original YF-16 was to maximize the usable maneuverability and agility of the aircraft in the air combat arena at a mission radius of 500 nmi. This objective was to be achieved within a flyaway cost of 3 million dollars per unit. To this end, emphasis was placed on small size and low weight/cost, on advanced technologies, and on design/aerodynamic innovations. The key configuration elements that offered clear superiority in terms of maximum lift, directional stability, drag-at-lift, and inlet flow field were bottom inlet, wing-body blending, variable camber, and single vertical tail. New wing planforms which are being tested on F-16, will allow even greater capabilities while retaining the low-cost concept. A single turbofan engine provides the best balance of combat capability and mission radius for the lowest weight. V.L.

A82-23470 **Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning (Verbesserung der Treibstoffökonomie durch Fliegen mit zulässiger rückwärtiger Schwerpunktlage).** M Caspari and D Kricke (Gesellschaft für Internationalen Flugverkehr mbH, Berlin, East Germany). *Technisch-ökonomische Information der Zivilen Luftfahrt*, vol. 17, no 3, 1981, p. 142-145. In German

The relationship between balance, stability, and maneuverability is established, and means of minimizing the moment of an aircraft's horizontal stabilizers and elevators to conserve energy are discussed. Requirements and peculiarities of INTERFLUG aircraft are described, and current techniques to save fuel by achieving a higher rearward center-of-gravity positioning are discussed. Particular attention is given to the retention of rearward center-of-gravity positioning in the IL-62/IL-62M aircraft. Calculations show that procedures exist to achieve a rearward center-of-gravity positioning of 33%, which would result in a minimum fuel savings of 4.1% at 165 g/km. J F

A82-23603 **High-frequency monitoring of surface layers of metals** A L Dorofeev, N P Kalinin, and V D Ostapenko (Kalinin Carburator Plant, Perm, USSR). *(Defektoskopia, Apr 1981, p 34-40)* *Soviet Journal of Nondestructive Testing*, vol 17, no 4, Dec. 1981, p 268-272. Translation.

A high-performance electromagnetic device working at 100-500

A82-23678

MHz is reported. Main trends in tests on the effects of the electrical conductivity, the gap, the closeness to edges, and the presence of microcracks on the parameters of the device are established. A reduction in the quality factor is observed when the transducer is placed on a part with a defect, which causes a reduction in the amplitude or even a halt to the oscillation, indicating that simple self-excited flaw detectors working at elevated frequencies can be made with high sensitivity to surface defects. D L G

A82-23678 On the sonic fatigue life estimation of skin structures at room and elevated temperatures. S. Maekawa (Kawasaki Heavy Industries, Ltd., Gifu, Japan). *Journal of Sound and Vibration*, vol. 80, Jan. 8, 1982, p. 41-59. 15 refs

The Monte Carlo method of nonlinear response analysis and a fatigue life estimation scheme based on a rheological model have been used to estimate the sonic fatigue life of heated skin structures. Calculations for a skin-stringer panel are compared with experimental data and it is found that, with properly selected fatigue notch factor, the analysis provides fairly accurate estimate of the acoustic fatigue life. The effects of temperature, static pressure, and oil canning on the acoustic fatigue life are discussed. V L

A82-23751 Welding technology for the aerospace industry. *Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980*. Conference sponsored by the American Welding Society. Miami, FL, American Welding Society, 1981. 183 p

The conference focused on the welding processes most important to future commercial and military aeronautic framework design and construction, aircraft hardware reclamation, and materials evaluation. Processes covered include diffusion welding, laser welding, electron beam welding, superplastic forming, keyhole plasma arc welding, inertia welding, and resistance welding. Other topics include weldability of critical materials and alternatives, welding supports such as adaptive controls, digital arc welding programmers, and the application of fracture control. Finally, repair welding is discussed. V L

A82-23753 Novel approaches to electron beam welding machine utilization. F. S. Pogorzelski (McDonnell Aircraft Co., St. Louis, MO). In *Welding technology for the aerospace industry*, *Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980*. Miami, FL, American Welding Society, 1981, p. 41-53

Several applications that require unique and novel approaches to the utilization of electron-beam welding equipment for profitable production are discussed. One of the applications is the welding of F-15 pylon posts fabricated from annealed Ti-6Al-4V. Die forging. A 100% penetration first weld pass in a tapered thickness butt joint is produced using a chart programmer set up with the plot of the high voltage required versus position along the length of the tapered joint; the programmer is coupled to the power-stat of the electron-beam welding machines so that the welding power is increased automatically to the proper value as the welding gun traverses from the thick to the thin section of the joint. Electron-beam welding of F-15 wing skin 'kick rib' machined from a solid plate of Ti-6Al-4V and the development of a blind tracking device for electron-beam welding are also discussed. V L

A82-23754 Diffusion bonding in superplastic forming/diffusion bonding. J. R. Williamson (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH). In *Welding technology for the aerospace industry*, *Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980*. Miami, FL, American Welding Society, 1981, p. 55-83. 8 refs

Mechanisms of the superplastic forming/diffusion bonding process are discussed with reference to the fabrication of titanium structures for aerospace applications. Primary factors affecting diffusion bonding are examined including process variables such as pressure, temperature, and time, and material variables such as surface roughness, surface cleanliness, and grain size. Two additional factors become important because of the nature of the process. When forming must occur prior to bonding, it is necessary to maintain surfaces to be bonded in a noncontaminated, nonoxidized condition. Secondly, when a maskant is used for selective diffusion bonding, it

is important to insure that the maskant does not interfere with diffusion bonding in the adjacent nonmasked areas. V L

A82-23755 Aluminum and its alloys - Weldability. I. B. Robinson (Kaiser Aluminum and Chemical Corp., Pleasanton, CA). In *Welding technology for the aerospace industry*, *Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980*. Miami, FL, American Welding Society, 1981, p. 85-108. 14 refs

Non-heat-treatable and heat-treatable aluminum alloys are examined with reference to their behavior during welding and their fusion weldability. It is shown that with existing aluminum alloys, the properties of fusion welded joints can be improved by minimizing the effective heat input and by using postweld heat treatments. High-intensity welding sources can provide greater penetration and narrower welds for higher strengths. However, poor fusion weldability of many high-strength alloys is due to their composition and microstructure, and great improvements in weldability and strength would require new alloys. The use of solid-state welding techniques in conjunction with heat treatment minimizes the problems of heat damage and offers possibilities of higher-strength welds in high-strength alloys. V L

A82-23757 Welding for low-cost advanced titanium airframe structures. R. W. Messler, Jr. and C. A. Paez (Grumman Aerospace Corp., Bethpage, NY). In *Welding technology for the aerospace industry*, *Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980*. Miami, FL, American Welding Society, 1981, p. 123-138

The fabrication of F-14 wing center section and other wing and fuselage parts, which relies heavily on electron beam welding, is described to demonstrate that welding is a valuable, versatile, and widely available technique for building low-cost advanced titanium structures for modern airframes. The advantages of welding include improved structural efficiency, improved material utilization, expanded near-net-shape processing capability, and structural optimization. To be most beneficial, the welding processes employed should provide high joint efficiencies for static and fatigue loading, high quality, low distortion and shrinkage, and high welding speeds or deposition rates to minimize welding labor intensity. V L

A82-23771 # Material/structure degradation due to fretting and fretting-initiated fatigue. D. W. Hoepfner (Toronto, University, Toronto, Canada). (*Canadian Aeronautics and Space Institute, Annual General Meeting, Montreal, Canada, May 11, 1981*) *Canadian Aeronautics and Space Journal*, vol. 27, 3rd Quarter, 1981, p. 213-221. 6 refs

The causes, effects, and possible remedies for fretting fatigue are examined. Fretting occurs on the surfaces of two objects in contact and in relative motion to one another, and results in either corrosion or wear, surface stress concentrations or surface and subsurface stresses, or component failure. Models of a fretting damage threshold are reviewed, noting that once the threshold has been crossed, no further fretting damage is of concern because fatigue cracks are proceeding from the fret-induced damage. Specific areas and components subject to fretting damage on aircraft airframes, transmissions, engines, and shafting are provided, and measures to reduce fretting have included vibration elimination, slip prevention, and sealing off the part from the atmosphere. Further techniques for individual cases are indicated. M S K

A82-23772 # A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum. W. Wallace (National Aeronautical Establishment, Structures and Materials Laboratory, Ottawa, Canada), M. C. de Malherbe (Carleton University, Ottawa, Canada), and J. C. Beddoes (*Canadian Aeronautics and Space Institute, Annual General Meeting, Montreal, Canada, May 11, 1981*) *Canadian Aeronautics and Space Journal*, vol. 27, 3rd Quarter, 1981, p. 222-232. 7 refs. Research supported by the Natural Sciences and Engineering Research Council of Canada

A study on the potentials of retrogression and reaging (RRA) aerospace aluminum alloys in the 7000 series to gain the T73 temper and T6 strength levels is reported. The investigation covered the determination of the form of the RRA reactions in 7075-T6 Al by using hardness, yield strength, and electrical conductivity measurements, a wider range of temperatures and times which would allow

thicker specimens to be treated, and confirmed the improved stress corrosion resistance. Fittings were heat treated in silicone oil baths, subjected to computer controlled servo-hydraulic tests, tested for stress corrosion crack growth rates, and treated with seawater solutions. No relation was found between stress corrosion and yield strength, and the RRA treatment produced crack growth rates similar to the T73 alloy with T6 strength. Additionally, the stress corrosion resistance of 7075 Al aged to or beyond the T6 condition was found proportional to the electrical conductivity of the material. M S K

A82-23774 # F/A-18 weapon system development M J Tkach (McDonnell Aircraft Co., St. Louis, MO) (*Canadian Aeronautics and Space Institute, Flight Test Symposium, Cold Lake, Alberta, Canada, Mar. 31-Apr. 1, 1981*) *Canadian Aeronautics and Space Journal*, vol. 27, 3rd Quarter, 1981, p. 242-252

The design and operation of the F/A-18 cockpit, controls, avionics displays, and weapons systems control are described. The cockpit is equipped with three head-down 5 in x 5 in CRTs, an up-front control for communication, navigation, and identification purposes, and an HUD. The pilot needs to move his head only 22 deg from the HUD to the up-front control, while the HUD displays navigation and weapon delivery information, both air-to-air and air-to-ground. A Hands On Throttle and Switching has switches on the stick and throttle for pilot control of the weapons, sensors, and displays during time-critical periods, in addition to control of the radar modes. All AIM-7 and -9 missile firings to date have resulted in hits, while the lack of traditional airspeed indicators, coupled with the quiet cockpit and new maneuvering flaps have caused problems in maintaining airspeed control, with rectification difficult due to the complexity of the electronics. M S K

A82-23826 * # Design of supercritical swept wings. P Garabedian and G McFadden (New York University, New York, NY) *AIAA Journal*, vol. 20, Mar 1982, p. 289-291. 11 refs. Grants No. NGR-33-015-201, No. NSG-1579

Computational fluid dynamics are used to discuss problems inherent to transonic three-dimensional flow past supercritical swept wings. The formulation for a boundary value problem for the flow past the wing is provided, including consideration of weak shock waves and the use of parabolic coordinates. A swept wing code is developed which requires a mesh of $152 \times 10 \times 12$ points and 200 time cycles. A formula for wave drag is calculated, based on the idea that the conservation form of the momentum equation becomes an entropy inequality measuring the drag, expressible in terms of a small-disturbance equation for a potential function in two dimensions. The entropy inequality has been incorporated in a two-dimensional code for the analysis of transonic flow over airfoils. A method of artificial viscosity is explored for optimum pressure distributions with design, and involves a free boundary problem considering speed over only a portion of the wing. M S K

A82-23828 # Oscillating supersonic/hypersonic wings at high incidence. W. H. Hui, M. F. Platzer (U.S. Naval Postgraduate School, Monterey, CA), and E. Youroukos *AIAA Journal*, vol. 20, Mar 1982, p. 299-304. 11 refs.

An approximate analytic method is developed for predicting the aerodynamic stability of oscillating supersonic/hypersonic flat wings at a mean angle of attack. It uses the known exact unsteady unified supersonic/hypersonic flow solution for a two-dimensional flat plate plus the strip theory approximation to obtain the formulas for the stability derivatives. They are applicable for wings of arbitrary planform shape at arbitrary angles of attack provided the shock wave is attached to the leading edge of the wing. Good agreement is obtained with existing theories in various special cases. The formulas for stability derivatives given here become exact in the Newtonian limit. (Author)

A82-24001 # Reliability centered maintenance /RCM/ F S Nowlan (United Air Lines, Inc., Chicago, IL) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb. 10-12, 1981, Paper 4 p*

Inherent reliability characteristics of transport aircraft are described, and principles of reliability-centered maintenance (RCM)

are discussed. Airworthiness regulations are noted to be directed at failure events that have not yet occurred, but which theoretical analyses indicate have an unacceptable probability of happening. Specific requirements are communicated to engineers, and compliance results in either no occurrence of failure, or sufficient redundancy of performance to offset failure. RCM procedures involve component inspection at specified intervals, part overhaul before the failure interval is approached, discarding parts before the failure life is passed, and finding failures in hidden-function items which crewmembers may not have noticed. On-condition tasks are given higher priority, followed by a rework task and then a discard task. The effects on safety of the aircraft is the measure of the task hierarchy. M S K

A82-24002 # A310 - Design for maintenance R Cutler (Airbus Industrie, Blagnac, Haute-Garonne, France) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb. 10-12, 1981, Paper 17 p*

The way in which Airbus Industrie deals with maintenance during the design phase is described, noting that by giving maintenance the attention it merits, its proportion of direct operating costs is kept to a minimum. Aircraft design is continuously subjected to a maintainability and reliability (M & R) review in order to ensure optimum trade-offs between M & R and other goals. This review process comprises five steps: (1) apportioning M & R goals to systems, components, etc., as required, (2) reviewing in-service experience to identify past problems and areas having the greatest potential for development, (3) evaluating design using M & R analytical techniques to identify questionable areas, (4) holding review meetings with designers and equipment suppliers to determine what improvements can be made, and (5) holding management progress review meetings to assess overall M & R performance in relation to goals, highlighting areas where goal attainment is unlikely, and specifying further actions. C R

A82-24003 # Development of maintenance programmes through the functional, structural and flight test phases R E Grigg (British Aerospace Public, Ltd., Co., Weybridge, Surrey, England) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb. 10-12, 1981, Paper 9 p*

Methods employed by British Aerospace to develop minimized maintenance plans for use by airline mechanics are described, with particular regard to the B Ae 146. The 146 was designed for simplicity with constraints imposed by maintenance cost targets and monitoring to meet contractual commitments. All systems were monitored at component levels, and the occurrence of full mock-up with real hardware initiated the development of maintenance schedules. A logic analysis procedure was used to determine cost effective maintenance programs by scheduling maintenance on parts which affect safety and operational economy, and defined the tasks to be performed. Failure modes were defined for each functional component and a probability level of acceptance before catastrophic failure was set. Further steps included flight development maintenance monitoring, task monitoring, the establishment of servicing locations, design of a structural inspection program, and the definition of structure life and inspection goals. M S K

A82-24004 # Air cooled engine test facilities G F Dawson (Industrial Acoustics Co., Ltd., Staines, Middx., England) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb. 10-12, 1981, Paper. 6 p*

The equipment and instrumentation of an operating comprehensive acoustic test facility for aircraft are described. Specifications include air cooling and the capability of handling a reheat engine with a back-on-the-bed time of 30 min after engine shut-off. The facility is totally demountable, yet includes an acoustic enclosure, an intake silencer, and augmentor tube, a primary diffuser, a secondary suppressor, a plenum chamber, exhaust splitter elements, an exhaust stack, and a weather-proofed and sound-insulated control room. Prerigged engines are mounted on the test bed over a trolley prewired and connected for all pneumatic and electronic parameters. Engine test time is reduced by 50% over conventional testing methods due to an instantaneous computerized display of test results, automatic input and logging of data, audible and visual alarm systems, diagnostic checking procedures, and manual reversion capabilities on the controls. M S K

A82-24005

A82-24005 # Maintenance objectives for future aircraft J G Borger *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 8 p*

Maintenance requirements for airline operations are discussed, noting the need for simpler designs which enhance maintenance procedures while still maintaining increasing fuel efficiency. Equipment redundancy is useful for safe operation with failed components, and modularizing aircraft parts has permitted on-line monitoring and replacement operations to maintain aircraft in flight-ready status with minimum delays due to repairs. The advent of advanced electronics has enhanced maintenance procedures in some cases, while in others the complexity of the monitoring system has led to greater down time. Higher performance engines degrade in performance after little more than a year's use, but refurbishment guided by high test stand acceptance standards, has improved engine removal rates. Finally, designing for reliability, ease of inspection and removal, and for in-flight potential problem indication are recommended. M S K

A82-24006 # Airworthiness regulation What is our strategy - What are the issues. M C Beard (FAA, Office of Airworthiness, Washington, DC) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 6 p*

The importance of international standards in the design, manufacture, and maintenance is stressed in view of the increase of the leasing, charter, and exchange of aircraft across national boundaries. Another trend noted in calling for international standards is the fact that the components of any given aircraft are, to an increasing extent, designed and manufactured in several different countries. C R

A82-24007 Reliable power J M S Keen (Rolls-Royce, Ltd, Derby, England) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper. 20 p*

Current Rolls-Royce engines are reviewed, with specific attention given to the implementation of a three-shaft concept for the modular development of engine thrust increases and fuel consumption decreases. The RB-211 three-shaft concept is reviewed, noting the development followed design goals of a short rigid engine with a minimum number of variables and cooled turbine stages. The E-4 engine employs a wide chord fan blade without snubbers and blends the turbine and bypass duct exhaust flows for passage through a single, final nozzle. Comprehensive access ports have been designed into the big fan engines, along with chip detectors in the oil system and vibration monitoring equipment for on-condition maintenance. Reliability management has resulted in the modular nature of the engines, featuring engine breakdown into separate, self-contained components, with comprehensive use records serving to notify when specific parts are due for inspection or replacement. M S K

A82-24008 # What the operator wants J Meline *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 6 p*

The design and manufacturing goals of aerospace industries for supplying airlines which have formed cooperative pools of maintenance and overhaul facilities and resources are examined. The manufacturers have gained feedback from the pooled labor forces who work on the increasingly standardized stocks of components in the common repair facilities, and are enabled to design-in improved features allowing easier and more thorough maintenance. Introduction of a new aircraft in any one fleet immediately introduces the vehicle to all maintenance personnel in the pool. The ATLAS group is noted to currently maintain a total fleet of 437 aircraft, and member agencies coordinate shared time to meet overhaul requirements. Differences in on-condition maintenance and overhaul grouping of work is described, and the benefits of pooling the most qualified personnel are emphasized. M S K

A82-24009 # The way ahead for helicopter maintenance W. E. Morris (Westland Helicopters, Ltd., Yeovil, Somerset, England) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb. 10-12, 1981, Paper. 9 p*

The progress made by a British helicopter company in improving maintainability and reliability (M & R) is surveyed. Among the practices that have been found to be significant are the following: (1) maintaining a comprehensive data bank on M & R that is linked with customer data banks, (2) mathematical modeling of the life cycle costs, (3) improving the ability to diagnose sources of vibration without detriment to the operational availability of the helicopter, and (4) introducing check out systems that record in-flight defects and malfunctions, thereby simplifying maintenance programming. C R

A82-24010 # The inter-relation between design, construction and maintenance J M Ramsden *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 5 p*

Methods of improving inspection and maintenance procedures, especially to compensate for an emphasized rise in poor workmanship during construction phases, are outlined. An improvement in detail design, to simplify and correctly place aircraft components, is recommended, as is better education of specialists in features of fasteners and electronics. On-line monitoring has become possible with self-checking, multiple probes for nearly all functional on-board equipment. The need to improve tires and brake systems to cope with increasing landing weights and speeds is noted, as is a necessity to integrate electronic systems and provide protection from disconnects due to the operating environment. Further suggestions are made for the elimination of corrosion, improvements in inspectability, and the need to measure in-service aerodynamics, and the demise of the U.S. Civil Aeronautics Board is mentioned as an erosion of the airline industry's data base. M S K

A82-24011 # MSG-3 structures S Schofield (British Airways, Hounslow, Middx., England) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 5 p*

The paper describes the philosophy and methodology used to develop the aircraft structures maintenance program contained and recently published in the ATA Airline/Manufacturer Maintenance Program Planning Document MSG-3. Particular consideration is given to the evolution of a separate logic analysis for structures, the consequence of failure evaluation, the separate assessment of the different forms of structural damage, the detectability of damage, the establishment of a continuing structural program for the life of the aircraft, fleet leader/age exploration inspections and the role of the manufacturer in the continuing structure program. B J

A82-24012 # Monitoring engine wear by oil analysis D F Sermin (Applied Research Laboratories of Florida, Inc., Hialeah, FL) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 5 p*

The application of spectroscopic techniques to the detection of metal particles in engine oils as an identifier and predictor of specific component wear and incipient failure is described. The current rotrode technique involves physically taking an oil sample for electrical discharge vaporization and subsequent spectrography. A succeeding step identifies the concentration computer calibrated graph. Inaccuracies in the method had led to the development of wear element contraction determination by the use of inductively coupled plasma excitation. The sample is introduced to the plasma within a quartz tube surrounded by a coil of wire which creates the magnetic field. The oil is nebulized and passed through a tube into the plasma, where the atoms dissociate and create individual optical spectra in the 7000-10,000 K heat. The method yields results within 1% of the signal value detected, or within 1 ppm. M S K

A82-24014 # MSG-3 overview R Valeika (Pan American World Airways, Inc., New York, NY) *International Aircraft Maintenance Engineering Exhibition and Conference, Zurich, Switzerland, Feb 10-12, 1981, Paper 4 p*

The paper surveys experience with programs developed in the framework of the ATA Airline/Manufacturer Maintenance Program Planning Document MSG-3. After a brief review of experience with MSG-1/2, attention is given to MSG-3 development, and to maintenance programs developed for systems, powerplants, and structures within the MSG-3 context. B J

A82-24022 * # Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance. W. H. Greene and J. Sobieszczyński-Sobieski (NASA, Langley Research Center, Hampton, VA) (AIAA, ASME, ASCE, and AHS, Structures, Structural Dynamics and Materials Conference, 21st, Seattle, WA, May 12-14, 1980, AIAA Paper 80-0724.) *Journal of Aircraft*, vol 19, Mar 1982, p 228-234 12 refs

A procedure for sizing an airframe for flutter-free performance is demonstrated on a large, flexible supersonic transport aircraft. The procedure is based on using a two-level reduced basis or modal technique for reducing the computational cost of performing the repetitive flutter analyses. The supersonic transport aircraft exhibits complex dynamic behavior, has a well-known flutter problem and requires a large finite-element model to predict the vibratory and flutter response. Flutter-free designs are produced with small mass increases relative to the wing structural weight and aircraft payload. In view of the ability of the resizing procedure to handle this supersonic transport configuration, it seems likely that the method could be used for many other aircraft (Author)

A82-24023 # Static pressure in the slipstream of a propeller. G. Schouten (Delft, Technische Hogeschool, Delft, Netherlands) *Journal of Aircraft*, vol 19, Mar 1982, p 251-253 9 refs

Prompted by the paradoxical implication of existing theory that static pressure in the slipstream of an active propeller would exceed the static pressure in the fluid outside the slipstream, a consistent theory is developed which yields a static pressure more plausibly tending to the freestream pressure. The theory adapts the flat trailing vortex sheet model to a propeller with a finite number of blades which moves at a finite velocity O C

A82-24025 Air transport in the 21st century. K. G. Wilkinson *Aerospace* (UK), vol 9, Jan 1982, p 18-23 8 refs

Trends in aircraft design into the 21st century are discussed, based on the driving need for higher fuel efficiency and alternative fuels. Noting that fuel presently accounts for 30% of air transportation, results of an international study on the world energy supply and growth are used to present several scenarios of future aerospace operations. Global energy is projected to be provided from renewables and nuclear, coal and gas, and oil, each group producing 1/3 of the world energy demands, with aerospace consuming 3% of the total oil consumed. Advances in aerodynamics from NASA studies, in lightweight synthetic materials, in active controls, and in propulsion systems are outlined, with mention made of the CO₂ contribution to a global rise in temperature. The development of nuclear technology and the availability of nuclear fuels is contrasted against the environmental costs of using hydrocarbon fuels, and the necessity of developing a hydrogen-based fuel economy is emphasized. M. S. K.

A82-24065 Navigational aids on-board the Concorde (Les moyens de navigation du Concorde). F. Vicens (Compagnie Nationale Air France, Paris, France) *Navigation (Paris)*, vol 30, Jan 1982, p 25-39. In French

The differences of navigational instrumentation on the Concorde from subsonic aircraft due to transonic and supersonic flight regimes are described. Speed classes at different heights are defined for optimal flight operations, with each minute of error from the most direct route causing an extra 100 kg of fuel to be consumed. The Concorde is equipped with an inertial navigation system (INS), automatic direction finder, distance measuring equipment, VOR, and a ground warning system. The INS gathers altitude information, guidance and navigation data, and coupled compass stabilization information with reference to the magnetic pole. The Air Data Computer gathers aerodynamic and meteorological information, including altitude and vertical airspeed, from sensors mounted on the nose, and further guidance is aided by radio compass readings (Automatic Directional Finder) and two systems of radio altimetry. M. S. K.

A82-24066 The birth of precision DME (La naissance du DME de précision). O. Carel (Direction Générale à l'Aviation Civile, Paris, France) *Navigation (Paris)*, vol 30, Jan 1982, p 53-65 6 refs. In French

The requirements, design, and deployment of precision distance measuring equipment (DME) for implementation at French civil

airports is described. The system is intended to equal the performance levels of military landing systems, and furnish coordinates at 20 nm distance with a landing aperture of plus or minus 80 deg. The DME permits curved approaches, thereby ameliorating flights over some urban areas, and offers the possibility of totally replacing radioaltimetry as an approach guide. Polar coordinates are transmitted with an accuracy of 250 m, which is matched by the transverse accuracy, while altimeter readings are made with a 30 m error. Methods of obtaining the precision measurements are presented, along with analyses of exponential damping, fabrication of the system, the presence of second or third impulses, and methods of interlocking the impulses, along with a demonstration of a 200 channel dual mode system. M. S. K.

A82-24077 # Recent developments in wing with stores flutter suppression. R. Destuynder (ONERA, Châtillon-sous-Bagneux, Hauts-de-Seine, France) (Deutsche Gesellschaft für Luft- und Raumfahrt and Deutsche Forschungs- und Versuchsanstalt für Luft- und Raumfahrt, International Symposium on Aeroelasticity, Nuremberg, West Germany, Oct. 5-7, 1981) ONERA, TP no 1981-145, 1981 11 p

Active flutter suppression calculations and wind tunnel tests were performed for the case of a half-scale model of the Mirage F-1 fighter wing, equipped with three underwing stores whose distribution has been modified to make flutter occur in the wind tunnel's Mach 0.80-0.94 transonic regime. Flutter control was achieved with a numerical control law designed to induce wing aerodynamic stiffness by means of a control surface. Further studies were conducted on nonlinearities due to the static aerodynamic characteristics of the control surface at high subsonic Mach numbers, and the influence of phase and gain variations on the control law. The results derived demonstrate the possibility of flutter control on military aircraft operating at high Mach numbers. O. C.

A82-24245 Recent improvements in aircraft Ni-Cd cells. R. Bonnaterre, J. Leonardi, and P. Oliva (Société des Accumulateurs Fixes et de Traction, Bordeaux, France) In Power sources 8. Research and development in non-mechanical electrical power sources, Proceedings of the Twelfth International Symposium, Brighton, England, September 1980. London, Academic Press, 1981, p 459-468, Discussion, p 469.

It is noted that the reliability, power performance, and durability of the alkaline Ni-Cd batteries used in such advanced technical fields as aeronautics and high-speed trains are becoming increasingly important. A new aircraft battery generation created to respond to such requirements is described. Increased reliability and durability result from the development and use of a new graft copolymer membrane, the properties of which are discussed. The use of the new membrane and the optimization of the electromechanical parameters of the cell design have significantly improved the power characteristics of Ni-Cd aircraft batteries. In particular, eliminating the 'potential well' phenomenon in low-temperature, high-rate discharges has led to substantial power gains for low-temperature aircraft starts. C. R.

A82-24301 Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. Conference sponsored by the Society of British Aerospace Companies. London, Society of British Aerospace Companies, Ltd., 1981 713 p \$59.50

Among the aircraft transparency design, testing and analysis topics covered are: (1) transparency development needs for military aircraft in the 1980s, (2) an aircraft transparency design guide, (3) deficiencies and constraints affecting the design of cockpit transparencies and enclosures, (4) bird strikes, (5) windshield system structural enhancement, (6) aircraft transparency bird impact analysis using the MAGNA computer program, (7) stretched acrylic transparency materials, (8) transport aircraft transparencies, and (9) impact resistance test methods. Also considered are: (10) abrasion-resistant coatings for aircraft, (11) the role of finite element analysis in the design of birdstrike-resistant transparencies, and (12) the effects of bird orientation on load profile and damage level. O. C.

A82-24302 Transparency development needs for military aircraft in the 1980's. N. C. Moore. In Conference on Aerospace

A82-24303

Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 3-13

Attention is given to the improvement and optimization of overall transparency configurations in military aircraft. A number of areas for development effort are identified. These include (1) the achievement of undistorted views from helicopter transparencies, (2) the need for distortionless, near-360-deg vision from fixed wing strike aircraft windcreens and canopies, (3) the reduction of transparency-induced cockpit noise, (4) the lowering of glint phenomena through transparency surface reflectivity reduction, (5) the design of alternative windscreen washers and wipers, (6) the reduction of strike aircraft combat losses due to pilot injury, by means of transparent armor, (7) emergency repair schemes under battle conditions, and (8) nuclear effects due to overpressure, flash and thermal effects, and radiation levels. O C

A82-24303 Deficiencies and constraints that affect the design of cockpit enclosures and transparencies. J H Lawrence, Jr (Douglas Aircraft Co., Long Beach, CA). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 15-24

Maximum-visibility cockpit enclosure and transparency design problems are considered in light of experience with the development of the DC-10, in which these design considerations were addressed by means of a systems approach. The strongest constraint is shown to be the aerodynamic shaping of the aircraft, which, because of the slopes and shapes required, may be unacceptable to the pilot on the grounds of distortion and can increase the difficulty of designing such subsystems as the electrical, anti-icing, and rain removal. Attention is also given to the inadequacies of glass-acrylic laminates under cyclic loading, thermal cycling and contact with moisture, the seals and mounting of the transparencies in their support structures, and up/down-left/right charts for both minimum recommended vision and the captain's binocular vision envelope. O C

A82-24304 Fuel-efficient windshields for transport, commuter and business aircraft. G L Wiser (Sierracin Corp., Sylmar, CA). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 25-95. 34 refs

The effects of weight and drag reduction measures involving windshields and their associated structures and systems on fuel efficiency are explored. It is shown that the incorporation of these techniques can save up to 80,000 gallons of fuel/year per aircraft in wide-body commercial aircraft applications, and 12,000 gallons/year per aircraft in the case of commuter designs. The alternatives considered include (1) flat glass windshields, (2) curved glass windshields, (3) curved high-strength glass windshields, (4) structurally-integrated curved windshields, (5) curved stretched acrylic windshields, (6) curved, chemically-strengthened glass windshields, and such associated systems as temperature controllers and rain removal. O C

A82-24305 Transparencies - What an aircraft designer should know. P J Sharp (Lucas Aerospace, Ltd, Luton, Beds, England). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 97-111

The effect of windscreen lay-back angle on aircraft weight, energy requirements and optical characteristics are quantified for a typical, small jet aircraft, and the problems associated with the electrical deicing of irregular areas are examined. Weight effects are due to the load-transfer requirements of pressurized cabin transparencies. Additional factors considered are bird strikes, windscreen visual distortion, heating element positioning, and certification criteria. O C

A82-24306 Transparency design decisions - Assessing their impact on visual performance. R G Eggleston and L V Genco (USAF, Aerospace Medical Research Laboratories, Wright-Patterson AFB, OH). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings.

London, Society of British Aerospace Companies, Ltd, 1981, p 113-128

The efficiency of aircraft transparency designs is considered as an information system in which the scene, transparency and pilot are separate elements. A transparency may alter the scene visible to a pilot in four ways: refraction, reflection, absorption and transmission. These are the bases for such common transparency optical degradation problems as (1) distortion, (2) multiple imaging, (3) rainbowing, (4) volume and surface haze, (5) internal reflections, and (6) transmission loss. The contribution to each of these defects by transparency slant, flatness, single or compound curvature, material, thickness, absorption characteristics, scratch resistance, UV resistance, and monolithic or laminated construction, are correlated in tabular form along with observer and scene factors that may contribute to the quality or degradation of performance. O C

A82-24307 Aircraft transparency design guide. L Moosman (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) and J H Lawrence, Jr (Douglas Aircraft Co., Long Beach, CA). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 129-139

The 'Guidelines for the Design of Aircraft Windshield/Canopy Systems' is a design manual which serves as a single source for all requirements, data and systems recommendations relevant to the development of aircraft transparencies. The guide covers (1) management of transparencies and related subsystems design, (2) the transparency/aircraft configuration relationship, (3) vision and optical design, (4) structural design and analysis, (5) bird impacts, (6) materials, (7) environmental design, (8) combat exposure design, (9) maintainability, (10) reliability, and (11) transparency design verification and quality assurance requirements. The data from which this compilation of requirements was derived include FAR 25, SAE AS580, and the Air Force Systems Command Design Handbook. O C

A82-24308 A new angular deviation measurement device for aircraft transparencies. H L Task, R G Eggleston, and L V Genco (USAF, Human Engineering Div, Wright-Patterson AFB, OH). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 141-147

An optoelectronic angular deviation measurement device incorporating a CCD array, which offers accuracy, repeatability and ease of operation while occupying a much smaller volume than long-throw laser devices of comparable performance, is described. The instrument's resolution is 0.07 mrad, and F-16 windscreen measurements have been found to compare favorably with data produced by alternative techniques. The device is to be used in characterizing distortion levels in such transparency-incorporating systems as head-up displays. O C

A82-24309 Portable transparency optical test system (P-TOTS). L V Genco, R G Eggleston, and H L Task (USAF, Aerospace Medical Research Laboratories, Wright-Patterson AFB, OH). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 149-160

The Portable Transparency Optical Test System (P-TOTS) described is a novel device for the collection of visual and optical data from installed transparencies, including the evaluation of time-dependent changes in optical quality. Although P-TOTS has to date been employed in the birefringence, distortion, binocular distortion, multiple image and haze characterization of F-111 windcreens, the device may be adapted to other aircraft through a mounting-fixture change estimated to cost \$4000. O C

A82-24310 Abrasion resistant coated plastic products for aircraft. W F Fischer and W C Harbison (Swedlow, Inc, Garden Grove, CA). In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings. London, Society of British Aerospace Companies, Ltd, 1981, p 185-204. 10 refs

Experimental results concerning the use of the application of abrasion-resistant coatings to polycarbonate and acrylic transparencies in architectural and ground-transportation installations are correlated to the use of such coatings on aircraft transparencies. A failure theory is substantiated through a combination of the experimental data with separate results of accelerated testing. A silica-filled polysiloxane coating is shown to offer the greatest resistance to abrasion. The failure mode of the coatings is generally mechanical degradation, consisting of cracking or microcracking from repeated tensile elongation/compression associated with thermal, moisture gain/loss and flexural cycling. O C

A82-24311 Proposed method for abrasion testing transparent plastics and coatings. A J Bunje (Texstar Corp., Texstar Plastics, Grand Prairie, TX) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 205-213

An examination is presented of methods for the abrasion testing of transparent plastics and coatings, with attention to the preparation and interpretation of the Taber Abraser and Falling Sand tests. A test methodology is described which allows the testing of all materials and coatings irrespective of hardness, and in which the entire sample surface is exposed to the abrading action. The larger area thereby measured yields more representative results, which are shown to be highly reproducible. Test results data are presented in tabular form. O C

A82-24312 Windshield system structural enhancement. R J Speelman, R H Walker, and R L Peterson (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, OH) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 217-243. 22 refs

Transparency technology investigations with emphases on improved birdstrike resistance and longer service life are being conducted by the Air Force Flight Dynamics Laboratory. In addition to supporting such existing systems as the T-38, F-16 and F-111, a technical base is emerging for the development of new transparencies which includes: (1) computer-aided design procedures for birdstrike structural analysis; (2) birdstrike hazard risk prediction techniques; (3) design procedures for the integration of birdstrike protection and large field-of-view capabilities with high-temperature operation; (4) design procedures for consideration of ballistic fragment impact resistance; (5) testing procedures for improved correlation between laboratory and field performance; and (6) a transparency system design-guideline manual. O C

A82-24313 # An analytical methodology to predict potential aircraft losses due to canopy birdstrikes. J C Halpin, J M Griffin, and K T Jackson, Jr. (USAF, Aeronautical Systems Div., Wright-Patterson AFB, OH) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 245-271

An analysis for the projection of birdstrike damage is presented in which data for the F-4 aircraft is used as a basis for the development of a model and the F-16 is used for verification. After determining the operational impact rate (OIR), a kinetic energy matrix is calculated and a line representing the expected canopy capability is drawn through this matrix. The canopy capability line from the kinetic energy matrix is then superposed on the birdstrike matrix, and the birdstrike number is derived by summing the appropriate values from the matrix. If the failure mode is deflection rather than penetration, critical areas corresponding to certain kinetic energy levels must be determined and then used to recalculate the expected birdstrike matrix. O C

A82-24314 The role of finite element analysis in the design of birdstrike resistant transparencies. B S West (Dayton, University, Dayton, OH) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 273-295. 8 refs. Contracts No. F33615-75-C-3134, No. F33615-76-C-3103, No. F33615-80-C-3401

The Materially and Geometrically Nonlinear dynamics Analysis problems (MAGNA) finite element code, for the efficient analysis of crew enclosure structures during bird impact, is described. The design variables typically incorporated into parametric design data in the code are: (1) transparency stiffness, which depends on material, configuration and thickness; (2) support structure stiffness; (3) load location; (4) load magnitude; and (5) edge member configuration. Transparency edge member integrity has proved to be critical to the birdstrike resistance of aircraft transparency/support systems. Computer run time increases by more than an order of magnitude if the parametric study is conducted using all available nonlinear options rather than linear elastic analysis. Several sample analyses are presented to demonstrate the linear and nonlinear solution capabilities of the MAGNA program. O C

A82-24315 Aircraft transparency bird impact analysis using the MAGNA computer program. R E McCarty (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, OH) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 297-313. 14 refs

The MAGNA computer program is shown to realistically simulate the nonlinear dynamic structural response of aircraft transparencies to birdstrike loading. It is not yet possible, however, to accurately predetermine the loads resulting from bird impact on very flexible transparencies, due to the fact that the magnitude of the loads and the surface area and time period over which they act strongly depend on the dynamic response of the transparency. MAGNA is especially applicable to relatively stiff transparencies, in which the effects of load-response coupling may be ignored, and may prove useful in the analysis of any problem involving the response of a structure subject to static or transient loads. O C

A82-24316 The effects of bird orientation on load profile and damage level. A Chailita and B S West (Dayton, University, Dayton, OH) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 315-338. 7 refs. Contract No. F33615-78-C-3402

A number of programs have been initiated with the aim to increase the birdstrike resistance of aircraft and their components. A description is presented of specific programs with two basic objectives. One objective is related to a characterization of the loads generated during birdstrike to use as input to the modern finite element structural analysis codes which are currently used as a transparency design tool. The second objective involves the evaluation of the testing procedures employed to evaluate the level of birdstrike protection afforded by a given flight hardware system. Of three orientations tested, end-on orientation was found to be as critical, or more critical, than the other orientations. Side-on orientation was the least critical orientation. During end-on birdstrike testing, pitch and yaw would tend to decrease critically. G R

A82-24317 Acrylic - A timely review. K G Granger (Swedlow, Inc., Garden Grove, CA) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p. 341-354, 356, 357

The review is concerned with the use of acrylics in applications related to aircraft transparencies, taking into account the principal aircraft grades of acrylic. Main qualities of acrylics with respect to the considered applications include its ability to maintain excellent strength, transparency, and clarity in environments which comparatively quickly cause deterioration in other transparent plastics. For aircraft glazings applications, only glass is superior to acrylic in terms of weatherability, solvent resistance, and surface hardness. However, glass is inferior to plastics in connection with greater weight, failure mode, and relative difficulties with respect to the formation of aerodynamic shapes. A number of case histories are discussed which demonstrate the advantages of a use of acrylic. Attention is also given to the proposed laminated F-16 canopy design and the development of modified acrylics. G R

A82-24318 Lucas stretched acrylic. D B Bell (Lucas Aerospace, Ltd., Luton, Beds., England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980,

A82-24319

Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 359-368

Selection criteria for the pressing processes in manufacturing stretched acrylic from as-cast billets at the Lucas facility are discussed. Advantages of a press over gripping around the edges include more parallel surfaces, better yield from the material, and the avoidance of sheet splitting which sometimes occurs when the material is stretched. Specifications for stretched acrylic are discussed, and the facility is described, including a discussion of the stretching press and the grinding/polishing machines. The planned expansion of the facility is also discussed, which includes the introduction of a pre-heater and additional polishing machines.

D L G

A82-24319 Problems associated with the quality assurance of stretched acrylic sheet. R L Worsdall (Ministry of Defence/Procurement Executive/, Material Quality Assurance Directorate, London, England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd., 1981, p 371-397

A description is presented of special problems arising in connection with an application of a manufacturer for Type Approval of a material intended for defense-related uses, taking into account the approaches employed to solve these problems. The material involved was stretched acrylic sheet. There were differences between test results obtained in the laboratories of the manufacturer and the Materials Quality Assurance Directorate. The differences were, in particular, observed in thermal relaxation studies, and increased as the thickness of the sheets examined became progressively larger. In an investigation of the reasons for these differences, it was found that in the conduction of thermal relaxation studies the temperature control is important and the moisture content is critical. An important factor is also the position from which the sample is taken in the sheet.

G R

A82-24320 The effects of absorbed moisture upon the physical properties of stretched acrylic materials. A J Mason (British Aerospace Public, Ltd, Co, Materials Laboratory, Weybridge, Surrey, England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 399-416. Research supported by the Ministry of Defence (Procurement Executive).

It is noted that stretched acrylic materials are often preferred to 'as-cast' acrylics for the manufacture of aircraft transparencies owing to their superior craze and crack propagation resistance. However, the service performance of stretched acrylics can be affected by their operational environment. The effects of absorbed moisture upon various physical properties of stretched acrylic materials, including thermal relaxation, surface shrinkback, solvent craze resistance, crack propagation resistance, and surface hardness, are described. It is pointed out that the base stock material and method of stretching may also influence physical properties. These have been assessed by including in the evaluation three materials that have been manufactured from two base stock materials and produced by two manufacturing techniques.

C R

A82-24323 The development of high strength light-weight windshields for the new generation of Boeing 757 and 767 airliners. R W Wright (Triplex Safety Glass Co, Ltd, Aircraft and Special Products Div, Birmingham, England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 533-548

Windshields based on multilaminate construction and electroconductive coatings were introduced in the 1970s on such aircraft as the Concorde, A300B, de Havilland Canada Dash 7, and Boeing 747. In all, more than 20,000 hours of flight have been recorded. The way in which this technology is being adapted to meet the needs of the new Boeing 757 and 767 aircraft, where weight saving and reliability are fundamental requirements, is discussed. A description is also given of design, development and qualification test features.

C R

A82-24324 D C 9 windshield - Effect of attachment retorque. J Christensen (Scandinavian Airlines System, Copenhagen,

Denmark) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 549-562

Reference is made to a paper by Christensen (1978) propounding a theory related to the influence of attachment method on failures for DC 8-60 and DC 9 windshields. The experience of regular retorquing of attachment fasteners on Scandinavian Airlines System aircraft is reported. It is noted that this has had a marked effect on reducing windshield failures. Further expected improvements are discussed.

C R

A82-24325 B A C One-Eleven flight deck glazing product improvement. J F Russell (British Aerospace Public, Ltd, Co, Weybridge, Surrey, England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 563-576

The modifications described include recessed bus-bars, fiberglass chip retarders, and the introduction of additional interlayer plies of a new material, all for the windshield. Another modification involved moving the de-mist film on the side windows from one glass ply to another. It is noted that, altogether, these modifications have led to a doubling of the windshield MTBF in eight years and to a great improvement in the side windows.

C R

A82-24326 Concorde glazings - 5 years of Mach 2 service. W P C Soper and R A Brown (British Aerospace Public, Ltd, Co, Bristol, England) In Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings London, Society of British Aerospace Companies, Ltd, 1981, p 577-601

A description is provided of the level of achievement obtained with respect to the transparencies of the Concorde project. Aircraft operating conditions are considered. It is pointed out that the transparency configuration was conceived such that the aircraft would key into the normal operating pattern of conventional jet transport traffic and that no preferential treatment would be needed. The visor panels of the aircraft are discussed, taking into account the current visor panel construction, aspects of cyclic testing, flight testing, alternative panel designs, and in-service performance. Attention is also given to the forward main windscreen, the D V and aft side windows, and the Series aircraft cabin window.

G R

A82-24338 # Air transportation of handicapped persons (Le transport aérien des handicapés). E Mapelli (Iberia Lineas Aéreas de España, Madrid, Spain) In Annals of air and space law Volume 5, Toronto, Carswell Co, Ltd, Paris, Editions A. Pedone, 1980, p 171-188. 16 refs. In French.

Various legal aspects of the air transportation of handicapped persons are reviewed. Consideration is given to the rights and obligations of passengers as they pertain to the handicapped, the physical ability of passengers to travel on aircraft and the right of carriers to exclude the handicapped, obligations of the carrier in relation to the handicapped passenger, and carrier liability in relation to the injury of a handicapped passenger.

B J

A82-24354 The coupling of electromagnetic interference into aircraft systems. R V Pankhurst (Aeroplane and Armament Experimental Establishment, Boscombe Down, Wilts, England) In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p 117-128

Results of tests performed to determine the electromagnetic transfer function for complete aircraft from 100 kHz to 250 MHz are presented. The current distribution within the wiring bundle is shown along with the effect of end terminations, and attention is given to the variability between aircraft of the same type and aircraft of different types. Also considered are the developing overall picture of these induced currents and the implications of these results for future clearance work as well as for the usefulness of this information to aircraft systems and equipment designers.

B J

A82-24355 The variation of induced currents in aircraft wiring. P M Newton (Ministry of Defence/Procurement Executive/,

London, England). In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p. 129-134.

The paper examines the use of the bulk current method to measure the variation of induced currents in aircraft wiring due to the operation of onboard transmitters and the variation of the RF environment. The measurement method is described and typical results of aircraft samples to date are discussed. Results to date have shown that current varies by a factor of three and the RF environment on the average by a factor of two. B J

A82-24357 MIL-STD 1553B Aircraft EM environmental susceptibility effects. G Gerbi and E R Totto (Aeritalia S.p.A., Turin, Italy). In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p. 147-155

The subject of this paper is the technology applied to aircraft to minimize EMI in the installation of MIL-STD-1553B digital transmission links. The electromagnetic interference generators normally installed on aircraft are considered, and the susceptibility of a typical MIL-STD-1553B data link is investigated. Experimental tests and computer aided analysis using the SEMCAP program, which have been performed for simple geometrical coupling models, are described. The results of this work give practical indications about the influence of mechanical and electrical harness parameters on EMC aspects of the aircraft installation of MIL-STD-1553B digital transmission lines. A good architecture for digital data link installations is also discussed. (Author)

A82 24358 Materials aspects of aircraft EMC design. M W Baskerville and J Brettell (Plessey Research/Caswell, Ltd, Allen Clark Research Centre, Towcester, Northants, England). In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p. 157-170. Research supported by the Ministry of Defence (Procurement Executive).

The effect of materials, construction methods, and corrosion protection schemes on the dc and RF impedance of structural and electrical joints in aircraft is considered. The development of the theory and practice of making resistance measurements in large structures is examined in the light of a survey of bond resistance measurements in service aircraft. It is shown that the resistance of structural and electrical bonds in aircraft is critically dependent on a number of variables, including the type of fastener used, materials, and conditions of the relevant surfaces. It is possible to choose a set of variables which give a low bond resistance which is constant with time even when exposed to corrosion conditions. B J

A82-24359 EMC clearance of modern military aircraft. I P Macdiarmid and D M Wormstone (British Aerospace Public, Ltd, Co., Military Aircraft Div, Warton, Lancs, England). In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p. 171-182. Research supported by the British Aerospace Public, Ltd, Co.

An approach to EMC testing which was recently adopted on a production version of a modern strike aircraft is described. The procedure involved a quantitative assessment of the switching transients occurring on bus bars and selected signal lines, an interaction test whereby each potentially susceptible system must be observed while other systems are operated in their most emissive modes, a study of the safety margin of the compatibility of aircraft systems with intentional onboard transmitters, an investigation of the compatibility of the aircraft systems with the external RF environment, a quantitative assessment of the extent of data corruption at transducer-computer interfaces due to onboard emissive sources, and an in-depth compatibility study of all onboard RF equipment. The methods used and the results obtained were considered adequate to provide an assessment of the EMC of the onboard systems, however, it is noted that the demonstration of compatibility could be improved in certain areas. B J

A82-24361 The testing of aircraft under near field conditions. M Elliott (Aeroplane and Armament Experimental Establishment, Boscombe Down, Wilts, England). In Conference on Electromagnetic Compatibility, Southampton, England, September 16-18, 1980, Proceedings London, Institution of Electronic and Radio Engineers, 1980, p. 199-206

Although the HF band is of considerable interest in external field EMC testing, the environment in a typical trials facility is highly complex in this frequency range. This is due to operation in the near field region of the transmitting antenna, the proximity of the ground, and the presence of the fields scattered by the object under test. This problem was investigated by comparing the surface currents induced by three near field sources and one far field source on a cylinder which modeled the aircraft. The effects of the orientation of the cylinder on the measured magnetic and electric components of the field are examined, and optimum positions and methods of field measurements are discussed. B J

A82-24371 Managing computer aided design, Proceedings of the Conference, London, England, November 19, 1980. Conference sponsored by Institution of Mechanical Engineers. London, Mechanical Engineering Publications, Ltd (I Mech E Conference Publications 1980-8), 1980. 51 p. \$30

Papers are presented on the problems encountered by the incorporation of computer-aided design and computer-aided manufacturing (CAD/CAM) systems into the process industries, such as aircraft manufacture and chemical production, in Britain. Attention is given to the use of CAD graphics by a mechanical engineering firm, the successful management of CAD, the use of CAD/CAM electronic data transfer to integrate geographically distributed aircraft production, experience with computer-aided building design system in an architectural firm, the acceptance of interactive graphics by industry, and the relation between the financial productivity impact of CAD/CAM and labor relations. O C

A82-24373 CAD/CAM in British Aerospace - Aircraft Group. J S Rawlins (British Aerospace Public, Ltd, Co., Aircraft Group, Kingston-on-Thames, Surrey, England). In Managing computer aided design, Proceedings of the Conference, London, England, November 19, 1980. London, Mechanical Engineering Publications, Ltd, 1980, p. 27-34

The use of computer-aided design and computer-aided manufacturing (CAD/CAM) techniques in aspects of aircraft structure geometry and electrical system definition is described for the case of the BAe 146 commuter aircraft. The use of electronic design and production data transfer is especially important in aircraft industry projects of the kind described because of the geographical distribution of component fabrication and assembly facilities. Emphasis is put on the ability of a CAD/CAM system to make information promptly available, from the conceptual design to the in-service product support stages, without need for manual transcription before distribution. O C

A82-24376 Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981. Congress sponsored by the Society of Automotive Engineers Warrendale, PA, Society of Automotive Engineers, Inc., 1981. 90 p. \$18 (SAE SP-500)

The design, testing, maintenance, requirements, and future needs for aircraft power supplies were covered. Specific attention was given to design considerations of DC-Link aircraft generator systems and to cost of ownership advantages such as weight reduction and maintainability with a shared-oil system. Considerations for the design of variable speed, constant frequency (VSCF) generators are presented, and advanced generating systems technology was discussed. The effect of critical design parameters on the selection of a VSCF system was examined, along with the evolution and development of high voltage (270 V), dc aircraft electric systems and packaging the VSCF system for a military aircraft environment. Finally, the development of an aircraft electric system test facility was detailed. M S K

A82-24377 Design considerations of DC-Link aircraft generation systems. M A Rosswurm (Westinghouse Electric Corp.,

A82-24378

Aerospace Electrical Div , Lima, OH) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 1-15

Design considerations in the development of the DC-Link VSCF electrical power systems for aircraft are presented, along with component descriptions, functional details, applications to the AV8-B and F-5G, and comparisons to alternate methods of power generation. The DC-Link system is compared with constant speed drive and cycloconverter energy systems, and the major components of the DC-Link system are shown to be a generator module, power electronics module, and the generator control module, which as a system yield a constant frequency output and employ transistorized switching. Specific descriptions are provided of the power transistors, the inverter power pole, the commutating diodes, and the base drive circuit. Operational characteristics such as the inverter waveform, neutral forming transformer and power stage sensing are considered, and functions of the generator control unit and inverter drive logic module are outlined. M S K

A82-24378 Cost of ownership advantages with a shared oil system. R C VanNocker and W A Carmine (General Electric Co , Binghamton, NY) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 17-21

The benefits and system features of coupling the aircraft gearbox oil to the generator cooling system are outlined. It is noted that in a constant speed drive system, weight, maintainability, and life cycle costs are aided by avoiding redundant oil pumping facilities. The shared system is favored when generator functions won't contaminate the oil, pose no risk to the gearbox, and do not command the use of excessive amounts of oil. A dry cavity concept is described, which features heat exchangers completely isolated from any generator electrical components, and the use of the shared system on the F/A-18 is mentioned. The addition of the shared-oil module alters the maintenance concept from on-condition to a scheduled maintenance procedure, and an ultimate repair and maintenance cost figure of \$2.70 per flight hr is derived. M S K

A82-24379 High speed VSCF generator design consideration. T L Ho (Westinghouse Electric Corp , Aerospace Electrical Div , Lima, OH) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 23-33

The employment of computer aided design (CAD) for VSCF generator design is examined, specifically with regard to thermal, stress, and dynamic analyses. Thermal analysis is accomplished through an iteration of a series of design modifications, and examples are presented for the design of inverter semiconductor stacks, a diode rectifier assembly, and a power pole assembly. Finite element programs are implemented in a structural analysis, focusing attention on weight reduction and stress concentration at specified speeds, and procedures are outlined for applications to an inverter cover plate and to a high speed rotor. Dynamic study comprises model analysis by a finite element method and a critical speed analysis of the rotating system by means of turbomachine dynamics programs, serving to define the structural stability of the system. M S K

A82-24380 Advanced generating system technology. R J Kennett (Lucas Aerospace, Ltd , Electrical Div , Hemel Hempstead, Herts , England) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 35-41. Research supported by the Ministry of Defence (Procurement Executive) and Department of Industry.

A design approach to the achievement of a maximum specific output of an aircraft 400 Hz ac 2-pole generator with operation at 24,000 rpm is presented. Locating the field assembly inside a nonmagnetic shaft eliminated mechanical conflicts and allowed an inherently stiff rotor, permitted flooding the rectifiers with cooling oil to reduce temperature gradients, and porting to the stator to minimize drag losses and avoid insulation erosion. The rectifiers were moved toward the shaft axis, and interconnection with the main

exciter was arranged to neutralize centrifugal forces on the rectifier connection. The rotor shaft is used to provide maximum support for the stressed elements along the length of the alternator, which has a single coil. Weight reduction is also provided over four-pole machines, and bearing life is protected by a low rotating mass and elimination of mechanical unbalance. Operation and maintenance are reviewed. M S K

A82-24381 The effect of critical design parameters on the selection of a VSCF system. D S Yorksie and W E Hyvarinen (Westinghouse Electric Corp , Aerospace Electrical Div , Lima, OH) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 43-50

A decision model of the critical design criteria for applications of either cycloconverter or DC-Link variable speed, constant frequency (VSCF) electric power generators onboard aircraft are examined. Power switching and controlling techniques and components are described for each type of generator, noting the advent of advanced high-power switching transistors. Critical parameters of choice include the system rating, cooling method and temperature, efficiency, weight, location, and gearbox speed and range. Each parameter is explored for effect in different applications, and it is concluded that rating, cooling temperature, efficiency, and weight are the most critical parameters. A fifth element is added to the four most critical criteria, and comprises system-specific features which customize the decision model to the application under consideration. M S K

A82-24382 Evolution and development of high voltage /270 volt/ dc aircraft electric systems in the United States. J D Segrest (U S Naval Material Command, Naval Air Development Center, Warminster, PA) and W W Cloud (Lockheed-California Co , Burbank, CA) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 51-63. 10 refs.

The system concept of high voltage dc power systems for aircraft applications is reviewed, with regard to the state-of-the-art in the hardware available. The history of dc system use is outlined, noting the continually increasing demand of higher voltage levels. Mention is also made of the inherent unsatisfactory lifetime levels of current constant speed 400 Hz power devices with respect to future aircraft. Cycloconverter and DC-Link power generating systems are subject to complex designs and display a poor power factor, wave form distortion, and EM incompatibility. Brushless dc motors are available for engine mounting, and provide 270 V dc, which offers high reliability, high efficiency, light weight, power continuity, fuel economy, and personnel safety. Existing systems and advanced systems are outlined, with operational performance and requirements, including the need to develop solid-state load controllers for over 50 amps power load. M S K

A82-24383 Packaging the VSCF system for an aircraft engine environment. D D Pollard and G E Krajci (Westinghouse Electric Corp , Aerospace Electrical Div , Lima, OH) In Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 Warrendale, PA, Society of Automotive Engineers, Inc , 1981, p 65-76

The integration of microprocessor modules, high power semiconductor arrays, and a high-speed generator to form a compact, low-weight variable speed constant frequency (VSCF) power system is described. With specific consideration of military systems, envelope concerns are defined as the allowable space and shape, power and logic electrical interfaces, coolant/lubricant lines and interfaces, and maintainability. Military aircraft are noted to require dense packaging, have common disconnect mechanisms, and allow removal of the entire system at once. Sensitive components are sealed off from the environment and vibrations, and thermal control is provided by air-oil and fuel-oil heat exchangers. Operation without oil flow is feasible for short periods of time due to the thermal inertia, and installations in the F-5G and AV-8B aircraft are detailed. M S K

A82-24384 Aircraft electric system development and test facilities D Cousins (Sundstrand Corp., Rockford, IL) In: Aircraft electrical power systems, Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981. Warrendale, PA, Society of Automotive Engineers, Inc., 1981, p 77-86

Specialized capabilities, requirements, and design considerations for a facility to construct electric power systems for aircraft are described. A test area is provided for development and qualification testing of aircraft generating systems, along with a multistand complex for accelerated life testing, and a facility for electronic and electric products. Individual test cells are required for examining the performance of test generators during specified voltage drops and impedance. Further provision is made for testing prime movers, gearboxes, generator feeders, control consoles, load systems, and main and auxiliary load controls. Instrumentation is dedicated to both test stand consoles and from multichannel data acquisition system recorders and displays. Finally, electromagnetic compatibility testing is accomplished by examining radiated and conducted EM interference and by exposure to EM pulses. M S K

A82-24385 Wind and temperature database for flight planning H C True and D E Winer (FAA, Office of Environment and Energy, Washington, DC) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811068* 8 p 17 refs

The importance of timely and accurate wind and temperature data to flight planning and aircraft fuel conservation is pointed out. Recent advances in meteorological data measurement make it possible to obtain the required information. Attention is given to aspects of flight planning, the existing observation network, an atmospheric model, fuel considerations, wind and temperature observation technology, the potential of satellite based wind observation systems, and the dissemination of observations to aviation flight planners. It is found to be technically and economically feasible to create a wind and temperature database for flight planning based on the Prototype Regional Observation and Forecasting System 'pro-filer'. G R

A82-24386 * Airline flight planning - The weather connection R Steinberg (NASA, Lewis Research Center, Cleveland, OH). *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct. 5-8, 1981, Paper 811067* 12 p

The history of airline flight planning is briefly reviewed. Over half a century ago, when scheduled airline services began, weather data were almost nonexistent. By the early 1950's a reliable synoptic network provided upper air reports. The next 15 years saw a rapid growth in commercial aviation, and airlines introduced computer techniques to flight planning. The 1970's saw the development of weather satellites. The current state of flight planning activities is analyzed. It is found that accurate flight planning will require meteorological information on a finer scale than can be provided by a synoptic forecast. Opportunities for a new approach are examined, giving attention to the available options, a mesoscale numerical weather prediction model, limited area fine mesh models, man-computer interactive display systems, the use of interactive techniques with the present upper air data base, and the implementation of interactive techniques. G R

A82-24387 * Integration of energy management concepts into the flight deck S A Morello (NASA, Washington, DC) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct. 5-8, 1981, Paper 811066* 10 p 7 refs

The rapid rise of fuel costs has become a major concern of the commercial aviation industry, and it has become mandatory to seek means by which to conserve fuel. A research program was initiated in 1979 to investigate the integration of fuel-conservative energy/flight management computations and information into today's and tomorrow's flight deck. One completed effort within this program has been the development and flight testing of a fuel-efficient, time-based metering descent algorithm in a research cockpit environment. Research flights have demonstrated that time guidance and control in the cockpit was acceptable to both pilots and ATC controllers. Proper descent planning and energy management can save fuel for the individual aircraft as well as the fleet by helping to maintain a regularized flow into the terminal area. G R

A82-24388 Application of damage tolerance technology to type certification. T Swift (FAA, Washington, DC). *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct. 5-8, 1981, Paper 811062* 20 p 29 refs

An attempt is made to clarify some of the questions related to the FAA philosophy which are currently being raised by manufacturers in attempting to comply with recently amended regulations for aircraft structures. A description is presented of opinions related to good damage tolerance design practice, and fracture analysis methodology. In general, an evaluation of the structure, under typical load and environmental spectra must show that catastrophic failure due to fatigue, corrosion, or accidental damage will be avoided throughout the operational life of the aircraft. Attention is given to a damage tolerance evaluation, aircraft utilization, the selection of critical elements, aspects of stress spectra development, environmental effects, and fracture toughness data. G R

A82-24389 Certification of civil composite aircraft structure J R Soderquist (FAA, Office of Airworthiness, Washington, DC) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811061* 10 p 19 refs

The certification of composite civil aircraft structures is shown to require a common, allowable material property data base in which the chemical characterization of the resin through the use of high pressure liquid chromatography and Fourier transform infrared spectroscopy is employed. In addition, improved damage-tolerance techniques and tougher material systems must be developed to allow higher design strain levels. Significant benefits can be derived from the continued operation of a composite structure in the post-buckled regime, provided that investigations continue into environmental effects, combined loading states, curvature, variations in skin thickness and impact damage effects. It is recommended that a portable nondestructive inspection technique be devised for use in field repairs. O C

A82-24392 Design technology for improved performance retention in turbofan engines D L Seiwert (General Electric Co., Fairfield, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811055* 10 p

General causes of performance loss in large turbofan engines after long time field use are examined, and programs whose objectives are to maximize engine performance retention are described. Advanced design concepts to produce significant improvement in performance retention of commercial turbofan engines are presented, and factors which cause clearance changes between rotating and static components are discussed. Engine generated and externally applied loads, and operating technique effects are addressed, and evaluation techniques for design verification including laser optics are described. Performance retention items include a substantially improved high pressure turbine shroud material, which reduces distortion and thereby avoids rubs. D L G

A82-24393 RB 211 powerplant deterioration - Review of current situation and lessons learned A G Collins (Rolls-Royce, Ltd., London, England) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811053* 6 p

The factors which cause aircraft engines to lose performance in a service environment are briefly examined. It is pointed out that in the case of the RB 211 engine many of the fundamental causes of deterioration are avoided or minimized in connection with basic engine design features. The -22B was the first of the RB 211 family of engines to enter service. Major causes of RB 211-22B deterioration were related to the accumulation of dirt on compressors, the distortion of HP NGV support rings, increased leakages in powerplant area, and erosion of turbine tip sealing segments. By suitable modifications of the engine design it was possible to eliminate the observed causes of engine deterioration in the RB211-524. Problems concerning engine deterioration observed in connection with RB 211-524 operation will be corrected in the RB 211-535 by the introduction of appropriate improvements. G R

A82-24394 Management of powerplant maintenance and restoration programs for fuel conservation C Reid (General Electric

Co., Fairfield, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811052* 15 p

Powerplant operational and maintenance procedures are reviewed to minimize fuel consumption and total operating costs of existing large turbofan engines. Recommendations are made to reduce the rate of on-wing performance deterioration and to define cost effective performance refurbishment. Measures being taken to increase fuel and cost savings include the development of performance diagnostic/analytical systems to permit better management control of engine operating costs. On-wing performance retention can be improved by the observance of line maintenance and operational procedures minimizing the impact of the major causes of performance deterioration, such as increased clearances, erosion, contamination and leakage. D L G

A82-24395 **Airline fuel saving through JT9D engine refurbishment** J W Allison and D R Weisel (United Technologies Corp., Pratt and Whitney Aircraft Group, East Hartford, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811051* 12 p

Since the JT9D engine entered airline service in 1970, increase in the price of jet fuel made it imperative to devise refurbishment procedures for in-service engines to improve their fuel economy. Developments leading to performance recovery and improvement of the engine are related to fan leading edge rework, and the one degree open first stator. Factors responsible for engine performance recovery and retention include also operational procedures, test configuration, and prevention of aircraft system pneumatic leakage. Attention is given to the fan strip panel concentric grinding tool, a properly repaired combustor with recently developed 'S-16' fuel nozzles, recommended refurbishment additions, operational procedures to maximize performance retention, a test configuration, and inspection techniques. G R

A82-24396 **Airworthiness considerations in the design of commercial transport aircraft** J R Koch (Lockheed California Co., Burbank, CA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811039* 14 p 8 refs

Design requirements and development, and the maintenance practices required in the certification of commercial transport aircraft and in the ensuring of their continuous airworthiness in operation, are considered with attention to (1) airworthiness philosophy and criteria, (2) the evolutionary character of design development, (3) the scope of development testing, and (4) the enlistment of manufacturer, operator and regulatory agency in airworthiness assurance throughout an aircraft's operational life. Also considered are the airworthiness regulation revisions and technological advances that have resulted in changes in the substantiation of airworthiness, especially in the case of structures. O C

A82-24397 **Designing for continued airworthiness - General aviation** C A Rembleske (Beech Aircraft Corp., Wichita, KS) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811038* 8 p

The Air Commerce Act of 1926 became the first piece of U.S. legislation which provided a basis for the writing of airworthiness standards for aircraft. The contents of the Air Commerce Regulations are briefly discussed. In connection with the technological developments of a rapidly growing industry, the regulations became more complex. Beginning in 1974, FAA introduced the term 'continued airworthiness'. Continuing airworthiness can be defined as keeping the aircraft flying safely and functioning properly over an indefinite period. Attention is given to the airframe, the propulsion system, basic flight instruments, vital hydraulic lines, fuel systems, electrical systems, and problems of wear and tear. G R

A82-24398 **The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFFC I.** V M Marti, J Woods, Jr. (McDonnell Aircraft Co., St. Louis, MO), and W F Swartz (USAF, Wright Aeronautical Laboratories, Dayton, OH) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811036* 17 p

The purpose of technology demonstration is to reduce the risk associated with developing an advanced operational system by

verifying the capability of advanced, and as yet unproven, technologies. Attention is given to today's conditions which require the use of a technology demonstrator aircraft, principally as a precursor to future military tactical aircraft systems. The ingredients of a good technology demonstrator are examined, taking into account the selection of the F-15B aircraft for the technology demonstration of the Integrated Flight and Fire Control (IFFC) program. The IFFC system concept is considered along with the IFFC data acquisition systems, and the IFFC onboard simulation systems. G R

A82-24399 **Mission-adaptive wing flight demonstration program.** D K Gould (Boeing Co., Seattle, WA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811035* 10 p

It is reported that the design and fabrication of the AFTI/F-111 mission-adaptive wing is nearing completion. The variable-camber airfoil design, unlike conventional wings, possesses no discontinuities from spoilers, flaps or fairings to disturb the flow of air over the wing. The flexible leading edge is continuous from wing root to tip, and the flexible trailing edge is divided into three segments to provide roll control redundancy, permit operation at various sweep-settings of the F-111 variable wing, and to allow spanwise shifting of the aerodynamic load. Wind tunnel and flight simulation tests indicate aerodynamic performance benefits, and the structural capability that has been checked by finite element analysis is in turn verified by tests of a wing section loads and actuation test rig. Flight tests are to begin in late 1982. O C

A82-24400 **Quality, quantity, and technology - A perspective on fighter development** S K Jackson, Jr. (General Dynamics Corp., Fort Worth, TX) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811097* 14 p 7 refs

The consequences of long-term technological development on military aircraft unit costs are illustrated, by means of comparisons between the capabilities and costs of such World War II aircraft as the P-51 fighter and B-17 bomber, on the one hand, and the contemporary F-16 fighter, on the other. A detailed historical analysis of the B-17 Schweinfurt raids and the extrapolation of the capabilities of the F-16 to that 1943 scenario shows that, while the modern fighter is able to deliver a greater bomb load with greater accuracy in a greater variety of conditions than the B-17, its cost, as a fraction of GNP, is only 1/6-2/3 times greater than that of the B-17. Similar improvements are demonstrated for the cases of operational readiness and numbers of maintenance personnel, showing that the continuing development of airframes is justified. The development of experimental aircraft is recommended. O C

A82-24401 * **Aircraft surface coatings for drag reduction/erosion protection** R L Kretinger (Boeing Commercial Airplane Co., Renton, WA) and D B Middleton (NASA, Langley Research Center, Hampton, VA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811070* 16 p 5 refs

The laboratory testing of a large number of films and liquid coatings for aircraft drag reduction and erosion protection has led to the identification of elastomeric polyurethanes, which fulfill smoothness, durability and protection requirements while being easily applied to large, compound-curvature areas with standard spray equipment. It was found that an epoxy primer produced a stronger bond between coating and substrate than a wash primer. A drag-reduction value of 0.2% was achieved with a commercially-available elastomeric polyurethane. O C

A82-24403 **Future strike fighter options - Concepts and technologies** P C Bavitz (Grumman Aerospace Corp., Bethpage, NY) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811099* 19 p 10 refs

Results are presented from a study of concepts of operation, and the technological capabilities required by them, for future strike fighter weapon systems. The design concepts considered by the study were (1) a low-altitude, medium-payload twin-turbofan design with mission-adaptive supercritical wing and close-coupled canard, (2) a low-altitude, heavy-payload craft with top-mounted inlets, (3) a

high-altitude concept with advanced turbojet engines and Alben-type nozzles, equipped with air-to-ground weapons that are currently in the conceptual-development stage, (4) a high-altitude/dive mission-profile craft possessing high payload/weapon carriage flexibility, (5) an advanced, low radar cross section design incorporating a delta wing planform, flush engine inlets and a top-mounted carriage for WASP weapons, and a gunship with a single, top-mounted turbojet whose primary armament is a GAU-8 30 mm cannon O C

A82-24404 Technology for quality and quantity in a new fighter W E Maillard (Northrop Corp., Los Angeles, CA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811100* 15 p 15 refs

It is demonstrated to be premature, in view of the complex and evolving character of tactical aircraft design problems requiring tradeoffs between system quality and production quantities, to hold a single design concept as superior to alternatives. However, technology application is held to be essential for the mediation of quality and quantity criteria. After identifying such major forces in cost escalation as the compounding of requirements and technology-packing, in response to mission requirement uncertainties over the course of a lengthy design development process, a design approach to lower-cost fighter concepts is introduced and quantitative methods are presented to illustrate potential improvements in the operational capabilities of aircraft in the size and cost range represented by the F-5E and F-16 fighters O C

A82-24405 Operating flight loads and their effect on engine performance R L Martin (Boeing Commercial Airplane Co., Renton, WA) and W J Olsson (United Technologies Corp., Pratt and Whitney Aircraft Group, East Hartford, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811071* 14 p

Flight loads imposed on high bypass turbofan engines and the response of the engines to these loads are examined. The effects of nacelle angle of attack, aircraft speed, and engine airflow are discussed. Results from an analysis of the NASA JT9D flight load test indicate that aerodynamic loads on the nacelle are the prime cause of cold section clearance closure and rubs, and aerodynamic loads, thrust, and differential thermal expansion cause hot section closure and rubs. Inboard and outboard engines are found to be equally affected by flight maneuvers, and a 0.7% increase in cruise thrust-specific fuel consumption is found to be typical of production aircraft acceptance testing D.L.G.

A82-24406 Restoration of performance, Models 727, 737, and 747 J C Baer and W M Staab (Boeing Commercial Airplane Co., Seattle, WA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811072* 12 p

A new generation of advanced technology, fuel-efficient jet transports, including the Models 757 and 767 will enter commercial airline service in 1982. Existing fleets of second-generation jet transports still in production, such as the 727, 737, and 747, have useful economic lives which will extend into the 1990s. Because of this longevity and the continual escalation of fuel prices, the economics of these transports will be improved. A description is presented of some of the performance improvement programs. Attention is given to aspects of operational efficiency, the in-flight fuel economy, a maintenance program to preserve low drag characteristics for the aircraft, the elimination of surface roughness, Model 727 drag improvement items, Model 747 improvement items, recently developed items, aerodynamic improvements under study, and propulsion system and flight management system improvements G R

A82-24407 High temperature engine control electronics. D. C. Dening (General Electric Co., Syracuse, NY). *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811074*. 11 p Contract No. N00173-79-C-0010

Integrated injection logic is shown to be operable at temperatures up to 300 C. The logic can thus be used in the digital control mounted on aircraft engines, where it is subjected to high temperatures and severe vibration. The design of integrated injection logic circuits for such high-temperature applications is discussed. Particular

attention is given to gate design, to the patterns of interconnection, and to the metallization system employed. Also described is a data input chip for an engine control computer that has been designed for high-temperature applications C R

A82-24408 Pressure transducer calibration process F Antonazzi, Sr (Bendix Corp., Energy Controls Div., South Bend, IN) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811076* 9 p

It is shown that quartz capsule pressure transducers using a closed loop capacitance bridge can be made highly accurate with virtually identical frequency response by using a calibration process that compensates for the quartz pressure sensor unit-to-unit variations. Digital integration gain scheduling as a function of N count results in a constant loop gain that is independent of pressure level. As a consequence, constant dynamic characteristics are obtained at all pressure levels. It is noted that plug-in pressure transducer units are interchangeable, requiring no select-at-test components or trim adjustments. The software loop closure allows use of a common printed wiring board with identical electrical components for a wide range of pressure transducers C R

A82-24409 Performance retention features of the PW2037. J K Carriere (United Technologies Corp., Pratt and Whitney Aircraft Group, East Hartford, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811054* 14 p

Studies that have been carried out on the causes of performance deterioration are surveyed, as are descriptions of design and maintenance features for improving performance retention. It is noted that short-term deterioration is caused by flight loads that cause rubbing of blades on seals and consequent loss of module efficiencies. Long-term deterioration derives from erosion of airfoils and seals during ground operation and cyclic-induced thermal distortion of the high pressure turbine vanes. Design features for improving performance retention include increased case and rotor stiffness, damped bearings on centering springs, a third low rotor bearing, active clearance control, abradable blade tips seals, controlled diffusion airfoils, dirt removal scoop, erosion-resistant compressor outer air seals, improved diffuser and combustor and reduced aspect ratio turbine vanes C R

A82-24410 Reliability analysis of a dual-redundant engine controller E Gai, J V Harrison, and R H Luppold (Charles Stark Draper Laboratory, Inc., Cambridge, MA) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811077* 11 p

A Markov model is developed for predicting the reliability of a full-authority, dual-redundant aircraft engine controller. The effects of failures on any of the controller's sensors, electronic interface modules, processors and actuators are modeled, as are the consequences of redundancy management decisions. The model's use in performing parameter sensitivity studies and developing quantitative data in support of design trade-offs is described. The effects of scheduled maintenance on the inflight shutdown rate of the engine are assessed C R

A82-24411 Propulsion multiplexer /PMUX/ system - The missing link M S Latina and W W Hixson (United Technologies Corp., Hamilton Standard Div., Windsor Locks, CT) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811078* 10 p 7 refs.

The importance placed by commercial airlines on more efficient and reliable engines with lower maintenance costs has led to the use of in-flight engine condition monitoring equipment as part of an airborne integrated data system (AIDS). This monitoring requires that the AIDS receive approximately 25 engine parameter signals. Problems arise in that the integrity of the AIDS input signals from the engine is not the responsibility of a single equipment supplier. To resolve this problem, a centralized, engine-mounted data processing device for the engine signals is proposed. It is pointed out that the unit for this Propulsion Multiplexer System can be divided into three major functional groups: (1) pressure sensors and signal interfaces, (2) digital processor and memory, and (3) serial digital data interface C R

A82-24412 LAMPS III recovery assist, securing and traversing /RAST/ system F Cracknell (DAF Indal, Ltd, Mississauga, Ontario, Canada) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811080* 9 p

The main portions of the RAST system are outlined, with descriptions given of their functions. Some of the ground and flight test experience gained thus far is summarized. The system is shown to meet the requirements of the Light Airborne Multi Purpose System (LAMPS). This latter system depends for its success upon the ability to operate helicopters safely and reliably under weather conditions where the ship roll angles reach about 30 deg and the wave heights reach 13 feet. C R

A82-24413 The use of 'Kapton' polyimide film in aerospace applications D H Berkebile and D L Stevenson (Du Pont de Nemours and Co, Wilmington, DE) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811091* 9 p

The principal steps involved in the manufacture of wire and cable insulated with 'Kapton' are described. The latest shop handling techniques are reviewed, among them automated stripping and high-speed marking. Additional aerospace applications in avionics and insulation blankets are discussed. Tables summarizing the performance characteristics of wire insulated with this polyimide film are included. C R

A82-24415 Fighter issues - 2000 D R Kozlowski (McDonnell Douglas Corp, St Louis, MO) *Society of Automotive Engineers, Aerospace Congress and Exposition, Anaheim, CA, Oct 5-8, 1981, Paper 811096* 13 p 6 refs

Consideration is given to the design requirements formulated for an advanced tactical fighter (ATF) that will operate in the electronic warfare and nuclear/biological/chemical warfare scenarios anticipated for the year 2000. The performance requirements may be characterized as speed, stealth and STOL (SSS). The SSS criteria have nominal values of (1) Mach 1.8 sustained supersonic speed, with Mach 2.5 as maximum for intercept and chase, (2) less than 0.5 sq m radar cross section, reduction of IR signature and engine exhaust contrail, and electromagnetic emission control, and (3) 1500 feet total required runway length. Attention is given to the problems posed by maintainability and cost-control criteria, as well as the emerging characteristics of air-to-air combat in view of the technological developments expected from potential adversaries. O C

A82-24416 Annual review of fluid mechanics Volume 14 Edited by M Van Dyke (Stanford University, Stanford, CA), J V Wehausen (California, University, Berkeley, CA), and J L Lumley (Cornell University, Ithaca, NY) Palo Alto, CA, Annual Reviews, Inc, 1982 463 p \$22

Applications of fluid mechanics are discussed for the study of strongly nonlinear waves, the topology of three-dimensional separated flows, and the mathematical theory of frontogenesis. Attention is also given to turbulent jets and plumes, gravity currents in the laboratory, atmosphere, and ocean, and to low-gravity fluid flows, specifically for convective flows. The computation of transonic potential flows is considered, as are the strange attractor theory of turbulence, numerical methods in free-surface flows, and the fluid dynamics of heart valves. M S K.

A82-24426 International Conference on Numerical Methods in Fluid Dynamics, 7th, Stanford University, Stanford and Moffett Field, CA, June 23-27, 1980, Proceedings Conference supported by NSF, U S Air Force, and U S Navy Edited by W C Reynolds (Stanford University, Stanford, CA) and R W MacCormack (NASA, Ames Research Center, Moffett Field, CA) Berlin and New York, Springer-Verlag (Lecture Notes in Physics Volume 141), 1981. 493 p \$28

Topics discussed include polygon transformations in fluid mechanics, computation of three-dimensional horseshoe vortex flow using the Navier-Stokes equations, an improved surface velocity method for transonic finite-volume solutions, transonic flow calculations with higher order finite elements, the numerical calculation of

transonic axial turbomachinery flows, and the simultaneous solutions of inviscid flow and boundary layer at transonic speeds. Also considered are analytical solutions for the reflection of unsteady shock waves and relevant numerical tests, reformulation of the method of characteristics for multidimensional flows, direct numerical simulations of turbulent shear flows, the stability and separation of freely interacting boundary layers, computational models of convective motions at fluid interfaces, viscous transonic flow over airfoils, and mixed spectral/finite difference approximations for slightly viscous flows. B J

A82-24562 # On-line control for the regulation of power source in multiple-servo electro-hydraulic systems B N Suresh (Indian Space Research Organization, Vikram Sarabhai Space Centre, Trivandrum, India), W L Green, and D J Sanger (Salford, University, Salford, Lancs., England) *American Society of Mechanical Engineers, Winter Annual Meeting, Washington, DC, Nov 15-20, 1981, Paper 81-WA/DSC-3* 8 p 8 refs Members, \$2 00, nonmembers, \$4 00

The efficiency of a multiple-servo electrohydraulic system, in which power can be reduced by means of an on-line self-optimizing control, depends on the selection of the most suitable among five search strategies. The strategies are considered in light of a hydraulic system mathematical model employing two velocity servos whose individual performance is simulated on a computer. Simulation results show that the Simplex is the most useful strategy for on-line implementation in a practical system, where the implementation scheme involves no more than six variables. O C

A82-24563 * # Wide field of view laser beacon system for three-dimensional aircraft position measurement L M Sweet, R B Miles, S G Webb, and E Y Wong (Princeton University, Princeton, NJ) *American Society of Mechanical Engineers, Winter Annual Meeting, Washington, DC, Nov 15-20, 1981, Paper 81-WA/DSC-9* 9 p 8 refs Members, \$2 00, nonmembers, \$4 00 Grant No NCC2-94

This paper presents a new wide field of view laser beacon system for measurement, in three dimensions, of aircraft or other remote objects. The system is developed for aircraft collision hazard warning independent of ground-based hardware, as well as for flight research, helicopter-assisted construction and rescue, and robotic manipulation applications. Accurate information describing the relative range, elevation, and azimuth of the aircraft are generated by the sweep of a low-power fan-shaped rotating laser beacon past an array of optical detectors. The system achieves a wide angle of acceptance of laser beacon light through use of compound parabolic concentrators, which collimate the light for spectral filtering to minimize solar interference. An on-board microprocessor system converts the pulse sequence to aircraft position in real time. System reliability and performance are enhanced through narrow pass filtering of the pulse signals, digital logic design to mask spurious signals, and adaptive modulation of trigger threshold levels. (Author)

A82-24565 # Describing function analysis of nonlinear nose gear shimmy T D Burton (Washington State University, Pullman, WA) *American Society of Mechanical Engineers, Winter Annual Meeting, Washington, DC, Nov 15-20, 1981, Paper 81-WA/DSC-20*. 9 p 10 refs Members, \$2 00, nonmembers, \$4 00 Research sponsored by the Boeing Military Airplane Co

The design of shimmy free nose landing gear is complicated by the action of the gear hydraulic steering system. During shimmy the steering system pressure response results in loads on the gear which are highly nonlinear functions of gear motion. In order to obviate the need for extensive numerical work to analyze gear stability, the describing function method has been used to linearize the steering system response, enabling the stability to be analyzed using linear system techniques. Application of this approach to a representative nose gear/steering system showed the limit cycle amplitudes and stability boundaries of the shimmy motion to be in good agreement with results obtained numerically, the transient response was also predicted reasonably well. (Author)

A82-24566 # Complete velocity profile and 'optimum' skin friction formulas for the plane wall-jet G P Hammond (Cranfield Institute of Technology, Cranfield, Beds, England) *American Society of Mechanical Engineers, Winter Annual Meeting, Washing-*

ton, DC, Nov 15-20, 1981, Paper 81-WA/FE-3 7 p 30 refs
Members, \$2 00, nonmembers, \$4 00 Science Research Council
Grants No B/RG/98590, No GR/A/44312

An analytic expression for the complete velocity profile of a plane, turbulent wall-jet in 'stagnant' surroundings is obtained by coupling Spalding's single formula for the inner layer with a sine function for the 'wake component'. This expression is transformed at the velocity maxima to yield an 'optimum log-law' for skin friction. An approximate skin friction formula based on the 'initial conditions' of the wall-jet is also presented. The formulas are generally in good agreement with experimental data. The complete velocity profile does not exhibit the conventional 'law of the wall' behavior and modifications are consequently recommended to the usual treatment of the near-wall region in numerical calculation procedures for wall-jet flows. The use of the 'Clauser plot' method of skin friction measurement is similarly shown to be in error when applied to wall-jets (Author)

A82-24602 * # Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts K J Baumeister (NASA, Lewis Research Center, Cleveland, OH) *American Society of Mechanical Engineers, Winter Annual Meeting, Washington, DC, Nov 15-20, 1981, Paper 81-WA/NCA-13* 8 p 24 refs Members, \$2 00, nonmembers, \$4 00

The cutoff mode instability problem associated with a transient finite difference solution to the wave equation is explained. The steady-state impedance boundary condition is found to produce acoustic reflections during the initial transient, which cause finite instabilities in the cutoff modes. The stability problem is resolved by extending the duct length to prevent transient reflections. Numerical calculations are presented at forcing frequencies above, below, and nearly at the cutoff frequency, and exit impedance models are presented for use in the practical design of turbofan inlets. D L G

A82-24643 Institute of Navigation, Annual Meeting, 37th, U S Naval Academy, Annapolis, MD, June 9-11, 1981, Proceedings Washington, DC, Institute of Navigation, 1981 171 p Members, \$30, nonmembers, \$35

The performance of a ring laser strapdown marine gyrocompass is considered along with a brief history of the use of marine radar, a marine NAVSTAR GPS receiver, the application of NAVSTAR differential GPS in the civilian community, the applications of a multiplexed GPS user set, and initial FAA tests on the NAVSTAR GPS Z-set. Attention is given to the Federal Radionavigation Plan, scanning strategies for Air Traffic Control radars, the View-Nav system, operational and economic benefits deriving from use of Ioran-C RNAV, Ioran-C RNAV in mountainous areas, and an analysis of Ioran-C system reliability for civil aviation. A description is presented of a strapdown configured land navigation system, aspects of marine simulation, bridge simulation, and an empirical INS difference monitoring procedure used to sequence SSBN NAVAIID fixes. G R

A82-24644 # A marine NAVSTAR GPS receiver R E Maine (Sperry Corp., Sperry Marine Systems, Charlottesville, VA) In *Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings* Washington, DC, Institute of Navigation, 1981, p 54-59

Attention is given to the design philosophy, construction, programming, testing, and test results of a simplified NAVSTAR Global Positioning System (GPS) receiver for marine applications. The GPS signals are received by an omnidirectional antenna, filtered to reduce out-of-band signal levels, amplified by a low noise preamplifier, and transmitted through a coaxial cable to the interior equipment. The technique used is to stop the code clock as precisely as possible at the occurrence of a timing mark. The GPS front end is considered along with the signal amplitude interface, the receiver gain control, the microcomputer, the phase shift interface, the pseudorandom noise code generator, and a real-time flow chart. A breadboard receiver constructed as described, using largely off-the-shelf components, has been found to acquire and track the experimental satellites quite successfully. G R

A82-24645 * # The application of NAVSTAR differential GPS in the civilian community J. Beser and B W Parkinson

(Intermetrics, Inc., Huntington Beach, CA) In *Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings* Washington, DC, Institute of Navigation, 1981, p 60-74 11 refs NASA-sponsored research

The NAVSTAR Global Positioning System (GPS), currently being developed by the DOD, is a space based navigation system that will provide the user with precise position, velocity, and time information on a 24 hour basis, in all weather conditions and at any point on the globe. The baseline GPS system will provide guaranteed high accuracy to only a limited number of users, mostly the military. The civilian community has to devise a variation of this system to allow for an assured, uninterrupted level of accuracy. Differential GPS provides such a capability. In connection with the conceived possibility of the use of GPS by an enemy, it is found to be necessary to implement a selective availability technical capability. Differential GPS provides an approach for the civilian community to have a guaranteed level of accuracy better than the 250 meters presently planned for GPS. G R

A82-24646 # Scanning strategies for air traffic control radars P R Mahapatra and D S Zrnic (NOAA, National Severe Storms Laboratory, Norman, OK) In *Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings* Washington, DC, Institute of Navigation, 1981, p 100-105 14 refs U S Department of Transportation Contract No FA01-80-1-Y-10524

In connection with a history of weather-related air traffic accidents near terminal areas, it is desirable that air traffic control (ATC) radars possess the capability to detect and identify elements of weather which are hazardous to aviation. To possess the capability of hazardous weather detection in a reliable manner, a radar must employ a scan strategy such that the scan cycle is not so slow as to miss shortlived for fast-growing weather phenomena. The separation of the elevation levels of the scan cycle must be close enough to ensure the detection of storm features which may endanger air traffic. Attention is given to a study conducted to determine the most suitable scanning techniques for ATC radars, taking into account the data base for the study, the photo-interpretation of the multimoment data, the vertical spacing of scan levels, and an investigation of the lifetime of an atmospheric feature by spatial correlation. G R

A82-24647 # Beyond the horizon coverage for air navigation/traffic control V I Weihe In *Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings* Washington, DC, Institute of Navigation, 1981, p 106-110 11 refs

An important segment of the aircraft population is engaged in routine flights under instrument flight rule conditions at low altitudes beneath and beyond the coverage of the current land-based air traffic control (ATC) aids. If the ATC system were expanded so that it readily accommodated low flying aircraft, many pilots would take advantage of the increased safety thereby made available. Attention is given to the available technical options, the Airing Communication Addressing and Reporting System (ACARS), the addition of airborne nodes to common carrier communications networks, and ATC ground communications network radio link interface subsystems. Approaches suitable for the Gulf of Mexico systems are also considered. G R

A82-24648 # Loran for precise position location - The VIEW-NAV system M Rogoff and P M Winkler (Emory University, Atlanta, GA) In *Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings* Washington, DC, Institute of Navigation, 1981, p 111-113

The VIEW-NAV system consists of a Loran receiver which is connected to a digital computer and visual display. The onboard computer is a small rugged and reliable digital processor. Aspects of system operation are discussed, taking into account the calibration of the Loran grid and the monitoring of the grid. A description of system performance is also provided, giving attention to a number of tests which have been conducted in Long Island Sound and Chesapeake Bay. When a monitor is employed, errors of as little as a few yards are observed. To obtain reliable and accurate results in critical locations, monitors should be employed in such places. G R

A82-24649

A82-24649 # Loran-C RNAV in mountainous areas L Rzonca (FAA, Technical Center, Atlantic City, NJ) In Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings Washington, DC, Institute of Navigation, 1981, p 129-140

The Loran-C kilohertz frequency provides stable ground wave propagation with signal coverage which is not limited to line-of-sight between transmitter and receiver. This feature makes Loran-C very attractive for aircraft RNAV between airports located in mountainous terrain or other areas not adequately served by the VOR/DME network. An important part of an airborne Loran-C evaluation program currently being conducted consists of Loran-C accuracy testing in mountainous areas. The first phase, consisting of flight tests in the state of Vermont, has been completed. A description of these tests is presented, taking into account the equipment, the test scenario, and aspects of data processing. The test results obtained verify the potential of Loran-C to provide aircraft navigation guidance under all terrain conditions. However, there appears to be a need for further refinement of hardware and of software techniques. G R

A82-24650 # Analysis of Loran-C system reliability for civil aviation G A Wong (Mitre Corp., McLean, VA) In Institute of Navigation, Annual Meeting, 37th, Annapolis, MD, June 9-11, 1981, Proceedings Washington, DC, Institute of Navigation, 1981, p 141-153 8 refs

The considered analysis is concerned with the ability of the Loran-C system to provide continuous and usable navigation signals for airborne applications. An overview is provided of the analysis techniques, and a description is presented of the computerized Loran-C coverage model which is used extensively in the reliability analysis. The probabilistic approach to reliability analysis is discussed, and the overall methodology for the analysis of Loran-C system reliability in the conterminous U.S. is illustrated with the aid of an example. The ultimate objective of the Loran-C system reliability assessment is to determine the ground station configuration which would meet the civil aviation reliability requirement in the post-1995 time period. G R

A82-24651 Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers Conference sponsored by the American Institute of Aeronautics and Astronautics. New York, American Institute of Aeronautics and Astronautics, 1982 332 p. Members, \$30, nonmembers, 40

Techniques, modeling, instrumentation, and applications of wind tunnels, wind tunnel apparatus, and models were discussed. The Shuttle testing and data base for aerodynamics predictions are examined, along with comparisons with flight data. Further attention was given to wind tunnel design and features, including tunnel liners, a quiet tunnel, choking valves, and slotted wall test sections. Techniques for instrumentation of boundary layers, surface shear stress measurements in compressible flows, laminar skin friction, and the use of aerodynamic balance systems to measure cross and cross-coupling derivatives are explored. The performance of a computer controlled variable geometry wing is described, along with the development of a self-optimizing flexible technology wing wind tunnel model, improvements in the National Full Scale Facility, and a color video display for flowfield surveys. M S K

A82-24656 * # Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LFC test P A Newman, E C Anderson, and J B Peterson, Jr (NASA, Langley Research Center, Hampton, VA) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 36-47 26 refs (AIAA 82-0568)

A contoured, nonporous, wind-tunnel liner has been designed in order to simulate a free-flight infinite yawed-wing, transonic-flow condition about a large-chord, supercritical-section, laminar-flow-control (LFC), swept-wing test panel. The numerical procedure developed for this aerodynamic liner design is based upon the simple idea of streamlining and incorporates several existing transonic and boundary-layer analysis codes. A summary of the entire procedure is presented to indicate what was done and why, the sequence of steps, and the overall data flow. The liner is being installed in the

NASA Langley 8-Foot Transonic Pressure Tunnel (TPT). Test results indicating the aerodynamic performance of the liner are not yet available, thus, the liner design results given here are examples of the calculated requirements and the hardware implementation. (Author)

A82-24657 * # Mean flow and noise measurements in a Mach 3.5 pilot quiet tunnel I E Beckwith and W O Moore, III (NASA, Langley Research Center, Hampton, VA) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 48-70 30 refs (AIAA 82-0569)

The use of Mach 3.5 two-dimensional rapid expansion nozzle for wind tunnel testing at supersonic speeds and low noise conditions encountered in high altitude flights is described. The supersonic pilot quiet tunnel is located at the NASA Langley Research Center and a description of the facility is provided, along with instrumentation and noise measurement test data at 30, 50, and 75 psia. The mean pitot pressure distributions, rms noise levels, the effect of unit Reynolds number, wall waviness, wall contaminants, and the effects of closing the bleed valve are analyzed. Typical laminar and turbulent spectra are presented, along with a summary of the effect of slot throat adjustment on the power spectra. Comparisons are made of the power spectra with the bleed valve open and closed, and of the rms fluctuating pressures with levels from conventional nozzles, and the performance capabilities are evaluated for use in transition studies. M S K

A82-24658 * # The effect of ejector augmentation on test-section flow quality in the Calspan 8-ft transonic wind tunnel W C Rose (Rose Engineering and Research, Inc., Incline Village, NV), R D Hanly, F W Steinle, Jr (NASA, Ames Research Center, Moffett Field, CA), and D W Chudyk (Calspan Advanced Technology Center, Buffalo, NY) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 71-86 (AIAA 82-0571)

Tests to determine the flow disturbances effects of four ejectors located in the corners just downstream of the diffuser in the Calspan wind tunnel are described. The flow quality in the nonejector mode is employed as the base-line configuration, and operating parameters are compared with data from other wind tunnels. During tests with the ejectors working, fluctuation levels increased between Mach 0.4-0.6, while temperature and vorticity levels remained constant. The ejector exhibited broad spectrum noise typical of free jet noise, yet static pressure measurements revealed only a slight increase in the broadband rms levels with the ejectors on, indicating negligible disturbances upstream caused by the ejectors. Choking the diffuser eliminated the jet noise, and the use of ejectors in the Mach range considered is concluded to cause no significant degradation in the Calspan tunnel flow quality. M S K

A82-24659 # An ejector augmented choking valve for the metering and control of inlet and bleed duct flows C H Boccadoro and B G Franco (Northrop Aerospace Sciences Laboratory, Hawthorne, CA) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 87-93 10 refs, (AIAA 82-0575)

The use of a choking valve in wind tunnel inlet-airframe models is described, along with the design of ejectors for augmentation in regulating higher weight flows and for upstream recovery conditions. The choking valve, with a plug insert, is operated by moving a plug in and out of the throat, and is calibrated for weight flow by use of Flegner's isentropic formula for air. The ejectors are designed to produce the proper back pressure to choke the plug for all weight flows and conditions required. One-dimensional ejector theory is reviewed and determinations are made for the primary pressure, the primary weight flow, and the area ratio for the ejector system to pump a specified weight flow. An optimization process is outlined for fitting an ejector system to a choke valve, and experimental results are reported in regards the effects of the area ratio, mixing length, and the primary pressure ratio. M S K

A82-24660 # Technical innovations in testing and analysis of heat and pressure models in hypersonic wind tunnels H. R

Carroll (Martin Marietta Aerospace, Denver, CO) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 94-100 7 refs (AIAA 82-0578)

Wind tunnel testing and analysis techniques for more cost-effective studies on projects using pressure and heat models to obtain flowfield and aerothermodynamic data in hypersonic flows are presented. Timed photographs were taken of paint melting off the nose of an MX missile model, with the paint actually an emulsified wax which retained the protuberance flow patterns when the test was terminated. Thin skin steel 0.030 in. thick was used on the cone and conic body instrumented with thermocouples and connected to a 260 channel multiplexor for data collection of millivolt output in response to heating and pressure changes due to unsteady shocks and laminar or turbulent flow. Temperature recovery methods in supersonic tunnels are discussed, along with tripping turbulent flow by means of twisted wires. Entropy measurements were accomplished by combining heating and pressure test results, Schlieren photographs, pressure rake data, and earlier data. M S K

A82-24661 # Slotted wall test section for automotive aerodynamic test facilities S Ramondo and P J F Clark (DSMA International, Inc., Toronto, Canada) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 101-109 7 refs. (AIAA 82-0585)

The use of slotted walled test sections for automotive facilities was experimentally investigated. The experiments were performed at 1/5-scale, with two test section sizes which correspond to 11 sq m and 8.5 sq m equivalent full-scale facilities. For the vehicle used, the model blockages tested were 16.4 and 21.4% respectively. Among the parameters varied were the slot open-area ratio, the axial position of model within the test section and the amount of plenum flow diverted directly into the test section diffuser. The results obtained will be important to the design of small auto-aero facilities, and showed that accurate model pressure distribution data which do not require blockage corrections can be achieved for both test sections. The importance of properly controlling plenum flow at the downstream end of the test section was evident from the present tests.

(Author)

A82-24663 * # Transonic wind tunnel wall interference corrections for three-dimensional models M H Rizk (Flow Research Co., Kent, WA), M Hafez (Flow Research Co., Kent, WA), George Washington University, Washington, DC), E M Murman (Flow Research Co., Kent, WA, MIT, Cambridge, MA), and D Lovell (NASA, Langley Research Center, Hampton, VA, Flow Research Co., Kent, WA) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p. 120-130 21 refs. Contract No. NAS1-16262 (AIAA 82-0588)

A procedure for the evaluation of wall interference corrections for three-dimensional models is presented. The Mach number and angle-of-attack corrections require the numerical solution of the potential equation about a simplified representation of the experimental model. Pressure measurements are required near the wind tunnel walls. The correction procedure also requires knowledge of the free-stream Mach number, the model angle of attack, and the lift force experienced by the model. The procedure provides an estimate of the accuracy of the correction. For slender configurations at Mach numbers close to one, the Equivalence Rule formulation is adopted to calculate the wall interference effects. Preliminary results are presented for both general and slender-body configurations.

(Author)

A82-24668 # Review of support interference in dynamic tests L E Ericsson and J P Reding (Lockheed Missiles and Space Co., Inc., Sunnyvale, CA). In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 166-190. 79 refs. (AIAA 82-0594)

A review of existing information about support interference has

revealed that the support interference effects are much more severe in dynamic than in static tests. Furthermore, the support interference is aggravated greatly by a boat-tail or dome shaped base, even by modest base shoulder roundness, from what it is for a flat-based model. The general conclusion is that asymmetric stings or sting-strut combinations should be avoided. For slender bodies at low angles of attack a transverse rod comes close to permitting the true dynamically destabilizing effect of a bulbous base to be measured whereas even a very slender sting will distort the near wake effect and produce an unconservatively high measure of the dynamic stability. At intermediate and high angles of attack the sting support is superior to the other support methods, the transverse rod or the strut mounting. In many cases half-model testing provides the means to avoid most of the support interference effects. In some cases, as for a short blunt body such as the Viking configuration, the best approach appears to be to allow sting plunging, using a very slender sting.

(Author)

A82-24669 # The use of a multi-degree-of-freedom dual balance system to measure cross and cross-coupling derivatives D R Haberman (Calspan Field Services, Inc., Arnold Air Force Station, TN) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 191-201 6 refs. (AIAA 82-0595)

Equations of motion and a data reduction method are presented for a dual balance system for measuring dynamic cross and cross-coupling derivatives for aerodynamic models in wind tunnel tests. The balances each weigh 1500 lb, with one to provide forced oscillation, pitch/yaw, and cross flexure as a motion generator, and the other to create pitch/yaw, or roll planes as a load measuring device. Both balances are noted to be similar to a five-component static force balance, and balance deflections are measured by holographic interferometry. The Lagrange method is used to derive the equation of motion in roll, and locations of the center of gravity are calculated from the known balance dimensions. Balance measurements are converted into a force and a moment about a selected reference point by substituting the measured load vectors into the static balance equation. Further consideration is given to roll data reduction and the correction of existing roll data. M S K

A82-24670 # Cross and cross-coupling derivative measurements on the standard dynamics model at AEDC S M Coulter and E J Marquart (Calspan Field Services, Inc., Arnold Air Force Station, TN) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 202-214 9 refs. (AIAA 82-0596)

A description of newly developed pitch, yaw, and roll forced-oscillation balance systems is presented. These systems were designed with a particular goal of obtaining cross and cross-coupling derivative measurements at high angles of attack. Results of laboratory and wind tunnel tests (from Mach 0.3 to 1.3) are discussed. Cross and cross-coupling derivatives, direct dynamic, and static data, obtained from testing the Standard Dynamics Model (SDM) are shown for several test conditions. Comparisons to a previously obtained dynamic and static data base for this model show good agreement, verifying the accuracy of the measured parameters. (Author)

A82-24673 # Development of a self-optimizing flexible technology /SOFT/ transonic wing wind tunnel model A A McClain and S. Pountney (General Dynamics Corp., Convair Div., San Diego, CA) In Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 230-238. Contract No. N00014-76-C-0742 (AIAA 82-0601)

The SOFT-wing concept automatically adapts the wing shape through computer control. Designing the model to meet the criteria of transonic testing required the investigation and application of innovative techniques. Major design and fabrication features of the model included rectangular hydraulic actuators machined integrally in the spar, highly accurate linear potentiometers, leading- and trailing-edge skins of composite materials, a leading-edge extension mechanism, flexible wing tips, and a self-trimming horizontal stabilizer. It was concluded that an automated model is expensive to

develop, however, its productivity reduces test costs significantly, thereby offsetting increased model costs (Author)

A82-24674 * # **Structural modeling of high Reynolds number wind tunnel models** S C Mehrotra (Vigyan Research Associates, Inc., Hampton, VA) and J C Robinson (NASA, Langley Research Center, Hampton, VA) In *Aerodynamic Testing Conference*, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 239-245 Contract No NAS1-16114 (AIAA 82-0602)

A solid uninstrumented wing and a pressure instrumented wing having a tongue and groove type joint have been structurally modeled by using SPAR Structural Analysis System The solid wing model can be analyzed by SPAR, using either solid elements or plate elements with reasonable accuracy The instrumented wing models with tongue and groove joint can be modeled by using solid elements A solid model representation for the wing with tongue and groove joint can be used for the cases where an error of 6 percent in deflections is acceptable (Author)

A82-24675 * # **Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels** E C Teague, T V Vorburger, F E Scire, S M Baker, S W Jensen (National Bureau of Standards, Washington, DC), B B Gloss (NASA, Langley Research Center, Hampton, VA), and C Trahan In *Aerodynamic Testing Conference*, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 246-251 6 refs NASA Order L-4718-B (AIAA 82 0603)

Current work by the National Bureau of Standards at the NASA National Transonic Facility (NTF) to evaluate the performance of stylus instruments for determining the topography of models under investigation is described along with instrumentation for characterization of the surface microtopography Potential areas of surface effects are reviewed, and the need for finer surfaced models for the NTF high Reynolds number flows is stressed Current stylus instruments have a radius as large as 25 microns, and three models with surface finishes of 4-6, 8-10, and 12-15 micro-in rms surface finishes were fabricated for tests with a stylus with a tip radius of 1 micron and a 50 mg force Work involving three-dimensional stylus profilometry is discussed in terms of stylus displacement being converted to digital signals, and the design of a light scattering instrument capable of measuring the surface finish on curved objects is presented M S K

A82-24676 * # **Status and capabilities of the National Full Scale Facility 40- by 80-foot wind tunnel modification** K W Mort, D F Engelbert, and J C Dusterberry (NASA, Ames Research Center, Moffett Field, CA) In *Aerodynamic Testing Conference*, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p 252-272 30 refs (AIAA 82-0607)

The background, requirements, and aerodynamic design of the modified NASA Ames 40 x 80 ft wind tunnel are reviewed, along with the systems integration and systems test results Advancing vehicle sizes and airspeeds required a larger wind tunnel test section and a capability for 100 and 300 knots airspeed simulation Acoustic mufflers at the inlet and exit of the nonreturn circuit provide noise suppression The enlarged test section is intended to accommodate the complex flowfields of wings with high lift coefficients, and the drive system is designed with minimum residual swirl Features of the fan blades are examined, along with characteristics of the test channels, control vanes and louvers, the exit, circuit losses, temperature rises during operation of the nonreturn circuit, and the facility acoustics Specific construction problems and solutions for the conversion process are outlined, and it is noted that operational status is expected at the end of 1982 M S K

A82-24677 * # **A new facility and technique for two-dimensional aerodynamic testing** J B McDevitt, T E Polek, and L A Hand (NASA, Ames Research Center, Moffett Field, CA) In *Aerodynamic Testing Conference*, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers New York, American Institute of Aeronautics and Astronautics, 1982, p. 273-295 6 refs (AIAA 82-0608)

The design and operational characteristics of a new test leg for the High Reynolds Number Facility at Ames Research Center are presented, and the unique features of a test section for obtaining two-dimensional airfoil data are reviewed The new facility operates at unit Reynolds numbers ranging from 1,000,000/ft to 30,000,000/ft Boundary-layer suction panels are used in the test section (16 in wide by 24 in. high) to minimize side-wall interference effects Flexible, easily adjustable upper and lower walls allow test-channel area-ruling so as to nullify Mach-number changes induced by mass removal, to correct for longitudinal boundary-layer growth, and to provide contouring compatible with the streamlines of the model in free air (Author)

A82-24701 **The Agusta's solution of AHS's hypothetical fatigue life problem** G Aldinio and P Alli (Costruzioni Aeronautiche Giovanni Agusta S p A, Gallarate, Italy) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper* 15 p 8 refs

The Agusta solution to the American Helicopter Society's hypothetical fatigue life problem is presented The fatigue analysis methodology for dynamic components is based on Miner's rule, which necessitates a proper load survey and some fatigue tests The component's life is calculated using peak value flight loads, cycle-counted flight loads, the rainflow method, the range-pair-range method, and counting methods GAG cycles are also discussed.

D L G

A82-24703 **The challenge of standardizing fatigue methodology** B Altman and J Pratt (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper* 14 p 7 refs

The Sikorsky methodology is described, and the goal of standardization of fatigue methodology as applied to a hypothetical fatigue problem is discussed Areas that can be successfully standardized include S/N curve shapes for specific materials, the use or non-use of Goodman corrections, the selection of test steady loads, and the determination of primary frequency It is concluded that the success with which standardization will set the balance between structural reliability and program costs will depend upon the assessment of the risks involved for the total methodology, a system approach is needed to understand and optimize the risks involved in the total methodology selected and the program advantages D L G

A82-24704 **Standardization of helicopter fatigue methodology - A manufacturer's view** J M Drees (Bell Helicopter Textron, Fort Worth, TX) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper* 11 p

It is pointed out that each helicopter company has its own way of determining component lives As the existence of such differences has created problems for the Army evaluation teams, it has been recommended that standardization of methods be imposed by the Army for future developments The present investigation is concerned with the question of whether standardization beyond what has already been specified is beneficial from an overall standpoint It is found that there are a number of aspects which make it difficult to recommend at the present time the introduction of new industry-wide standards Thus, it appears unlikely that safety will be improved by such standards, because many field failures are caused by factors which are not part of the methodology presently followed The recommendation is made that an independent 'Helicopter Fatigue Methodology Council' be formed Feasibility of standardization may be explored as well as many other subjects of common interest during workshop-type meetings G R

A82-24705 **Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft** H S Faust (Boeing Vertol Co., Philadelphia, PA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper* 18 p

A fatigue cracking problem in the aft rotor drive shaft of the CH-46 helicopter is described The cracking occurred in a pinned joint between two sections of the shaft, at service times below the retirement life indicated by the original fatigue test and life calculations Crack propagation and strain survey tests are discussed

together with their use in defining periodic inspection intervals and joint improvements. In addition, a new stress analysis technique for joints of this type is introduced. (Author)

A82-24706 Evolution of the Aeroscout G Fossum, II (U.S. Army, Training and Doctrine Command, Fort Monroe, VA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper 7 p*

The development of the aerial scout is discussed, taking into account medical evacuation roles assigned to the first helicopters purchased by the Army, the role of the helicopter during the Korean War, the scout/gunship role for the OH-13 helicopter, and scout missions performed in Vietnam. The adaptation of helicopter scout tactics for modern combat conditions is considered, giving attention to the need to increase the helicopter's survivability on the mid to high intensity battlefield. The present concept of scout employment calls for the scout to be the integrator of aerial antiarmor firepower of the combined arms team. Four major roles identified are related to operations as air cavalry scout, attack helicopter scout, artillery scout, and an aid to battlefield management. G R

A82-24707 Flight test data acquisition and interpretation C. Hutchinson and H. Steinmann (Boeing Vertol Co., Philadelphia, PA). *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper, 18 p*

Data acquisition comprises the selection of measurements, optimization of recording methods, and processing of the measurements for interpretation. Basic measurements are related to the determination of airspeed, altitude, gross weight, the center of gravity, rotor speed, outside air temperature, attitudes, rates, stick positions, and load factor. The complete list of the parameters is dependent on the type of helicopter being tested. However, the intent is to be able to verify the suitability of maneuvers for the flight load survey requirements. Data interpretation considers safety of the test aircraft, load studies, and fatigue life predictions. Variations in operating restrictions, based on fatigue loads, can have dramatic effects on the outcome of the fatigue life assessment. G R

A82-24708 Structural testing of composites with known defects P. F. Maloney (Kaman Aerospace Corp., Bloomfield, CT) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper, 14 p, 5 refs*

In connection with the application of composite materials in primary structural components of production aircraft, an understanding of the significance of typical defects in the material is very important. The present investigation has the objective to make a contribution to such an understanding. Specific experiences discussed are derived from four separate development programs of relatively recent completion. Attention is given to the composite main rotor blade for the AH-1 Cobra helicopter, the composite rotor hub development program, the composite main rotor blade for the circulation control rotor, and the development of a composite blade for a 300 foot diameter wind turbine. A description is presented of salient features of each of these programs, taking into account significant findings relative to defects as they may affect composite materials. G R

A82-24709 A method of determining safe service life for helicopter components. G. W. McCloud (Bell Helicopter Textron, Fort Worth, TX) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper 12 p*

It is pointed out that the considered methods have been used by an American helicopter manufacturer for many years and were found to be reliable. In general, these methods follow those outlined in FAA Advisory Circular 20-95. The information required for the determination of the fatigue life of a component includes the fatigue strength characteristics of the component, the stresses associated with normal flight maneuvers, and the frequency of occurrence of those maneuvers. Attention is given to the approaches employed to obtain information regarding the fatigue strength, the operating loads spectrum, a fatigue life calculation, and prospects for improving state-of-the-art procedures. G R

A82-24710 Hughes helicopters - Fatigue life methodology. J. McDermott (Hughes Helicopters, Inc., Culver City, CA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper 20 p*

A description is presented of the approach used by an American helicopter manufacturer in solving a hypothetical fatigue problem. The solution of the problem was undertaken to identify and evaluate the different methodologies existing in the industry. The hypothetical fatigue problem provides loads data, fatigue test data, and defines the spectrum. The required solutions include the calculation of fatigue life using cycle counted data, the calculation of fatigue life using peak loads applied throughout the time slice of duration of maneuver, and the determination of the effect of GAG cycles. The results of the investigation show the importance of the determination of the S-N curve, using either best data fit or standard material curve shape. Assumption of peak cycle loads for duration of maneuver is found to be ultra conservative, leaving out the GAG cycle is unconservative. G R

A82-24712 Flight condition recognition /FCR/ technique. D. M. Saylor (U.S. Army, Research and Technology Laboratories, Fort Eustis, VA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar 25-27, 1980, Paper 7 p*

A U.S. Army contract, entitled 'Structural Integrity Monitoring System' was performed to design, qualify, flight test, and demonstrate the Structural Integrity Recording System (SIRS). SIRS provides a cost-effective method of tracking the accumulation of fatigue damage on critical helicopter dynamic components. The system monitors the variations in fleet utilization on a helicopter by-helicopter basis for safer and more economical operation. SIRS is a total system comprising an airborne microprocessor-based recorder, a portable flight-line retrieval unit, and a data processing package. Attention is given to the airborne recorder, the transducer package, the retrieval unit, fatigue damage assessment software, flight test programs, aspects of operational test and evaluation, and a flight test program. G R

A82-24713 NDE of composite rotor blades during fatigue testing R. Shuford, W. Houghton (U.S. Army, Army Materials and Mechanics Research Center, Watertown, MA), J. R. Mitchell (Becton, Dickinson and Co., Dunegan-Endevco, San Juan Capistrano, CA), and J. W. Sobczak (U.S. Army, Applied Technology Laboratory, Fort Eustis, VA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper, 17 p, 11 refs*

A description is presented of progress made in a continuing project concerned with the evaluation of the usefulness of several nondestructive evaluation (NDE) techniques for monitoring flaw initiation and growth in composite helicopter rotor blades. The acoustic emission (AE) results indicate minor fatigued damage. It appears, therefore, feasible to project an AE failure curve based on the emissions from periodic proof overloads. This technique could have wide application in new product certification and in-service inspection of composite rotor blades. Indications from the vibrometry portion of the program suggest that it may provide an excellent method for locating, characterizing, and understanding defect development and growth during cyclic loading of composite structures. Results from the ultrasonic, radiographic and visual examinations indicate that these procedures are very useful for the evaluation of defects in composite rotor blades. G R

A82-24714 Fundamentals of helicopter fatigue life determination. D. P. Schrage (U.S. Army, Aviation Research and Development Command, St. Louis, MO) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper, 28 p, 10 refs*

This paper reviews the fundamentals of helicopter fatigue life determination by discussing the sources and definitions of helicopter loads, the relationships between these loads and critical stresses, and helicopter fatigue methodology. Helicopter fatigue methodology is the process by which the various aspects and disciplines are incorporated into a procedure for calculating helicopter fatigue lives. (Author)

A82-24715 **Fatigue test of the typical main rotor controls component.** J Slack and J Cernosek (Bell Helicopter Textron, Fort Worth, TX) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 17 p*

The general procedure used to qualify a fatigue critical component is illustrated with the aid of a flow chart. The decision regarding the condition of fatigue tests for a particular component is made as soon as practical in a program. The decision takes into consideration the expected fatigue environment on the helicopter. An early diagnosis of potential component fatigue problems is important to prevent certification delays, and costly manufacturing charge requirements. Considerations of the plan of test are discussed, giving attention to the test specimen, the type of test, the test loads, and the test machine. The more important aspects concerning the implementation of the test plan are related to the test set up, the failure analysis, and the feedback requirements. G R

A82-24716 **Hypothetical fatigue life problem - Application of Aérospatiale method.** G Stievenard (Société Nationale Industrielle Aérospatiale, Division Hélicoptères, Marignane, Bouches-du-Rhône, France) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 34 p*

The mean fatigue curve calculation is considered, taking into account the permissible alternating load and the plotting of the unit Wohler curve. The Wohler curve makes it possible to calculate, from test results, a mean fatigue curve and a standard deviation representative of the scatter. Attention is given to safe fatigue curve calculation, aspects of flight load determination, the fatigue life calculation using peak value flight loads, a fatigue life calculation using cycle-counted flight loads, and the values for a G A G cycle. It is pointed out that the Wohler curves for steels loaded without fretting are generally flat and that this results in very high difference in the number of cycles for low variations of loading. G R

A82-24717 **The cargo helicopter - A logistical vehicle.** R L Stoessner and R C Heehn (U S Army, Training and Doctrine Command, Fort Monroe, VA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 13 p 9 refs*

The availability of adequate supplies is a crucial factor for an army engaged in a battle. In the case of highly mobile forces involved in other than light assault missions, supply requirements combined with the factor of time sensitivity dictate the use of air logistics helicopters. The logistical helicopters are considered an integral part of the support command's transportation service. Attention is given to the employment of air transport units providing combat service support from a logistical base to a combat force such as a division or brigade which is operating in an underdeveloped area. The Tactical Mobility Requirements Board report of 1962, laid the foundation for true airmobility of Army Forces. The versatility of the cargo helicopter was demonstrated in Vietnam. However, much of the operational experience gained is not applicable to a mid- or high-intensity combat environment. The air defense threat envelope will require the cargo helicopter to utilize terrain masking to the maximum. G R

A82-24718 **Boeing Vertol fatigue life methodology.** G H Thompson (Boeing Vertol Co., Philadelphia, PA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 8 p 7 refs*

It is pointed out that, with respect to basic philosophy, the fatigue life methodology of the considered American helicopter manufacturer has changed little over the years. Major changes have been only in the mechanics of calculation. High-speed computers are performing the work which once had to be done manually. The life calculation procedure is started by developing the mission profile. This consists of a fatigue loading schedule and flight profile splits. To determine the endurance limit of a helicopter dynamic component, full-scale bench fatigue tests are conducted. The use of the fatigue life methodology is illustrated with the aid of an example involving the solution of a hypothetical fatigue life problem. Attention is given to life calculation without cycle counting, life calculation with cycle counting, and the ground-air-ground condition. G R

A82-24719 **Helicopter rotor load prediction.** J G Yen (Bell Helicopter Textron, Fort Worth, TX) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 10 p 12 refs*

In the preliminary design of rotor components, the fatigue design loads must be estimated. The methods which have been used for estimating the design loads at Bell Helicopter Textron (BHT) are discussed in this paper. A review of rotor loads prediction methods starting with the empirical method used in the earlier years of helicopter design through the application of the sophisticated computer analysis of today is presented. Examples of correlation of blade and pitch-link loads between flight test and analytical prediction for a two-bladed teetering rotor and a four-bladed hingeless rotor in level flight are shown. Results indicate that the accuracy of analytical prediction depends upon an accurate representation of the rotor structure and the use of state-of-the-art aerodynamics and, to a great extent, the user's knowledge and experience with the analysis. Applications of C81 to predicting loads following blade damage are also discussed briefly. (Author)

A82-24720 **Advanced attack helicopter fatigue testing - Overview.** G D Deveaux (Hughes Helicopters, Inc., Test Laboratories, Culver City, CA) *American Helicopter Society, Specialists Meeting on Helicopter Fatigue Methodology, St. Louis, MO, Mar. 25-27, 1980, Paper 13 p*

A description is presented of tests conducted to study the fatigue life of critical components of the YAH 64 helicopter. In accordance with the Airworthiness Qualification Specification six specimens are required to substantiate a fatigue life of 4500 hours. Constant load amplitude, S-N type testing is used for all component tests with the exception of the gun support structure, where spectrum loading type testing is specified. The components required to be fatigue tested belong to the main rotor group, the tail rotor group, the controls group, the drive system group, and the fuselage. The test loading system is discussed, taking into account the general approach, the actuators, and the air springs. Details regarding the data acquisition system are also provided. G R

A82-24803 **Novel metal-ceramics-composite sealing coatings in aircraft engines (Neuartige Metall-Keramik-Verbund-Dichtungsbeläge in Flugtriebwerken).** A Sickinger and V Wilms (Motoren- und Turbinen-Union München GmbH, Munich, West Germany) In *Composite materials, Lecture and Discussion Meeting, Constance, West Germany, April 17, 18, 1980, Reports*

Oberursel, West Germany, Deutsche Gesellschaft für Metallkunde, 1981, p. 133-140. In German.

Requirements for the enhancement of the performance of aircraft engines and the reduction of fuel consumption make it necessary to operate aircraft engines at higher gas pressures and temperatures. The development of novel metal-ceramics-composite sealing coatings makes it possible to overcome certain problems related to more exacting sealing requirements and greater thermal extension in connection with the new operational conditions. The sealing coating provides a means to compensate for different thermal extensions and manufacturing tolerances existing for rotating and stationary structural components. It is feasible to obtain minimum clearance values and to reduce attrition effects for the rotating component. Other important benefits of the coating are related to its thermal-barrier characteristics. Attention is given to the requirements which the coating has to satisfy, its application by thermal spraying, the coating composition, and some test results. G.R

A82-24805 **Carbon-fiber composites - A fiber composite material for highly stressed light-construction components (CFK - Ein Faserverbundwerkstoff für hochbelastete Leichtbauteile).** G Stoffler, W Scheer, and H Wurtinger (M A N - Neue Technologie, Munich, West Germany) In *Composite materials, Lecture and Discussion Meeting, Constance, West Germany, April 17, 18, 1980, Reports*

Oberursel, West Germany, Deutsche Gesellschaft für Metallkunde, 1981, p. 235-250. 7 refs. In German.

The properties of the basic materials used in fiber-reinforced nonmetallic materials are considered, and the calculation of the strength characteristics of the composite material is discussed, taking into account stresses and fiber orientation in the case of the wing of an aircraft. Attention is given to the elasticity characteristics of a unidirectional layer, a fracture criterion for the unidirectional layer,

a computational flow diagram for the calculation of the loading capacity of the composite, the fracture characteristics and the mechanical characteristics of carbon-fiber composites (CFC), and the thermal properties of CFC. A description is presented of examples which illustrate various possibilities for an employment of CFC. G.R.

A82-24814 # Efficient combinations of numerical techniques applied to aircraft turning performance optimization. D. Blank and J. Shinar (Technion - Israel Institute of Technology, Haifa, Israel). *Journal of Guidance, Control, and Dynamics*, vol. 5, Mar-Apr 1982, p. 124-130. 23 refs.

This paper presents efficient combinations of numerical optimization techniques summarizing their relative merits. Four basic methods handling constraints without penalty functions, are considered: (1) sequential gradient-restoration, (2) quasilinearization, (3) neighboring extremals, and (4) direct shooting. The first two are modifications of algorithms introduced by Miele, avoiding numerical differentiation and eliminating the anchoring effect of the original formulation. The third one is a generalization of an algorithm due to Bryson and Ho. The individual and combined methods are tested by solving the optimization of vertical and three-dimensional turning maneuvers as examples. Results show that an appropriate combination of algorithms reduces the computational effort by more than 50%. (Author)

A82-24825 Recent developments in materials and processes for aircraft corrosion control. S. J. Ketcham and J. J. De Luccia (US Naval Material Command, Naval Air Development Center, Warminster, PA). *SAMPE Quarterly*, vol. 13, Jan 1982, p. 32-37. 10 refs.

This paper describes advances in materials and processes for aircraft corrosion control currently in use and those under development in the laboratory for future use. Areas covered are corrosion preventive compounds, organic and inorganic coatings, alloy selection and heat treatments. Available materials highlighted are water displacing compounds, sealant primers, aluminum alloys 7050 and 7010 including a state-of-the-art report on the use of exfoliation and stress corrosion resistant tempers. Materials under development that offer promise of contributing to future advances include water displacing paints, flexible primer, crack arrestment compounds, powder metallurgy, aluminum alloys and substitutes for cadmium plating. (Author)

A82-24892 † A method for the investigation of gyro-stabilization systems (Ob odnom metode issledovaniia sistem giroskopicheskoi stabilizatsii). L. K. Kuz'mina. In: *The direct method in stability theory and its applications*. Novosibirsk, Izdatel'stvo Nauka, 1981, p. 195-200. 9 refs. In Russian.

The paper examines gyro-stabilization systems whose differential equations of motion include a large parameter. The conditions under which a simplified low-order mathematical model can be used to study such systems are investigated. Results are presented for the example of a single-axis gyro-stabilizer. B.J.

A82-24970 Angle of downwash behind a wing in unsteady flow (Srazovy uhel za neustalene obtekanym kridlom). M. Zadnik. *Zpravodaj VZLU*, no. 4, 1981, p. 167-171. 5 refs. In Czech.

The paper presents a method for determining the angle of downwash behind a wing in the plane of symmetry of the aircraft when the circulation about the wing varies periodically with time. The solution is obtained for an inviscid medium on the assumption of the total rollup of the free and starting vortices. The results are presented in the form of a nomogram. B.J.

A82-24972 The reliability and safety of small passenger aircraft (Problematika spoehlivosti a bezpecnosti maleho dopravnio letounu). O. Gregor and V. Kahanek. *Zpravodaj VZLU*, no. 4, 1981, p. 189-195. 5 refs. In Czech.

Problems associated with the reliability and safety assurance of small passenger aircraft during certification are discussed. The philosophy of flight safety assessment according to NLGS-2 requirements is described, and the quantitative limits of the probability of an accident due to damage are determined. Methods of aircraft reliability analysis and testing are briefly described. B.J.

A82-24973 Spoilers or auxiliary flaps (Spoilery nebo pomocna kridelka). V. Pokorný. *Zpravodaj VZLU*, no. 5, 1981, p. 213-217. In Czech.

The possibilities and advantages of using auxiliary flaps (that part of ailerons or extended flaps controlled by a servo actuator) instead of spoilers for the improvement of lateral control are discussed. It is shown that the auxiliary flaps have definite advantages over spoilers and allow a wider range of application. B.J.

A82-24974 Oscillations and vibrations of aircraft on runways (Kmitani a vibrace letadel pri pozemnich operacich). O. Kropac, J. Sprinc, and M. Prochazka. *Zpravodaj VZLU*, no. 5, 1981, p. 219-234. 8 refs. In Czech.

Analytic and experimental studies on the vibration of aircraft on runways are summarized. The aircraft and the runway are considered as interacting components of a dynamic system. This is taken into account in developing a classification of runways according to surface irregularities and the corresponding dynamic response of the aircraft. Attention is given to the motion of the aircraft as a whole, to vibrations of its parts, and to certain special phenomena, particularly the inverse effect of damping. B.J.

A82-25002 Analysis of the crossed dipole antenna as a model for aircraft in an electromagnetic environment. R. W. Burton (Colorado, University, Colorado Springs, CO) and R. W. P. King (Harvard University, Cambridge, MA). In: *International Symposium on Electromagnetic Waves*, Munich, West Germany, August 26-29, 1980, Proceedings. Munich, International URSI-Symposium, 1981, p. 311 A/1-311 A/4. 14 refs.

The currents and charges induced on the metallic skin of a crossed dipole antenna immersed in an electromagnetic plane wave field are analyzed experimentally and theoretically for both electrically thin and electrically thick arm diameters over a wide range of arm lengths highlighting critical boundary conditions. An analysis is also carried out of electrically thick cylinders with flat plate cross arms. The boundary conditions at the junction of the crossed dipole with electrically thin arms are developed and correlated with experimental results over a range of arm lengths that clearly define the boundary conditions on charge and current in the junction area. The results are interpreted in terms of the forced and resonant currents directly evolved from an understanding of the electrically thin receiving unit. C.R.

A82-25011 Calculation and measurement of electric field strength for airborne antennas in the LF/MF range. R. J. Luebbers and J. Bash (Ohio University, Athens, OH). In: *International Symposium on Electromagnetic Waves*, Munich, West Germany, August 26-29, 1980, Proceedings. Munich, International URSI-Symposium, 1981, p. 334 A/1-334 A/4. 5 refs.

A technique has been developed to calibrate in absolute field strength the loop antenna and associated receiving system for the Automatic Direction Finding equipment for three different aircraft. The calibrated receiving systems are flown at a variety of altitudes over various types of terrains, and field strengths for signals in the desired frequency range are measured. A comparison is made between calculated and measured results, showing good agreement to within a few dB, and confirming the accuracy of both the calibration method and the propagation model. D.L.G.

A82-25050 # AFWAL turbine engine controls research and development - Present and future. L. L. Small (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH). *American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 20th, Orlando, FL, Jan. 11-14, 1982, Paper 82-0321*. 7 p. 9 refs.

It is noted that, within the next few years, digital computer-based engine controls will see operational use in both military and commercial applications. Current and planned activities at the Air Force Wright Aeronautical Laboratories in the areas of multivariable control logic, control system integration, and reliability/flight safety are reviewed. C.R.

A82-25113 # Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data. W. L. Smith (NOAA, National Earth

Satellite Service, Madison, WI) and F. X. Zhou. *Applied Optics*, vol 21, Mar 1, 1982, p 924-928. 5 refs

Algorithms are presented which allow fast retrieval of major meteorological parameters from individual radiance measurements, thereby avoiding the time consuming radiative transfer equation inversion process as required for detailed vertical profile determinations. The relative humidity and geopotential thickness patterns from satellite data are shown to be consistent with radiosonde data. The atmospheric stability index, total-totals, calculated from satellite derived relative humidities and geopotential thicknesses is in good agreement with subsequent convective weather. Computer programs based on the proposed algorithms produce contour displays of the humidity, geopotential thickness, and total-totals within 10 min of the ingestion of the satellite data. V. L.

A82-25119 Aircraft/airport compatibility - A constant challenge for aircraft designers W. E. Parsons and M. E. Wilfert (Douglas Aircraft Co., Long Beach, CA). *Exxon Air World*, vol 34, no 1, 1982, p 18-21, 30.

The consideration given during airport planning and aircraft design to the compatibility of the two systems is described, with attention to the impact of design alternatives on direct, indirect and total operating costs through the reduction of ground time for storage and maintenance. Major aspects of existing and planned airport facilities considered during aircraft design include runway length and width, taxiway width, pavement fillets, and pavement strength, along with the location and accessibility of the various servicing points of the aircraft. Emphasis is placed on the avoidance of sequencing in servicing operations, so that lavatory, water, electrical, pneumatic and air conditioning systems may be readied for flight simultaneously. O. C.

A82-25154 * # The design of a wind tunnel VSTOL fighter model incorporating turbine powered engine simulators R. O. Bailey (NASA, Ames Research Center, Moffett Field, CA), M. R. Maraz, and P. E. Hiley (Douglas Aircraft Co., St. Louis, MO). *American Institute of Aeronautics and Astronautics and NASA Ames Research Center, V/STOL Conference, Palo Alto, CA, Dec. 7-9, 1981, AIAA Paper 81-2635*. 27 p. 8 refs. Contract No. F33615-77-C-2097.

A wind-tunnel model of a supersonic VSTOL fighter aircraft configuration has been developed for use in the evaluation of airframe-propulsion system aerodynamic interactions. The model may be employed with conventional test techniques, where configuration aerodynamics are measured in a flow-through mode and incremental nozzle-airframe interactions are measured in a jet-effects mode, and with the Compact Multimission Aircraft Propulsion Simulator which is capable of the simultaneous simulation of inlet and exhaust nozzle flow fields so as to allow the evaluation of the extent of inlet and nozzle flow field coupling. The basic configuration of the twin-engine model has a geometrically close-coupled canard and wing, and a moderately short nacelle with nonaxisymmetric vectorable exhaust nozzles near the wing trailing edge, and may be converted to a canardless configuration with an extremely short nacelle. Testing is planned to begin in the summer of 1982.

A. L. W.

A82-25213 Conflicts between random flights in a given area S. Ratcliffe and R. L. Ford (Royal Signals and Radar Establishment, Malvern, Worcs., England). *Journal of Navigation*, vol 35, Jan 1982, p 47-71. Discussion, p 72-74. 18 refs.

The present investigation is concerned with the segregation of air traffic in space and a division of the available sky in various sections to minimize conflicts between the various users. Random air traffic in a bounded volume of airspace outside the controlled airspace is considered. It is assumed that aircraft are all in straight line flight. The constraints make it possible to construct a model whose behavior can be defined quantitatively as an algebraic function of the small number of input parameters. Attention is given to a computer model, two-dimensional traffic, the constraints on the use of airspace, conflicts in three-dimensional airspace, the collision rate as a function of traffic mix, and alarm criteria for an advisory service.

G. R.

A82-25216 * # Advanced electronic displays and their potential in future transport aircraft J. J. Hatfield (NASA, Langley

Research Center, Hampton, VA). *International Air Transport Association, Technical Symposium on Aviation Technology in the 80's, Montreal, Canada, Dec 1-4, 1981, Paper 26*. p 29. refs.

It is pointed out that electronic displays represent one of the keys to continued integration and improvement of the effectiveness of avionic systems in future transport aircraft. An employment of modern electronic display media and generation has become vital in connection with the increases in modes and functions of modern aircraft. Requirements for electronic systems of future transports are examined, and a description is provided of the tools which are available for cockpit integration, taking into account trends in information processing and presentation, trends in integrated display devices, and trends concerning input/output devices. Developments related to display media, display generation, and I/O devices are considered, giving attention to a comparison of CRT and flat-panel display technology, advanced HUD technology and multifunction controls. Integrated display formats are discussed along with integrated systems and cockpit configurations. G. R.

A82-25323 # Secondary radar problems - The presence of false echoes (Problemas del radar secundario - Presencia de ecos falsos) M. G. Duran (Paracuellos del Jarama, Centro de Control de Navegación Aérea, Paracuellos del Jarama, Spain). *IAA/Ingeniería Aeronáutica y Astronáutica*, vol 34, Jan 1982, p 5-10. In Spanish.

Techniques are described for the suppression of false radar echoes due to (1) lateral lobe radar responses, (2) radar responses out of synchrony with the signals of the radar system, (3) responses corresponding to signals from previous radar repetition periods, (4) responses produced by a split in the number of echoes from a target aircraft, and (5) responses due to reflections. The most frequently used technique for the correction of these false-echo effects is improved side lobe suppression (ISLS), which involves the emission of radar pulse signals from an omnidirectional antenna. Techniques complementing ISLS include the false return elimination device and transponder suppression transmitter. False echo suppression by data processor programming techniques is also described. O. C.

A82-25324 # Electronic flight instrument systems (EFIS), the instrumentation of the 1980s (La instrumentación de los 80 /E F I S/) J. B. Galente. *IAA/Ingeniería Aeronáutica y Astronáutica*, vol 34, Jan 1982, p 18-23. In Spanish.

The development of high-luminosity, high-resolution color coded CRT systems for the display of symbolic and alphanumeric flight data in cabins of 767/757-type commercial aircraft is discussed. These electronic flight instrument systems (EFIS) depend for their effectiveness on the incorporation of two techniques: (1) the shadow mask tube, derived from the trinitron color CRTs in use in radar color display terminals, and (2) stroke writing, in which each CRT electron gun can prolong its excitation of a given screen area under the control of a microprocessor. Progress in the development and experimental validation of these instruments has been so rapid as to allow general aviation use to begin in 1982. The more extensive use of CRTs in an 'all glass cockpit', pending further development, is also considered. O. C.

A82-25325 # The toll of ILS-preventable aviation accidents (Costo de los accidentes aéreos evitables con ILS) E. L. Abella. *IAA/Ingeniería Aeronáutica y Astronáutica*, vol 34, Jan 1982, p 31-34. In Spanish.

Based on the statistical analysis of Simpson (1975), observations are presented concerning the aviation accidents which occurred in the U.S. from January 1964 to December 1972, with emphasis on landings. An attempt is made to determine the portion of those landing approach accidents that could have been prevented through the use of IFR procedures of a high degree of precision. Results are presented for the cases of commercial aviation, commuter aviation, and general aviation, and comparisons are made with general aviation VFR accidents. All comparative data are presented in tabular form. Attention is given to the estimation of preventable property losses as well as loss of lives. J. C.

A82-25347 † Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles (O zadachakh chislennogo modelirovaniia nestatsionarnykh prostranstvennykh techenii viazkogo gaza v soplakh) A. T. Fedorchenko. *Zhurnal Vychislitel'noi*

Matematika i Matematicheskoi Fiziki, vol 22, Jan-Feb 1982, p. 178-196 26 refs In Russian

The paper examines certain general problems involving the use of the complete Navier-Stokes equations for the numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles. Models of porous boundaries are examined, and their acoustic characteristics are investigated. Attention is given to aspects of the control of gasdynamic (especially acoustic) parameters in such flows. As an example, a numerical analysis is presented of axisymmetric unsteady flows of a viscous gas in a region containing a Laval nozzle.

B J

A82-25353 † Stability of a three-stage dynamic stand (Ob ustoyichivosti trekhstepennogo dinamicheskogo stenda) N V Osadchenko *Akademiia Nauk SSSR, Izvestia, Mekhanika Tverdogo Tela*, Jan-Feb 1982, p. 20-27. 10 refs In Russian

The small-parameter method is used to derive equations of partial motion components for a three-stage dynamic stand designed for simulating the angular motions of moving objects. The fast-motion stability of the system is analyzed using a previously proposed method whereby the stability problem for three-axis systems is reduced to that for single-axis systems. A matrix interpretation of this method is presented, and stability bounds are determined.

V L

A82-25499 Importance of a tactical cargo aircraft in emergency relief (Intérêt d'un avion cargo tactique dans les secours d'urgence) J P Chabanne (Service de Santé pour l'Armée de l'Air, Ecole d'Application, Centre de Recherche de Médecine Aéronautique, Paris, France) and G Jacob (Commandement du Transport Aérien Militaire, Vélizy-Villacoublay, Yvelines, France) *Médecine Aéronautique et Spatiale, Médecine Subaquatique et Hyperbare*, vol 20, no 79, 1981, p. 210-214. 7 refs In French.

The use of the C 160 Transall aircraft in emergency relief operations at the site of medical disasters is discussed. Capabilities of the C 160 allow it to be useful for a number of purposes: (1) the transport of medical personnel and equipment into the disaster region, (2) the medical evacuation of the seriously ill and injured, (3) the resupply of the stricken area with food, fuel and medical supplies, (4) the supplementation of communications damaged by the disaster. Despite limitations in range, velocity and capacity, experience in humanitarian relief operations in Peru, Jordan and Nicaragua has shown its capacity to land on uneven terrain and robustness to make the C 160 a valuable tool in disaster intervention.

A L W

A82-25510 Selection of telecommunication equipment - A new approach to the equivalent cost concept (Choix d'investissements en matériels de télécommunications - Une nouvelle approche de la notion de coût équivalent) M Minoux (CNET, Paris, CNET, Issy-les-Moulineaux, Hauts-de-Seine, France) and A Guerard (CNET, Issy-les-Moulineaux, Hauts-de-Seine, France) *Annales des Télécommunications*, vol 36, Nov-Dec 1981, p. 602-612. 5 refs In French.

In order to apply cost equivalence to the purchase of telecommunication equipment from components with equal functional features, but with different costs and length of payback, an extension of amortization calculations was performed. It is shown that the increase in demand is not necessarily exponential, that the law of variation of optimal cost equivalence can be read directly from the curve of net costs of the equipment under consideration, that actualized costs depend on the criteria of the actual payback period. Each year of functional addition to the operating system is included in the calculations, rather than the projected lifetime. The payback period then becomes the prime criteria for determining the economics of the equipment added incrementally to the capacity of the network. The economics of a linear growth of demand are determined, and then extended to any form of growth with a constant economy-of-scale coefficient.

M S K

A82-25538 Where is cobalt irreplaceable (Wo ist Kobalt unersetzlich) J C Agarwal (Charles River Associates, Inc., Boston, MA) (*International Conference on Cobalt-Metallurgy and Uses, Brussels, Belgium, Nov 10-13, 1981, Paper J Metall*, vol. 36, Mar 1982, p. 292, 293. In German).

It is pointed out that cobalt, at least on a short-term basis, is nearly irreplaceable in connection with certain of its applications, taking into account, in particular, its use in catalysts and in heat-resistant superalloys. Cobalt-containing superalloys are employed in gas turbines and engines, in connection with efforts related to the search for oil reservoirs and their exploitation, and in medical implants. A number of aircraft engines utilize cobalt as alloy component. The irreplaceableness of cobalt on a short-term basis is partly related to the long time required to develop a new aircraft engine. Cobalt is also widely used in the manufacture of permanent magnets. A crucial asset of cobalt with respect to its employment in equipment used for offshore drilling operations is its resistance against hydrogen sulfide and effects of marine climate conditions. Attention is also given to aspects of cobalt production and market trends.

G R

Page Intentionally Left Blank

STAR ENTRIES

N82-18119# Deutsche Gesellschaft fuer Luft- und Raumfahrt
Cologne (West Germany)

SEVENTH EUROPEAN ROTORCRAFT AND POWERED LIFT AIRCRAFT FORUM

1981 951 p refs Proceeding of Conf Held in Garmisch-
Partenkirchen West Germany 8-11 Sep 1981 Original
contains color illustrations

Avail NTIS HC A99/MF A01

Aspects of helicopter and turbine rotor are addressed

N82-18120# Southampton Univ (England) Dept of Aeronautics
and Astronautics

DEVELOPMENTS IN ROTARY WING AIRCRAFT AERODY- NAMICS

I C Cheeseman /in DGLR Seventh European Rotorcraft and
Powered Lift Aircraft Forum 1981 27 p refs

Avail NTIS HC A99/MF A01

Developments in helicopter aerodynamics are reviewed,
including new blade sections and planforms Computer modelling
of the flow and the need for further work in predicting oscillating
loadings are considered The greater attention being given to
the need to reduce drag in forward flight due to extended range
and fuel conservation costs is recognized A forecast of advances
is made

NW

N82-18121# Massachusetts Inst of Tech Cambridge

A SIMPLIFIED APPROACH TO THE FREE WAKE ANALYSIS OF A HOVERING ROTOR

R H Miller /in DGLR Seventh European Rotorcraft and Powered
Lift Aircraft Forum 1981 15 p refs

Avail NTIS HC A99/MF A01

Rotor wake geometry and the number of blades are analyzed
Simplified approaches to the free wake aerodynamic analysis of
hovering rotors permitting rapid evaluation of rotor aerodynamic
characteristics are discussed Analytical results are compared with
existing measurements of blade bound circulation and wake
geometry

NW

N82-18122# Politecnico di Milano (Italy) Istituto di Ingegneria
Aerospaziale

AN EXPERIMENTAL ANALYSIS OF THE SHAPE OF A ROTOR WAKE

Sergio DePonte and Luigi Vigeveno /in DGLR Seventh European
Rotorcraft and Powered Lift Aircraft Forum 1981 8 p refs

Avail NTIS HC A99/MF A01

Although the shape of a rotor wake may be described by
potential flow methods, to get reasonable calculation costs it is
necessary to introduce some simplification in the calculations
In order to check the accuracy and the validity field of the
various assumptions a set of experimental data may be a good
tool for comparisons A hot wire technique to detect the presence
of the blade wake is presented

NW

N82-18123# Tokyo Univ (Japan)

AN EXTENSION OF THE LOCAL MOMENTUM THEORY TO THE ROTORS OPERATING IN TWISTED FLOW FIELD

Akira Azuma Ken-ichi Nasu and Takatoshi Hayashi /in DGLR
Seventh European Rotorcraft and Powered Lift Aircraft Forum
1981 19 p refs

Avail NTIS HC A99/MF A01

The local momentum theory was developed to calculate the
dynamic airloading of a helicopter rotor where the velocity

perpendicular to the plane of rotation was assumed to be negligibly
low in comparison with the rotating velocity In the case of
propellers or windmills, however this assumption is no longer
adequate and the flow field seen in the rotor-fixed-coordinate
system is noticeably twisted along the span In order to permit
calculation of the induced velocity distribution as well as the
airloading of the blade in such a twisted flow field we have
carried out an extension of the local momentum theory Since
our method of calculation is based on the instantaneous circulation
distribution rather than the instantaneous momentum balance, it
may be called the Local Circulation Method The present method
is also applicable to propellers and windmills in yawed flow

Author

N82-18124# Nanjing Aeronautical Inst (China)

A SIMPLIFIED METHOD FOR PREDICTING ROTOR BLADE AIRLOADS

Wahg Shi-cun and Xu Zhi /in DGLR Seventh European Rotorcraft
and Powered Lift Aircraft Forum 1981 28 p refs

Avail NTIS HC A99/MF A01

Relations of first two harmonic induced velocities to the
lower and same-order harmonic circulations are obtained from
the generalized classical vortex theory of the rotor Then, based
on the blade element theory, a closed form of equations for
circulation is established and by taking the flapping condition
into account simplified formulae for predicting rotor blade
airloads are set up In particular expressions of flapping coefficients
are derived including the effect of variable induced velocity
distribution but in terms of blade parameters and flight parameters
only Finally, a calculation of a typical example is made and
comparisons of airloads with those from the more accurate
numerical solution are shown that the present method is fairly
suitable for aerodynamic analysis and preliminary design of
helicopters

Author

N82-18125# Deutsche Forschungs- und Versuchsanstalt fuer
Luft- und Raumfahrt Goettingen (West Germany) Inst fuer
Aeroelastik

A THREE-DIMENSIONAL APPROACH TO LIFT AND MOMENT COEFFICIENTS OF ROTATING BLADES

Wolfgang Send /in DGLR Seventh European Rotorcraft and
Powered Lift Aircraft Forum 1981 16 p refs (For primary

Avail NTIS HC A99/MF A01

The three dimensional incompressible flow around a thick blade
is calculated in the limiting case of an infinitely high Reynolds
number The solution for a four bladed rotor is achieved by
interacting the mutual influence of the induced velocities on the
blades Several properties of the three dimensional approach are
compared with two dimensional theories Unsteady results are
obtained by combining the quasi-steady flow with the calculation
for a given oscillation mode The integral equation for the flow
around the blades is solved by a higher order panel technique
for the vorticity vector, continuous on the blade and downstream
in the wake An improper description of the wake integral is
evident The helical wake is substituted by its rectilinear
counterpart for which an analytical description was found

NW

N82-18126# Societe Nationale Industrielle Aerospatiale,
Marignane (France) Helicopter Div

A COMPLETE METHOD FOR COMPUTATION OF BLADE MODE CHARACTERISTICS AND RESPONSES IN FOR- WARD FLIGHT

J P Lefrancq and B Masure /in DGLR Seventh European
Rotorcraft and Powered Lift Aircraft Forum 1981 9 p

Avail NTIS HC A99/MF A01

Hypotheses and equations methods of calculation and
numerical adaptation concerning the dynamics of helicopter rotors
are dealt with Two problems raised by a spinning rotor are
also dealt with determination of natural models qualified by
their eigen frequency and damping and forward flight using
the azimuth method which avoids those difficulties inherent to
the modal methods The calculation process used to improve a
rotor while at design stage is illustrated

NW

N82-18127# Deutsche Forschungs- und Versuchsanstalt fuer
Luft- und Raumfahrt Goettingen (West Germany) Inst fuer
Aeroelastik

MODAL CHARACTERISTICS OF ROTOR BLADES: FINITE

ELEMENT APPROACH AND MEASUREMENT BY GROUND VIBRATION TEST

D Ludwig /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 23 p refs

Avail NTIS HC A99/MF A01

The mass and stiffness matrices for a rotating blade are established by the finite element method. The formulation is based on the Lagrange function for combined flapwise bending chordwise bending, and torsion of twisted nonuniform rotor blades. The element matrices are created by the non-numeric computer program REDUCE. An ordering scheme was introduced to demonstrate which terms may be simplified or neglected. As examples, eigen analyses with the finite element computer program, are performed for a homogeneous beam and for the nonrotating blade of a wind energy converter. The results of the calculations for the beam are compared with the analytical solutions. The rotor blade of the wind energy converter was tested in a ground vibration test. A short description of the ground vibration test technique and performance is given. NW

N82-18129# Westland Helicopters Ltd Yeovil (England) Dynamics Dept

A STUDY OF THE TECHNIQUES OF DYNAMIC ANALYSIS OF HELICOPTER TYPE STRUCTURES

G M Venn and D J Boon /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 21 p

Avail NTIS HC A99/MF A01

The techniques used in the dynamic analysis of helicopter type structures using finite elements are discussed. A test structure was designed and built which incorporated many design features found in helicopter structures. Experiments were performed on this structure to determine the natural frequencies and normal modes. These experimental results were compared with theoretical finite element results. Altering the build state added one or two extra problems so that these could be studied. The modelling problems investigated were riveted panel-stringer constructions, deep fabricated beams, discontinuous load paths, bolted joints, honeycomb panels, gearboxes, engine mounts, and engines. The techniques used to model these features are discussed. Problems were found when attempting to compare the theoretical and experimental results. NW

N82-18130# Virginia Polytechnic Inst and State Univ., Blacksburg

THE EFFECTS OF SLIGHT NON-LINEARITIES ON MODAL TESTING OF HELICOPTER-LIKE STRUCTURES

D J Ewins (Imperial College of Science and Technology) /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 11 p refs

Avail NTIS HC A99/MF A01

A comprehensive series of modal tests was made on a specially built test piece designed to simulate many of the characteristics of helicopter structures. These tests identified the presence of a 'slight' degree of nonlinearity and further established that this almost unnoticed effect causes significant discrepancies in the modal properties deduced from measured data. However, systematic analysis of the measurements may be used to isolate the nonlinear effects and to eliminate them from the results. Author

N82-18131# Societe Nationale Industrielle Aerospatiale, Marignane (France) Helicopter Div

PARAMETRIC STUDY OF THE INFLUENCE OF THE ENGINE UPON THE OPERATING COST OF A CIVIL HELICOPTER

Gilbert Beziac, Jean-Pierre Dedieu, and Philippe Cabrit /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 5 p

Avail NTIS HC A99/MF A01

The influence of engine characteristics (weight, fuel consumption, price, power range) upon the helicopter operating cost were studied. The parametric relationship between the various factors were defined. Several engine alternatives for a medium weight helicopter were compared. The following conclusions were made: (1) a sufficient power reserve is necessary but too high a value is not profitable; (2) the fuel consumption should be the result of a compromise; interest of a low value, engine complexity, reliability; and (3) a substantial increase in helicopter cost

effectiveness is obtained thanks to a simultaneous evolution of aircraft and engine. MDK

N82-18132# Technische Hogeschool Delft (Netherlands) Dept of Aerospace Engineering

PREDICTION OF OFF-DESIGN PERFORMANCE OF TURBO-SHAFT ENGINES A SIMPLIFIED METHOD

H Wittenberg /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p refs

Avail NTIS HC A99/MF A01

Estimation of the off-design performance of a given gas turbine is generally based on detailed performance characteristics of compressor and turbine(s). An approximate method for the estimation of the off-design behavior of turbojet and turbofan engines was developed using thermodynamic relationships only. The method is based on a matching procedure with generalized mass flow characteristics of the turbine(s) or exhaust nozzle(s). The method was adopted to turbo-shaft engines for this study. Examples are given for an actual engine type. There is fair agreement between the calculated off-design performance and the data derived from the manufacturer's engine brochure. MDK

N82-18133# Rolls-Royce Ltd., Watford (England)

MEASUREMENT TECHNIQUES USED TO ASSESS THE INSTALLED POWER OF A HELICOPTER ENGINE

T G Morton /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p. Original contains color illustrations

Avail NTIS HC A99/MF A01

To improve helicopter performance predictions, it is important to quantify any change in engine performance between the test bed and as installed in the aircraft, and to attribute the reasons for any change as accurately as possible. Measurement techniques used to quantify performance for a particular Rolls-Royce Gem Engine installation is discussed. Extra sensors were added to engines in a production Lynx helicopter which was fitted with recorder equipment in the cabin and flown to a defined schedule. If the engine is considered as a thermodynamic unit, the input/output equation must balance. Test point data based on these inlet and exhaust conditions were obtained from both test bed and flight tests. Analysis of results when compared to a thermodynamic model of the engine, shows that the resultant data is very sensitive to the quality of measurements and will quickly show the deviation from predicted characteristics. Author

N82-18134# Motoren- und Turbinen-Union Muenchen G m b H (West Germany)

COMPONENT DESIGN AND DEVELOPMENT FOR FUTURE HELICOPTER ENGINES

Jean Hourmouziadis and Horst B Kreiner /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p refs

Avail NTIS HC A99/MF A01

Advances achieved today and results available from both rig and demonstrator test programs for present and future helicopter engines are discussed. These will form the basis for further component improvement required to yield a successful next generation engine. The significance of reduced fuel consumption, improved overall system performance, and reliability are considered in relation to design activity and reaction to changing customer needs. MDK

N82-18135# General Electric Co., Cincinnati, Ohio Systems and Controls

THREE-ENGINE CONTROL SYSTEM FOR THE PROTOTYPE EH-101 HELICOPTER

E A Chiuchio and J J Curran /In DGLR Seventh European Rotorcraft and Powered Lift Aircraft 1981 10 p refs

(AEBG-9/81-1568L) Avail NTIS HC A99/MF A01

The T700 control system configured for installation in the three-engined WG 34A helicopter (prototype for European Helicopter Industries EH-101) provides for a versatile control system which may be operated normally to provide the helicopter propulsion or may be operated as a totally independent system to power airframe avionics and power accessories. It is designed to maintain constant speed for accessories or load share with second and third engines and is independent of position in the aircraft. The total system is automatic and provides not only constant rotor speed but also closely matched torques. Modifica-

tions made to the T700 control system to provide the above capabilities are discussed Discussion of the need for these modifications and the present status of the design is also discussed
Author

N82-18136# I A M Rinaldo Piaggio, Finale Ligure (Italy)
ENGINE SUPERFICIAL TEMPERATURE AND INFRARED SIGNATURE

A M Ricci A N Allavena and W Esposti (I C I T E S Giuliano Milanese Italy) /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p

Avail NTIS HC A99/MF A01

A system calibration and data processing method was set up to provide spatial information on temperature and a spatially accurate radiant intensity map under different angles The methodology was developed to evaluate the thermal exchange between engine and engine-cowling and their infrared signature in the 1 - 6 micrometer range in order to evaluate special infrared treatment to reduce infrared emission The infrared imagery camera was coupled to an analogic/digital data acquisition system Calibration studies were conducted in an infrared laboratory to provide the absolute calibration on the thermograph in the previously defined spectral range The results are presented in profiles of temperature and radiance
Author

N82-18137# Societe Nationale Industrielle Aerospatiale, Marnane (France) Helicopter Div
POINT OF VIEW OF A HELICOPTER MANUFACTURER ON AIRWORTHINESS REGULATIONS

Jean Boulet /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 5 p

Avail NTIS HC A99/MF A01

Helicopter airworthiness regulations are discussed The need for airworthiness regulations to be drafted and modified through a process of constant consultation between Civil Aviation Authorities and manufacturers is discussed The need to introduce the concept of probability to be able to come closer to the actual risks and to avoid penalizing aircraft with useless systems and demonstration requirements is also considered It is suggested that these regulations tend toward one single international set of regulations and one single demonstration of compliance with the regulations The possibility of reconciling a continuously improved safety level and a progressive reduction in helicopter costs is also considered
M D K

N82-18138# Italian Army General Staff, Rome
MILITARY REQUIREMENTS, TOO LITTLE OR TOO MUCH
Emidio Valente /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 18 p

Avail NTIS HC A99/MF A01

Concepts useful for a better understanding of the military requirements, operational requirements for helicopters are discussed The need for an understanding between military operators of rotary-wing aircraft, helicopter designers, and manufacturers is considered Two viewpoints are summarized (1) The helicopter is a weapon system featuring the same indispensability level of all other systems required to integrate the battlefield (2) The helicopter must be designed to reflect military requirements which cover all those elements likely to condition its operation this is to say operational environment, human factor and economical aspects The following considerations are recommended for further investigation (1) whether commercial operators are really affected and (2) whether solutions can be found which in the end prove to be a saving rather than a deterioration in cost weight and complexity
M D K

N82-18139# Italian Air Force Pratica di Mare Rome Flight Test Centre
PARAMETRIC CRITERIA AND IMPACT ON DESIGN TRENDS

Roberto dePompeis and Fulvio Gagliardi (Ministry of Defence) /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 25 p refs

Avail NTIS HC A99/MF A01

Laws or trends of typical parameters which contribute to the definition of an 'ideal' specific helicopter which can be used as a reference model and give a nondimensional measure of

effectiveness are discussed Operative requirements, taking into account the main factors affecting missions were transferred into a mathematical model The procedure was derived from theoretical studies already applied to aircraft selections and consists of three main steps (1) Effectiveness program (2) Total operating cost estimation and (3) Evaluation of effectiveness-cost ratio and optimization of the fleet selection All costs (manufacturing, maintenance, training, operating, etc) for the operative life are estimated with a similar methodology and lead to the determination of the effectiveness-cost ratio which may be optimized taking into account the fleet consistency required to fulfill the task
M D K

N82-18140# Hughes Helicopters, Culver City, Calif
DESIGN PHILOSOPHY OF THE HUGHES MODEL 600 HELICOPTER

R S Taylor /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p

Avail NTIS HC A99/MF A01

The design philosophy of a new model helicopter, the Hughes model 600X, which took into consideration a number of factors is discussed The following subjects are discussed and a rationale for the selected approach is given (1) whether to grow or develop a totally new configuration To be cost effective, a growth helicopter would need to produce significant additional advantages which would be offset by the ever present compromises of the old design, (2) how to grow an 'egg', especially one with internal structure, (3) how to replace the old model or is the new model to be produced in addition to the old one, and (4) how is the market potential to be assessed Details of approaches are presented with reasons for accepting or rejecting each one Results of market analysis and response of the helicopter public is presented to show the viability of the selected configuration
M D K

N82-18141# United Technologies Corp, East Hartford Conn
Aircraft Div

SH-608 TEST PROGRAM

Frederick J Silverio /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p

Avail NTIS HC A99/MF A01

The SEAHAWK Program, a successful helicopter development program, is discussed in detail The following program tests are described modifications for shipboard compatibility and mission requirements, preflight ground tests, flight and shakedown testing, evaluation of the pitot-static system and digital computer system, reliability tests and component systems analysis Failure modes not detected in flight tests or qualifications bench tests, but discovered in testing under service use, are discussed
M D K

N82-18142# Societe Nationale Industrielle Aerospatiale, Marnane (France) Helicopter Div
NAVAL VERSIONS OF THE DAUPHIN AND THE AS 15 TT WEAPON SYSTEM

J P Dubreuil /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 10 p

Avail NTIS HC A99/MF A01

Aerospatiale's Dauphin II helicopter family, initially intended to satisfy civil market demand, is presently subject to development that makes it possible to derive military versions from it The equipment specific to naval versions whose basic system is the AS 15 TT is discussed in detail All the arrangements and modifications that were necessary to adapt the N aircraft to naval, rescue and attack missions and which led to the SA 365 F version are discussed The AS 15 TT and surface vessel system are described in detail The modifications which affected almost all the constitutive elements and aimed at improving not only performance but also maintenance led to a reduction in fabrication and operation costs
M D K

N82-18143# Westland Helicopters Ltd Yeovil (England)
ARMY LYNX. PRODUCT DEVELOPMENT MATCHED TO MILITARY COMBAT DEVELOPMENT

D A S Howell /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p

Avail NTIS HC A99/MF A01

The Lynx helicopter program to date and planned product

N82-18144

development related to the evolution of military combat thinking especially the anti-armour role are presented The background for this product development is the impact of technology in the areas of materials, sensors, armaments and systems, both in the context of the helicopter as a total weapon system and the development of air defense systems that pose a threat to the helicopter in the battlefield scenario Author

N82-18144# Societe Nationale Industrielle Aerospatiale, La Courmeuve (France)

A LIGHT HELICOPTER FOR NIGHT FIRING

J F Candau /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 18 p

Avail NTIS HC A99/MF A01

Structural design criteria and armament system requirements for a flight combat helicopter for night firing are discussed Helicopter characteristics and performance requirements for night time antitank missions are considered The following areas of consideration are discussed piloting, navigation, target seeking, and firing Operational use crew organization, and program development are also reviewed M D K

N82-18145# Dornier-Werke G m b H, Friedrichshafen (West Germany)

TETHERED ROTORPLATFORMS AND THEIR MISSION POTENTIAL

W Goeller /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 13 p

Avail NTIS HC A99/MF A01

A definition of tethered rotorplatforms is given and the main objectives that are pursued with these vehicles are presented A short retrospect on rotorplatform history is given The Dornier 'Kiebitz' is described It is designed to lift payloads for battlefield surveillance air defense, EW or communication to some hundred meters above ground for long mission times A very small tethered rotorplatform for elevating electro optical sensors of 5 to 10 kg is described The energy for its flight time of about 70 seconds is stored in a massive momentum ring surrounding its rotor Finally, a proposed rotorplatform with an electric drive system for payloads of about 30 kg for target acquisition and target designation, is also discussed M D K

N82-18146# Southampton Univ (England)

WIND TUNNEL INVESTIGATION OF HIGH SPEED ROTOR NOISE

H Tadghighi and I C Cheeseman /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 25 p refs

Avail NTIS HC A99/MF A01

A high speed model rotor (tip Mach number of 0.75) was developed to investigate tail rotor noise in forward flight conditions The existing 2.1 by 1.5 m low speed (30 m/sec) closed circuit wind tunnel was modified and utilized to enable acoustic measurements of forward flight to be made Check tests in the 24 ft anechoic wind tunnel show excellent agreement with the development tests The model rotor noise data are found to correlate well with full scale helicopter rotor values Simultaneously recorded aerodynamic performance of the model rotor (blade loading, steady thrust, torque and trimmed moments) is compared with theoretical aeroacoustic treatments It is concluded that the model rotor accurately simulates full scale rotor aeroacoustic data J M S

N82-18147*# Army Research and Technology Labs, Moffett Field, Calif Aeromechanics Lab

PREDICTION OF BLADE VORTEX INTERACTION NOISE FROM MEASURED BLADE PRESSURE

Yoshiya Nakamura /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 20 p refs Sponsored by NASA

Avail NTIS HC A99/MF A01 CSCL 0.A

The impulsive nature of noise due to the interaction of a rotor blade with a tip vortex is studied The time signature of this noise is calculated theoretically based on the measured blade surface pressure fluctuation of an operational load survey rotor in slow descending flight and is compared with the simultaneous microphone measurement Particularly, the physical understanding of the characteristic features of a waveform is extensively studied in order to understand the generating mechanism and

to identify the important parameters The interaction trajectory of a tip vortex on an acoustic planform is shown to be a very important parameter for the impulsive shape of the noise The unsteady nature of the pressure distribution at the very leading edge is also important to the pulse shape The theoretical model using noncompact linear acoustics predicts the general shape of interaction impulse pretty well except for peak amplitude which requires more continuous pressure information along the span at the leading edge Author

N82-18148# Westland Helicopters Ltd Yeovil (England)

PRELIMINARY THOUGHTS ON HELICOPTER CABIN NOISE PREDICTION METHODS

J S Pollard /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 14 p refs

Avail NTIS HC A99/MF A01

The problems of predicting helicopter cabin noise are discussed with particular reference to the Lynx helicopter Available methods such as modal analysis adopted for propeller noise prediction do not cope with the higher frequency discrete tone content of helicopter gear noise, with the airborne and structure-borne noise contributions Statistical energy analysis methods may be the answer but until these are developed, one has to rely on classical noise transmission analysis and transfer function methods Author

N82-18149# Royal Aircraft Establishment Farnborough (England) Aerodynamics Dept

THE MEASUREMENT OF THE MOBILITY OF STRUCTURES AT ACOUSTIC FREQUENCIES

Susan M Damms /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 21 p refs

Avail NTIS HC A99/MF A01

The development of a technique to measure the response of structures to vibrational input forces and moments is described So far, simple structures with known properties have been used but it is intended to apply the technique in the design of an interface which isolates vibrationally the gearbox of a helicopter from the cabin at acoustic frequencies In a first experiment, no moments were applied The main object was to demonstrate that measurements could be made on two components of a structure with sufficient accuracy to correctly predict measurements on the assembled structure The two components were a beam and a dynamic absorber In a second experiment a special block was attached to a beam to enable forces and moments to be applied and translations and rotations to be measured The particular mobilities measured were chosen so that they could be easily compared with theory and also with measurements without a block J M S

N82-18150# Messerschmitt-Boelkow-Blohm G m b H, Munich (West Germany)

FLIGHT CHARACTERISTICS DESIGN AND DEVELOPMENT OF THE MBB/KHI BK117 HELICOPTER

H Huber and T Masue (Kawasaki Heavy Industries) /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 21 p refs

Avail NTIS HC A99/MF A01

The BK 117 light twin-engine helicopter was designed to provide high flexibility of operations attractive performance characteristics, and outstanding handling qualities Dominant features result from the hingeless rotor system which provides inherent high control power and high angular velocity damping Further optimization is achieved through refinement of the fuselage aerodynamic design, and by a proper layout of the empennage configuration taking into account the interactional aerodynamic phenomena The particular design features and their impact on the helicopter flight characteristics are described The results obtained in the areas of static and dynamic stability (longitudinal lateral directional), control response and maneuver characteristics aeromechanical stability and loads and vibrations are presented, including correlation of flight test data with computer model simulations J M S

N82-18151# Politecnico di Milano (Italy) Dipartimento di Ingegneria Aerospaziale

A GENERAL PURPOSE PROGRAM FOR ROTOR BLADE DYNAMICS

M Borri, M Lanz and P Mantegazza /n DGLR Seventh European

Rotorcraft and Powered Lift Aircraft Forum 1981 15 p refs

Avail NTIS HC A99/MF A01

A computer program for rotor blade dynamics capable of dealing both with hinged and hingeless rotors, suitable for steady state flight analysis and stability evaluation was developed. Blade motion is represented by finite elements in the space-time domain covering the span of one or more rotor revolutions and allowing for different nonlinearities. This method gives a flexible unitary approach for the very different model complexities required by the different design phases, such as the simplest rigid blade schemes and the more sophisticated ones including nonlinearities arising from large blade flexibilities and large movements in control links. The aerodynamics at the present development state, considers prescribed wake geometry and blade element theory, including stall and compressibility effects. J M S

**N82-18153# National Aerospace Lab Amsterdam (Netherlands)
A CONTROL MODEL FOR MANEUVERING FLIGHT FOR
APPLICATION TO A COMPUTER-FLIGHT TESTING PRO-
GRAM**

H Havendings /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p refs

Avail NTIS HC A99/MF A01

A computer-flight-testing (CFT) program for helicopters to evaluate helicopter dynamics and handling and control qualities is described. The nonlinear six degrees of freedom helicopter model is driven by control inputs generated by a specially developed control model (or pseudo pilot) to eliminate problems in estimating control inputs during maneuvering flight. This is an adaptation of a linear optimal control model as used in human factor analysis. The helicopter model is based on two-dimensional strip aerodynamics steady-state rotor blade dynamics using only out-of-plane bending mode shapes, which are suitable for various types of rotor articulation. The pilot model consists of a flight path generation (FPG)-model and a stabilization (STAB)-model. The FPG-model is based on linearized system dynamics using terminal optimal control, generating both required flight path and the control inputs to achieve it. These controls are input into the helicopter model. The two flight paths are compared, and differences are fed back to the STAB-model to generate corrective control inputs of such a nature that the helicopter-model-generated flight path tracks the required flight path generated by the FPG-model. Also the STAB-model is based on linearized system dynamics. As an example, two flare maneuvers are 'flown', and the results discussed. The pseudo-pilot model performs well, provided that helicopter dynamics do not change much during a specific maneuver. J M S

**N82-18154# Westland Helicopters Ltd Yeovil (England)
THE ROLE OF SIMULATION IN THE DESIGN PROCESS**

I F Montgomerie and G C F Wyatt /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p

Avail NTIS HC A99/MF A01

Real-time simulation of helicopters and their avionic systems is discussed. The nature of the problems facing the helicopter and systems designers are reviewed, and the potential benefits accruing from the timely and effective use of simulation are examined. The development of simulation as a design tool over the last two decades are reviewed, and the characteristics of the simulation facilities are described. J M S

**N82-18155# Royal Aircraft Establishment, Farnborough (England)
PRELIMINARY INVESTIGATION INTO THE ADDITION OF
AUXILIARY LONGITUDINAL THRUST ON HELICOPTER
AGILITY**

P J Legge, P W Forestcue (Southampton Univ) and P Taylor (Southampton Univ) /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p refs

Avail NTIS HC A99/MF A01

The agility requirements in specific maneuvers performed by military helicopters are investigated. A simple mathematical simulation of the helicopter accelerating and decelerating longitudinally is used to examine the advantages of auxiliary thrust. For helicopters operating in the Nap-of-Earth environment the longitudinal acceleration and deceleration performance

is shown to be uniquely important. Large improvements in agility measured by a performance function, are obtained by adding auxiliary thrust. The need for the helicopter to change its attitude is drastically reduced, and the pilot workload improved. The type of flight profile used is also examined using a nondimensional Froude number. There was no benefit in a maximum effort flight profile, which consequently further improves the pilot workload. Auxiliary thrust improved agility performance by increasing the helicopters ability to change position while maintaining precise attitude control. J M S

**N82-18156# National Defence Academy, Yokosuka (Japan)
Dept of Aeronautical Engineering
OPTIMUM PERFORMANCE AND WAKE GEOMETRY OF
CO-AXIAL ROTOR IN HOVER**

Tomoari Nagashima and Kenji Nakanishi /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p refs

Avail NTIS HC A99/MF A01

Numerical studies to clear out the rotor-wake interference effects on the optimum performance and wake geometry of a coaxial rotor in hover are performed using the generalized momentum theory and the simplified free wake analysis. For applying the momentum concept to the performance predictions of the coaxial rotor system each wake of rotors and flow fields around them are modeled so as to properly incorporate wake contractions, rotational velocities and nonlinear mutual interference effects. In case of the free wake analysis, it is approximated by a finite number of discrete circular vortices whose numbers and core radii are deduced from the sensitivity analysis. The numerical results clearly show that the performances and its wake geometries are largely dependent on the axial spacings and the pitch differences between rotors and there are unique combinations of them which could produce the optimum performance. It is also understood that the upwash effect of the contracted upper rotor wake on the lower rotor plays a fundamental role to improve the hover performance with coaxial rotor arrangement. Author

**N82-18157# Tokyo Univ (Japan) Inst of Interdisciplinary Research
A NUMERICAL APPROACH TO CO-AXIAL ROTOR
AERODYNAMICS**

Shigeru Saito and Akira Azuma /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p refs

Avail NTIS HC A99/MF A01

In the simple momentum theory, the aerodynamic characteristics of the lower rotor of a coaxial rotor system are usually evaluated under the highly deteriorated conditions caused by the fully developed wake of the upper rotor specifically under the conditions of hovering flight. Analysis using the Local Momentum Theory not only shows the performance of the lower rotor to be higher than that calculated by the simple momentum theory but also makes it possible to calculate the instantaneous airloading of blades operating in a complex wake system. By introducing the radial shrinkage of the rotor wake, the accuracy of the analysis of blade airloading is further improved. The calculated results are compared with those of wind tunnel tests in both hovering and forward flights. In forward flight the performance of the lower rotor improves not only with increases in the forward speed but also with increase in the vertical distance between the upper and lower rotors. In hovering flight, the improvement in the performance is not remarkable because the lower rotor is strongly influenced by the upper rotor wake. Author

**N82-18158# Institut fuer Flugmechanik, Brunswick (West Germany)
HELICOPTER ROTOR DOWNWASH - RESULTS OF
EXPERIMENTAL RESEARCH AT THE DFVLR-ROTOR TEST
STAND AND THEIR COMPARISON WITH THEORETICAL
RESULTS**

B Junker and H-J Langer /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 23 p refs

Avail NTIS HC A99/MF A01

System tests and dynamic researches at the rotor test stand were compared with several downwash measurements to demonstrate the dependency between mathematical parameter values and rotor control values, e.g. thrust advance ratio and

N82-18159

control angles. For comparisons mathematical models like the local momentum theory, and a fixed vortex model were applied. For these experiments a four bladed hingeless rotor and a two bladed See Saw rotor (with an advance ratio of up to $\mu = 0.2$) were used. Numerous tests were performed to study the flow field of rotor downwash in different wind tunnels. The measuring equipment for the downwash was set up on both sides of the rotor stand. So it was possible to receive two values at the same time. At first pneumatic probes were applied that gave acceptable mean values, and then hot-wire probes in X-configuration were used to investigate downwash dynamics in more detail. Measurements were conducted in the x-z-plane. Wind tunnel test results, correlation to the mathematical models and errors are discussed. J M S

N82-18159* Ohio State Univ., Columbus Dept. of Mechanical Engineering

HOVER TESTS OF A MODEL H-FORCE ROTOR

H R Velkoff /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p refs

(Contract NCA2-OR565-001)

Avail NTIS HC A99/MF A01

The potential of using tip vanes at the ends of helicopter rotor blades to obtain a controllable H-force is considered. The addition of vanes placed perpendicular to the blade tips can be used to obtain an inplane force. By varying the angle of the vanes a radial force can be created which can be controllable in azimuth position. Such a force could be used to provide translational motion of the rotor and aircraft without the requirement for rotor tilting. In addition an H-force generated at high flight speed could be used as a propulsive force in a manner similar to a propeller. The force generated by the vanes could also affect the aircraft's stability characteristics. The H-force could also modify rotor performance in hovering since they could be thought to act as a virtual shroud. Tests were run with a model rotor which has a 6 foot diameter with a 3 inch chord blade. Test data are presented on the effects of various tip-vane configurations on the hovering figure of merit. The extreme sensitivity of the performance to vane arrangement is shown.

Author

N82-18160* Messerschmitt-Boelkow-Blohm G m b H Munich (West Germany)

THE PROBLEM OF CALCULATION OF THE FLOW AROUND HELICOPTER ROTOR BLADE TIPS

H Stahl /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 18 p refs

Avail NTIS HC A99/MF A01

There are special problems with the theoretical analysis of the flow around helicopter rotor blade tips that are based on the fact that the flow is three dimensional unsteady, rotational and on the advancing blade in fast forward flight also transonic. Theories for this problem based upon potential flow theory are presented. Calculations show that this approach can lead to a sufficient description of the actual flow. Computer programs for the three dimensional steady and the unsteady two dimensional flow past fixed wings were modified for rotating rotor blades. Results are shown. T M

N82-18161* Office National d'Etudes et de Recherches Aeronautiques, Paris (France)

APPLICATION OF THE ONER DYNAMIC STALL MODEL TO A HELICOPTER BLADE IN FORWARD FLIGHT

C T Tran and D Falchero (SNIA Marignane France) /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 26 p refs

Avail NTIS HC A99/MF A01

The model was applied to the case of a helicopter rotor system in forward flight. Aspects of stability and periodic response are described and include the form of the Floquet modes-subharmonic oscillation and almost periodic oscillation, the evolution of these modes as functions of the rotor advance ratio, the periodic response and aerodynamic force and moment, and a comparison with a quasi-steady aeroelastic calculation showing the effects of unsteady phenomena. T M

N82-18162* Royal Aircraft Establishment, Farnborough (England)

SOME UNSTEADY AERODYNAMIC EFFECTS ON HELICOPTER ROTORS

P G Wilby, M J Riley and Judith Miller /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 14 p refs

Avail NTIS HC A99/MF A01

Unsteady effects have an important influence on the aerodynamic loading experienced by a helicopter rotor in forward flight. These effects include dynamic stall characteristics with the associated stall delay and large nose-down change in pitching-moment. All unsteady effects must be taken into account when predicting rotor loads, performance and flight envelope. However the full unsteady effects on the rotor result from simultaneous oscillatory variations of both incidence and Mach number, and it is difficult to study these effects in isolation from the rest of the rotor environment. Empirical methods for modelling these effects, especially dynamic stall characteristics, were developed and incorporated in the rotor loads prediction methods. Results from a program of work involving oscillatory aerofoil tests, flight experiments and unsteady aerodynamic prediction methods are presented. T M

N82-18163* Messerschmitt-Boelkow-Blohm G m b H Munich (West Germany)

SEPARATED FLOW AROUND HELICOPTER BODIES

G Polz and J Quentin /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p refs

Avail NTIS HC A99/MF A01

On the rear part of the helicopter fuselage, flow separation is often unavoidable owing to the shape of the afterbody which is often defined more in accordance with operational requirements (for example cargo door) and with only minor consideration to aerodynamic aspects. Because of the separated flow an analytical calculation of the flow field using potential flow theory is not possible. After an overview about the separated flow phenomena a method is explained based on a combination of panel methods with boundary layer analysis. In this method the wake flow region is represented by a wake body which consists of a uniformly distributed vorticity. Calculated pressure distributions and flow fields are shown in comparison with wind tunnel test results. The main interest lies in the more downstream part of the wake which is very important for the tail surface and tail rotor effectiveness. Author

N82-18164* Southampton Univ (England) Dept. of Aeronautics and Astronautics

A METHOD OF PREDICTING FUSELAGE LOADS IN HOVER

P Taylor /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 13 p refs

Avail NTIS HC A99/MF A01

A computer program called DOWNLOAD was developed in which the fuselage separated flow is modelled using a vortex sheet representation. The vortex sheet model can predict the separated flow pressure distribution provided the separation point is known. Unfortunately the poor behavior of the vorticity vector in the separation region prevents an accurate prediction of the separation line. DOWNLOAD was applied to three simple fuselage shapes with a simple triangular representation of the rotor downwash. The predicted download values were in the lower region of the figures usually quoted as a percentage of thrust. T M

N82-18165* Messerschmitt-Boelkow-Blohm G m b H Munich (West Germany)

IMPACT OF SYSTEMS TECHNOLOGY AND INTEGRATION ON HELICOPTER DESIGN

K Schymanietz /in DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 20 p refs

Avail NTIS HC A99/MF A01

A helicopter design depends on a variety of parameters, criteria and requirements. A new design is generated either by a direct order of a customer or due to industrial investigations in the different fields like market trend studies, application of advanced or new technologies and/or overall efficiency improvements. A complete design includes not only the vehicle design with its main functional groups but also the integration of the systems/equipment concept. In the past a new helicopter design was conducted mainly due to the task for a new vehicle. The

fact that - especially in the military field - the impact of systems gets an increasing influence in all design areas gives an impression of the importance of systems technology and integration in the helicopter design. Future changes in design concepts are considered in terms of the chronological advance in the design of the different system components: new technologies for new systems, e.g. in the field of visionics and system architecture based on a digital bus connection. T M

N82-18166# Army Aviation Research and Development Command St Louis, Mo

REVIEW OF HELICOPTER MAST MOUNTED SIGHT (MMS) BASE MOTION ISOLATION AND LINE-OF-SIGHT (LOS) STABILIZATION CONCEPTS

Daniel P Schrage / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 16 p refs

Avail NTIS HC A99/MF A01

Incorporation of a MMS or any precision stabilized pointing system on a helicopter is a complex and interesting dynamic design problem which combines automatic control through a servomechanism with vibration reduction techniques. Generally the helicopter disturbance inputs to the MMS must be accommodated by a stiffer MMS structure and servo-system. However weight and cost are usually critical and many benefits could be derived from incorporation of a lightweight vibration isolator. There are important design considerations on both sides of the interface, the airframe and the MMS. A review of these design considerations and several vibration isolation concepts is presented. The need for adequate simulation modeling of this complex dynamic environment is discussed. T M

N82-18167# Messerschmitt-Boelkow-Blohm G m b H Munich (West Germany)

MAST MOUNTED VISUAL AIDS

R D vonReth / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 24 p refs

Avail NTIS HC A99/MF A01

Initial flight tests with a spherical mock up, having the same shape, weight and moments of inertia as the actual system were carried out on a Bo 105 with two different rotormast extensions (90 and 120 cm). A vibration survey over most of the Bo 105's flight envelope showed vibrational loads which can be tolerated by the actual system. As a next step the actual stabilized platform with FLIR, TV-camera and laser range finder was installed on the rotormast. In addition several subsystems used for the display of the video images with superimposed symbology are described. For direct comparison purposes three different systems: head up, head down and helmet mounted sight and display were evaluated. The influence of the rotorplane vibrational loads and meteorological conditions on the performance of the FLIR image is described. T M

N82-18168# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany) Inst fuer Flugfuehrung

EXPERIMENTAL INVESTIGATION OF VISUAL AIDS FOR HELICOPTERS LOW LEVEL FLIGHT AT NIGHT AND POOR VISIBILITY

R Beyer, E Danneberg, E Kohnen and H Stein / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 15 p refs

Avail NTIS HC A99/MF A01

The potential and the limitations of advanced display systems for visual aids in helicopters were investigated. A combination of the sensor image and computer generated instrument displays in a head-down display, helmet mounted sight/display and night goggles were evaluated. The layout of the instrument display is considered assuming transport mission and various display modes are implemented. The visual aids were flight tested in Bo 105 and Bell UH-1D helicopters with particular emphasis on the usefulness of the display modes on flight performance and low level flight performance. T M

N82-18169# Litton Systems (Canada) Ltd., Toronto (Ontario) Advance Programs

THE MULTI MODE MATRIX FLAT PANEL DISPLAY TECHNOLOGY AND APPLICATIONS

A Moffat and P Wright / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 19 p refs

Avail NTIS HC A99/MF A01

An important aspect of current developments in advanced cockpit design is the introduction of a small number of interactive multi-function electronic displays with digital data processing in conjunction with a MIL-STD-1553 type of multiplex data bus in an integrated system as opposed to the conventional approach of large numbers of stand-alone electro-mechanical instruments and a variety of different and independent dedicated inputs. Advances in high speed vector graphic display systems based on modular LED flat panel technology and micro-programmable multiprocessor data handling with MIL-STD-1553B compatible interfaces are described. Applications and systems performance are discussed in terms of typical military airborne mission-oriented display image formats and associated hardware and software characteristics. The real-time vector graphic presentations as described include flight control, navigation, communications, engine and fuel management, weapons management, symbolic map, signal communication and other types of real-time cockpit advisory information. T M

N82-18170# Bodenseewerk Geraetetechnik G m b H, Ueberlingen (West Germany)

A REDUNDANCY CONCEPT FOR A DIGITAL CSAS

P Wuest and M Keller / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 12 p refs

Avail NTIS HC A99/MF A01

One of the promises of digital technology is the possibility of implementing more intelligent monitoring techniques for example, self monitoring methods. Typical redundancy and monitoring concepts, which were realized in aircraft, helicopter and engine control systems were reviewed. A system which was originally not designed for a helicopter application but which shows all characteristics of a CSAS is described. The system is based on two essentially autonomous computing lanes each able to provide all the necessary control and monitoring functions. T M

N82-18171# Newmark (Louis) Ltd., Croydon (England)

THE INFLUENCE OF SENSOR AND ACTUATOR CHARACTERISTICS ON OVERALL HELICOPTER AFCS DESIGN

S G Spreadborough / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p

Avail NTIS HC A99/MF A01

The overall performance of a flight control system is dependent on the characteristics of sensors-type and performance, control law, computing and logic actuation-performance, configuration redundancy and authority. The specifications in each of these areas are considered in producing an integrated AFCS design which is compatible with the basic aircraft characteristics. The choice of sensors and the configuration and performance of the actuation, important decisions involving a high level of interdependence with the control law and system logic design, are discussed. T M

N82-18172# Institut fuer Flugmechanik Brunswick (West Germany)

EVALUATION OF THE HELICOPTER LOW AIRSPEED SYSTEM LASSIE

J Kaletka / In DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 23 p refs

Avail NTIS HC A99/MF A01

To evaluate the airspeed sensing capability and the dynamic response characteristics of the system, both flight tests and wind tunnel tests were conducted. The system uses a swivelling pitot static probe designed to operate within rotor downwash in the low airspeed regime and out of downwash for higher speeds. Due to nonlinearities in the sensor transition phase an accurate system characterization is necessary to obtain reliable airspeed data. Flight tests that were conducted to characterize the system for a Bo 105 helicopter are described. The evaluation method and results, showing uncalibrated and calibrated data are discussed in detail. To investigate the dynamic behaviour of the system, dynamic tests in a wind tunnel equipped with a gust generating system were conducted. LASSIE transfer functions were measured for four different wind tunnel speeds. Representative results are shown and discussed. T M

N82-18173# Elektronik-System G m b H Munich (West Germany)

INTEGRATION OF INERTIAL SENSORS IN HELICOPTERS

Volkmar Held /n DGLR Seventh European Rotorcraft and Powered Lift Aircraft Forum 1981 17 p
Avail NTIS HC A99/MF A01

The demand for saving weight, volume and especially cost requires new design concepts for avionic systems. In future, highly integrated systems will replace the conventional systems with specific stand-alone equipment for each system function. A concept for the integration of inertial function flight control, sight-stabilization, navigation of a helicopter is presented. A configuration with a minimum number of dislocated inertial sensors is proposed. The system functions are accomplished on system level by integration and multiple use of the sensor signals. It is shown that the navigation functions, attitude and heading can be derived from the flight control and stabilization hardware so that the usually required separate attitude and heading reference system for the navigation is saved. Moreover, the proposed concept provides as an additional function the autonomous initial alignment to north. TM

N82-18179*# National Aeronautics and Space Administration Ames Research Center, Moffett Field, Calif
AN ANALYTICAL INVESTIGATION OF THE FREE-TIP ROTOR FOR HELICOPTERS
Robert H Stroub Feb 1982 30 p refs
(NASA-TM-81345, A-8806) Avail NTIS HC A03/MF A01 CSCL 01A

A rotor configuration called the free-tip rotor was analytically investigated for its potential to improve helicopter forward-flight performance characteristics. This rotor differs from a conventional rotor only in the blade tip region. In this configuration, the tip is self-adjusting in pitch with respect to the rest of the blade, in accordance with a moment balance about its pitch axis. With this self-adjusting capability, the resulting pitch motion generates a more uniform airload distribution around the azimuth. Computer math models were used to compare performance characteristics of the free tip rotor with those of a conventional rotor operation at flight speeds from 130 to 160 knots. The results of this analysis indicate that the free-tip rotor improves cruise lift-drag ratio by at least 22%. Author

N82-18183*# National Aeronautics and Space Administration Langley Research Center Hampton Va
SPIN-TUNNEL INVESTIGATION OF A 1/13-SCALE MODEL OF THE NASA AD-1 OBLIQUE-WING RESEARCH AIRCRAFT
William L White and James S Bowman Jr Feb 1982 28 p ref
(NASA-TM-83236 L-14834) Avail NTIS HC A03/MF A01 CSCL 01A

The spin and recovery characteristics of a 1/13-scale model of the NASA AD-1 oblique-wing research aircraft at wing-skew positions of 0, 25, 45 and 60 deg (right wing forward) were investigated. Spins were obtained for all wing-skew positions tested. For the unskewed wing position two spin modes were possible. One spin mode was very steep and recoveries were obtained within 1 turn or less by rudder reversal. The second spin mode was flat and fast the angle of attack was about 75 deg and the spin rate was about 145 deg/sec (2.5 seconds per turn). For the skewed wing positions spins were obtained only in the direction of the forward-skewed wing (right wing forward). No spins were obtained to the left when the wing was skewed with the right wing forward. Recoveries should be attempted by deflecting the rudder to full against the spin the ailerons to full with the spin, and movement of the wings to 0 deg skew. If the wing is skewed the recovery may not be effected until the wing skew approaches 0 deg. BW

N82-18187# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany) Betriebsbereich
ON THE CALCULATION OF TRANSONIC BLADE TIP FLOW FOR HELICOPTER ROTORS [ZUR BERECHNUNG DER TRANSSONISCHEN BLATTSPITZENSTROMUNG BEI HUBSCHRAUBERROToren]
H Stahl and V Mikulla 8 May 1981 27 p refs In GERMAN Presented at DGLR Jahrestagung 1981, Aachen 12-14 May 1981
(MBB-UD-320-81-O DGLR-81-025) Avail NTIS HC A03/MF A01

Blade element theory (two dimensional) based on the rotor calculation program, its radials and its chronological relationship was demonstrated. Blade tip flow is three dimensional and

interstationary and the forward moving blade in a fast forward flight becomes transonic. Theories based on potential theory are proposed, though these do not perform on rotary wings. This method demonstrates the real flow rate. A three dimensional calculation of the aerodynamic characteristics of the fixed wings was utilized, to show that by introducing a Mach number per gradient along the rotor radius, rotor calculation can be modified. Transl by EAK

N82-18188# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany)
ON THE CALCULATION OF SEPARATED FLOW ON HELICOPTER FUSELAGES [ZUR BERECHNUNG DER ABGELOESTEN STROEMUNG AN HUBSCHRAUBER-RUEMPFEN]
G Polz 11 May 1981 28 p refs In GERMAN Presented at DGLR Jahrestagung 1981 Aachen 12-14 May 1981
(MBB-UD-321-81-O DGLR-81-026) Avail NTIS HC A03/MF A01

Separated flows in helicopters with dead water formation on the fuselage tail were examined. A model was developed which is based on a combination of panel and interface calculation method, which is simulated in the dead water area by a similar circulation coated track alignment body. The point of gravity lies more on the fuselage, which is especially significant for helicopter, because of its effect on tail rotor and tail plane. Results from wind tunnel tests and flight tests are presented. Transl by EAK

N82-18189# Messerschmitt-Boelkow-Blohm G m b H, Otto-brunn (West Germany) Unternehmensbereich Flugzeuge
INVESTIGATIONS OF THE SEPARATION BEHAVIOR ON AIRFOILS AT HIGH ANGLES OF ATTACK, USING LINEAR LIFT THEORY Thesis - Hochschule der Bundeswehr, Munich [UNTERSUCHUNGEN ZUM ABREISSVERHALTEN VON TRAGFLUEGELN IM HOHEN ANSTELLWINKELBEREICH MIT HILFE DER TRAGLINIENTHEORIE]
Karl-Heinz Haerdtl 1 Nov 1980 157 p refs In GERMAN (MBB-FE-122/S/PUB/37, Rept-80/7) Avail NTIS HC A08/MF A01

Different methods for calculating the lift coefficient of an airfoil wing were examined. The calculation of aerodynamic characteristics of airplanes is of great importance. Complex three dimensional boundary layers, especially for swept back wings with leading edge slats and trailing edges with split flaps which very much effect airfoil flows. Two different methods to calculate three dimensional boundary layers are presented. Transl by EAK

N82-18190# European Space Agency, Paris (France)
LAMINAR AIRFOILS FOR TRANSPORT AIRCRAFT
Armin Quast Oct 1981 33 p refs Transl into ENGLISH of "Laminarprofile fuer verkehrsflugzeuge" Rept DFVLR-Mitt-80-07 DFVLR, Brunswick, Mar 1980 33 p
(ESA-TT-680, DFVLR-Mitt-80-07) Avail NTIS HC A03/MF A01 DFVLR, Cologne DM 8,30

The development of laminar airfoils in order to save fuel by reducing drag is discussed. Laminarization through shaping is considered. Laminar and turbulent boundary layer theory and subjective assessment indicate that laminar airfoils for high Reynolds numbers are feasible, with a 22% fuel saving. The reduced cruising speeds required, however decrease passenger comfort, making them more suitable for freight carrying. Author (ESA)

N82-18192# Rockwell International Corp, El Segundo, Calif
MULTIPLE EJECTION EFFECTS ANALYSIS Final Report, 8 May - 30 Dec 1980
G A Freeman and G R Casteel Wright-Patterson AFB, Ohio Air Force Medical Research Labs Aug 1981 92 p refs
(Contract F33615-80-C-0519, AF Proj 7231)
(AD-A108277 NA-80-545 AFAMRL-TR-80-140) Avail NTIS HC A05/MF A01 CSCL 05/5

Wind tunnel data for the ACES-B1 ejection seat in the presence of the B-1 forebody are documented and analyzed. Significant aerodynamic interactions exist at high speed between dual seats and between seat/forebody. Trajectory data are presented with and without the forebody effect upon the seat. The forebody flow field is shown to increase the human engineering/biomechanical problems during high-speed ejection. Author (GRA)

N82-18193# Douglas Aircraft Co, Inc, Long Beach, Calif

AIRCREW RESTRAINT AND MOBILITY TEST FIXTURE Final Report

A Blair McDonald Wright-Patterson AFB, Ohio AMRL Jul 1981 33 p refs
(Contract F33615-79-C-0522 AF Proj 7231)
(AD-A108274 AFAMRL-TR-81-27) Avail NTIS
HC A03/MF A01 CSCL 14/2

The next generation combat aircraft with advanced aerodynamic and control features will have combat maneuver capability which will impose multi-axial accelerations on the aircrew. Advanced aircrew systems will be required for restraint, support, and mobility during these combat conditions. New concepts for these systems have been defined, but tests under representative dynamic conditions are necessary to evaluate the effectiveness of these concepts when implemented. Author (GRA)

N82-18194# Naval Air Development Center, Warminster, Pa
Aircraft and Crew Systems Technology Directorate
**PHYSIOLOGICAL ACCEPTABILITY TESTS OF THE SJU-5/A
EJECTION SEAT: SECOND PHYSIOLOGICAL ACCEPTANCE
DEMONSTRATION Final Report**

William G. Ward, Jr and Kenneth L. Miller 1 Jul 1981 23 p refs
(AD-A108688, NADC-81215-60) Avail NTIS
HC A02/MF A01 CSCL 01/3

This program was conducted to evaluate solutions to deficiencies of the F18 Aircraft Martin-Baker SJU-5/A escape system which had been identified during the initial Physiological Acceptability Demonstration (Report No. NADC-79040-60). The proposed solutions evaluated during this program included incorporation of 'toe guides' on the rudder pedals, relocation of the head rest, modification of the back support, and incorporation of leg garters into the anti-'G' suit. Of these, the head rest and back support still require additional modification. Upon satisfactory correction of the head rest and back support deficiencies, physiological acceptance of the F18 escape system will be recommended for the pilot's station. Author (GRA)

N82-18195# RAND Corp Santa Monica, Calif
**DISTRIBUTED INTELLIGENCE FOR AIR FLEET CONTROL
Interim Report**

Randall Steeb, Stephanie Cammarata, Frederick A. Hayes-Roth, Perry W. Thorndyke and Robert E. Wesson Jun 1981 59 p refs
(Contract MDA903-78-C-0029 ARPA Order 3640)
(AD-A108611, RAND/R-2728-ARPA LC-81-13913,
ISBN-0-8330-0353-4) Avail NTIS HC A04/MF A01 CSCL
17/7

Distributed planning and control techniques provide potential advantages over centralized processing in speed, cost, reliability, flexibility, and minimization of long-distance communications for a variety of tasks, including military threat assessment, command and control decisionmaking, disaster relief coordination, and civilian air traffic control. Six different architectures for distribution of control among multiple processors are presented and the influences of different task environments on each are discussed. The work focuses primarily on the use of distributed planning and control for civilian air traffic control. One architecture, in which each aircraft is controlled by a separate processor, is described in detail in an illustrative scenario. An initial system design is presented in which cooperating experts comprise a processor. These cooperating experts sense or infer aircraft intentions, generate and evaluate plans, control and monitor plan execution, and communicate with other processors. Author (GRA)

N82-18196# Army Missile Command, Redstone Arsenal Ala
Guidance and Control Directorate
**SOFTWARE FEATURES APPLICABLE TO INERTIAL
MEASUREMENT UNIT SELF ALIGNMENT**

H. V. White, J. C. Hung, and W. G. Cantrell Dec 1980 36 p refs
(AD-A108511, AD-E950182 DRSMI/RG-81-11-TR) Avail
NTIS HC A03/MF A01 CSCL 12/1

This report documents two software features applicable to inertial measurement unit self-alignment. Features are the continuous-time algorithm and the 'scrapping' technique. FORTRAN programs for least-square with and without scrapping are included. Author (GRA)

N82-18197# Nebraska Univ., Lincoln Dept of Electrical
Engineering

**IMPROVEMENTS AND EXTENSIONS OF THE GEOMETRI-
CAL DILUTION OF PRECISION (GDOP) CONCEPT FOR
SELECTING NAVIGATION MEASUREMENTS Final Report,
1 May 1980 - 1 May 1981**

William L. Brogan Wright-Patterson AFB, Ohio AFWAL Sep 1981 69 p refs
(Contract F33615-80-C-1092, AF Proj 6095)
(AD-A108607 AFWAL-TR-81-1142) Avail NTIS
HC A04/MF A01 CSCL 17/7

The optimal measurement selection problem was studied for the Global Positioning Satellite system (GPS). The fundamentals of the Geometrical Dilution of Precision (GDOP) concept were briefly reviewed because GDOP is frequently used to rank the effectiveness of potential measurements. It is shown that GDOP does not always select the best measurements in the sense of minimum mean square navigation error. For this reason, weighted least-squares and minimum variance (Kalman filter) methods were used to derive several improved measurement ranking schemes. Nonuniform measurement noise and a priori knowledge about the state are taken into account. Any specified weighted combination of the component error variances can be minimized. Eigenvalue-eigenvector theory was used to derive useful bounds and to provide geometrical insight. A purely algorithmic approach is also presented and applied to a number of representative GPS cases. GRA

N82-18198# European Space Agency, Paris (France)
**A POSSIBLE WAY OF SPECIFICALLY CORRECTING
LOCATION AND NAVIGATIONAL ERRORS CAUSED BY
REFLECTION AND OTHER PROPAGATION ANOMALIES**

Fritz Stelzel Jul 1981 125 p refs. Transl into ENGLISH of
"Über eine Möglichkeit zur gezielten Korrektur von Ortungs- u.
Navigationsfehlern, die durch Reflexionen u. sonstige Ausbreitung-
sanomalien verursacht werden" Rept DFVLR-Mitt-79-17 DFVLR
Oberpfaffenhofen, West Germany, May 1979
(ESA-TT-667, DFVLR-Mitt-79-17) Avail NTIS
HC A06/MF A01, DFVLR, Cologne DM 21,20

Electromagnetic wave propagation in urban areas is discussed in relation to vehicle location. Current methods are reviewed for vehicles on an arbitrary route. Isophase and hyperbola systems are compared. The isophase system is more accurate. A correction procedure for multipath induced errors is presented, based on measuring time signals from four transmitters. The use of measured times in order to reduce location errors caused by propagation anomalies is described. The methods were tested on a simulated city area covered by transmitters on the corners of a 25 km square. Results are inconclusive. Author (ESA)

N82-18199# European Space Agency Paris (France)
**EXTENSION OF PROPORTIONAL NAVIGATION BY THE USE
OF OPTIMAL FILTERING AND CONTROL METHODS**

Hans-Dieter Joos Aug 1981 31 p refs. Transl into ENGLISH of
'Erweiterung der Proportionalnavigation durch Anwendung
optimaler Filterungs- und Regelungsmethoden' Rept
DFVLR-FB-80-10 DFVLR, Oberpfaffenhofen, West Germany Mar 1980 38 p
(ESA-TT-683, DFVLR-FB-80-10) Avail NTIS HC A03/MF A01,
DFVLR, Cologne DM 8,30

A suboptimal guidance law for homing missiles, based on quadratic optimal stochastic control theory, is investigated. On-line backward integration from final time to actual time is not required. A Kalman-Bucy filter which takes nonlinearity and target maneuvers into account is presented. The model is compared to the conventional and extended proportional navigation systems (simulated on a nonlinear guidance loop model). Positional error behavior improves by 45% (Author (ESA))

N82-18200# European Space Agency Paris (France)
**MIDAIR AND NEAR MIDAIR COLLISIONS ON TWO- AND
THREE-DIMENSIONAL CURVILINEAR FLIGHT PATHS**

Otto Weber Aug 1981 119 p refs. Transl into ENGLISH of
'Zusammenstöße und gefährliche Begegnungen bei zwei- und
dreidimensionalen Kurvenflügen' Rept DFVLR-FB-80-13
DFVLR, Brunswick, Mar 1980 107 p
(ESA-TT-685, DFVLR-FB-80-13) Avail NTIS HC A06/MF A01,
DFVLR, Cologne DM 21

Collision avoidance by the see and avoid concept, advanced

N82-18201

secondary radar systems on the ground, and independent electronic systems onboard are discussed. For two and three dimensional stationary turns, basic geometrical and physical aspects of conflict detection are derived and details are given on the apparent size and motion of the other aircraft on the windshield. For conflict warning by means of ground based or onboard electronic systems, a linear track model is used. The predicted minimum distance at the closest approach, the lead times to this event or to the penetration of a zone of protection around the intruder, and the zeta parameter are analyzed as potential conflict criteria. Similarly rules and the separation of three dimensional conflicts into horizontal and vertical problems are treated. Commercial pilots lack special training in optically based risk assessment. Autonomous onboard warning systems do not make the see and avoid concept obsolete. Author (ESA)

N82-18201# National Ocean Survey, Rockville, Md
UNITED STATES COAST PILOT 9 PACIFIC AND ARCTIC COASTS ALASKA CAPE SPENCER TO BEAUFORT SEA
Jan 1981 425 p Revised
(PB82-109562, NOAA-81021105) Avail NTIS
HC A18/MF A01 CSCL 17G

Coast Pilot subjects include navigation regulations, outstanding landmarks, channel and anchorage peculiarities, dangers, weather, ice, freshets, routes, pilotage, and port facilities. Information is included on navigation regulations, Cape Spencer to Beaufort Sea, Cape Spencer to Cook Inlet, Kodiak Island, Alaska Peninsula, Aleutian Islands, Bering Sea and Arctic Ocean. GRA

N82-18202*# McDonnell-Douglas Corp., Long Beach, Calif
A STUDY TO DEFINE THE RESEARCH AND TECHNOLOGY REQUIREMENTS FOR ADVANCED TURBO/PROPFAN TRANSPORT AIRCRAFT Final Report
Irene M Goldsmith Feb 1981 313 p refs
(Contract NAS2-10078)
(NASA-CR-166138, ACEE-16-FR-0016) Avail NTIS
HC A14/MF A01 CSCL 01C

The feasibility of the propfan relative to the turbofan is summarized, using the Douglas DC-9 Super 80 (DS-8000) as the actual operational base aircraft. The 155 passenger economy class aircraft (31,775 lb [14,413 kg] payload) cruise Mach at 0.80 at 31,000 ft (8,450 m) initial altitude, and an operational capability in 1985 was considered. Three propfan arrangements: wing mounted, conventional horizontal tail aft mounted, and aft fuselage pylon mounted are selected for comparison with the DC-9 Super 80 P&WA JT8D-209 turbofan powered aircraft. The configuration feasibility, aerodynamics, propulsion structural loads, structural dynamics, sonic fatigue, acoustics, weight maintainability, performance, rough order of magnitude economics and airline coordination are examined. The effects of alternate cruise Mach number, mission stage lengths, and propfan design characteristics are considered. Recommendations for further study, ground testing, and flight testing are included. Author

N82-18203*# National Aeronautics and Space Administration
Langley Research Center, Hampton, Va
SLOTTED VARIABLE CAMBER FLAP Patent Application
Dana G Andrews inventor (to NASA) (Boeing Commercial Airplane Co Seattle) Filed 30 Oct 1981 13 p Sponsored by NASA
(NASA-Case-LAR-12541-1, US-Patent-Appl-SN-315588) Avail
NTIS HC A02/MF A01 CSCL 01C

Variable camber actuator assemblies broaden the range of speeds at which lift to drag performance is maximized for slotted flap wings. Lift is improved by varying wing camber with rotational flap movements that do not introduce wing slots and induced drag. Forward flaps are secured to forward flange links which extend from, and are a part of, forward flap linkage assemblies. The forward flaps rotate about flap pivots with their rotational displacement controlled by variable camber actuator assemblies located between the forward flaps and the forward flange links. Rear flaps are held relative to the forward flaps by rear flap linkage assemblies which may act independently from the forward flap linkage assemblies and the variable camber actuator assemblies. Wing camber is varied by rotating the flaps with the variable camber actuator assemblies while the flaps are in a deployed or tucked position. Rotating flaps in a tucked position does not introduce significant wing surface discontinuities and reduces aircraft fuel consumption on most flight profiles. NASA

N82-18204*# National Aeronautics and Space Administration
Langley Research Center, Hampton, Va
DYNAMICS OF AIRCRAFT ANTISKID BRAKING SYSTEMS
John A Tanner, Sandy M Stubbs, Robert C Dreher, and Eunice G Smith Feb 1982 100 p refs
(NASA-TP-1959 L-14788) Avail NTIS HC A05/MF A01
CSCL 01C

A computer study was performed to assess the accuracy of three brake pressure-torque mathematical models. The investigation utilized one main gear wheel, brake, and tire assembly of a McDonnell Douglas DC-9 series 10 airplane. The investigation indicates that the performance of aircraft antiskid braking systems is strongly influenced by tire characteristics, dynamic response of the antiskid control valve, and pressure-torque response of the brake. The computer study employed an average torque error criterion to assess the accuracy of the models. The results indicate that a variable nonlinear spring with hysteresis memory function models the pressure-torque response of the brake more accurately than currently used models. T M

N82-18205# Committee on Armed Services (U S House)
REVIEW OF DEFENSE-RELATED VERTICAL AND SHORT TAKEOFF AND LANDING (V/STOL) AIRCRAFT PROGRAMS
Walter Z Collings Washington GPO 1979 206 p refs
Presented to the Comm on Armed Serv., 96th Congr., 1st Sess., Sep 1978. Prepared by AIAA, New York
(GPO-55-278) Avail Committee on Armed Services

A technology review of bases supporting the development of Vertical of Short Takeoff and Landing (V/STOL) aircraft is presented. Representative aircraft were summarized according to their type of lift generation mechanisms. Successes, failures, problems encountered in development and plans for the future are also presented. Some discussion of the Navy's environment/commitment to V/STOL aircraft is also presented. M D K

N82-18206# Rockwell International Corp., Columbus, Ohio
Aircraft Div
XFV-12A DIAGNOSTIC AND DEVELOPMENT PROGRAMS Summary Report, Jan 1979 - May 1981
P M Bevilacqua and C P Combs Nov 1981 367 p refs
(Contract N00019-73-C-0053)
(AD-A108354, NR81H-50) Avail NTIS HC A16/MF A01
CSCL 01/3

Activity during the XFV-12A thrust augmentor development program conducted from May 1979 to June 1981 is reported and documented. Diagnostic tests indicated a major source of performance deficiency could be attributed to feed duct/augmentor component interface problems rather than basic augmentor configuration. Interface problems seriously affected both isolated performance and flow quality of the primary augmentor nozzles, resulting in significantly low levels of augmentation. A remedial program, the subject of this report, was initiated. The primary objective of this program was to systematically improve the performance of the XFV-12A aircraft's thrust augmentor lift systems. Major emphasis was placed not only on correcting flow deficiencies but also identifying and incorporating improvements in the augmentor design which would increase its performance potential. GRA

N82-18207# General Accounting Office, Washington, D C
POTENTIAL REDUCTIONS IN AIRCRAFT OPERATION AND MAINTENANCE COSTS BY USING THRUST COMPUTING SUPPORT EQUIPMENT Report to the Honorable Joseph P Addabbo, Chairman, Subcommittee on Defense, Committee on Appropriations, House of Representatives
27 Oct 1981 17 p
(AD-A108463, GAO/PLRD-82-4) Avail NTIS
HC A02/MF A01 CSCL 01/2

This report addresses the evaluation of thrust measuring equipment. We interviewed Air Force officials and contractor representatives, reviewed documentation pertaining to the key events in the evaluation of the thrust computing system program, reviewed test data and analyses by Air Force and contractor engineers, and observed the operation of the thrust computing system. Our analyses show that the accurate measurement and setting of thrust for installed jet engines is of vital importance not only for aircraft readiness and safety but also for operation and maintenance cost reductions. Although test results indicate

that a system is available that can perform such measurements the services have not been using it. The Air Force has conducted extensive tests that will measure thrust for installed J85-5 engines, but has not implemented a system. The Navy has not performed any tests to determine whether its aircraft jet engines might benefit from such a system. GRA

N82-18208# Institute for Defense Analyses Arlington, Va Systems Evaluation Div
C-5A AUSTERE AIRFIELD OPERATIONAL UTILITY EVALUATION PHASE 2 OPERATION ON UNPAVED SOIL SURFACES FOLLOWING RAINFALL Final Report
 Waldemar O Breuhaus Oct 1981 46 p refs
 (Contract MDA903-79-C-0018)
 (AD-A108597 AD-E500466 IDA-P-A1621
 IDA/HQ-81-23896) Avail NTIS HC A03/MF A01 CSCI 01/3

During the summer of 1980 and the winter of 1980-1981 an Operational Utility Evaluation (OUE) was conducted to determine operating characteristics of the C-5A airplane when taxiing or being towed and off-loaded on unpaved soil surfaces and on snow-covered surfaces. Subsequent to the successful completion of those tests questions arose concerning the effects of rainfall that wets otherwise adequate bare soil areas to a significant depth. Tests with simulated rainfall of various amounts applied by agricultural sprinkler systems were conducted at March AFB, California during July 1981. The airplane performed well though it approached its performance limits in the most severe test conditions. Difficulties were encountered in arriving at a sprinkler system configuration reasonably approximating naturally occurring rainfall and in arriving at a single simple descriptor to properly characterize the strength of soil in such a complex situation. GRA

N82-18209# Army Aeromedical Research Lab Fort Rucker Ala Biodynamics Research Div
VIBRATION LEVELS IN ARMY HELICOPTERS MEASUREMENT RECOMMENDATIONS AND DATA Final Report
 John C Johnson and David B Priser Sep 1981 35 p refs
 (DA Proj 3E1-6277-A-878)
 (AD-A108131 USAARL-81-5) Avail NTIS HC A03/MF A01 CSCI 01/3

Surveys on vibration levels found in currently fielded helicopters were used to prepare a comparative summary of vibration exposure levels at crew stations and of the test methods used to measure these levels. This effort was initiated at the request of the Air Standardization Coordinating Committee (ASCC) Working Party 61 and because of the wide variety of methods used in data capture and instrumentation documentation. Sources of the literature reviewed included technical reports of U.S. Government agencies and papers in open literature. Articles were reviewed based upon three criteria: (1) quantitative description of vibration in currently fielded U.S. Army rotary winged aircraft, (2) article contents are unclassified and available for publication in open literature, (3) article describes human exposure levels of aircraft vibration. Author (GRA)

N82-18210# Aeronautical Systems Div, Wright-Patterson AFB Ohio Flight Technology Div
A DIGITAL SIMULATION PROGRAM DESCRIBING THE MOTION OF AN AIRCRAFT UNDERGOING ENGINE FAILURE DURING ITS TAKEOFF GROUND ROLL Final Report, Jun 1980 - Mar 1981
 Michael J Miedlar Sep 1981 77 p refs
 (AD-A108420 ASD-TR-81-5030) Avail NTIS HC A05/MF A01 CSCI 01/2

This report presents a non-interactive MIMIC program developed to generate the time history of an aircraft undergoing an engine failure during its ground roll. The program calculates the forces and moments acting on the aircraft and uses MIMIC's implicit integration routine to track its motion. The equations and assumptions used are presented and discussed. This report also lists the program and delineates its functions. Author (GRA)

N82-18211# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany) Unternehmensbereich Flugzeuge
THEORETICAL INVESTIGATIONS ON THE INFLUENCE OF DIFFERENT STRAKE, TAIL UNIT, AND CONVENTIONAL HLW ARRANGEMENT AS WELL AS OF CCV ON THE AERODYNAMIC CHARACTERISTICS OF FIGHTER AIRCRAFT CONFIGURATIONS Thesis - Hochschule der Bundeswehr, Munich [THEORETISCHE UNTERSUCHUNGEN

UEBER DEN EINFLUSS VON VERSCHIEDENEN STRAKE, ENTENLEITWERKS- UND KONVENTIONELLEN HOEHENLEITWERKSANORDNUNGEN SOWIE VON CCV AUF DIE AERODYNAMISCHEN EIGENSCHAFTEN VON KAMPF-FLUGZEUG-KONFIGURATIONEN]

Herbert Klimt Dieter Oberst and Walter Schmalhofer 1 Oct 1980 486 p refs In GERMAN
 (MBB-FE-122/S/PUB/36) Avail NTIS HC A01/MF A01

Linear and nonlinear aerodynamic characteristics for fighter airplane configurations with three separate tail-wing-surface ratios as related to lift coefficients were optimized. The optimal configurations were reduced by 5% for stability and 10% for instability and their lifting responses are compared. Fuselage effect and convergence of aerodynamic factors are also studied.

Transl by E A K

N82-18212# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany) Unternehmensbereich Flugzeuge
INTERPRETATION AND CONSTRUCTION OF A DYNAMIC SIMILARITY MODEL OF THE A 310 WINGS [AUSLEGUNG UND BAU EINES DYNAMISCH AEHNLICHEN MODELLS DES A 310 FLUEGELS]

H Hoenlinger 5 May 1981 34 p refs In GERMAN Presented at DGLR-Jahrestagung 1981, Aachen 11-14 May 1981
 (MBB-FE-17/S/PUB/42 DGLR-81-035) Avail NTIS HC A03/MF A01

The design and construction of a model for directional oscillation flutter for the A-310 wing with supercritical profile is discussed. The rigidity distribution in the model is simulated by a simple metal box. The profile geometry and the mass distribution of the model is copied exactly by a foam structure coated with a fiberglass laminate. A finite element model is used to explain the complicated engine mount which is supported by a profile beam. Data on rigidity and vibration measurements are included.

Transl by E A K

N82-18213# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany)
CHARACTERIZATION OF THE AIRBUS HORIZONTAL STABILIZERS OF CFRP CONSTRUCTION AND STRUCTURAL ANALYSIS WITH THE FINITE ELEMENT METHOD [AUSLEGUNG DES AIRBUSSEITENLEITWERKS IN CFK-BAUWEISE UND STRUKTURANALYSE MIT DER FINITE-ELEMENTE-METHODE]

Erhard Winkler May 1981 22 p Reprint from Verarbeiten u Anwenden kohlenstoffaserverstaerkter kunststoffe Vereins Deut Ingr May 1981 p 181-198 In GERMAN
 (MBB-UT-13-81-O) Avail NTIS HC A02/MF A01

The use of carbon fiber reinforced plastics as a substitute for light weight metals in aircraft construction which decreases the weight by 30% is discussed. Environmental parameters like temperature and humidity must be considered. A construction method with a variety of possibilities to fulfill these requirements and which competes with metal structures is developed. This means either a simplified weight reduction at the same or less cost or a less costly method for the same or less weight.

Transl by E A K

N82-18214# European Space Agency Paris (France)
TENDENCIES IN THE DEVELOPMENT OF SUBSONIC TRANSPORT AIRCRAFT WITH SPECIAL CONSIDERATION OF AERODYNAMICS

Horst Koerner Oct 1981 42 p refs Transl into ENGLISH of "Entwicklungstendenzen bei Unterschall-Transportflugzeugen unter besonderer Beruecksichtigung der Aerodynamik" Rept DFVLR-Mitt-80-15 Brunswick Jun 1981 62 p
 (ESA-TT-705 DFVLR-Mitt-80-15) Avail NTIS HC A03/MF A01

Tendencies in subsonic transport aircraft development specifically due to progress in aerodynamics are surveyed. Prospective wing profile designs and improved integration of body dimensions are considered citing examples from the AIRBUS development program. Possible fuel savings through supercritical wing technology and by optimizing reduction in friction drag are also studied. Advantages to be gained by active control particularly from adaptive wing technology, are reviewed. As a potential application an unconventional canard configuration including transonic propellers for an aircraft in the AIRBUS class is proposed. Author (ESA)

N82-18215 Royal Aircraft Establishment, Farnborough (England)

NEW DEVELOPMENTS IN COCKPIT-HUMAN INTERFACES

E B Davies and J B Peckham 15 Jun 1981 16 p Presented at 12th ICAS Congr Munich, Oct 1980 (RAE-TM-FS-412, BR80500) Copyright Avail Issuing Activity

Touch sensing displays, helmet sights and direct voice inputs (DVI) are discussed. Cathode ray tubes (CRT) are cheaper than keyboards for touch sensing, but lack tactile differentiation capabilities. For designation tasks, e.g., touching the required radar return accuracy must be much higher than for keyboarding. Head movement filtering is a problem with helmet sights, since output is delayed if too much filtering is attempted, and accuracy suffers if vibration is ignored. Cuing by LED's is restricted by the number of leads the helmet can incorporate and CRT's are too heavy. Factors affecting DVI performance include electronic noise on intercoms, microphone to mouth distance, voice changes caused by stress, and the number of commands pilots can remember. Author (ESA)

N82-18216# Instituto de Pesquisas Espaciais Sao Jose dos Campos (Brazil)

AN ON BOARD SUPERVISORY SYSTEM FOR APPLICATIONS IN SPACE MISSIONS [UM SISTEMA DE SUPERVISAO DE BORDO PARA APLICACOES EM MISSOES ESPACIAIS]

Jose Carlos Maldonado and Ricardo deAzevedo Mendes Jun 1981 13 p refs In PORTUGUESE, ENGLISH abstract Presented at the 2nd Natl Automation Meeting, Salvador, Bahia, Brazil, Jul 1981

(INPE-2097-RPE/327) Avail NTIS HC A02/MF A01

The system, developed in the digital and analog system group/program, enables full duplex communication between an onboard and a ground microcomputer, based on a reserved protocol. The system performs the following functions: data acquisition, control, transmission and reception between an onboard payload and a ground station. It also executes housekeeping tasks and telecommand operations. This system was, in particular, utilized in the balloon mission PEROBA-I. The performance of the system in the mission was satisfactory. TM

N82-18217# Hughes Aircraft Co Canoga Park Calif ANALYSIS OF BUILT-IN-TEST (BIT) FALSE ALARM CONDITIONS Final Technical Report, 24 Jan 1980 - 28 Feb 1981

John G Malcolm and Richard W Highland Griffiss AFB NY RADC Aug 1981 122 p refs

(Contract F30602-80-C-0074 AF Proj 2338)

(AD-A108752 RADC-TR-81-220) Avail NTIS HC A06/MF A01 CSCL 14/2

Usefulness of BIT is seriously affected by the presence of false alarms. False alarms can degrade mission effectiveness of systems and contribute to the expenditure of excessive maintenance resources. The objectives of this study were to determine the root causes of the false alarm problem and to develop design guidelines to minimize the occurrence and the effect of false alarms. False alarm rates have been established for the three systems investigated and prediction factors defined. Author (GRA)

N82-18218# Lockheed-Georgia Co Marietta ANALYTICAL STUDY OF COCKPIT INFORMATION REQUIREMENTS Final Report, Oct 1979 - Nov 1980

J D Caldwell and T G Jones Washington FAA Apr 1981 165 p refs

(Contract DOT-FA79WA-4368)

(AD-A108524 LG80ER0200, FAA/RD-81/4) Avail NTIS HC A08/MF A01 CSCL 01/3

An assessment is made of cockpit information requirements likely to be imposed on aircraft in the next fifteen years as a result of improvements in the ATC system and in aircraft design. These requirements are analyzed by work centers and include flight control navigation, collision avoidance flight management, communications, caution/warning and monitoring and checklist functions. From a baseline of current requirements and technology, the application of new requirements and technology is analyzed. Three aircraft are hypothesized representing three time periods of technical development. The purpose is to investigate the impact of future ATC changes on differently equipped aircraft. GRA

N82-18219# Arinc Research Corp Annapolis, Md IMPACT OF TECHNOLOGY ON AVIONICS COST TRENDS

Steven Toth, William Lovelace, and Kelly Markin Nov 1981 84 p

(Contract DTFA-01-80-C-10030)

(AD-A108494 Rept-1378-40-2-2553, FAA-EM-82-6) Avail NTIS HC A05/MF A01 CSCL 09/3

This study provides an overview of nonmilitary generally aviation and commercial avionics price and cost structures as influenced by technology. It quantifies computes, and evaluates the unique characteristics and behavior patterns of the industry, especially those that affect the frequency of innovation, the rate of technology diffusion from manufacturer to manufacturer or from product to product, and the anticipated major cost drivers of the future. The report reviews the impact of technology on the cost of avionics during the past 20 years and projects this impact for the next 20 years. This report concentrates on avionics in the low-performance general aviation aircraft category because they are the major components of the avionics industry. Typical units of detailed study are transponders, transceivers, navigation receivers and course deviation indicators (CDIs). An examination of the price histories of more than twenty equipment families indicates that unit prices have been and are likely to continue increasing at the Producer Price Index (PPI) rate. This rate of price growth results from a balance between costs rising at the Consumer Price Index (CPI) rate and manufacturing cost reductions made possible through the introduction of new technologies. Author (GRA)

N82-18220# National Aerospace Lab Amsterdam (Netherlands) Scientific Services Div

TRENDS IN AIRLINE AVIONICS

F J Abbink 13 Mar 1980 30 p refs Presented at Netherlands Assoc of Aeron Engr Symp on Develop in Avionics, Delft, 25 Apr 1980

(NLR-MP-80013-U) Avail NTIS HC A03/MF A01

The evolution of aeronautical electronics is described. Trends towards system integration for airliners are indicated. The development of airline avionics specifications by the airlines and constructors is outlined. The design and function of avionics equipment, e.g., navigation aids, are explained. The Aeronautical Radio Incorporated 700 automatic flight system is introduced as an example of a system suited to the next generation of airliners. Radio navigation, communication and identification equipment are controlled by the digital frequency/function selection unit. Automatic flight control and auto-throttle functions are executed by flight control and thrust control computers. Author (ESA)

N82-18221# Messerschmitt-Boelkow-Blohm GmbH Otto-brunn (West Germany) Betriebsbereich

INTEGRATION OF COMPLEX SYSTEMS IN CURRENT AND FUTURE AIRCRAFT PROJECTS FOR THE EXAMPLE OF AVIONICS [INTEGRATION KOMPLEXER SYSTEME IN LAUFENDE UND ZUKUNFTIGE FLUGZEUGPROGRAMME AM BEISPIEL DER AVIONIK]

H Hauser 31 Jan 1980 38 p In GERMAN

(MBB-UH-18-80-O) Avail NTIS HC A03/MF A01

Equipment for electrical and avionic systems, and special equipment needed in the airplane program were developed. Avionics is defined as airplane structure, airplane equipment (besides the mechanical system) includes that part of the equipment system which is supported by the electric and electronic system and construction and general instruments necessary in airplane construction. Avionics enables the supply, transfer processing and production (activation) of information for the management of airplane systems, control of airplanes and the execution of special functions. Transl by E A K

N82-18222# National Aeronautics and Space Administration Lewis Research Center, Cleveland, Ohio

EFFECTS OF FAN INLET TEMPERATURE DISTURBANCES ON THE STABILITY OF A TURBOFAN ENGINE

Mahmood Abdelwahab Dec 1981 36 p refs

(NASA-TM-82699 E-982) Avail NTIS HC A03/MF A01 CSCL 21E

The effects of steady-state and time-dependent fan inlet total temperature disturbances on the stability of a TF30-P-3 turbofan engine were determined. Disturbances were induced by a gaseous-hydrogen-fueled burner system installed upstream of the fan inlet. Data were obtained at a fan inlet Reynolds number index of 0.50 and at a low-pressure-rotor corrected speed of 90 percent of military speed. All tests were conducted with

a 90 deg extent of the fan inlet circumference exposed to above-average temperatures T M

N82-18223# Vereinigte Flugtechnische Werke-Fokker GmbH Bremen (West Germany)

FURTHER DEVELOPMENT OF THE TEST CONCEPT OF THE ALPHA JET ENGINE LARZAC 04 [WEITERENTWICKLUNG DES PRUEFKONZEPTEDES FUER DAS ALPHA-JET-TRIEBWERK LARZAC 04]

Ernst Lerche 1981 33 p In GERMAN Presented at Seminars, Prueftech und Pruefstandstech, Hannover, 3 Apr 1981

Avail NTIS HC A03/MF A01

The test stand for the LARZAC 04 jet unit for the Alpha jet aircraft was developed. The test stand is outlined and equipment extension, and a maintenance procedure for the driving system are presented Transl by E A K

N82-18224# Honeywell Systems and Research Center, Minneapolis, Minn Aerospace and Defense Group

INTEGRATED CONTROL DESIGN TECHNIQUES Final Report, Jun. 1979 - Nov 1980

A L Jones, J K Mahesh, M A Kollodge, D P Pledger, E R Rang, and K D Graham Wright-Patterson AFB Ohio AFWAL Aug 1981 314 p refs

(Contract F33615-79-C-3609 AF Proj 2403)

(AD-A108223 Rept-80SRC82, AFWAL-TR-81-3074) Avail NTIS HC A14/MF A01 CSCL 01/3

A total systems approach methodology and computer-aided design tool for integrated flight control design and evaluation has been formulated. This methodology is a composition of classical system design steps and system performance, reliability/survivability packaging and cost evaluation techniques assembled for interactive computer-based execution. The interactive sensor integration program developed under this methodology addresses the sensor requirements of the flight control, guidance and navigation and weapon delivery functions as directed interactively by the designer and the mission, the system configuration, cost, power, weight, volume constraints and total system performance. The demonstration program contains performance, reliability, size, power, weight, cost data for gyros, accelerometers, radars, seekers and air data systems in addition to analysis tools for evaluating navigation system accuracy, probability of target acquisition, and probability of kill for selected targets and weapons.

Author (GRA)

N82-18225# Instituut TNO voor Bouwmaycnalen en Bouwconstructies Delft (Netherlands)

INVESTIGATION INTO THE UTILITY OF SOME QUICK SETTING CEMENTS FOR RUNWAY REPAIR [ONDERZOEK NAAR DE BRUIKBAARHEID VAN ENKELE SNELVERHARDENDE BINDMIDDELEN VOOR REPARATIE VAN START-BANEN]

Mar 1980 39 p refs In DUTCH

(B-80-157/607 0157, TDCK-75056)

Avail NTIS

HC A03/MF A01

The application of quick setting cements in rapid runway repair was investigated. Needed strength and layer thickness of the hardening material was determined. The following results are reported: (1) it is possible to fill up a hollow space with quick setting cements even in combination with proper additives like super plastifiers; (2) pressure strength for hardening time is accomplished within one hour; (3) a fast operating method is needed to prevent debinding of cement, continuous mixers for smaller quantities are recommended Transl by E A K

N82-18226# Institute for Perception RVO-TNO Soesterberg (Netherlands)

THE LINK-HILES DRIVER TRAINING SIMULATOR FOR TRACKED VEHICLES THE EFFECT OF METHOD AND DURATION OF TRAINING ON THE TRANSFER OF TRAINING

K J Poll 1980 20 p refs In DUTCH ENGLISH summary (Contract A76/KL/148)

(IZF-1980-28 TDCK-75019) Avail NTIS HC A02/MF A01

Transfer of training through different methods and durations of training from a driving simulator to a task was investigated. In method A the candidates were under strict guidance of the instructor while in method B the candidates trained more on their own and paid more attention to the integration of the part-tasks. The duration of training was dependant on the performance-level on which the candidate turned over from the simulator to the real tanks. These performance-levels were the

single trial execution of all tasks (low level) having all tasks under control (medium level) and sufficient integration of all part-tasks (high level). From the results it is clear that when the candidates were trained in pairs the mean number of kilometers for the two candidates shows to difference as a function of training method. Although the first candidate needs less kilometers with method B and 'second' candidate learns more from the first with method A. The number of kilometers on the tank necessary to pass the final drivers test, is a linear relation as a function of the duration of simulator training.

J M S

N82-18227# Coppin State Coll Baltimore Md

TASK ANALYTIC TECHNIQUES APPLICATION TO THE DESIGN OF A FLIGHT SIMULATOR INSTRUCTOR/OPERATOR CONSOLE Final Report

Charles D Sanders Brooks AFB Tex Air Force Human Resources Lab Dec 1981 21 p refs Prepared for Southeastern Center for Electrical Engineering Education, St Cloud Fla Submitted for publication

(Contract F49620-79-C-0038 AF Proj 9983)

(AD-A108724 AFHRL-TP-81-38)

Avail NTIS

HC A02/MF A01 CSCL 14/2

Instructional Systems Development (ISD) has contributed to the efficiency and low cost of air flight training through the medium of the simulator. Task analysis is a component of ISD and its application to the improvement of devices such as simulator instructor/operator consoles will continue to enhance the quality of flight training. Task analytic techniques are inextricably interwoven into the design of an instructor/operator console. The application involves the process persons and a machine within the context of a flight simulator. The tasks of the instructor and student are primary in the design process. The efficiency and economy of the task analytic process has implications for its use in the future developments of automated flight training.

Author (GRA)

N82-18228# SRI International Corp Arlington Va

EVALUATION OF THE NORTH ISLAND A/C CRASH/RESCUE TRAINING FACILITY

R S Alger Aug 1981 153 p refs

(Contract N00014-80-C-0696 SRI Proj PYU-1943)

(AD-A108740) Avail NTIS HC A08/MF A01 CSCL 05/9

Under Executive Order 11752, the Navy and the Air Force began a cooperative effort to develop training facilities that could provide more fire fighting training with less smoke and water pollution. Soon the central issue of pollution control was surrounded by a series of satellite questions that had to be answered before training facilities could be designed, e.g., what type of training is required, how much training should be provided, where should fireman train and how much departure from the real emergency situation is permissible. Various public and private groups contributed answers. The Naval Air Station, North Island, San Diego, Calif., Aircraft/Crash Fire Rescue Training Facility is the first Navy facility constructed as an outgrowth of this effort to improve training while reducing the environmental impact to an acceptable level. This report evaluates the performance of the North Island facility in a series of environmental and training tests. The scope includes: (1) the evaluation procedure and results; (2) a comparison to other training options; and (3) recommendations for future training activity.

GRA

N82-18229# Army Engineer Waterways Experiment Station, Vicksburg Miss Geotechnical Lab

BOMB CRATER REPAIR TECHNIQUES FOR PERMANENT AIRFIELDS REPORT 1 SERIES 1 TESTS Technical Report, Jul - Nov 1978

David L Cooksey Oct 1981 129 p refs

(AD-A108716, WES/MP/GL-81-12)

Avail NTIS

HC A07/MF A01 CSCL 13/2

A test section with six simulated bomb craters was constructed for the purpose of developing an improved field method of repair and restoration of air base runways damaged by enemy attack. The crater repair materials tested in the reconstruction were a high-quality crushed stone grouted concrete, portland cement concrete (PCC), and asphaltic concrete (AC). The performances of the different materials were evaluated under full-scale load testings with the F-4 and C-141 aircraft loadings. The gravity grout solution and the high-quality crushed stone method performed beyond required coverage levels and seem to be the two high candidate material systems for further research. The solutions were accomplished with the time.

N82-18230

manpower, equipment, and performance constraints of operational requirements GRA

N82-18230# Army Engineer Waterways Experiment Station Vicksburg, Miss Geotechnical Lab
INVESTIGATION OF COMPACTION CRITERIA FOR AIRPORT PAVEMENT SUBGRADE SOILS Final Report, Mar 1978 - Apr 1981

William N Brabston Washington D C FAA Oct 1981 174 p refs

(Contract DOT-FA78WAI-876)

(AD-A108518 WES/TR/GL-81-11 FAA-RD-81-48) Avail NTIS HC A08/MF A01 CSCL 08/13

A study was conducted to determine the effect of lowering soil density requirements for subgrades under airport pavements. The investigation was primarily a laboratory effort in which molded specimens of three different soil types, compacted to densities at and below those currently specified by FAA criteria, were subjected to repeated axial loadings in a triaxial compression chamber. The primary response parameters of interest were permanent and resilient axial strain. Test results were formulated into a statistical model to predict permanent soil strain based on soil characteristics such as density, clay content, compaction characteristics, and shear strength. The strain model was used to calculate values of permanent soil deformation at the surface of the subgrade for various combinations of soil density. Results of the test indicated that the wide variation in soil response among the three materials tested precluded any general alteration in current FAA compaction criteria. Author (GRA)

N82-18231# Textron Bell Helicopter Fort Worth Tex
ROTORCRAFT FLIGHT SIMULATION COMPUTER PROGRAM C81 WITH DATAMAP INTERFACE VOLUME 2 PROGRAMMER'S MANUAL Final Report

P Y Hsieh Oct 1981 264 p Supersedes USAAMRDL-TR-76-41A, USAAMRDL-TR-76-41B and USAAMRDL-TR-76-41C

(Contract DAAK51-79-C-0015, DA Proj 1L1-62209-AH-76) (AD-A108294 BHT-699-099-111-Vol-2,

USAAVRADCOM-TR-80-D-388 USAAMRDL-TR-76-41A, USAAMRDL-TR-76-41B, USAAMRDL-TR-76-41C) Avail NTIS HC A12/MF A01 CSCL 09/2

This report documents the current version in the C81 family of rotorcraft flight simulation programs developed by Bell Helicopter Textron. This current version of the digital computer program is referred to as AGAP80. The accompanying program for calculating fully coupled rotor blade mode shapes is called DNAM05, and an associated rotor wake program is called AR9102. The AGAP80 version of C81 was developed by adding some analytical features to the AGAJ76 version and including the ability to generate Data Transfer Files for use by the File Creation Program of DATAMAP. An overview of the computer program capabilities and the principal mathematical models incorporated in the program are given in Volume I of the documentation for the AGAJ76 version of the program. Volume I, the User's Manual, contains detailed information necessary for setting up an input data deck and interpreting the computed data. Volume II includes a catalog of subroutines and a discussion of programming considerations. GRA

N82-18232# Naval Air Engineering Center, Lakehurst N J Ship Installation Engineering Dept

INVESTIGATION OF CROSSDECK PENDANT CATAPULT SLOT INTERACTION, PROPOSED CORRECTIVE MEASURES Final Report, Apr 1978 - Mar 1979

Alvin Hittner 20 Nov 1981 56 p ref

(AD-A108149 NAEC-91-7964) Avail NTIS HC A04/MF A01 CSCL 01/5

This report documents the investigation of the crossdeck pendant failure aboard USS JOHN F KENNEDY (CV 67) in March 1978, which caused the loss of an F-14A. Included are the results of a survey to determine the scope of the deck pendant/catapult slot interaction problem, testing to confirm the failure sequence and the evaluation of slot filler devices (buttons) to resolve the problem. Author (GRA)

N82-18233# MGA Research Corp, Buffalo N Y
TEST SITE INSTRUMENTATION STUDY VOLUME 2 CRASH 1 AND CRASH 2 RAW DATA Final Report, 22 Mar 1980 - 31 Mar 1981

Rudy H Arendt and Patrick M Miller Jun 1981 150 p refs (Contract DOT-HS-8-01936)

(PB82-111832, G22-V-2 DOT-HS-805980-Vol-2) Avail NTIS

HC A07/MF A01 CSCL 13F

The data acquisition and reduction practices at fifteen crash and sled testing facilities which normally produce impact test data for the NHTSA were reviewed. Attention was focused on dynamic response characteristics instrumentation calibration procedures, filtering techniques, equipment properties and analog to digital conversion techniques. GRA

N82-18327# Boeing Commercial Airplane Co, Seattle, Wash
A STUDY OF THE EFFECTS OF LONG-TERM EXPOSURE TO FUELS AND FLUIDS ON THE BEHAVIOR OF ADVANCED COMPOSITE MATERIALS Final Report

E Y Tanimoto Aug 1981 40 p ref

(Contract NAS1-12428)

(NASA-CR-165763, D6-41185-9) Avail NTIS HC A03/MF A01 CSCL 11D

The periodic testing and evaluation of graphite/epoxy and Kevlar/epoxy material systems after subjecting test specimens to prolonged exposure to several laboratory-controlled environments deemed typical of normal aircraft operations is discussed. It is noted that specimen immersion in water or water-based fluids resulted in the greatest effect on the mechanical properties tested. Also, the environmental fluids showed a tendency to affect Kevlar/epoxy systems at an earlier exposure period than the graphite/epoxy systems. Results also indicate mechanical property strength retention generally being lower for the Kevlar/epoxy systems when compared to the corresponding graphite/epoxy systems in similar environments, after prolonged exposure. B W

N82-18349# Naval Weapons Center, China Lake, Calif
FUEL-RICH PLUME COMBUSTION Annual Progress Report, 1 Oct. 1980 - 30 Sep 1981

K C Schadow, M J Lee, and K C Wilson 30 Sep 1981 7 p refs

(AD-A108136) Avail NTIS HC A02/MF A01 CSCL 21/2

Experiments are being performed using an axisymmetric gas generator ramjet. Axial and radial profiles of pressure, velocity, turbulence intensity, temperature, and species concentration are being determined using non-interference optical diagnostic techniques (laser Doppler velocimeter (LDV)) and intrusive probes. The experimental data are being compared with analytical models developed by Science Application, Inc (SAI) under an Air Force Office of Scientific Research (AFOSR) contract. An axisymmetric, 5-inch diameter laboratory ramjet combustor was built and checked out. Experiments were initiated using (1) an LDV and a hot-wire anemometer for velocity and turbulence intensity measurements, (2) coated thermocouples for temperature measurement, and (3) a gas chromatograph for analysis of gas samples. GRA

N82-18419# Messerschmitt-Boelkow-Blohm G m b H Otto-brunn (West Germany) Betriebsbereich

ELECTROFORMING OF SPACE AND AIRCRAFT STRUCTURES

R Suchentrunk 1981 9 p refs

(MBB-BB-491-0) Avail NTIS HC A02/MF A01

Application of electroforming, a production technique for complicated structures, to aircraft and spacecraft structures and components is addressed. The process of electrodeposition is described and the advantages of the electroformed structures are highlighted. Materials suitable for the mandrels and for electrodeposition are discussed, emphasizing preferred properties. J M S

N82-18464# Rome Air Development Center, Griffiss AFB N Y
TM/TE POLARIZATION RATIOS IN A SAMPLE OF 30 kHz SPHERICS RECEIVED AT ALTITUDES FROM 0 TO 70 km R F Harrison, E A Lewis, J B Donohoe (Megapulse, Inc), and J E Rasmussen Aug 1981 17 p refs

(AF Proj 4600)

(AD-A108182, RADC-TR-81-235) Avail NTIS HC A02/MF A01 CSCL 20/14

A rocket-borne payload, carrying both vertical and horizontal magnetic dipole antennas and receiving instrumentation, was flown from Wallops Island, Virginia, to observe the Transverse Electric (TE) and Transverse Magnetic (TM) polarization components of individual spherics at 30 kHz. During the 2-1/2 min flight to apogee at 96 km, 293 individual spherics were observed. Upon applying corrections for difference in azimuthal antenna patterns, it was concluded that the TM noise fields were larger than the

TE fields by about 15 dB near the ground and approximately equal at 60 km
Author (GRA)

**N82-18471# Strategic Air Command Offutt AFB Nebr Aircraft Engineering Div
AN/ALQ-135 TAIL WARNING SYSTEM FOLLOW-ON OPERATIONAL TEST AND EVALUATION Final Report**

Vincent M Jenkins 23 Nov 1981 5 p
(AD-A108348, SAC/LGME-P-405) Avail NTIS
HC A02/MF A01 CSCL 15/3

This is a study of the reliability and maintainability of the tail warning system (TWS) AN/ALQ-153. This TWS is a solid state pulsed Doppler radar designed to provide warning and initiate countermeasures against threats attacking from the tail of B-52G/H aircraft
Author (GRA)

**N82-18483# European Space Agency Paris (France)
VOLUMETRIC PATTERN PREDICTION OF ANTENNAS ON AIRCRAFT USING THE GEOMETRICAL THEORY OF DIFFRACTION Ph D Thesis - Kaiserslautern Univ**

Thomas Jank Oct 1981 146 p refs Transl into ENGLISH of 'Bestimmung des raemlichen Strahlungsdiagramms von Antennen auf Flugzeugen mittels des geometrischen Beugungstheorie', Rept DFVLR-FB-80-01 DFVLR Oberpfaffenhofen West Germany, Nov 1979

(ESA-TT-677, DFVLR-FB-80-01) Avail NTIS HC A07/MF A01 DFVLR Cologne DM 29 90

High frequency radiation patterns of aircraft dipole and slot antennas are calculated using the geometrical theory of diffraction (GTD). A mathematical model of an aircraft is presented. Arbitrary pattern sections are obtained by solving the ray tracing problem for rays which contribute significantly to the total field. Storage techniques and integration methods for the ray tracing problem (a boundary value problem) are discussed. Comparison with measured results obtained from physical models validate the use of the GTD and model
Author (ESA)

**N82-18493* National Aeronautics and Space Administration
Hugh L Dryden Flight Research Center, Edwards Calif**

APPARATUS FOR DAMPING OPERATOR INDUCED OSCILLATIONS OF A CONTROLLED SYSTEM Patent

John W Edwards and John W Smith inventors (to NASA)
Issued 3 Nov 1981 13 p Filed 29 Feb 1980 Supersedes
N80-20488 (18 - 11, p 1409)

(NASA-Case-FRC-11041-1 US-Patent-4 298,833,
US-Patent-Appl-SN-126064 US-Patent-Class-318-561
US-Patent-Class-318-620 US-Patent-Class-318-621
US-Patent-Class-318-622) Avail US Patent and Trademark
Office CSCL 09C

Flight control-related apparatus for damping operator induced oscillations of a controlled system responding to an operator controlled signal is described. The device utilizes a lag-lead filter for frequency and amplitude estimation of the control input, and a rectification and smoothing filter for producing a signal proportional to the absolute value of the frequency and amplitude estimate for use in suppression of the control system output signal. In one embodiment, this is accomplished by computing a correction signal in a correction generating section. In a second embodiment, a second rectification and smoothing filter produces a signal proportional to the absolute value of the controlled input signal. A ratio of the outputs of the first and second rectification and smoothing filters is then used in a generator to generate a gain factor $k_{sub q}$ for the control system to reduce the gain of the output signal of the control system, thereby to provide a damped control output signal without rate limiting the controlled element.

Official Gazette of the U S Patent and Trademark Office

**N82-18503 Royal Aircraft Establishment Farnborough (England)
A DESIGN FOR A 32-CHANNEL MULTIPLEXER**

P F Martinson 26 Jan 1981 35 p refs
(RAE-TM-RAD-NAV-145 BR77700) Copyright Avail Issuing
Activity

A time scan analog system multiplexer used for recording data during flight trials of unmanned aircraft navigation sensors is described. The 32 inputs are buffered then multiplexed in groups of 8 onto 4 lines. These four are multiplexed onto one line and the signal passes through the output buffer to the recorder. Aircraft attitude, heading and height are recorded. Signals from a camera and a kinetheodolite tracking system are synchronized. Operating conditions were simulated using a

helicopter. Noise and drift are due to the recorder. The multiplexer copes well with signals of several kHz bandwidth (raw data) and signals of a few Hz bandwidth (processed data, test signals). It can be used with any multitrack tape recorder having an FM recording format on at least two tracks. It can be converted for use in a digital telemetry system.
Author (ESA)

**N82-18553# Thermo Electron Corp, Waltham Mass
OPEN-CYCLE VAPOR COMPRESSION HEAT PUMP Annual Progress Report, 1980**

Ravi Sakhuja and Frederick E Becker 5 May 1981 54 p
(Contract GRI-5011-342-0094)
(PB82-110503 TE4224-243-81, GRI-80/0064) Avail NTIS
HC A04/MF A01 CSCL 13A

Recovery and upgrading of low-grade steam or waste heat sources offers a great potential of energy conservation. Thermo Electron is developing an open cycle vapor compression steam heat pump to meet this objective. The system utilizes excess low-pressure steam or that produced from an industrial excess heat source with a waste heat boiler and compresses this steam to the desired pressure level for process use. The compressor is driven by a prime mover such as a gas turbine, gas engine, etc. The prime mover exhaust heat also can be recovered to generate additional process steam. The fuel consumption of this system can be as low as 30 to 50 percent in comparison to a direct-fired boiler over the expected range of process conditions. Simple payback periods as low as one year can be achieved.
GRA

**N82-18612*# National Aeronautics and Space Administration
Lewis Research Center Cleveland, Ohio**

METAL HONEYCOMB TO POROUS WIREFORM SUBSTRATE DIFFUSION BOND EVALUATION

A Vary, P E Moorhead and D R Hull 1982 12 p refs
Presented at the Spring Conf of the Am Soc for Nondestructive Testing, Boston, 22-25 Mar 1982
(NASA-TM-82793, E-959) Avail NTIS HC A02/MF A01 CSCL 14D

Two nondestructive techniques were used to evaluate diffusion bond quality between a metal foil honeycomb and porous wireform substrate. The two techniques, cryographics and acousto-ultrasonics, are complementary in revealing variations of bond integrity and quality in shroud segments from an experimental aircraft turbine engine.
S L

N82-18628# Purdue Univ Lafayette, Ind School of Aeronautics and Astronautics

A COMPILATION OF STRESS INTENSITY FACTOR SOLUTIONS FOR FLAWED FASTENER HOLES Final Report, Jun 1978 - Aug 1981

A F Grandt Jr and T E Kullgren (US Air Force Academy)
Nov 1981 86 p refs
(AF Proj 2307 AF Proj 2418)
(AD-A108753 AFWAL-TR-81-4112) Avail NTIS
HC A05/MF A01 CSCL 20/1

Several sets of stress intensity factor solutions are provided for through-the-thickness corner and surface flawed holes. Results are given for both remote tensile and crack face pressure loading. It is suggested that the crack face pressure solutions can be used with the linear superposition method to analyze many other practical crack problems. The superposition technique is demonstrated with several sets of example calculations.
Author (GRA)

N82-18803*# Colorado State Univ Fort Collins Dept of Atmospheric Science

AIRCRAFT MEASUREMENTS AND ANALYSIS OF SEVERE STORMS- 1976 FIELD EXPERIMENT Final Report

P C Sinclair Feb 1982 101 p refs
(Grant NSG-5105)
(NASA-CR-168519) Avail NTIS HC A06/MF A01 CSCL 04B

Severe storm aircraft measurements are documented as well as the instrumentation and operational features of aircraft mobility capabilities. The measurements and data analyses indicate that the concept of a highly mobile research aircraft capability for obtaining detailed measurements of wind, temperature, moisture, sphereics, etc. near and within severe storm systems forecast 48 hours in advance in a 1000 nm operating radius is feasible and was successfully demonstrated. The measurements and analyses reveal several severe storm features and insights with respect to storm air flow circulations and inflow-outflow.

N82-18835

orientation. Precipitation downdraft air is recirculated back into the updraft core below the cloud in both back and front feeder type storms. In a back feeder type storm the downdraft outflow air ahead of the storm is also recirculated back into the updraft region near cloud base. S L

N82-18835# National Oceanic and Atmospheric Administration, Boulder, Colo

DEVELOPMENT OF A CLEAR AIR RADAR TO DETECT METEOROLOGICAL HAZARDS AT AIRPORTS Final Report, 1 Oct 1978 - 21 Sep 1981

R B Chadwick, K P Moran, W C Campbell, K B Eamshaw, and T R Detman. 21 Sep 1981. 113 p refs.
(Contract ESD-0-0630 AF Proj 6670)
(AD-A108236 AFGL-TR-81-0268) Avail NTIS HC A06/MF A01 CSCL 17/9

To be useful in detecting meteorological hazards such as low-level wind shear near airports, a radar must be able to (1) detect backscatter from both clear air and rain, (2) operate at short ranges and low elevation angles, and (3) measure Doppler frequencies caused by air motion. The development of a radar with these characteristics is described and the results of testing this radar at airports are presented. Special emphasis is placed on the problems of low elevation angle operation and clutter suppression. The importance of proper siting is pointed out. In addition, it is demonstrated that the radar can readily detect the turbulent wakes of large jet aircraft. Author (GRA)

N82-18920# Naval Research Lab., Washington, D C. Computer Science and Systems Branch

A-7E SOFTWARE MODULE GUIDE Interim Report

K H Britton and D L Parnas. 8 Dec 1981. 36 p refs.
(AD-A108649, NRL-MR-4702) Avail NTIS HC A03/MF A01 CSCL 09/2

This document describes the basic organization of NRL's version of the A-7E onboard flight software. The report describes a structure in which modules have been designed in accordance with the Information Hiding Principle. Because of the larger number of modules that result when this principle is applied, the modules are arranged in a hierarchy. The hierarchy should simplify the task of a maintenance programmer assigned to make a specific modification. The document also describes the principles used in the design of the software. It is intended to be useful both as a guide to the A-7E software and as a model for those developing other software systems. Author (GRA)

N82-18922# Massachusetts Inst of Tech., Cambridge. Artificial Intelligence Lab

A PROGRAM TESTING ASSISTANT

David Chapman. Nov 1981. 25 p refs.
(Contract N00014-80-C-0505)
(AD-A108147, AI-M-651) Avail NTIS HC A02/MF A01 CSCL 09/2

This paper describes the design and implementation of a program testing assistant which aids a programmer in the definition, execution and modification of test cases and executes them automatically when appropriate. It modifies test cases to preserve their usefulness when the program they test undergoes certain types of design changes. The testing assistant acts as a fully integrated part of the programming environment and cooperates with existing programming tools including a display editor, compiler, interpreter, and debugger. Author (GRA)

N82-18995*# Modern Analysis, Inc., Ridgewood, N J
STUDY OF CABIN NOISE CONTROL FOR TWIN ENGINE GENERAL AVIATION AIRCRAFT

R Vaicatis and M Slazak. Hampton, Va. NASA Langley Research Center. Feb 1982. 147 p refs.
(Contract NAS1-16117)
(NASA-CR-165833, MAI-1) Avail NTIS HC A07/MF A01 CSCL 20A

An analytical model based on modal analysis was developed to predict the noise transmission into a twin-engine light aircraft. The model was applied to optimize the interior noise to an A-weighted level of 85 dBA. To achieve the required noise attenuation, add-on treatments in the form of honeycomb panels, damping tapes, acoustic blankets, septum barriers and limp trim panels were added to the existing structure. The added weight of the noise control treatment is about 1.1 percent of the total gross take-off weight of the aircraft. B W

N82-18996*# National Aeronautics and Space Administration, Langley Research Center, Hampton, Va

ANNOYANCE CAUSED BY PROPELLER AIRPLANE FLYOVER NOISE. PRELIMINARY RESULTS

David A. McCurdy and Clemans A. Powell. Dec 1981. 35 p refs.
(NASA-TM-83244) Avail NTIS HC A03/MF A01 CSCL 20A

The annoyance response of people to the noise of propeller airplane flyovers was examined. The specific items of interest were (1) the annoyance prediction ability of current noise metrics, (2) the effect of tone corrections on prediction ability, (3) the effect of duration corrections on prediction ability, and (4) the effect of 'critical band' corrections on the prediction ability of perceived noise level. Preliminary analyses of the data obtained from two experiments are presented. The first experiment examined 11 propeller airplanes with maximum takeoff weights greater than or equal to 5700 kg. The second experiment examined 14 propeller airplanes weighing 5700 kg or less. Also included in each experiment were five different commercial service jet airplanes. Each airplane noise was presented at D-weighted sound pressure levels of 70, 80 and 90 dB to subjects in a testing room which simulates the outdoor acoustic environment. Subjects judged 108 stimuli in the first experiment and 132 stimuli in the second experiment. Perceived noise level predicted annoyance better than A, D or E-weighted sound pressure level. Corrections for tones greater than or equal to 500 Hz generally improved prediction ability for the heavier propeller airplanes. B W

N82-19084*# National Aeronautics and Space Administration, Washington, D C

NASA POCKET STATISTICS

Jan 1982. 70 p
(NASA-TM-84134) Avail NTIS HC A04/MF A01 CSCL 05A

NASA program goals and objectives, major mission performance, USSR space flights, comparisons of the USA and USSR space records, and selected technical, financial and manpower data are summarized. N W

N82-19132*# National Aeronautics and Space Administration, Washington, D C

BIBLIOGRAPHY OF NASA PUBLISHED REPORTS ON GENERAL AVIATION, 1975 TO 1981

Jun 1981. 277 p
(NASA-TM-83307) Avail NTIS HC A13/MF A01 CSCL 01B

This bibliography lists 478 documents which relate to all heavier-than-air fixed wing aircraft exclusive of military types and those used for commercial air transport. An exception is the inclusion of commuter transport aircraft types within the general aviation category. NASA publications included in this bibliography are conference publications (CP), reference publications (RP), technical memorandums (TM, TMX), technical notes (TN), technical papers (TP), and contractor reports (CR). In addition, papers and articles on NASA general aviation programs published by technical societies (AIAA, SAE, etc.) are included as well as those listed in NASA's Scientific and Technical Aerospace Reports (STAR) Journal. Author and subject indexes are also provided to facilitate use of the bibliography. T M

N82-19134*# National Aeronautics and Space Administration, Langley Research Center, Hampton, Va

ELECTRIC FLIGHT SYSTEMS

Nelson J. Groom, ed. and Ray V. Hood, ed. Feb 1982. 269 p. Proceedings of workshop held in Hampton, Va. 9-10 Jun 1981.

(NASA-CP-2209, L-14965) Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating presentations on the development of electric flight systems for the all-electric aircraft and for spacecraft are presented.

N82-19135*# Lockheed-California Co., Burbank

ELECTRIC FLIGHT SYSTEMS, OVERVIEW

Michael J. Cronin. In NASA Langley Research Center. Elec Flight Systems. Feb 1982. p. 61-94.

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on electric flight systems

are presented Fuel consumption the power plant assembly flight control technology, electromechanical actuator systems and components of possible power systems are surveyed J D H

N82-19136*# General Electric Co., Cincinnati, Ohio Aircraft Engine Group
A PROPULSION VIEW OF THE ALL-ELECTRIC AIRPLANE

Robert P Wagner /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 95-102

Avail NTIS HC A12/MF A01 CSCL 21E

Materials illustrating a presentation on electric propulsion systems are presented The electric engine and engine/generator configurations are described and NASA's role outlined J D H

N82-19137*# Pratt and Whitney Aircraft Group, East Hartford Conn Commercial Products Div
POTENTIAL PROPULSION CONSIDERATIONS AND STUDY AREAS FOR ALL-ELECTRIC AIRCRAFT
Thomas G Lenox /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 103-112

Avail NTIS HC A12/MF A01 CSCL 21E

Materials illustrating a presentation on all-electric aircraft propulsion systems are presented Propulsion system impacts on aircraft design and areas requiring further study are outlined J D H

N82-19138*# Westinghouse Electric Corp Lima, Ohio Air All-Electronics Div
A LOOK INTO THE FUTURE THE POTENTIAL OF THE ALL-ELECTRIC SECONDARY POWER SYSTEM FOR THE ENERGY EFFICIENT TRANSPORT
Alan E King /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 113-124

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on the all-electric aircraft power system are presented The advantages of the system and the planning time table are outlined J D H

N82-19139*# Sundstrand Aviation-Rockford, Ill
THE 400-HERTZ CONSTANT-SPEED ELECTRICAL GENERATION SYSTEMS
Richard McClung /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 125-146

Avail NTIS HC A12/MF A01 CSCL 09C

Materials illustrating a presentation on 400 Hz constant speed generation systems are presented The system features are outlined, components and functioning described, and display graphics illustrated J D H

N82-19140*# AirResearch Mfg Co Torrance Calif
ELECTRIC ECS

Dale O Moeller /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 147-154

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on electric environmental control systems for electric flight systems are presented Requirements are outlined and schematics presented J D H

N82-19141*# Hamilton Standard Windsor Locks Conn
ENVIRONMENTAL CONTROL SYSTEMS

Fred M Rosenbush /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 155-188

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on environment control systems for electric flight systems are presented Schematics and flow diagrams of fresh air source and air conditioning systems, and vapor cycle and air cycle parts lists are presented J D H

N82-19142*# Honeywell Inc Clearwater Fla
OVERVIEW OF HONEYWELL ELECTROMECHANICAL ACTUATION PROGRAMS

Charles Wyllie /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 163-187

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on electromechanical actuation programs (EMA) are presented The development history is outlined Space shuttle flight control systems and the advantages of EMAS and EMA technology status and development requirements are outlined J D H

N82-19143*# Rockwell International Corp Cedar Rapids Iowa
DIGITAL FLIGHT CONTROLS

John C Hall /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 189-212

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on digital flight controls for electric flight systems are presented System architecture and design criteria are outlined and components described J D H

N82-19144*# Boeing Commercial Airplane Co Seattle Wash
ELECTRIC FLIGHT SYSTEMS

C William Clay /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 213-234

Avail NTIS HC A12/MF A01 CSCL 09C

Materials used to illustrate a presentation on the development of electric flight systems are presented Systems concepts are outlined J D H

N82-19145*# National Aeronautics and Space Administration Lewis Research Center, Cleveland Ohio

ENGINE TECHNOLOGY

Anthony C Hoffman /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 235-240

Avail NTIS HC A12/MF A01 CSCL 21E

Materials used in a presentation on development of engine technology for electric flight systems are presented Component and system technology issues, NASA's role and flight test requirements are outlined J D H

N82-19146*# National Aeronautics and Space Administration Lewis Research Center, Cleveland Ohio

POWER SYSTEMS

Robert Finke /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 241-246

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation of the development of power systems are presented The technology issues and tradeoffs the role of NASA, and testing requirements are outlined J D H

N82-19148*# National Aeronautics and Space Administration Lyndon B Johnson Space Center, Houston Tex

ELECTROMECHANICAL ACTUATORS

James Bigham /in NASA Langley Research Center Elec Flight Systems Feb 1982 p 253-258

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on the development of electromechanical actuators (EMA) for electric flight systems are presented Technology issues are identified, and major steps relative to EMA development NASA's role and a technology procurement plan are outlined J D H

N82-19149*# National Aeronautics and Space Administration Langley Research Center, Hampton Va

DIGITAL FLIGHT CONTROLS

Billy Dove /in its Elec Flight Systems Feb 1982 p 259-261

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating the presentation on digital flight controls are presented Technology issues the role of NASA, and steps in the development of flight controls are outlined J D H

N82-19150*# National Aeronautics and Space Administration Langley Research Center Hampton, Va

ELECTRIC FLIGHT SYSTEMS INTEGRATION

Ray V Hood /in its Elec Flight Systems Feb 1982 p 263-268

Avail NTIS HC A12/MF A01 CSCL 01C

Materials illustrating a presentation on the integration of

N82-19154

components and subsystems of electric flight systems are presented. The technology issues are outlined, and near and far term implications of issues affecting the systems integration are outlined. J D H

N82-19154# Office National d'Etudes et de Recherches Aérospatiales, Paris (France)

MULTIVARIABLE AIRCRAFT CONTROL BY MANEUVER COMMANDS. AN APPLICATION TO AIR TO SURFACE GUNNERY

Binh DangVu. *In its* La Rech Aérospatiale, Bimonthly Bull No 1981-3, May-Jun 1981 (ESA-TT-714) Oct 1981 p 9-19 refs. Transl into ENGLISH of 'La Rech Aérospatiale, Bull Bimestriel (Paris) No 1981-3, May-Jun 1981' p 149-159

Avail NTIS HC A05/MF A01, original report in FRENCH available at ONERA, Paris FF 45

Aircraft control where pilot commands are variables directly related to aircraft motion in opposition to deflection angles of control surfaces is described. Linear optimal control theory is applied so as to improve flight qualities and reduce the work load of the pilot. A control system for sideslip, rate of roll, and rate of pitch was tested in numerical simulation and its efficiency for aiming in air-to-surface gunnery was assessed. Results show that control of the rate of pitch is well adapted for cancelling longitudinal aiming deviations, but that control of yaw rate is preferable to roll for cancelling lateral deviations. Another system obtained by integrating the flight control and fire control systems is also suggested. Author (ESA)

N82-19156# Office National d'Etudes et de Recherches Aérospatiales, Paris (France)

ELECTRICAL GROUND TESTING OF AIRCRAFT ANTISTATIC PROTECTION

A Bruere. *In its* La Rech Aérospatiale, Bimonthly Bull No 1981-3, May-Jun 1981 (ESA-TT-714) Oct 1981 p 47-56 refs. Transl into ENGLISH of 'La Rech Aérospatiale, Bull Bimestriel (Paris), No 1981-3, May-Jun 1981' p 187-196

Avail NTIS HC A05/MF A01, original report in FRENCH available at ONERA, Paris FF 45

Methods of ensuring aircraft protection against electrostatic spurious phenomena are reviewed and a device for ground testing of this protection is described. The equipment provides for checking the surface resistance of antistatic treatments as well as the quality of the electrical connections between the various components of the external structure and the aircraft potential reference point. Problems in electrostatic quality control for aircraft when testing in the presence of a finishing coat of paint are emphasized. The prototype device is depicted while operating and performance principles are explained. Author (ESA)

N82-19158# Office National d'Etudes et de Recherches Aérospatiales, Paris (France)

INDUCTION DRIVEN TRANSONIC WIND TUNNEL T2 OPERATION AT ROOM TEMPERATURE AND CRYOGENIC ADAPTATION

A Mignosi, D Faulmann, and A Seraudie. *In its* La Rech Aérospatiale, Bimonthly Bull No 1981-3, May-Jun 1981 (ESA-TT-714) Oct 1981 p 63-74 refs. Transl into ENGLISH of 'La Rech Aérospatiale, Bull Bimestriel (Paris), No 1981-3, May-Jun 1981' p 203-215

Avail NTIS HC A05/MF A01, original report in FRENCH available at ONERA, Paris FF 45

The transformation of the induction driven wind tunnel T2 (0.4 m X 0.4 m) into a cryogenic intermittent wind tunnel which uses high pressure air as driving gas and nitrogen as coolant is described. The operating mode and optimization of the wind tunnel for low temperature operation are discussed. Theoretical and experimental aspects of the transformed facilities, i.e. modification of the circuit, thermal insulation techniques, liquid nitrogen injection, startup process, cryogenic operating mode and expected performance, are presented. Author (ESA)

N82-19160# Network Analysis Corp., Vienna, Va
NATIONAL AIRSPACE DATA INTERCHANGE NETWORK (NADIN) SUPPORT OF REMOTE MAINTENANCE MONITORING SYSTEM (RMMS) Final Report
Dec 1981 111 p refs

(Contract DOT-FA79WA-4335)

(AD-A109125 NAC/FR-303J/01 FAA-RD-81-109) Avail NTIS HC A06/MF A01 CSCL 05/2

National Airspace Data Interchange Network (NADIN) architectural enhancements necessary to support the Remote Maintenance Monitoring System (RMMS) and MMS programs are described. Several alternative approaches are formulated. These alternatives are compared and recommendations are made. It is found that the NADIN backbone has sufficient capacity to handle initial RMMS traffic at adequate performance levels. An X 25 compatible interface for the NADIN and MPS connection is recommended. Additional frame routing capabilities at the NADIN concentrator and front end processors are required and future MPS communications will be best served by a fully distributed packet switched NADIN capable of supporting complete X 25 functions. Author (GRA)

N82-19161# Aeronautical Research Labs., Melbourne (Australia)
AERONAUTICAL RESEARCH LABORATORIES STRUCTURES DIVISION Annual Report, 1979 - 1980

F H Hooke ed. Apr 1981 46 p
(AD-A109049 ARL/STRUC-NOTE-473) Avail NTIS HC A03/MF A01 CSCL 01/3

This report describes the functions organization, staffing, unclassified research activities and ad-hoc investigations in progress in the Structures Division, Aeronautical Research Laboratories during the year 1979/80. Author (GRA)

N82-19167# Boeing Military Airplane Development, Seattle, Wash

TRANSONIC PERTURBATION ANALYSIS OF WING-FUSELAGE-NACELLE-PYLON CONFIGURATIONS WITH POWERED JET EXHAUSTS

J C Wai, C C Sun, and H Yoshihara. Feb 1982 67 p refs
(Contract NAS1-15887)
(NASA-CR-165852) Avail NTIS HC A04/MF A01 CSCL 01A

A method using a transonic small disturbance code with successive line over-relaxation is described for treating wing/fuselage configurations with a nacelle/pylon/powered jet. Examples illustrating its use for the NASA transport research model are given. Reasonable test/theory comparisons were obtained. Author

N82-19170# National Aeronautics and Space Administration, Washington, D C

NASA/HAA ADVANCED ROTORCRAFT TECHNOLOGY AND TILT ROTOR WORKSHOPS VOLUME 1 EXECUTIVE SUMMARY

5 Dec 1980 115 p refs. Workshop held at Palo Alto, Calif. 3-5 Dec 1980
(NASA-TM-84149) Avail NTIS HC A06/MF A01 CSCL 01A

This presentation provides an overview of the NASA Rotorcraft Program as an introduction to the technical sessions of the Advanced Rotorcraft Technology Workshop. It deals with the basis for NASA's increasing emphasis on rotorcraft technology, NASA's research capabilities, recent program planning efforts, highlights of its 10-year plan and future directions and opportunities. L F M

N82-19171# National Aeronautics and Space Administration, Washington, D C

NASA/HAA ADVANCED ROTORCRAFT TECHNOLOGY AND TILT ROTOR WORKSHOPS VOLUME 2 OPERATORS' VIEWS

5 Dec 1980 111 p refs. Workshop held at Palo Alto, Calif. 2-5 Dec 1980
(NASA-TM-84148) Avail NTIS HC A06/MF A01 CSCL 01A

A special panel of helicopter users give presentations in 12 basic areas of helicopter applications. Development of the helicopter and the needs for future growth are discussed. L F M

N82-19172# National Aeronautics and Space Administration, Washington, D C

NASA/HAA ADVANCED ROTORCRAFT TECHNOLOGY AND TILT ROTOR WORKSHOPS VOLUME 3 AERODYNAMICS AND STRUCTURES SESSION

4 Dec 1980 285 p refs. Workshop held at Palo Alto, Calif. 2-5 Dec 1980

(NASA-TM-84147) Avail NTIS HC A13/MF A01 CSCL 01A

Advanced rotorcraft technology and tilt rotor aircraft were discussed Rotorcraft performance acoustics and vibrations were discussed as was the use of composite materials in rotorcraft structures Rotorcraft aerodynamics specifically the aerodynamic phenomena of a rotating and the aerodynamics of fuselages, was discussed R J F

N82-19173*# National Aeronautics and Space Administration Washington, D C
NASA/HAA ADVANCED ROTORCRAFT TECHNOLOGY AND TILT ROTOR WORKSHOPS. VOLUME 4. FLIGHT CONTROL AVIONICS SYSTEMS AND HUMAN FACTORS
 5 Dec 1980 149 p refs Workshop held at Palo Alto, Calif 2-5 Dec 1980

(NASA-TM-84146) Avail NTIS HC A07/MF A01 CSCL 01A

Helicopter user needs, technology requirements and status, and proposed research and development action are summarized It is divided into three sections flight dynamics and control, all weather operations, and human factors L F M

N82-19181*# National Aeronautics and Space Administration Langley Research Center Hampton, Va
EFFECTS OF INSTALLATION OF F101 DFE EXHAUST NOZZLES ON THE AFTERBODY-NOZZLE CHARACTERISTICS OF THE F-14 AIRPLANE

David E Reubush and John R Carlson Mar 1982 133 p refs

(NASA-TM-83250 L-14895) Avail NTIS HC A07/MF A01 CSCL 01A

A wind-tunnel investigation was conducted to determine the effects of F101 DFE (derivative fighter engine) nozzle axial positioning on the afterbody-nozzle longitudinal aerodynamic characteristics of the F-14 airplane The model was tested in the Langley 16-Foot Transonic Tunnel at Mach numbers from 0.7 to 1.25 and angles of attack from about -2 to 6 degrees Compressed air was used to simulate nozzle exhaust flow at jet total-pressure ratios from 1 (jet off) to about 8 The results of the investigation show that for subsonic Mach numbers the intermediate cruise nozzle position of the three positions tested resulted in the lowest drag Author

N82-19194# Bristol Univ (England) Dept of Aeronautical Engineering
THE EFFECT OF A WELL ON THE AERODYNAMICS OF A SPOILER B S Thesis

N A Cemm and J J Ovens Jun 1981 82 p refs Original contains color illustrations

(BU-268) Avail NTIS HC A05/MF A01

As an aid to spoiler design the aerodynamics of a spoiler and its well were investigated Particular attention was paid to gap and deployment angle Three different shapes of spoiler and three types of well were tested All tests were two dimensional, the spoiler being attached to a flat plate at zero incidence A well was cut into the plate such that the spoiler was flush when not deployed The Reynolds number was 62 000, based on fence chord Flow visualization techniques and static pressure measurements were used both along the flat plate and around the spoiler to determine and understand the pressure distribution Integration of the pressure results shows the normal force distribution The application of the results to spoiler design is discussed through examples Author (ESA)

N82-19195 Department of Trade and Industry, London (England)
REPORT OF THE AIR TRAFFIC FORECASTING WORKING PARTY, 1981

Sep 1981 30 p ref

Copyright Avail Issuing Activity

The U K forecasting model (improved by including relative tourist prices as a variable in leisure traffic equations and by refining business traffic specifications) is used to predict air traffic demand in the 1990s London airports are treated separately The effects of oil price rises, a channel tunnel and hotel constraints in London are discussed An increase of between 28 and 70 million passengers is predicted, i.e a 2.5% to 5% annual growth rate Growth rates for domestic traffic are lower than those projected for international traffic so that domestic traffic, which was 26% of the total in 1979, falls by 1995 to 23% on the low scenario and 20% on the high scenario Author (ESA)

N82-19196*# Little (Arthur D) Inc, Cambridge Mass
AN ASSESSMENT OF THE CRASH FIRE HAZARD OF LIQUID HYDROGEN FUELED AIRCRAFT Final Report
 Feb 1982 132 p refs

(Contract NAS3-22482)

(NASA-CR-165526 ADL-85161)

Avail NTIS

HC A07/MF A01 CSCL 01C

The crash fire hazards of liquid hydrogen fueled aircraft relative to those of mission equivalent aircraft fueled either with conventional fuel or with liquefied methane were evaluated The aircraft evaluated were based on Lockheed Corporation design for 400 passenger Mach 0.85 5500 n mile aircraft Four crash scenarios were considered ranging from a minor incident causing some loss of fuel system integrity to a catastrophic crash Major tasks included a review of hazardous properties of the alternate fuels and of historic crash fire data a comparative hazard evaluation for each of the three fuels under four crash scenarios a comprehensive review and analysis and an identification of areas further development work The conclusion was that the crash fire hazards are not significantly different when compared in general for the three fuels although some fuels showed minor advantages in one respect or another R J F

N82-19197# Federal Aviation Administration, Atlantic City NJ
ANALYSIS OF A NONLINEAR ALTITUDE TRACKING METHOD Final Report, Sep - Dec 1980

Barry R Billmann Nov 1981 57 p refs

(FAA Proj 052-242-320)

(AD-A108878 FAA-CT-81-15 FAA-RD-81-60) Avail NTIS HC A04/MF A01 CSCL 01/2

This report analyzes the performance of the nonlinear altitude tracker developed for the Active Beacon Collision Avoidance System (BCAS) by Lincoln Laboratory The tracker is intended for use in the collision avoidance logic of the BCAS system The nonlinear tracker performance was characterized through comparisons with the previous altitude tracker The original tracker, used by the collision avoidance logic was a simplistic alpha-beta tracker The nonlinear tracker performance evaluation was conducted in three phases (1) The stand-alone error characteristics of the tracker were obtained Simulated mode C report sequences were provided directly to the tracker (2) The nonlinear tracker was integrated directly into the collision avoidance logic With the use of the Fast-Time Encounter Generator (FTEG), a comparative study of performance with the nonlinear tracker versus the alpha-beta tracker was made (3) Selected live flight test encounters were used to analyze the relative performance of the alpha-beta tracker versus the nonlinear tracker The stand-alone analysis revealed that the nonlinear tracker consistently had smaller maximal errors in vertical rate estimation and a smaller transient rate response delay than did the alpha-beta tracker Both the live flight test encounter simulations and the FTEG scenario simulation indicated that nonlinear tracking often caused an increase in separation for encounters with vertically accelerating threats and reduced occurrences of incorrect command sense choice Author (GRA)

N82-19198# Federal Aviation Administration, Washington, D C
 Office of Management Systems

FAA STATISTICAL HANDBOOK OF AVIATION Annual Report, period ending 31 Dec 1980

31 Dec 1980 183 p

(AD-A109289) Avail NTIS HC A09/MF A01 CSCL 01/2

This report presents statistical information pertaining to the Federal Aviation Administration The National Airspace System, Airports, Airport Activity, U S Civil Air Carrier Fleet, U S Civil Air Carrier Operating Data, Airmen, General Aviation Aircraft, Aircraft Accidents, and a Glossary of the terms used in this publication Author (GRA)

N82-19199# Aeronautical Research Labs, Melbourne (Australia)
DISENGAGEMENT OF SAFETY HARNESS BUCKLES - CT4 Report, Aug - Dec 1979

S R Sarraillhe and G A Thomas Mar 1981 25 p

(AD-A109048 ARL/STRUC-NOTE-469)

Avail NTIS

HC A02/MF A01 CSCL 13/12

During the crash of a CT4 Airtrainer in August 1979 both safety harness buckles disengaged The crash was very severe but the harnesses did not show signs of overloading After a series of tests it was concluded that the buckles disengaged because of misalignment of the loads onto the buckle This misalignment may not be represented in the standard test procedures and they may give a false sense of security New

N82-19200

tests are proposed but further work would be desirable to establish design and test criteria Author (GRA)

N82-19200 Virginia Univ Charlottesville OPTIMAL AIRCRAFT LANDING PATTERNS FOR MINIMAL NOISE IMPACT Ph D Thesis

Robert Chi-Tuan Chang 1981 183 p
Avail Univ Microfilms Order No 8129300

A total system to perform the task of optimizing aircraft landing trajectories with respect to aircraft noise annoyance in the area near airports was developed. The noise annoyance considered was solely due to aircraft. Multiple aircraft on multiple landing paths were studied by the total system developed. While many of the subsystems such as the aircraft noise signature model annoyance model optimization methods etc already existed, the task was to combine all these together into a single working system. The various subsystems included an annoyance model (aircraft noise signature model population model impact intensity weighting function) formulation of aircraft landing paths and constraints performance measure and optimization. A single numerical number noise impact index which represents the average severity of noise impact over the entire population of a community was adopted as the annoyance index. Dissert Abstr

N82-19201# Committee on Science and Technology (U S House)

AIRCRAFT COLLISION AVOIDANCE SYSTEMS

Washington GPO 1981 443 p refs Hearings before the Subcomm on Transportation Aviation and Mater of the Comm on Sci and Technol 97th Congr 1st Sess No 5 31 Mar and 3 Apr 1981
(GPO-79-431) Avail Subcommittee on Transportation Aviation and Materials

Midair collision avoidance systems especially the beacon collision avoidance system is discussed. Magazine articles, letters, and statements of government and industry personnel are included. R J F

N82-19202# Committee on Science and Technology (U S House)

AIR TRAFFIC CONTROL EN ROUTE COMPUTER SYSTEM

Washington GPO 1981 10 p Rept to accompany H R 202 presented by the Comm on Sci and Technol 97th Congr 1st Sess, 14 Oct 1981
(GPO-89-008 H-Rept-97-271) Avail US Capitol House Document Room

Amendments to the House Resolution requiring the Administrator of the FAA to submit full research and development program planning documentation to the Committee with respect to the modernization and replacement of the en route computer system are presented. Background material included covers the current ATC system as well as the justification, benefits, costs and acquisition strategy for replacing the computer. It is recommended the FAA establish a mechanism whereby the judgements and experience of operating personnel and users of the air system be included in the en route computer development process. A R H

N82-19203# Mitre Corp McLean Va ACTIVE BEACON COLLISION AVOIDANCE SYSTEM (BCAS) LOGIC PERFORMANCE DURING OPERATIONAL FLIGHT TESTS Report, 13 Jul - 9 Sep 1980

R A Tornese and A L McFarland Washington FAA Jan 1981 123 p refs
(Contract DTFA01-81-C-10001)
(AD-A108893 MTR-80/W352 FAA-RD-80-138) Avail NTIS HC A06/MF A01 CSCL 17/7

Between 13 July and 9 September 1980, operational flight tests of an Active BCAS Experimental Unit (BEU) were conducted. The flight tests included 129 approaches to 28 different airports during 60 hours of flight. 14 unplanned encounters which gave rise to BCAS alerts were recorded. In each of the encounters the aircraft carrying the BEU came into a conflict with another aircraft entirely by chance. The other aircraft was not associated with the BCAS test program in any way. The primary purpose of the flight tests was to determine how many unplanned alerts would occur during normal flight operations and to assess whether each was a desirable or unwanted alert. In addition alert correctness timeliness, and utility were considered along with the potential impact of BCAS on the ATC system. The data was also used to determine approximately the region(s) where

desensitization of BCAS threat logic should be applied to limit unwanted alerts. GRA

N82-19205# Jet Propulsion Lab California Inst of Tech, Pasadena

VEHICLE TEST REPORT BATTRONIC PICKUP TRUCK

Theodore W Price, Thomas W Shain, Raymond J Freeman, and Michael F Pompa 1 Jan 1982 47 p refs
(Contracts NAS7-100 DE-A101-78CS-54209)
(NASA-CR-168637 JPL-Pub-82-8 DOE/CS-54209/6) Avail NTIS HC A03/MF A01 CSCL 13F

An electric pickup truck was tested to characterize certain parameters and to provide baseline data that can be used for the comparison of improved batteries that may be incorporated into the vehicle at a later time. The vehicle tests were concentrated on the electrical drive subsystem, i.e., the batteries, controller, and motor. The tests included coastdowns to characterize the road load and range evaluations for both cyclic and constant speed conditions. A qualitative evaluation of the vehicle's performance was made by comparing its constant speed range performance with other vehicles. S L

N82-19206# Canyon Research Group Inc, Westlake Village, Calif

DESCENT-RATE CUING FOR CARRIER LANDINGS EFFECTS OF DISPLAY GAIN, DISPLAY NOISE AND AIRCRAFT TYPE Intern Report, 1 May 1980 - 30 Nov 1981

Gavan Lintern, Daniel J Sheppard, and Charles E Kaul Oct 1981 42 p refs
(Contract N61339-78-C-0060)
(AD-A108801 TR-81-015, NAVTRAEQUIPCEN-78-C-0060-8) Avail NTIS HC A03/MF A01 CSCL 01/2

Two studies are reported concerning the utility of modifying a conventional Fresnel Lens Optical Landing System (FLOLS) to include variable-length vertical light arrays, or arrows, in order to provide descent-rate information to pilots making carrier landings. In the first study, the Descent-Rate Cuing (DRC) algorithm incorporated an angular gain to provide glideslope displacement information. The DRC system did not significantly improve glideslope tracking performance. Lineup performance was not adversely affected. The effects of aircraft type and noise on the DRC were also examined. In the second study, the DRC algorithm incorporated a modified linear gain to provide glideslope displacement information. The DRC system consistently reduced glideslope error throughout the approach. Comparison of the data and previous research suggests that a DRC system incorporating a linear gain can produce a strong and consistent improvement in glideslope control in carrier landings. Author (GRA)

N82-19207# Federal Aviation Administration, Atlantic City, N J TRANSPORT AIRCRAFT COCKPIT STANDARDIZATION (FEDERAL AVIATION REGULATIONS PART 25) Final Report

Richard Sulzer Nov 1981 42 p
(FAA Proj 161-200-130)
(AD-A108924, FAA-CT-80-54, FAA-EM-81-11) Avail NTIS HC A03/MF A01 CSCL 01/3

The present status of transport aircraft cockpit standardization was evaluated by examination of regulations and other design practice documents and by interviews with airline pilots and engineers. Flight critical areas most in need of increased standardization were identified as (1) primary flight guidance instrumentation and (2) pilot input keyboards. Additional areas proposed for further industry consultation, possibly leading to further standardization at a future date, include flap, slat, and leading-edge device control and display systems indicated airspeed (IAS)-Mach indicators, powerplant instrumentation, and electric and hydraulic power diagrams, displays, and controls. The continued use of a mixed metric and English unit measurement plan in both United States and foreign manufactured aircraft is noted and the incidence of pilot dual qualifications and the need for criteria for digital system software certification are also discussed. GRA

N82-19208# Army Aviation Engineering Flight Activity, Edwards AFB, Calif Directorate of Development and Qualification HELICOPTER ICING SPRAY SYSTEM (HISS) NOZZLE IMPROVEMENT EVALUATION Final Report

Daumants Belte Sep 1981 53 p refs
(AD-A109405, USAAEFA-79-02-2) Avail NTIS HC A04/MF A01 CSCL 01/2

The U'S Army Aviation Engineering Flight Activity (USAAEFA) operates a modified CH-47C helicopter as an airborne spray tanker to create a simulated icing test environment. This system was modified to improve its spray cloud characteristics with respect to uniformity of liquid water content (LWC) and reduction of drop size median volumetric diameter (MVD). The existing atomizers on the spray boom assembly were replaced by Sonic Development Corporation model 125-H 'Sonicore' nozzles. A UH-1H helicopter equipped with particle measuring spectrometers conducted in-flight sampling and calibration of a modified HISS spray cloud in conjunction with other helicopter icing tests. Average cross sectional dimensions of the present spray cloud was estimated as 36 ft wide and 8 ft deep. Usable values of cloud LWC in excess of 1 gram per cubic meter with a drop size MVD range of 20 to 35 microns can be generated at a 90 knot airspeed. GRA

N82-19209# Kaman Aerospace Corp., Bloomfield Conn
DEVELOPMENT OF MANUFACTURING TECHNOLOGY FOR FABRICATION OF A COMPOSITE HELICOPTER MAIN ROTOR SPAR BY TUBULAR BRAIDING Final Report, Sep 1978 - Sep 1980

Mark L White St Louis, Mo Army Aviation Research and Development Command Apr 1981 81 p refs
(Contract DAAG46-78-C-0070)
(AD-A109377 R-1618, AVRADCOM-TR-81-F-9) Avail NTIS HC A05/MF A01 CSCL 11/4

Mechanical tubular braiding has been shown to be a viable blade spar manufacturing process in a program which included preliminary design of an improved main rotor blade for the OH-58 helicopter. The blade incorporates an advanced aerodynamic shape and has as its primary structural member a Kevlar 49/epoxy spar fabricated by braiding. Achievement of an analytically acceptable blade and spar design meeting critical structural and dynamic requirements was not hindered by braiding process constraints. Mechanical property tests of flat panels and spar sections exhibited excellent correlation with analytical predictions, substantiating the applicability of normal composite laminate analysis methods and the validity of the specific design. Ballistic testing of spar sections demonstrated superior containment of structural damage compared to composite spars produced by more conventional methods. Manufacturing cost estimates predict a price reduction of 1/3 for the braided spar relative to a similar S-glass/epoxy spar for an OH-58 blade of identical external shape fabricated by orthodox, low-cost technology. Author (GRA)

N82-19210# Messerschmitt-Boelkow-Blohm G m b H., Otto-brunn (West Germany) Betriebsbereich

EXPERIENCE DURING THE DEVELOPMENT OF THE GERMAN-JAPANESE HELICOPTER BK 117 [ERFAHRUNGEN WAEREND DER ENTWICKLUNG DES DEUTSCH-JAPANISCHEN HUBSCHRAUBERS BK 117]

Klaus Szczepanik and Hans Fabian 1981 17 p In GERMAN Presented at DGLR Jahrestagung, Brunswick 1980
(MBB-UD-318-81-O) Avail NTIS HC A02/MF A01

The German-Japanese collaboration in building the BK 117 helicopter is described. The exchange of know-how, information dissemination, telecommunication, and technical expertise, are enumerated. It is shown that since international cooperation is possible, the German industries should be able to exchange and cooperate in the development of new products. Transl by EAK

N82-19211# Messerschmitt-Boelkow-Blohm G m b H., Otto-brunn (West Germany) Unternehmensbereich Raumfahrt
PERSPECTIVES FOR CONTROLLED WEAPONS TECHNOLOGY REPORT OF THE 90TH HELICOPTER FORUM [PERSPEKTIVEN DER LENKWAFFENTECHNIK FUER DIE 90ER JAHRE VORTRAGE VOR DEM HUBSCHRAUBER FORUM BUECKEBURG]

D Weis 2 May 1980 13 p In GERMAN Forum held in Bueckeburg West Germany 5-7 May, 1980
(MBB-UA-532-80-O) Avail NTIS HC A02/MF A01

A general forecasting for the essential guided missile system technology in the 1990s is presented. The development of armored guided missiles since its conception in 1955 and an outline of goals and trends of armored defense for the near and far future are presented. Possibilities of acceleration in mission accomplishments of future armored defensive weapon systems are examined. Transl by EAK

N82-19212# National Aerospace Lab., Amsterdam (Netherlands)

Flight Div

A METHOD FOR APPLYING LINEAR OPTIMAL CONTROL THEORY TO THE DESIGN OF A REGULATOR FOR A FLEXIBLE AIRCRAFT

L J J Erkelenz and J L Simons 31 Mar 1980 83 p refs
Previously announced as NLR-TR-75118-C Sponsored by Directorate of Material Air RNLAf
(NLR-TR-80032-U NLR-TR-75118-C) Avail NTIS HC A05/MF A01

A hypothetical control system that provides improved rigid body and structural mode damping of a flexible aircraft in order to improve the riding quality and minimize the wing bending moment during flight in turbulence is considered. The equations of motion are related to a high performance fighter aircraft with external stores. The feedback gains are determined using linear optimal control theory. A quadratic optimization criterion taking into account the normal acceleration at the pilot seat and the wing root bending moment is used. A number of optimal and suboptimal regulators are calculated. The system performance is expressed in terms of pole location, frequency response and power spectra for both pilot seat acceleration and wing root bending moment. Aircraft response to a deterministic gust disturbance is presented. Author (ESA)

N82-19213# Technische Hogeschool, Delft (Netherlands) Dept of Aerospace Engineering

ON THE DESIGN OF SOME AIRFOILS FOR SAILPLANE APPLICATION

L M M Boermans and H J W Selen Apr 1981 47 p refs
Presented at 17th OSTIV Congr Paderborn West Germany 1981

(VTH-LR-326) Avail NTIS HC A03/MF A01

Airfoils were designed such that by adding material to the surface an existing wing could be modified and tested in flight. Wind tunnel experiments on inner and outer wing segments are described giving information on the quality of actual airfoils achieved in serial production and of the LSL airfoil analysis and design computer program. The characteristics of several modern airfoils used in standard class sailplanes are analyzed and typical differences in the case of smooth surface and of rough leading edge are clarified. Wind tunnel measurements with real insect remains on a wing segment are compared with a well known simulated bug pattern and shown to have greatly different drag characteristics. The application of pneumatic turbulators to reduce the drag of an airfoil is discussed. The computer program was used to modify the wing of an ASW-193 sailplane. Flight tests are satisfactory. Author (ESA)

N82-19214# Bristol Univ (England) Dept of Aeronautical Engineering

A FURTHER STUDY OF HELICOPTER ROTOR PITCH-FLAP-PHASE COUPLING B S Thesis

A East and N S Sehmi Jun 1981 81 p refs
(BU-259) Avail NTIS HC A05/MF A01

Pitch-flap phase coupling between the blades of a helicopter rotor was studied in order to improve overall aircraft stability. A mathematical model was constructed for the Westland Lynx helicopter which incorporates a semiarticulated rotor head. Full expressions are derived in a lengthy but accurate fashion for the blade flapping motion as well as for rotor hub forces and moments. The rotor state defined is believed to be more accurate than that of any previous known treatment. Pitch-flap phase coupling of the form blade pitch angle at rotor center line - blade pitch control angle + pitch-flap coupling gain (blade flap angle + pitch-flap-phase coupling lead/lag) is introduced. The effect on the rotor derivatives is given with change in phase lead/lag angle and control gain. A full six degrees of freedom model is extensively used for the study of stability with the results beset with problems which are discussed. Author (ESA)

N82-19215# Bristol Univ (England) Dept of Aeronautical Engineering

A DESIGN STUDY OF THE MARSHAL B S Thesis

D Suen and G H Tan Jun 1981 55 p refs
(BU-262) Avail NTIS HC A04/MF A01

The feasibility of a six seat variant of the Britten Sheriff twin-engined aircraft the Marshal was studied. Results show that the Marshal, powered by two 200 hp engines and at an all-up-weight (AUW) of 3550 lb can compete in the open market both in terms of performance and price. No major structural alterations, except on the fuselage to accommodate two additional passengers, are envisaged. This aircraft is expected to be suitable.

N82-19216

for a touring role. For business flying a high cruise speed is favored and so a turbocharged version was also considered. The performance level attainable with two 200 h.p. turbocharged engines compares well with the competition. However, at an AUW of 3700 lb certain modifications to the wing are necessary. The indication is that the Marshal is a commercially viable project. Author (ESA)

N82-19216# Bristol Univ (England) Dept of Aeronautical Engineering

DESIGN STUDY INTO A HIGH ENDURANCE MINIROTORCRAFT BS Thesis

D A E Beedell and J C Hendy Jun 1981 71 p refs
Original contains color illustrations
(BU-265) Avail NTIS HC A04/MF A01

Competing models in a minirotorcraft competition for maximum endurance with an all up weight no greater than 5 kg, must fly above a height of 5 m within an area 10 m square are discussed. A design in which aerodynamics, stability and control, and mechanical and structural aspects are considered to obtain the size and angular velocity of the rotor for minimum power while sufficient stability and control for a long flight are still inherent in the overall system is presented. Weights of individual components are also examined. It is found that a rotor mounted engine configuration with rotor radius about 1.6 m and rotational velocity 4 to 5 revs/sec with engines half way along the rotors and with Hiller control rotors, is the most promising design. The possible endurance is some 12 hr and hence pilot error and mechanical failure become deciding factors. Author (ESA)

N82-19217*# Mitre Corp McLean, Va
A CONCEPT FOR A FUEL EFFICIENT FLIGHT PLANNING AID FOR GENERAL AVIATION Final Report

B P Collins A L Haines and C J Wales Washington NASA Mar 1982 96 p refs
(Contract NAS1-16430)
(NASA-CR-3533 MTR-81W233) Avail NTIS
HC A05/MF A01 CSCL 01D

A core equation for estimation of fuel burn from path profile data was developed. This equation was used as a necessary ingredient in a dynamic program to define a fuel efficient flight path. The resultant algorithm is oriented toward use by general aviation. The pilot provides a description of the desired ground track, standard aircraft parameters, and weather at selected waypoints. The algorithm then derives the fuel efficient altitudes and velocities at the waypoints. BW

N82-19218# Institute for Defense Analyses Arlington Va
ASSESSMENT OF AVIONIC EQUIPMENT FIELD RELIABILITY AND MAINTAINABILITY AS FUNCTIONS OF UNIT COST

Mark I Knapp and Joseph W Stahl 7 Oct 1981 24 p refs
Presented at the 16th Ann Dept of Defense Cost Analysis Symp., Arlington, Va 4-7 Oct 1981
(AD-A109373) Avail NTIS HC A02/MF A01 CSCL 01/3

Pound-for-pound avionics is generally recognized as the most expensive, complex and sophisticated part of an aircraft. Reliability and maintainability are critical characteristics that influence spares provisioning, maintenance resource requirements, system operational availability and, ultimately, investment and operating costs. Consequently, much attention has been focused upon improving the reliability and maintainability of avionics which, in the past, have been disappointingly low. This paper addresses avionics reliability and maintainability. The analysis was performed last year in partial response to a request of IDA by OASD (C3I) to provide information for use by DSARC principals at the Full-Scale Development milestone. Since the 5000 series of DoD Directives and Instructions emphasize analytical comparisons of any new systems under consideration by the DSARC with current, comparable systems, we undertook analyses to determine if there may be one or more historical relationships between field reliability and maintainability and avionic equipment characteristics that would assist in forecasting those attributes. GRA

N82-19219# European Space Agency Paris (France)
EQUIPMENT FOR TESTING AND MEASURING A 'HELMET MOUNTED SIGHT AND DISPLAY' SYSTEM WITH A COUPLED MOVABLE TV CAMERA IN THE FLIGHT SIMULATOR FOR RESEARCH OF THE DFVLR

Friedrich Erdmann R Dierke E Biertuempel, R Ehlers, and H

Loehr Nov 1981 70 p refs Transl into ENGLISH of Ein Versuchsaufbau zum Ausmessen eines Helmet Mounted Sight/Display mit Nachgeschaltetem Kameraschwenkrahmen im Forschungsflugsimulator der DFVLR Rept DFVLR-Mitt-80-04 DFVLR, Brunswick Jan 1980 Original report in GERMAN previously announced as ESA-95301
(ESA-TT-675 DFVLR-Mitt-80-04) Avail NTIS
HC A04/MF A01 DFVLR Cologne DM 17 40

A test installation capable of static and dynamic measurements on a helmet mounted sight and display (HMS/D) during simulated helicopter motion, by means of a steerable camera rotation framework was built. The rotation frame is gyro controlled and moves about two axes (in pitch and yaw). The HMS/D generates the helmet line of sight referred to the simulator platform (the aircraft based system) in terms of azimuth and elevation. Through the helmet mounted display using a semitransparent mirror an electronically produced cross hair (the helmet mounted sight) is superimposed on the image in the right eye of the pilot. The TV picture is also reflected into his eye enabling him to aim at a target on the sensor image. Test equipment accuracy is 40 min in azimuth, 20 min in elevation. Author (ESA)

N82-19220*# National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio
DILUTION JET BEHAVIOR IN THE TURN SECTION OF A REVERSE FLOW COMBUSTOR

Steven M Riddlebaugh Abraham Lipshitz (Ahuzar, Haifa Israel), and Isaac Greber (Case Western Reserve Univ., Cleveland, Ohio) Jan 1982 15 p refs Presented at the 20th Aerospace Sci Meeting, Orlando Fla, 10-14 Jan 1982 sponsored by AIAA (NASA-TM-82776 E-1107 AIAA-82-0192) Avail NTIS
HC A02/MF A01 CSCL 21E

Measurements of the temperature field produced by a single jet and a row of dilution jets issued into a reverse flow combustor are presented. The temperature measurements are presented in the form of consecutive normalized temperature profiles and jet trajectories. Single jet trajectories were swept toward the inner wall of the turn whether injection was from the inner or outer wall. This behavior is explained by the radially inward velocity component necessary to support irrotational flow through the turn. Comparison between experimental results and model calculations showed poor agreement due to the model's not including the radial velocity component. A widely spaced row of jets produced trajectories similar to single jets at similar test conditions, but as spacing ratio was reduced penetration was reduced to the point where the dilution jet flow attached to the wall. Author

N82-19221*# Garrett Turbine Engine Co., Phoenix Ariz
COOLED VARIABLE-AREA RADIAL TURBINE TECHNOLOGY PROGRAM Final Report

G D Large and L J Meyer Jan 1982 303 p refs
(Contract NAS3-22004)
(NASA-CR-165408) Avail NTIS HC A14/MF A01 CSCL 21E

The objective of this study was a conceptual evaluation and design analyses of a cooled variable-area radial turbine capable of maintaining nearly constant high efficiency when operated at a constant speed and pressure ratio over a range of flows corresponding to 50- to 100-percent maximum engine power. The results showed that a 1589K (2400 F) turbine was feasible that would satisfy a 4000-hour duty cycle life goal. The final design feasibility is based on 1988 material technology goals. A peak aerodynamic stage total efficiency of 0.88 was predicted at 100 percent power. Two candidate stators were identified: an articulated trailing-edge and a locally movable sidewall. Both concepts must be experimentally evaluated to determine the optimum configuration. A follow-on test program is proposed for this evaluation. Author

N82-19222*# National Aeronautics and Space Administration Lewis Research Center Cleveland Ohio

PERFORMANCE OF SINGLE-STAGE AXIAL-FLOW TRANSONIC COMPRESSOR WITH ROTOR AND STATOR ASPECT RATIOS OF 1.63 AND 1.78, RESPECTIVELY, AND WITH DESIGN PRESSURE RATIO OF 1.82

Royce D Moore and Lonnie Reid Feb 1982 112 p refs
(NASA-TP-1974 E-259) Avail NTIS HC A06/MF A01 CSCL 21E

The overall and blade-element performance of a transonic

compressor stage is presented over the stable operating flow range for speeds from 50 to 100 percent of design. The stage was designed for a pressure ratio of 1.82 at a flow 20.2 kg/sec and a tip speed of 455 m/sec. At design speed the stage achieved a peak efficiency of 0.821 at a pressure ratio of 1.817. The stage stall margin at design speed based on conditions at stall and peak efficiency was about 11 percent. Author

N82-19223 Royal Aircraft Establishment, Farnborough (England)
A CRITERION FOR THE PREDICTION OF THE RECOVERY CHARACTERISTICS OF SPINNING AIRCRAFT

T H Kerr 1981 24 p refs

(RAE-TN-AERO-2251) Copyright Avail Issuing Activity

Full scale spinning tests were analyzed in order to produce a recovery estimation method for straight and swept wing aircraft. The rate of rotation about spin axis X wing span/true rate of descent in ft/sec, was estimated from the general layout and loading of the aircraft. Antispin rolling moment coefficient (wind axis) due to the body at a mean incidence of 45 deg and antispin moment due to the movement of the rudder from neutral to fully antispin were calculated. The unbalanced (antispin) rolling moment coefficient is derived. This is plotted against $(I - (\text{pitching moment of inertia/rolling moment of inertia}))$ and whether the aircraft is likely to have a satisfactory spin recovery characteristic is assessed by reference to the empirical boundary tables provided. Data for Spitfire and Hurricane aircraft are provided. Recovery standards improve as pitching moment of inertia/rolling moment of inertia increases. Author (ESA)

N82-19224* Pennsylvania State Univ University Park Dept of Aerospace Engineering

AN EXPERIMENTAL STUDY OF THE EFFECT OF TAIL CONFIGURATION ON THE SPINNING CHARACTERISTICS OF GENERAL AVIATION AIRCRAFT M S Thesis

Mark G Ballin Mar 1982 182 p refs

(Grant NAG1-73)

(NASA-CR-168578) Avail NTIS HC A09/MF A01 CSCL 01C

The feasibility of using static wind tunnel tests to obtain information about spin damping characteristics of an isolated general aviation aircraft tail was investigated. A representative tail section was oriented to the tunnel free streamline at angles simulating an equilibrium spin. A full range of normally encountered spin conditions was employed. Results of parametric studies performed to determine the effect of spin damping on several tail design parameters show satisfactory agreement with NASA rotary balance tests. Wing and body interference effects are present in the NASA studies at steep spin attitudes but agreement improves with increasing pitch angle and spin rate, suggesting that rotational flow effects are minimal. Vertical position of the horizontal stabilizer is found to be a primary parameter affecting yaw damping and horizontal tail chordwise position induces a substantial effect on pitching moment. A R H

N82-19225* National Aeronautics and Space Administration Langley Research Center, Hampton, Va
SIMULATOR STUDY OF VORTEX ENCOUNTERS BY A TWIN-ENGINE, COMMERCIAL, JET TRANSPORT AIRPLANE

Earl C Hastings Jr and Gerald L Keyser, Jr Feb 1982 65 p refs

(NASA-TP-1966 L-14187) Avail NTIS HC A04/MF A01 CSCL 01C

A simulator study of vortex encounters was conducted for a twin-engine, commercial, jet transport airplane encountering the vortex flow field of a heavy, four-engine commercial, jet transport airplane in the final-approach configuration. The encounters were conducted with fixed controls and with a pilot using a state-of-the-art, manual-control system. Piloted encounters with the base-line vortex flow field out of ground effect (unattenuated) resulted in initial bank-angle excursions greater than 40 deg, coupled with initial sideslip-angle excursions greater than 10 deg. The severity of these initial upsets was significantly reduced when the vortex center was moved laterally or vertically away from the flight path of the encountering airplane. Smaller reductions occurred when the flow field was attenuated by the flight spoilers on the generating airplane. The largest reduction in the severity of the initial upsets, however, was from aging in ground effect. The severity of the initial upsets of the following airplane was relatively unaffected by the approach speed. Increasing the lift coefficient of the generating airplane resulted in an increase in the severity of the initial upsets. Author

N82-19226* Boeing Aerospace Co., Kent, Wash

A STUDY OF FLIGHT CONTROL REQUIREMENTS FOR ADVANCED, WINGED, EARTH-TO-ORBIT VEHICLES WITH FAR-AFT CENTER-OF-GRAVITY LOCATIONS Final Report

Andrew K Hepler Howard Zeck William H Walker and Alexander Polack Washington NASA Feb 1982 121 p

(Contract NAS1-16128)

(NASA-CR-3491) Avail NTIS HC A06/MF A01 CSCL 01C

Control requirements of Controlled Configured Design Approach vehicles with far-aft center of gravity locations are studied. The baseline system investigated is a fully reusable vertical takeoff/horizontal landing single stage-to-orbit vehicle with mission requirements similar to that of the space shuttle vehicle. Evaluations were made to determine dynamic stability boundaries, time responses, trim control operational center-of-gravity limits and flight control subsystem design requirements. Study tasks included a baseline vehicle analysis, an aft center of gravity study, a payload size study and a technology assessment. Author

N82-19227* Purdue Univ Lafayette, Ind School of Aeronautics and Astronautics

FLUTTER AND TIME RESPONSE ANALYSES OF THREE DEGREE OF FREEDOM AIRFOILS IN TRANSONIC FLOW Final Report, Nov 1979 - Dec 1980

T Y Yang and C H Chen Wright-Patterson AFB, Ohio AFAWL Aug 1981 60 p refs

(Grant AF-AFOSR-3523-78 AF Proj 2307)

(AD-A108987, AFWAL-TR-81-3103)

Avail NTIS HC A04/MF A01 CSCL 20/4

Flutter and time response analyses are performed for a NACA 64A006 conventional and a MBB A-3 supercritical airfoil, both oscillating with plunge, pitch, and aileron pitch dof s in small disturbance, transonic flow. The aerodynamic coefficients are calculated using the transonic code LTRAN2-NLR. The effects of various kinds of aeroelastic parameters on flutter speeds for the bending-torsion, bending-aileron, and torsion-aileron branches are studied. The flutter speeds associated with the bending-torsion branch are plotted against Mach number for different parameter values. The flutter speed, the amplitude ratio, and the phase difference at different Mach numbers are plotted against the mass ratio for both of two dof and a three dof case. Time-response results are obtained for the NACA 64A006 and the MBB A-3 airfoils at $M = 0.85$ and 0.765 , respectively. Using the same sets of parameter values, the flight speeds used to obtain all the neutrally stable response are very close to the flutter speeds obtained in the flutter analysis. The principle of linear superposition of airloads is used in the flutter analysis but not in the response analysis. Author (GRA)

N82-19228* Messerschmitt-Boelkow-Blohm GmbH Otto-brunn (West Germany) Unternehmensbereich Flugzeuge

ACTIVE GUST AND MANEUVER LOAD CONTROL CONCEPTS WITH THE EXAMPLE OF THE AIRBUS A300 PART 1 EXPLANATION OF A REGULAR IN THE TIME ZONE OF WIND GUST LOAD DECREASE AND EXAMINATION OF ITS EFFECTIVENESS IN STOCHASTIC GUSTS [AKTIVE BOEEN- UND MANOEVERLASTREGELUNGSKONZEPTE AM BEISPIEL DES AIRBUS A-300 TEILL AUSLEGUNG EINES REGLERS IM ZEITBEREICH ZUR BOENLASTMINDERUNG UND NACHPRUEFUNG DER WIRKSAMKEIT FUER STOCHASTISCHE BOEEN]

J Becker O Sensburg and F Weiss 28 Apr 1981 60 p refs

In GERMAN Presented at DGLR-Jahrestagung 1981

Aachen 11-14 May 1981

(MBB-FE-172/S/PUB/39-Pt-1)

Avail NTIS HC A04/MF A01

The development of active control technology and its application to flutter stabilization in aviation as well as maneuvering squall load control in the structural reduction and improvement of flying comfort was investigated. The design of the squall load control and the plotting of the simulation model for the flexible airplane are examined. Transl by E A K

N82-19231* Bristol Univ (England) Dept of Aeronautical Engineering

THE PRESSURE SIGNATURE METHOD FOR BLOCKAGE CORRECTIONS, AND ITS APPLICATIONS TO THE INDUSTRIAL WIND TUNNEL B S Thesis

A S Walker and N P Wiseman Jun 1981 43 p refs

(BU-263) Avail NTIS HC A03/MF A01

N82-19343

A recent method of correcting for errors due to blockage applicable to complex shapes and high blockage ratios was applied to the Aeronautical Engineering Department industrial wind tunnel. A tunnel centerline source-sink distribution was derived from measured wall pressure signatures. The interference effect of the tunnel walls was calculated. Blockage corrections were applied to in-tunnel measurements of forces and pressures. The drag coefficient of a normal flat plate of deliberately high blockage ratio (12%) was measured in the tunnel then corrected to the value in unconfined flow. This is found to be close to the expected value and indicates that the pressure signature method can be reliably used to correct measurements obtained from models, up to this value of blockage. The effective body implied by the equivalent potential flow was also calculated. This compares well with the known effective body shapes of flat normal plates in confined flow. Author (ESA)

N82-19343# Federal Aviation Administration, Atlantic City. N.J. **WORKSHOP ON MATHEMATICAL FIRE MODELING**
Aug 1981 227 p Workshop held 24-27 Mar 1981
(AD-A108876 FAA-CT-81-209) Avail NTIS
HC A11/MF A01 CSCL 01/2

Computerized simulation of aircraft fires is discussed. Cabin fires are emphasized with particular attention given to the study of the flammability of construction materials. Three types of aircraft fires are analyzed: ramp fires, in-flight fires, and post crash fires. Flame spread, heat fluxes, and fire dynamics are discussed. R J F

N82-19358* Rockwell International Corp., El Segundo, Calif. Aircraft Operations
EVALUATION OF SUPERPLASTIC FORMING AND CO-DIFFUSION BONDING OF Ti-6Al-4V TITANIUM ALLOY EXPANDED SANDWICH STRUCTURES Technical Report, May 1979 - Dec 1980
G H Arvin, L Israeli, J H Stolpestad, and G W Stacher
Sep 1981 134 p refs
(Contract NAS1-15788)
(NASA-CR-165827 NA-81-185-1) Avail NTIS
HC A07/MF A01 CSCL 11F

The application of the superplastic forming/diffusion bonding (SPF/DB) process to supersonic cruise research is investigated. The capability of an SPF/DB titanium structure to meet the structural requirements of the inner wing area of the NASA arrow-wing advanced supersonic transport design is evaluated. Selection of structural concepts and their optimization for minimum weight, SPF/DB process optimization, fabrication of representative specimens, and specimen testing and evaluation are described. The structural area used includes both upper and lower wing panels, where the upper wing panel is used for static compression strength evaluation and the lower panel, in tension, is used for fracture mechanics evaluations. The individual test specimens, cut from six large panels, consist of 39 static specimens, 10 fracture mechanics specimens and one each full size panel for compression stability and fracture mechanics testing. Tests are performed at temperatures of -54 C (-65 F), room temperature, and 260 C (500 F). B W

N82-19391# Naval Ship Research and Development Center, Annapolis, Md. Propulsion and Auxiliary Systems Dept.
FOUNDATIONS FOR COMPUTER SIMULATION OF A LOW PRESSURE OIL FLOODED SINGLE SCREW AIR COMPRESSOR M S Thesis - Purdue Univ
Thomas W Bein Dec 1981 122 p refs
(AD-A108230 DTNSRDC/PAS-81/24) Avail NTIS
HC A06/MF A01 CSCL 13/7

The necessary logic to construct a computer model to predict the performance of an oil flooded single screw air compressor is developed. The geometric variables and relationships used to describe the general single screw mechanism are developed. The governing equations to describe the processes are developed from their primary relationships. The assumptions used in the development are also defined and justified. The computer model predicts the internal pressure, temperature, and flowrates through the leakage paths throughout the compression cycle of the single screw compressor. The model uses empirical external values as the basis for the internal predictions. The computer values are compared to the empirical values and conclusions are drawn based on the results. Recommendations are made for future efforts to improve the computer model and to verify some of the conclusions that are drawn. Author (GRA)

N82-19396# Engineering Dynamics International, St. Louis, Mo.
AIRPORT RELATED RESIDENTIAL ACOUSTICAL INSULA-

TION DEMONSTRATION PROJECT REPORT 1720 Final Report

J T Weissenburger, J C McBryan and L F Heitkamo Jun 1981 107 p refs Sponsored by St. Louis Airport Authority Mo
(PB82-100777) Avail NTIS HC A06/MF A01 CSCL 13B

A demonstration project to evaluate the feasibility of retrofit acoustical insulation in single family residences as a possible remedial measure for homes impacted by airport and aircraft noise is described. Six private residences generally located in an area to the east and southeast of Lambert St. Louis International Airport were used. The program involved making before and after noise measurements, selecting contractors and overseeing the installation of selected acoustical controls and evaluating the effectiveness of the program. A description of each individual house and measured data pertaining to the house is presented. GRA

N82-19419# Radio Technical Commission for Aeronautics, Washington, D C
FM BROADCAST INTERFERENCE RELATED TO AIRBORNE ILS, VOR AND VHF COMMUNICATIONS
18 Nov 1981 96 p refs
(RTCA/DO-176 RTCA/SC-141) Avail NTIS
HC A05/MF A01

Recommendations for controlling the problem of FM broadcast interference with airborne communications are given.

N82-19420# Radio Technical Commission for Aeronautics, Washington, D C
INVESTIGATION OF TECHNICAL REQUIREMENTS
In its FM Broadcast Interference Related to Airborne ILS, VOR and VHF Commun 18 Nov 1981 p 7-8

Avail NTIS HC A05/MF A01

Tolerances and standards applicable to FM broadcast stations are given, and minimum performance standards for airborne receiving equipment are identified. Performance standards for ILS localizer receiving equipment for VOR receiving equipment operating at 108-118 MHz, and for radio communication receiving equipment operating at 117.975-136.000 MHz are considered. J D H

N82-19421# Radio Technical Commission for Aeronautics, Washington, D C
INVESTIGATION OF AIRBORNE VHF COMMUNICATION AND NAVIGATION EQUIPMENT
In its FM Broadcast Interference Related to Airborne ILS, VOR and VHF Commun 18 Nov 1981 p 9-22 ref

Avail NTIS HC A05/MF A01

The Federal Aviation Administration test program investigating the problem of FM broadcast interference is described. The communication signal level to be protected, receiver minimum performance standards, antenna characteristics and receiver interference tests are described for airborne VHF communications and for ILS and VOR navigation equipment. J D H

N82-19422# Radio Technical Commission for Aeronautics, Washington, D C
INVESTIGATION OF THE EFFECTS OF AIRBORNE INSTALLATION FACTORS ON RECEIVER INTERFERENCE
In its FM Broadcast Interference Related to Airborne ILS, VOR and VHF Commun 18 Nov 1981 p 23-52

Avail NTIS HC A05/MF A01

Significant variables which may have an impact on protection criteria are discussed. A rationale for developing voltage limits at a VHF receiver input is presented. A system model consisting of an antenna, transmission line and receiver is developed to define system equations. Distance criteria using model and 100 kW ERP FM broadcast propagation data is developed for various transmission line lengths. J D H

N82-19423# Radio Technical Commission for Aeronautics, Washington, D C
FAA/FCC COORDINATION PROCEDURES FOR FM BROADCAST STATIONS
In its FM Broadcast Interference Related to Airborne ILS, VOR and VHF Commun 18 Nov 1981 p 53-60

Avail NTIS HC A05/MF A01

Procedures for coordination between the Federal Aviation Administration and the Federal Communications Commission are given and their effectiveness evaluated. Recommendations for strengthening the present informal coordination procedures are presented. J D H

N82-19448# Air Force Systems Command Wright-Patterson AFB, Ohio Foreign Technology Div
ANTENNA (SELECTED ARTICLES)
4 Nov 1981 64 p refs Transl into ENGLISH from Antenny (USSR), no 15 1972 p 31-79
(AD-A108174, FTD-ID(RS)T-0940-81) Avail NTIS HC A04/MF A01 CSCL 20/14

A statistical analysis of field focused systems and the properties of connected vibrator structures was made. The efficiency and input impedance of analyzing and reducing the directive gain and direction dispersion of the main maximum of the beam pattern of a sectional traveling wave antenna were derived and are discussed. An assessment of aircraft capacitive circuit medium wave antennas' efficiency is also presented.

N82-19453# Air Force Systems Command Wright-Patterson AFB, Ohio Foreign Technology Div
ASSESSMENT OF AIRCRAFT CAPACITIVE CIRCUIT MEDIUM WAVE ANTENNAS ACCORDING TO THEIR EFFICIENCY

E O Brudnyy and L Ya Ilitskiy In *its Antenna (Selected Articles)* (FTD-ID(RS)T-0940-81) 4 Nov 1981 p 53-59 refs Transl into ENGLISH from Antenny (USSR), no 15 1972

Avail NTIS HC A04/MF A01 CSCL 20/14

A method for assessing aircraft capacitive circuit medium wave antennas according to their efficiency is presented. The measure of efficiency is the product of the antenna capacitance times the active altitude. An expression was obtained which links the antenna efficiency to its geometric dimensions. The suggested method discussed produces the optimal dimensions for aircraft capacitive circuit antennas direction during their designing. Author

N82-19570# National Aerospace Lab., Tokyo (Japan)
ACOUSTIC FATIGUE ENDURANCE TEST OF USB FLAP STRUCTURE MODELS AT ELEVATED TEMPERATURE
Masaaki Sano, Yoshinori Fukumori, Souseiro Iida, Keiji Komatsu and Koichi Egawa Oct 1981 59 p refs In JAPANESE ENGLISH summary
(NAL-TR-683) Avail NTIS HC A04/MF A01

Five substructural models of upper surface blown flaps were tested to verify the safety of the flap structure during a planned flight evaluation of the NAL-STOL experimental aircraft. All models consisted of the face panel with stringers and ribs rivetted on the backside in shape. Four panels were flat, one had the same curvature as the actual flap structure. Three face panels and stiffeners were of Ti-6Al-4V, the others were of 2024C-T3 alloy. Results of thermal buckling tests, resonant frequencies of all panels, the dynamic and the measurement of dynamic strain response are discussed. All structural models proved strong enough to resist both acoustic and thermal loading. No detectable damage was found on the panel face nor around the rivet holes. Estimated lives based on simulated and experimental strain histories suggest confirmation of the fatigue test results. A R H

N82-19571# Advisory Group for Aerospace Research and Development Neuilly-Sur-Seine (France) Structures and Materials Panel
PRACTICAL APPLICATIONS OF FRACTURE MECHANICS
Harold Liebowitz ed (George Washington Univ.) May 1980 425 p refs
(AGARD-AG-257 ISBN-92-835-1359-2) Avail NTIS HC A16/MF A01

Practical applications of fracture mechanics for all aspects of aircraft design, manufacture and testing are presented. Although theoretical discussions are included to provide an appreciation of the complexity of the problems involved, the emphasis is on practical examples. Applications to engine components, built-up structures, joints, lugs and fasteners, integral structures and forgings are covered. The effects of stress corrosion and problems of scatter affecting determination of stress concentration factors, fatigue crack propagation and residual strength are discussed. S L

N82-19583# Kaman Aerospace Corp., Bloomfield Conn
STRUCTURAL SYSTEM IDENTIFICATION TECHNOLOGY VERIFICATION Final Report

N Giansante, A Berman, W G Flannelly and E J Nagy Ft Eustis Va Army Research and Technology Labs Nov 1981 218 p refs

(Contract DAAK51-78-C-0017 DA Proj 1L1-62209-AH-76) (AD-A109181 R-1631 USAAVRADCOM-TR-81-D-28) Avail NTIS HC A10/MF A01 CSCL 13/13

Structural system identification is the method of obtaining structural and dynamic mathematical models and improving existing mathematical models using ground vibration test data. The purpose of the subject program was to perform experimental development and research work to verify the concepts of structural system identification technology. To accomplish this system identification techniques were applied to a U S Army AH-1G helicopter fuselage to create a mathematical model from ground vibration test data to improve a reduced model of an existing NASTRAN model of the AH-1G using shake test data and to test the effectiveness of these new mathematical models in predicting the effects of stiffness and mass changes to the airframe. The results of the program indicate that system identification is a viable and cost-effective technique for developing new models and for improving existing finite-element models of an airframe using ground vibration test data. Author (GRA)

N82-19587# Georgetown Univ Washington D C Dept of Civil Mechanical and Environmental Engineering

FRACTURE AND FATIGUE CHARACTERIZATION OF AIRCRAFT STRUCTURAL MATERIALS UNDER BIAXIAL LOADING Final Scientific Report, 1 Oct 1976 - 30 May 1980

D L Jones and J Eftis Dec 1981 204 p refs

(Grant AF-AFOSR-3096-76, AF Proj 2307)

(AD-A109054, AFOSR-81-0856TR) Avail NTIS HC A10/MF A01 CSCL 01/3

A general fracture mechanics analysis was performed to examine the influence of biaxial applied loads on the mechanical state of the body. The geometries examined were the single crack and two coplanar cracks with an arbitrary orientation and the cracked shear panel. It was found that the biaxial loads influenced all aspects of the mechanical state of the body, with the exception of the stress intensity factor for a crack oriented parallel to the biaxial load. The extent and nature of the biaxial effect on the crack-tip stress field, stress intensity factor, angle of initial crack extension, crack-tip displacements, elastic strain energy, fracture load and fatigue crack growth rates are all discussed. A biaxial test facility was developed and a considerable number of photoelastic fracture toughness and fatigue crack growth rate experiments were performed. Confirmation of the analytical predictions was obtained for the biaxial effects on the crack-tip stress field, the angle of initial crack extension, the fracture load and the fatigue crack growth rates. The biaxial loads were seen to influence all of these parameters in varying degrees. GRA

N82-19707*# National Aeronautics and Space Administration Langley Research Center Hampton Va

EFFECTS OF REPETITION RATE AND IMPULSIVENESS OF SIMULATED HELICOPTER ROTOR NOISE ON ANNOYANCE

Clemans A Powell and David A McCurdy Feb 1982 59 p refs

(NASA-TP-1969, L-14936) Avail NTIS HC A04/MF A01 CSCL 20A

Annoyance judgements were obtained for computer generated stimuli simulative of helicopter impulsive rotor noise to investigate effects of repetition rate and impulsiveness. Each of the 82 different stimuli was judged at 3 sound pressure levels by 48 subjects. Impulse repetition rates covered a range from 10 Hz to 115 Hz, crest factors covered a range from 3.2 dB to 19.3 dB. Increases in annoyance with increases in repetition rate were found which were not predicted by common loudness or annoyance metrics and which were independent of noise level. The ability to predict effects of impulsiveness varied between the noise metrics and was found to be dependent on noise level. The ability to predict the effects of impulsiveness was not generally improved by any of several proposed impulsiveness corrections. Instead, the effects of impulsiveness were found to be systematically related to the frequency content of the stimuli. A modified frequency weighting was developed which offers improved annoyance prediction. Author

N82-19944

N82-19944*# National Aeronautics and Space Administration
Lewis Research Center Cleveland Ohio

EFFECT OF FACILITY VARIATION ON THE ACOUSTIC CHARACTERISTICS OF THREE SINGLE STREAM NOZZLES

Orlando A Gutierrez 1980 38 p refs Presented at the 100th Meeting of the Acoust Soc of Am Los Angeles 17-21 Nov 1980

(NASA-TM-81635 E-646) Avail NTIS HC A03/MF A01 CSCL 20A

The characteristics of the jet noise produced by three single stream nozzles were investigated statistically at the NASA-Lewis Research Center outdoor jet acoustic facility. The nozzles consisted of a 7.6 cm diameter convergent conical, a 10.2 cm diameter convergent conical and an 8-lobe daisy nozzle with 7.6 cm equivalent diameter flow area. The same nozzles were tested previously at cold flow conditions in other facilities such as the Royal Aircraft Establishment (RAE) 7.3 m acoustic wind tunnel. The acoustic experiments at NASA covered pressure ratios from 1.4 to 2.5 at total temperatures of 811 K and ambient. The data obtained with four different microphone arrays are compared. The results are also compared with data taken at the RAE facility and with a NASA prediction procedure. Author

N82-19945# National Aerospace Lab Tokyo (Japan) Noise and Emission Research Group

AERODYNAMIC NOISE GENERATED BY JET WING/FLAP INTERACTIONS OF THE EXTERNAL USB CONFIGURATION OF STOL AIRCRAFT PART 2 FULL SCALE MODEL EXPERIMENT USING FJR710 TURBOFAN ENGINE

Masataka Maita Shigemi Shindo Shin Nakayama Masakatsu Matsuki Tadao Torisaki Mitsuo Morita Akira Yoshida, Katsumi Takeda, Shizuo Sekine, and Hiroshi Kondo Oct 1981 26 p refs

(NAL-TR-687T-Pt-2 ISSN-0389-4010) Avail NTIS HC A03/MF A01

Acoustic characteristics of the external upper surface blowing (USB) concept of a propulsive lift configuration were studied by full scale model static experiments. Test components included an FJR710 turbofan engine with an acoustically treated nacelle and a USB wing/flap assembly. These were utilized in conjunction with the ground verification testing of the propulsive systems of the National Aerospace Laboratory Quiet STOL Research Aircraft. Results were compared with the previous 8% scale cold flow model data. The defect of shielding provided by the wing/flap surface on aft-radiated turbofan engine noise was studied and some attempts were made to reduce USB noise. Author

N82-19946*# National Aeronautics and Space Administration
Langley Research Center, Hampton Va

AIRCRAFT NOISE PREDICTION PROGRAM THEORETICAL MANUAL, PART 1

William E Zorumski Feb 1982 180 p refs 2 Vol

(NASA-TM-83199-Pt-1 L-14805-Pt-1) Avail NTIS HC A09/MF A01 CSCL 20A

Aircraft noise prediction theoretical methods are given. The prediction of data which affect noise generation and propagation is addressed. These data include the aircraft flight dynamics, the source noise parameters, and the propagation effects. R J F

N82-19947*# National Aeronautics and Space Administration
Langley Research Center Hampton, Va

AIRCRAFT NOISE PREDICTION PROGRAM THEORETICAL MANUAL, PART 2

William E Zorumski Feb 1982 296 p refs 2 Vol

(NASA-TM-83199-Pt-2 L-14805-Pt-2) Avail NTIS HC A13/MF A01 CSCL 20A

Detailed prediction methods for specific aircraft noise sources are given. These sources are airframe noise, combustion noise, fan noise, single and dual stream jet noise, and turbine noise. Modifications to the NASA methods which comply with the International Civil Aviation Organization standard method for aircraft noise prediction are given. R J F

N82-19952# Air Force Wright Aeronautical Labs, Wright-Patterson AFB, Ohio

ACOUSTIC MEASUREMENTS OF F100-PW-100 ENGINE OPERATING IN HUSH HOUSE NSN 4920-02-070-2721 Final Report, May - Sep 1981

Vincent R Miller, G A Plzak, and J M Chinn Sep 1981 58 p refs

(AD-A108814 AFWAL-TM-81-133-FIBE) Avail NTIS HC A04/MF A01 CSCL 20/1

The purpose of this test program was to measure the acoustic environment in the hush house facility located at Kelly AFB Texas during operation of the F100-PW-100 engine to ensure that engine structural acoustic design limits were not exceeded. The acoustic measurements showed that no sonic fatigue problems are anticipated with the F100-PW-100 engine structure during operation in the hush house. The measured acoustic levels were less than those measured in an existing F100-PW-100 engine wet-cooled noise suppressor but were increased over that measured during operation on an open test stand. It was recommended that the acoustic load increases measured in this program should be specified in the structural design criteria for engines which will be subjected to hush house operation or defining requirements for associated equipment. Author (GRA)

N82-19956# Loughborough Univ of Technology (England)
Dept of Transport Technology

AN EXPERIMENTAL STUDY OF THE EFFECTS OF AN INLET FLOW CONDITIONER ON THE NOISE OF A LOW SPEED AXIAL FLOW FAN

J Scoles and J B Ollerhead Jan 1981 92 p refs

(Contract AT/2170/049/XR)

(TT-8101) Avail NTIS HC A05/MF A01

The effects of inflow condition on the noise generated by a 40kW 560mm diameter, seven blade ducted fan at speeds up to 5000rpm in an anechoic chamber were measured. A 1.25m diameter hemispherical honeycomb flow conditioner (HFC) which could be fitted with an internal gauze liner was used. Fan entry flow was measured by static and rotating hot-wire anemometers. Noise levels in the first few harmonics of blade passing frequency are very sensitive to inflow condition, but the HFC reduces them to a residual level independent of upstream disturbance levels. Broadband noise is reduced (by a smaller amount) at high blade angles and flow rates. No systematic effect of the gauze liner is detected. Experimental difficulties are caused by unsteadiness in the chamber airflow which causes harmonic level fluctuations with amplitudes of up to 10dB. Although the inlet flow conditioner reduces these fluctuations markedly, long term variations reduce confidence in the data. Author (ESA)

N82-19957# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany) Abt Technische Akustik

NOISE MEASUREMENTS ON THE HELICOPTER BK 117 DESIGN WEIGHTED NOISE LEVELS AND INFLUENCE OF AIRSPEED

Wolf R Splettstoesser, Klaus P Anders, and Karl-Heinz Spiegel Aug 1981 93 p refs In GERMAN, ENGLISH summary. Report will also be announced as translation (ESA-TT-748) (DFVLR-Mitt-81-18) Avail NTIS HC A05/MF A01, DFVLR, Cologne DM 22,95

Noise measurements on the prototype helicopter BK 117 were performed in strict compliance with the proposed International Civil Aviation Organization regulations for noise certification of helicopters. Measurement procedure, noise data acquisition, analysis and reduction as well as applied correction procedures are described. Effective perceived noise levels (EPNL) and other noise descriptors were evaluated and related to the proposed noise limits. Additional level flyover tests with variable airspeed were conducted to investigate the resulting effect on the EPNL and other noise measures. Author (ESA)

N82-19958# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany) Abteilung Technische Akustik

COLLECTION AND EVALUATION OF PROPELLER AIRCRAFT NOISE CERTIFICATION DATA

Manfred Ahlswede and Klaus Peter Anders Aug 1981 87 p refs In GERMAN, ENGLISH summary (DFVLR-Mitt-81-20) Avail NTIS HC A05/MF A01, DFVLR, Cologne DM 25,20

More than 300 individual noise certification levels were measured for propeller driven airplanes up to 5700 kg takeoff weight and for powered gliders in accordance with the rules and regulations as set forth in International Civil Aviation Organization Annex 16. Information on the airplanes, the engines and the propellers is provided as well as on the prevailing meteorological parameters and the operational parameters together with acoustic data. Of the latter, the measured

A-weighted levels with their 90% confidence limit are listed, the performance correction is given and the certification level as well as the noise-limit are provided. Data are evaluated by plotting the measured A-weighted levels versus the helical blade tip Mach number. Author (ESA)

N82-20126*# Jet Propulsion Lab., California Inst of Tech
Pasadena

GLOBAL POSITIONING SYSTEM TIMING RECEIVERS IN THE DSN

P A Clements *In its* The Telecommun and Data Acquisition
Rept 15 Feb 1982 p 90-99 refs

Avail NTIS HC A07/MF A01 CSCL 17G


The system (GPS) is a worldwide navigation system using a constellation of Earth satellites with onboard clocks. The GPS is also usable to transfer time and frequency. Preliminary tests with the breadboard receiver at NBS produced precision in time and frequency transfer between the United States Naval Observatory (USNO) and NBS. JPL's plans to install receivers in the DSN to demonstrate their ability to transfer time and frequency within the DSN and between the DSN and outside agencies are discussed. T M

SUBJECT INDEX

AERONAUTICAL ENGINEERING/A Continuing Bibliography (Suppl. 149)

JUNE 1982

Typical Subject Index Listing



The title is used to provide a description of the subject matter. When the title is insufficiently descriptive of the document content a title extension is added separated from the title by hyphens. The NASA or AIAA accession number is included in each entry to assist the user in locating the abstract in the abstract section of this supplement. If applicable, a report number is also included as an aid in identifying the document.

A

A-7 AIRCRAFT

A-7E software module guide
[AD-A108649] N82-18920

ABRASION RESISTANCE

Transparency design decisions - Assessing their impact on visual performance N82-24306
Abrasion resistant coated plastic products for aircraft N82-24310
Proposed method for abrasion testing transparent plastics and coatings N82-24311

AC GENERATORS

High speed VSCP generator design consideration --- computer aided design for Variable Speed Constant Frequency generator N82-24379
Advanced generating system technology N82-24380

ACCELERATED LIFE TESTS

Aircraft electric system development and test facilities N82-24384
Advanced attack helicopter fatigue testing - Overview N82-24720

ACCELERATION (PHYSICS)

Aircrew restraint and mobility test fixture [AD-A108274] N82-18193

ACCEPTABILITY

Physiological acceptability tests of the SJU-5/A ejection seat: Second physiological acceptance demonstration [AD-A108688] N82-18194

ACCIDENT PREVENTION

Scanning strategies for air traffic control radars N82-24646
The toll of ILS-preventable aviation accidents N82-25325

ACOUSTIC DUCTS

Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts [ASME PAPER 81-WA/NCA-13] N82-24602

ACOUSTIC EMISSION

NDE of composite rotor blades during fatigue testing N82-24713

ACOUSTIC FATIGUE

On the sonic fatigue life estimation of skin structures at room and elevated temperatures N82-23678

ACOUSTIC IMPEDANCE

Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts [ASME PAPER 81-WA/NCA-13] N82-24602

ACOUSTIC PROPAGATION

Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts [ASME PAPER 81-WA/NCA-13] N82-24602

ACOUSTIC PROPERTIES

Effect of facility variation on the acoustic characteristics of three single stream nozzles [NASA-TN-81635] N82-19944

ACOUSTIC RETROFITTING

Airport related residential acoustical insulation demonstration project: Report 1720 [PB82-100777] N82-19396

ACRYLIC RESINS

Acrylic - A timely review N82-24317
Lucas stretched acrylic N82-24318
Problems associated with the quality assurance of stretched acrylic sheet N82-24319
The effects of absorbed moisture upon the physical properties of stretched acrylic materials N82-24320

ACTIVE CONTROL

Fighters - Tomorrow's terminology N82-23368
Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts [NBB-FE-172/S/PUB/39-PT-1] N82-19228

ACTUATORS

The influence of sensor and actuator characteristics on overall helicopter AFCS design N82-18171
Slotted variable camber flap [NASA-CASE-LAR-12541-1] N82-18203
Overview of Honeywell electromechanical actuation programs N82-19142
Electric flight systems N82-19144
Electromechanical actuators N82-19148
Electric flight systems integration N82-19150

ADAPTIVE CONTROL

Mission-adaptive wing flight demonstration program [SAE PAPER 811035] N82-24399
Apparatus for damping operator induced oscillations of a controlled system --- flight control [NASA-CASE-FRC-11041-1] N82-18493

ADAPTIVE FILTERS

Apparatus for damping operator induced oscillations of a controlled system --- flight control [NASA-CASE-FRC-11041-1] N82-18493

AEROACOUSTICS

Acoustic fatigue endurance test of USB flap structure models at elevated temperature [NAL-TR-683] N82-19570

AERODYNAMIC BALANCE

SUBJECT INDEX

AERODYNAMIC BALANCE

A general purpose program for rotor blade dynamics
N82-18151

AERODYNAMIC CHARACTERISTICS

Aerodynamic Testing Conference, 12th,
Williamsburg, VA, March 22-24, 1982, Collection
of Technical Papers

Numerical design of the contoured wind-tunnel
liner for the NASA swept-wing LFC test
[AIAA 82-0568] A82-24651

The use of a multi-degree-of-freedom dual balance
system to measure cross and cross-coupling
derivatives
[AIAA 82-0595] A82-24656

Status and capabilities of the National Full Scale
Facility 40- by 80-foot wind tunnel modification
[AIAA 82-0607] A82-24676

Angle of downwash behind a wing in unsteady flow
A82-24970

Design philosophy of the Hughes model 600 helicopter
N82-18140

Multiple ejection effects analysis
[AD-A108277] N82-18192

Theoretical investigations on the influence of
different strake, tail unit, and conventional
HLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36] N82-18211

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 3: Aerodynamics and
Structures Session
[NASA-TM-84147] N82-19172

Effects of installation of F101 DFE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TM-83250] N82-19181

An experimental study of the effect of tail
configuration on the spinning characteristics of
general aviation aircraft --- static wind tunnel
force measurements
[NASA-CR-168578] N82-19224

AERODYNAMIC COEFFICIENTS

Theoretical investigations on the influence of
different strake, tail unit, and conventional
HLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36] N82-18211

A criterion for the prediction of the recovery
characteristics of spinning aircraft
[RAE-TN-AERO-2251] N82-19223

AERODYNAMIC CONFIGURATIONS

Parametric criteria and impact on design trends
N82-18139

The effect of a well on the aerodynamics of a
spoiler --- wind tunnel flow visualization and
pressure measurement
[BU-268] N82-19194

AERODYNAMIC INTERFERENCE

Transonic wind tunnel wall interference
corrections for three-dimensional models
[AIAA 82-0588] A82-24663

Optimum performance and wake geometry of co-axial
rotor in hover
N82-18156

A numerical approach to co-axial rotor aerodynamics
N82-18157

Helicopter rotor downwash: Results of
experimental research at the DFVLR-rotor test
stand and their comparison with theoretical
results
N82-18158

Investigations of the separation behavior on
airfoils at high angles of attack, using linear
lift theory
[MBB-FE-122/S/PUB/37] N82-18189

The effect of a well on the aerodynamics of a
spoiler --- wind tunnel flow visualization and
pressure measurement
[BU-268] N82-19194

AERODYNAMIC LOADS

RB 211 powerplant deterioration - Review of
current situation and lessons learned
[SAE PAPER 811053] A82-24393

Operating flight loads and their effect on engine
performance
[SAE PAPER 811071] A82-24405

Hypothetical fatigue life problem - Application of
Aerospatiale method
A82-24716

Helicopter rotor load prediction
A82-24719

Developments in rotary wing aircraft aerodynamics
N82-18120

Some unsteady aerodynamic effects on helicopter
rotors
N82-18162

A method of predicting fuselage loads in hover
N82-18164

Fast mounted visual aids
N82-18167

AERODYNAMIC NOISE

Wind tunnel investigation of high speed rotor noise
N82-18146

Prediction of blade vortex interaction noise from
measured blade pressure
N82-18147

AERODYNAMIC STABILITY

Oscillating supersonic/hypersonic wings at high
incidence
A82-23828

Review of support interference in dynamic tests
[AIAA 82-0594] A82-24668

Cross and cross-coupling derivative measurements
on the standard dynamics model at AEDC
[AIAA 82-0596] A82-24670

A control model for maneuvering flight for
application to a computer-flight testing program
N82-18153

Active gust and maneuver load control concepts
with the example of the Airbus A300. Part 1:
Explanation of a regular in the time zone of
wind gust load decrease and examination of its
effectiveness in stochastic gusts
[MBB-FE-172/S/PUB/39-PT-1] N82-19228

AERODYNAMIC STALLING

Application of the ONEB dynamic stall model to a
helicopter blade in forward flight
N82-18161

Some unsteady aerodynamic effects on helicopter
rotors
N82-18162

AERODYNAMICS

International Conference on Numerical Methods in
Fluid Dynamics, 7th, Stanford University,
Stanford and Moffett Field, CA, June 23-27,
1980, Proceedings
A82-24426

XFV-12A diagnostic and development programs
[AD-A108354] N82-18206

Tendencies in the development of subsonic
transport aircraft with special consideration of
aerodynamics
[ESA-TT-705] N82-18214

AEROELASTICITY

Fighters - Tomorrow's terminology
A82-23368

Application of the ONEB dynamic stall model to a
helicopter blade in forward flight
N82-18161

Flutter and time response analyses of three degree
of freedom airfoils in transonic flow
[AD-A108987] N82-19227

AERONAUTICAL ENGINEERING

NASA pocket statistics
[NASA-TM-84134] N82-19084

Aeronautical Research Laboratories Structures
Division
[AD-A109049] N82-19161

AEROSPACE ENGINEERING

Deficiencies and constraints that affect the
design of cockpit enclosures and transparencies
A82-24303

AEROSPACE INDUSTRY

Welding technology for the aerospace industry;
Proceedings of the Conference, Las Vegas, NV,
October 7, 8, 1980
A82-23751

What the operator wants --- airline cooperation in
aircraft maintenance
A82-24008

The use of 'Kapton' polyimide film in aerospace
applications
[SAE PAPER 811091] A82-24413

SUBJECT INDEX

AIRCRAFT ACCIDENTS

AEROTHERMODYNAMICS

Technical innovations in testing and analysis of
heat and pressure models in hypersonic wind
tunnels
[AIAA 82-0578] A82-24660

AH-64 HELICOPTER

Advanced attack helicopter fatigue testing -
Overview A82-24720

AIR COOLING

Air cooled engine test facilities A82-24004

AIR DEFENSE

Army Lynx: Product development matched to
military combat development N82-18143

A light helicopter for night firing N82-18144
Tethered rotorplatforms and their mission potential
N82-18145

AIR FLOW

The effect of ejector augmentation on test-section
flow quality in the Calspan 8-ft transonic wind
tunnel
[AIAA 82-0571] A82-24658

AIR LAW

Air transportation of handicapped persons A82-24338

AIR NAVIGATION

Navigational aids on-board the Concorde A82-24065

Institute of Navigation, Annual Meeting, 37th,
U.S. Naval Academy, Annapolis, MD, June 9-11,
1981, Proceedings A82-24643

The application of NAVSTAR differential GPS in the
civilian community A82-24645

Beyond the horizon coverage for air
navigation/traffic control A82-24647

Loran for precise position location - The VIEW-NAV
system A82-24648

Analysis of loran-C system reliability for civil
aviation A82-24650

Integration of inertial sensors in helicopters N82-18173

FAA/FCC coordination procedures for FM broadcast
stations N82-19423

AIR TRAFFIC

Report of the Air Traffic Forecasting Working
Party, 1981 N82-19195

FAA statistical handbook of aviation
[AD-A109289] N82-19198

AIR TRAFFIC CONTROL

Utilization of radio equipment at airports and on
airways --- Russian book A82-22407

Stereographic projection in the National Airspace
System A82-23031

Air Traffic Control Association, Annual Fall
Conference, 25th, Arlington, VA, October 19-24,
1980, Proceedings A82-23309

The requirements for reduced IFR separations on
final approach A82-23311

Analysis of system problems using aviation safety
reporting system data A82-23312

Reducing reflections on the front surface of air
traffic control displays A82-23314

Utilizing the helicopter's versatility to improve
the ATC system A82-23316

International plans for civil and military
co-ordination A82-23317

Operational air traffic in the Federal Republic of
Germany A82-23318

Distributed data processing modeling for future
ATC systems A82-23319

Lightweight ATC systems A82-23321

Discrete Address Beacon System /DABS/ A82-23322

A Microwave Landing System simulation A82-23323

Voice communications - The vital link A82-23324

Institute of Navigation, Annual Meeting, 37th,
U.S. Naval Academy, Annapolis, MD, June 9-11,
1981, Proceedings A82-24643

Scanning strategies for air traffic control radars
A82-24646

Beyond the horizon coverage for air
navigation/traffic control A82-24647

Conflicts between random flights in a given area
A82-25213

Distributed intelligence for air fleet control
[AD-A108611] N82-18195

Analytical study of cockpit information requirements
[AD-A108524] N82-18218

National Airspace Data Interchange Network (NADIN)
support of Remote Maintenance Monitoring System
(RMS) [AD-A109125] N82-19160

FAA statistical handbook of aviation
[AD-A109289] N82-19198

Air traffic control en route computer system
[GPO-89-008] N82-19202

AIR TRANSPORTATION

Air Traffic Control computer replacement -
Specification issues and problems A82-23313

Air transport in the 21st century A82-24025

Air transportation of handicapped persons A82-24338

Report of the Air Traffic Forecasting Working
Party, 1981 N82-19195

AIRBORNE EQUIPMENT

LAMPSS III recovery assist, securing and traversing
/RAST/ system --- Light Airborne Multi-Purpose
System [SAE PAPER 811080] A82-24412

Integration of complex systems in current and
future aircraft projects for the example of
avionics [MBB-UH-18-80-0] N82-18221

FM broadcast interference related to airborne ILS,
VOR and VHF communications [RTCA/DO-176] N82-19419

AIRBORNE/SPACEBORNE COMPUTERS

The use of dynamic mock-ups in the design of
advanced systems --- USAF's Digital Avionic
Information System and NAVI's Advanced
Integrated Display System A82-22902

High temperature engine control electronics
[SAE PAPER 811074] A82-24407

Loran for precise position location - The VIEW-NAV
system A82-24648

Analysis of loran-C system reliability for civil
aviation A82-24650

Flight condition recognition /FCR/ technique ---
microprocessor-based recording for helicopter
structural component fatigue damage A82-24712

A-7E software module guide
[AD-A108649] N82-18920

AIRCRAFT

Flight characteristics design and development of
the MBB/KHI BK117 helicopter N82-18150

AIRCRAFT ACCIDENTS

Operational air traffic in the Federal Republic of
Germany A82-23318

The toll of ILS-preventable aviation accidents
A82-25325

AIRCRAFT ANTENNAS

SUBJECT INDEX

An assessment of the crash fire hazard of liquid hydrogen fueled aircraft
[NASA-CR-165528] N82-19196

Aircraft collision avoidance systems
[GPO-79-431] N82-19201

AIRCRAFT ANTENNAS

Analysis of the crossed dipole antenna as a model for aircraft in an electromagnetic environment
A82-25002

Calculation and measurement of electric field strength for airborne antennas in the LF/MF range
A82-25011

TM/TE polarization ratios in a sample of 30 kHz spherics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464

Volumetric pattern prediction of antennas on aircraft using the geometrical theory of diffraction
[ESA-TT-677] N82-18483

Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency
N82-19453

AIRCRAFT BRAKES

Dynamics of aircraft antiskid braking systems --- conducted at the Langley aircraft landing loads and traction facility
[NASA-TP-1959] N82-18204

AIRCRAFT CARRIERS

Review of defense-related vertical and short takeoff and landing (V/STOL) aircraft programs
[GPO-55-278] N82-18205

Investigation of crossdeck pendant catapult slot interaction; proposed corrective measures
[AD-A108149] N82-18232

Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type
[AD-A108801] N82-19206

AIRCRAFT COMMUNICATION

Voice communications - The vital link
A82-23324

Beyond the horizon coverage for air navigation/traffic control
A82-24647

Loran-C RNAV in mountainous areas
A82-24649

Investigation of the effects of airborne installation factors on receiver interference
N82-19422

FAA/FCC coordination procedures for FM broadcast stations
N82-19423

AIRCRAFT COMPARTMENTS

Preliminary thoughts on helicopter cabin noise prediction methods
N82-18148

The measurement of the mobility of structures at acoustic frequencies
N82-18149

Study of cabin noise control for twin engine general aviation aircraft
[NASA-CR-165833] N82-18995

AIRCRAFT CONFIGURATIONS

Transparency development needs for military aircraft in the 1980's
A82-24302

AIRCRAFT CONSTRUCTION MATERIALS

Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings
A82-24301

Aircraft transparency design guide
A82-24307

B.A.C. One-Eleven flight deck glazing product improvement
A82-24325

Concorde glazings - 5 years of Mach 2 service
A82-24326

Materials aspects of aircraft EMC design
A82-24358

Aircraft surface coatings for drag reduction/erosion protection
[SAE PAPER 811070] A82-24401

Structural testing of composites with known defects
A82-24708

Carbon-fiber composites - A fiber composite material for highly stressed light-construction components
A82-24805

Recent developments in materials and processes for aircraft corrosion control
A82-24825

A study of the effects of long-term exposure to fuels and fluids on the behavior of advanced composite materials
[NASA-CR-165763] N82-18327

AIRCRAFT CONTROL

Analysis and optimization of control systems in piloted flight vehicles --- Russian book
A82-22398

Sensitivity reduction by double perfect model following --- with application to aircraft control
A82-23029

Aircraft parameter identification in the presence of atmospheric turbulence
A82-23227

Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers
A82-23426

Fixed gain controller design for aircraft
A82-23441

F/A-18 weapon system development
A82-23774

MIL-STD 1553B - Aircraft EM environmental susceptibility effects
A82-24357

Multivariable aircraft control by maneuver commands: An application to air to surface gunnery
N82-19154

Transport aircraft cockpit standardization (Federal Aviation regulations part 25)
[AD-A108924] N82-19207

A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft --- improving riding quality in fighter aircraft
[NLR-TR-80032-U] N82-19212

AIRCRAFT DESIGN

Complete guide to Rutan homebuilt aircraft --- Book
A82-22880

History of the sweptback wing
[DGLR PAPER 81-070] A82-22898

Fighters - Tomorrow's terminology
A82-23368

Boeing's big, quiet 737-300
A82-23369

Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers
A82-23426

YF-16 design concept and philosophy
A82-23444

Design of supercritical swept wings
A82-23826

A310 - Design for maintenance
A82-24002

Development of maintenance programmes through the functional, structural and flight test phases
A82-24003

Maintenance objectives for future aircraft
A82-24005

What the operator wants --- airline cooperation in aircraft maintenance
A82-24008

The inter-relation between design, construction and maintenance
A82-24010

Air transport in the 21st century
A82-24025

Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings
A82-24301

Deficiencies and constraints that affect the design of cockpit enclosures and transparencies
A82-24303

Fuel-efficient windshields for transport, commuter and business aircraft
A82-24304

Transparencies - What an aircraft designer should know
A82-24305

Transparency design decisions - Assessing their impact on visual performance
A82-24306

Aircraft transparency design guide
A82-24307

SUBJECT INDEX

AIRCRAFT EQUIPMENT

An analytical methodology to predict potential aircraft losses due to canopy birdstrikes	A82-24313	High temperature engine control electronics [SAE PAPER 811074]	A82-24407
The role of finite element analysis in the design of birdstrike resistant transparencies	A82-24314	Performance retention features of the PW2037 [SAE PAPER 811054]	A82-24409
The development of high strength light-weight windshields for the new generation of Boeing 757 and 767 airliners	A82-24323	Reliability analysis of a dual-redundant engine controller [SAE PAPER 811077]	A82-24410
Materials aspects of aircraft EMC design	A82-24358	Propulsion multiplexer /PMUX/ system - The missing link [SAE PAPER 811078]	A82-24411
CAD/CAM in British Aerospace - Aircraft Group	A82-24373	Novel metal-ceramics-composite sealing coatings in aircraft engines	A82-24803
Application of damage tolerance technology to type certification [SAE PAPER 811062]	A82-24388	APWAL turbine engine controls research and development - Present and future [AIAA PAPER 82-0321]	A82-25050
Airworthiness considerations in the design of commercial transport aircraft [SAE PAPER 811039]	A82-24396	Where is cobalt irreplaceable	A82-25538
Designing for continued airworthiness - General aviation [SAE PAPER 811038]	A82-24397	A digital simulation program describing the motion of an aircraft undergoing engine failure during its takeoff ground roll [AD-A108420]	N82-18210
Quality, quantity, and technology - A perspective on fighter development [SAE PAPER 811097]	A82-24400	Further development of the test concept of the ALPHA JET engine LARZAC 04	N82-18223
Future strike fighter options - Concepts and technologies [SAE PAPER 811099]	A82-24403	Electric Flight Systems [NASA-CP-2209]	N82-19134
Technology for quality and quantity in a new fighter [SAE PAPER 811100]	A82-24404	Electric flight systems, overview	N82-19135
Fighter issues - 2000 [SAE PAPER 811096]	A82-24415	A propulsion view of the all-electric airplane	N82-19136
Development of a self-optimizing flexible technology /SOFT/ transonic wing wind tunnel model [AIAA 82-0601]	A82-24673	Potential propulsion considerations and study areas for all-electric aircraft	N82-19137
Spoilers or auxiliary flaps	A82-24973	A look into the future: The potential of the all-electric secondary power system for the energy efficient transport	N82-19138
Aircraft/airport compatibility - A constant challenge for aircraft designers	A82-25119	The 400-Hertz constant-speed electrical generation systems	N82-19139
The design of a wind tunnel VSTOL fighter model incorporating turbine powered engine simulators [AIAA PAPER 82-2635]	A82-25154	Electric ECS	N82-19140
Advanced electronic displays and their potential in future transport aircraft	A82-25216	Environmental Control Systems	N82-19141
Tendencies in the development of subsonic transport aircraft with special consideration of aerodynamics [ESA-TT-705]	N82-18214	Overview of Honeywell electromechanical actuation programs	N82-19142
Electric Flight Systems [NASA-CP-2209]	N82-19134	Digital flight controls	N82-19143
Electric flight systems, overview	N82-19135	Electric flight systems	N82-19144
The 400-Hertz constant-speed electrical generation systems	N82-19139	Engine technology	N82-19145
Engine technology	N82-19145	Power systems	N82-19146
Power systems	N82-19146	Electromechanical actuators	N82-19148
Electromechanical actuators	N82-19148	Digital flight controls	N82-19149
Aeronautical Research Laboratories Structures Division [AD-A109049]	N82-19161	Electric flight systems integration	N82-19150
Practical applications of fracture mechanics [AGARD-AG-257]	N82-19571	Practical applications of fracture mechanics [AGARD-AG-257]	N82-19571
AIRCRAFT DETECTION		An experimental study of the effects of an inlet flow conditioner on the noise of a low speed axial flow fan --- in an aircraft engine [TT-8101]	N82-19956
Wide field of view laser beacon system for three-dimensional aircraft position measurement [ASME PAPER 81-WA/DSC-9]	A82-24563	AIRCRAFT EQUIPMENT	
AIRCRAFT ENGINES		Recent improvements in aircraft Ni-Cd cells	A82-24245
Lineup of the IM-series aircraft-derivative gas turbines	A82-22896	The coupling of electromagnetic interference into aircraft systems	A82-24354
Reliable power --- Rolls-Royce aircraft engine designs	A82-24007	MIL-STD 1553B - Aircraft EM environmental susceptibility effects	A82-24357
Monitoring engine wear by oil analysis	A82-24012	Aircraft electrical power systems; Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981 [SAE SP-500]	A82-24376
Packaging the VSCP system for an aircraft engine environment	A82-24383	Design considerations of DC-Link aircraft generation systems	A82-24377
RB 211 powerplant deterioration - Review of current situation and lessons learned [SAE PAPER 811053]	A82-24393	Advanced generating system technology	A82-24380
		The effect of critical design parameters on the selection of a VSCP system	A82-24381

AIRCRAFT FUELS

SUBJECT INDEX

- Evolution and development of high voltage /270
volt/ dc aircraft electric systems in the United
States A82-24382
- Aircraft electric system development and test
facilities A82-24384
- The cargo helicopter - A logistical vehicle A82-24717
- Aircrew restraint and mobility test fixture
[AD-A108274] N82-18193
- AIRCRAFT FUELS**
- Low grade fuels for turbo and jet engines A82-23439
- An assessment of the crash fire hazard of liquid
hydrogen fueled aircraft
[NASA-CR-165526] N82-19196
- AIRCRAFT HAZARDS**
- An analytical methodology to predict potential
aircraft losses due to canopy birdstrikes A82-24313
- The effects of bird orientation on load profile
and damage level A82-24316
- An assessment of the crash fire hazard of liquid
hydrogen fueled aircraft
[NASA-CR-165526] N82-19196
- Simulator study of vortex encounters by a
twin-engine, commercial, jet transport airplane
[NASA-TP-1966] N82-19225
- Workshop on Mathematical Fire Modeling
[AD-A108876] N82-19343
- AIRCRAFT INDUSTRY**
- Experience during the development of the
German-Japanese helicopter BK 117
[MBB-UD-318-81-0] N82-19210
- AIRCRAFT INSTRUMENTS**
- The multi mode matrix flat panel display:
Technology and applications N82-18169
- Analytical study of cockpit information requirements
[AD-A108524] N82-18218
- Integration of complex systems in current and
future aircraft projects for the example of
avionics [MBB-UH-18-80-0] N82-18221
- Transport aircraft cockpit standardization
(Federal Aviation regulations part 25)
[AD-A108924] N82-19207
- AIRCRAFT LANDING**
- Methodology for multi-aircraft minimum noise impact
landing trajectories A82-23037
- Oscillations and vibrations of aircraft on runways
A82-24974
- The toll of ILS-preventable aviation accidents
A82-25325
- Optimal aircraft landing patterns for minimal
noise impact N82-19200
- Descent-rate cuing for carrier landings: Effects
of display gain, display noise and aircraft type
[AD-A108801] N82-19206
- AIRCRAFT MAINTENANCE**
- Reliability centered maintenance /RCM/ A82-24001
- A310 - Design for maintenance A82-24002
- Development of maintenance programmes through the
functional, structural and flight test phases A82-24003
- Maintenance objectives for future aircraft A82-24005
- What the operator wants --- airline cooperation in
aircraft maintenance A82-24008
- The way ahead for helicopter maintenance A82-24009
- The inter-relation between design, construction
and maintenance A82-24010
- MSG-3 structures --- inspection program for
aircraft maintenance A82-24011
- MSG-3 overview --- aircraft maintenance program
development A82-24014
- Cost of ownership advantages with a shared oil
system A82-24378
- Management of powerplant maintenance and
restoration programs for fuel conservation
[SAE PAPER 811052] A82-24394
- Potential reductions in aircraft operation and
maintenance costs by using thrust computing
support equipment [AD-A108463] N82-18207
- AIRCRAFT MANEUVERS**
- Utilizing the helicopter's versatility to improve
the ATC system A82-23316
- Efficient combinations of numerical techniques
applied to aircraft turning performance
optimization A82-24814
- Multivariable aircraft control by maneuver
commands: An application to air to surface
gunnery N82-19154
- AIRCRAFT MODELS**
- Analysis of the crossed dipole antenna as a model
for aircraft in an electromagnetic environment
A82-25002
- Prediction of off-design performance of
turbo-shaft engines a simplified method N82-18132
- Measurement techniques used to assess the
installed power of a helicopter engine N82-18133
- Parametric criteria and impact on design trends
N82-18139
- Interpretation and construction of a dynamic
similarity model of the A 310 wings
[MBB-FE-17/S/PUB/42] N82-18212
- Design study into a high endurance mini-rotorcraft
[BU-265] N82-19216
- Structural system identification technology
verification [AD-A109181] N82-19583
- AIRCRAFT NOISE**
- Direct comparison of community response to road
traffic noise and to aircraft noise A82-22974
- Methodology for multi-aircraft minimum noise impact
landing trajectories A82-23037
- Study of cabin noise control for twin engine
general aviation aircraft
[NASA-CR-165833] N82-18995
- Annoyance caused by propeller airplane flyover
noise: Preliminary results [NASA-TM-83244] N82-18996
- Optimal aircraft landing patterns for minimal
noise impact N82-19200
- Airport related residential acoustical insulation
demonstration project: Report 1720
[PB82-100777] N82-19396
- Effects of repetition rate and impulsiveness of
simulated helicopter rotor noise on annoyance
[NASA-TP-1969] N82-19707
- Aircraft noise prediction program theoretical
manual, part 1 [NASA-TM-83199-PT-1] N82-19946
- Aircraft noise prediction program theoretical
manual, part 2 [NASA-TM-83199-PT-2] N82-19947
- Noise measurements on the helicopter BK 117
design. Weighted noise levels and influence of
airspeed [DFVLR-MITT-81-18] N82-19957
- Collection and evaluation of propeller aircraft
noise certification data [DFVLR-MITT-81-20] N82-19958
- AIRCRAFT PARTS**
- The inter-relation between design, construction
and maintenance A82-24010
- Lucas stretched acrylic A82-24318
- The Agusta's solution of AHS's hypothetical
fatigue life problem A82-24701
- A method of determining safe service life for
helicopter components A82-24709

SUBJECT INDEX

AIRCRAFT STRUCTURES

- Boeing Vertol fatigue life methodology 82-24718
- Advanced attack helicopter fatigue testing - Overview 82-24720
- AIRCRAFT PERFORMANCE**
- Boeing's big, quiet 737-300 82-23369
- Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers 82-23426
- YF-16 design concept and philosophy 82-23444
- Maintenance objectives for future aircraft 82-24005
- Quality, quantity, and technology - A perspective on fighter development [SAE PAPER 811097] 82-24400
- Restoration of performance, Models 727, 737, and 747 [SAE PAPER 811072] 82-24406
- Fighter issues - 2000 [SAE PAPER 811096] 82-24415
- SH-608 test program 82-18141
- C-5A austere airfield operational utility evaluation. Phase 2: Operation on unpaved soil surfaces following rainfall [AD-A108597] 82-18208
- AIRCRAFT PRODUCTION**
- The inter-relation between design, construction and maintenance 82-24010
- CAD/CAM in British Aerospace - Aircraft Group 82-24373
- Technology for quality and quantity in a new fighter [SAE PAPER 811100] 82-24404
- AIRCRAFT PRODUCTION COSTS**
- Impact of technology on avionics cost trends [AD-A108494] 82-18219
- AIRCRAFT RELIABILITY**
- Reliability centered maintenance /RCM/ 82-24001
- Airworthiness regulation: What is our strategy - What are the issues 82-24006
- The way ahead for helicopter maintenance 82-24009
- MSG-3 overview --- aircraft maintenance program development 82-24014
- Airworthiness considerations in the design of commercial transport aircraft [SAE PAPER 811039] 82-24396
- Designing for continued airworthiness - General aviation [SAE PAPER 811038] 82-24397
- Reliability analysis of a dual-redundant engine controller [SAE PAPER 811077] 82-24410
- Hypothetical fatigue life problem - Application of Aerospace method 82-24716
- The reliability and safety of small passenger aircraft 82-24972
- Point of view of a helicopter manufacturer on airworthiness regulations 82-18137
- Aeronautical Research Laboratories Structures Division [AD-A109049] 82-19161
- AIRCRAFT SAFETY**
- MSG-3 overview --- aircraft maintenance program development 82-24014
- Designing for continued airworthiness - General aviation [SAE PAPER 811038] 82-24397
- Scanning strategies for air traffic control radars 82-24646
- Standardization of helicopter fatigue methodology - A manufacturer's view 82-24704
- Flight test data acquisition and interpretation 82-24707
- The reliability and safety of small passenger aircraft 82-24972
- Point of view of a helicopter manufacturer on airworthiness regulations 82-18137
- Electrical ground testing of aircraft antistatic protection 82-19156
- Disengagement of safety harness buckles - CT4 [AD-A109048] 82-19199
- Active Beacon Collision Avoidance System (BCAS) logic performance during operational flight tests [AD-A108893] 82-19203
- Workshop on Mathematical Fire Modeling [AD-A108876] 82-19343
- AIRCRAFT SPECIFICATIONS**
- Point of view of a helicopter manufacturer on airworthiness regulations 82-18137
- Army Lynx: Product development matched to military combat development 82-18143
- A light helicopter for night firing 82-18144
- AIRCRAFT SPIN**
- Spin-tunnel investigation of a 1/13-scale model of the NASA AD-1 oblique-wing research aircraft [NASA-TN-83236] 82-18183
- A criterion for the prediction of the recovery characteristics of spinning aircraft [BAE-TN-AERO-2251] 82-19223
- An experimental study of the effect of tail configuration on the spinning characteristics of general aviation aircraft --- static wind tunnel force measurements [NASA-CR-168578] 82-19224
- AIRCRAFT STABILITY**
- Aircraft parameter identification in the presence of atmospheric turbulence 82-23227
- AIRCRAFT STRUCTURES**
- On the sonic fatigue life estimation of skin structures at room and elevated temperatures 82-23678
- Novel approaches to electron beam welding machine utilization 82-23753
- Diffusion bonding in superplastic forming/diffusion bonding 82-23754
- Aluminum and its alloys - Weldability 82-23755
- Material/structure degradation due to fretting and fretting-initiated fatigue 82-23771
- A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum 82-23772
- MSG-3 structures --- inspection program for aircraft maintenance 82-24011
- Transparency development needs for military aircraft in the 1980's 82-24302
- Portable transparency optical test system /P-TOTS/ 82-24309
- Windshield system structural enhancement 82-24312
- D.C.9 windshield - Effect of attachment retorquer 82-24324
- Application of damage tolerance technology to type certification [SAE PAPER 811062] 82-24388
- Certification of civil composite aircraft structure [SAE PAPER 811061] 82-24389
- Standardization of helicopter fatigue methodology - A manufacturer's view 82-24704
- The effects of slight non-linearities on modal testing of helicopter-like structures 82-18130
- Theoretical investigations on the influence of different strake, tail unit, and conventional HLW arrangement as well as of CCV on the aerodynamic characteristics of fighter aircraft configurations [HBB-FE-122/S/PUB/36] 82-18211
- Interpretation and construction of a dynamic similarity model of the A 310 wings [HBB-FE-17/S/PUB/42] 82-18212

AIRCRAFT SURVIVABILITY

SUBJECT INDEX

Characterization of the Airbus horizontal stabilizers of CFRP construction and structural analysis with the finite element method [MBB-UT-13-81-0]	N82-18213	Report of the Air Traffic Forecasting Working Party, 1981	N82-19195
A study of the effects of long-term exposure to fuels and fluids on the behavior of advanced composite materials [NASA-CR-165763]	N82-18327	AIRPORT PLANNING	
Electroforming of space and aircraft structures [MBB-BB-491-0]	N82-18419	Methodology for multi-aircraft minimum noise impact landing trajectories	A82-23037
Aeronautical Research Laboratories Structures Division [AD-A109049]	N82-19161	Aircraft/airport compatibility - A constant challenge for aircraft designers	A82-25119
Practical applications of fracture mechanics [AGARD-AG-257]	N82-19571	AIRPORTS	
Structural system identification technology verification [AD-A109181]	N82-19583	Utilization of radio equipment at airports and on airways --- Russian book	A82-22407
AIRCRAFT SURVIVABILITY		Development of a clear air radar to detect meteorological hazards at airports [AD-A108236]	N82-18835
Fighter issues - 2000 [SAE PAPER 811096]	A82-24415	FAA Statistical handbook of aviation [AD-A109289]	N82-19198
Evolution of the aeroscout	A82-24706	AIRSPACE	
Army Lynx: Product development matched to military combat development	N82-18143	International plans for civil and military co-ordination	A82-23317
A light helicopter for night firing	N82-18144	AIRSPRED	
AIRCRAFT TIRES		Evaluation of the helicopter low airspeed system LASSIE	N82-18172
Dynamics of aircraft antiskid braking systems --- conducted at the Langley aircraft landing loads and traction facility [NASA-TP-1959]	N82-18204	Noise measurements on the helicopter BK 117 design. Weighted noise levels and influence of airspeed [DFVLR-MITT-81-18]	N82-19957
AIRCRAFT WAKES		ALASKA	
The requirements for reduced IFR separations on final approach	A82-23311	United States Coast Pilot 9. Pacific and Arctic Coasts Alaska: Cape Spencer to Beaufort Sea [PB82-109562]	N82-18201
Simulator study of vortex encounters by a twin-engine, commercial, jet transport airplane [NASA-TP-1966]	N82-19225	ALPHA PARTICLES	
AIRFOIL PROFILES		Linear alpha-ray altimeter	A82-23225
A new facility and technique for two-dimensional aerodynamic testing [AIAA 82-0608]	A82-24677	ALTIMETERS	
Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory [MBB-FE-122/S/PUB/37]	N82-18189	Linear alpha-ray altimeter	A82-23225
Laminar airfoils for transport aircraft [ESA-TT-680]	N82-18190	ALTITUDE	
On the design of some airfoils for sailplane application --- additions to existing wings for inflight testing [VTH-LR-326]	N82-19213	Analysis of a nonlinear altitude tracking method [AD-A108878]	N82-19197
AIRFRAME MATERIALS		ALUMINUM ALLOYS	
Fracture and fatigue characterization of aircraft structural materials under biaxial loading [AD-A109054]	N82-19587	Aluminum and its alloys - Weldability	A82-23755
AIRFRAMES		A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum	A82-23772
Welding for low-cost advanced titanium airframe structures	A82-23757	ANGLE OF ATTACK	
Material/structure degradation due to fretting and fretting-initiated fatigue	A82-23771	Oscillating supersonic/hypersonic wings at high incidence	A82-23828
Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance [AIAA PAPER 80-0724]	A82-24022	Review of support interference in dynamic tests [AIAA 82-0594]	A82-24668
Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures [NASA-CR-165827]	N82-19358	Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory [MBB-FE-122/S/PUB/37]	N82-18189
AIRLINE OPERATIONS		ANTENNA ARRAYS	
Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning	A82-23470	Antenna (selected articles) [AD-A108174]	N82-19448
What the operator wants --- airline cooperation in aircraft maintenance	A82-24008	ANTENNA DESIGN	
MSG-3 overview --- aircraft maintenance program development	A82-24014	Antenna (selected articles) [AD-A108174]	N82-19448
Wind and temperature database for flight planning [SAE PAPER 811068]	A82-24385	ANTENNA RADIATION PATTERNS	
Airline flight planning - The weather connection [SAE PAPER 811067]	A82-24386	TM/TE polarization ratios in a sample of 30 kHz spherics received at altitudes from 0 to 70 km [AD-A108182]	N82-18464
Integration of energy management concepts into the flight deck [SAE PAPER 811066]	A82-24387	Volumetric pattern prediction of antennas on aircraft using the geometrical theory of diffraction [ESA-TT-677]	N82-18483
		Antenna (selected articles) [AD-A108174]	N82-19448
		ANTENNAS	
		Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency	N82-19453
		ANTIMISSILE DEFENSE	
		Perspectives for Controlled Weapons Technology: Report of the 90th Helicopter Forum [MBB-UA-532-80-0]	N82-19211
		ANTIREFLECTION COATINGS	
		Reducing reflections on the front surface of air traffic control displays	A82-23314

SUBJECT INDEX

BIRD-AIRCRAFT COLLISIONS

ANTISKID DEVICES

Dynamics of aircraft antiskid braking systems ---
conducted at the Langley aircraft landing loads
and traction facility
[NASA-TP-1959] N82-18204

APPLICATIONS PROGRAMS (COMPUTERS)

Modal characteristics of rotor blades: Finite
element approach and measurement by ground
vibration test
N82-18127

ARCHITECTURE

Airport related residential acoustical insulation
demonstration project: Report 1720
[PB82-100777] N82-19396

ARCHITECTURE (COMPUTERS)

ATC automation - A look forward:
Technology/architecture
N82-23320
Discrete Address Beacon System /DABS/
N82-23322

ARRESTING GEAR

Investigation of crossdeck pendant catapult slot
interaction; proposed corrective measures
[AD-A108149] N82-18232

ARTIFICIAL CLOUDS

Helicopter Icing Spray System (HISS) nozzle
improvement evaluation
[AD-A109405] N82-19208

ASPECT RATIO

Performance of single-stage axial-flow transonic
compressor with rotor and stator aspect ratios
of 1.63 and 1.78, respectively, and with design
pressure ratio of 1.82
[NASA-TP-1974] N82-19222

ATMOSPHERIC CIRCULATION

Aircraft measurements and analysis of severe
storms: 1976 field experiment
[NASA-CR-168519] N82-18803

ATMOSPHERIC SOUNDING

Rapid extraction of layer relative humidity,
geopotential thickness, and atmospheric
stability from satellite sounding radiometer data
N82-25113

ATMOSPHERIC TEMPERATURE

Wind and temperature database for flight planning
[SAE PAPER 811068] N82-24385

ATMOSPHERIC TURBULENCE

Aircraft parameter identification in the presence
of atmospheric turbulence
N82-23227

ATMOSPHERICS

TM/TE polarization ratios in a sample of 30 kHz
spherics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464

ATTACK AIRCRAFT

Aircrew restraint and mobility test fixture
[AD-A108274] N82-18193

AUTOMATED EN ROUTE ATC

Air Traffic Control computer replacement -
Specification issues and problems
N82-23313

NAS system load - Utilization of the DARC system
N82-23315

ATC automation - A look forward:
Technology/architecture
N82-23320

AUTOMATIC CONTROL

Three-engine control system for the prototype
EH-101 helicopter
[AEBG-9/81-1568L] N82-18135

AUTOMATIC FLIGHT CONTROL

A control model for maneuvering flight for
application to a computer-flight testing program
N82-18153

AUTOMATIC TRAFFIC ADVISORY AND RESOLUTION

Conflicts between random flights in a given area
N82-25213

AUTOMOBILES

Slotted wall test section for automotive
aerodynamic test facilities
[AIAA 82-0585] N82-24661

AUXILIARY POWER SOURCES

Electric Flight Systems
[NASA-CP-2209] N82-19134

Electric flight systems, overview
N82-19135

Electric ECS
N82-19140

Electric flight systems integration

N82-19150

AVIONICS

The use of dynamic mock-ups in the design of
advanced systems --- USAF's Digital Avionic
Information System and NAVI's Advanced
Integrated Display System
N82-22902

The coupling of electromagnetic interference into
aircraft systems
N82-24354

The variation of induced currents in aircraft wiring
N82-24355

EMC clearance of modern military aircraft
N82-24359

The testing of aircraft under near field conditions
N82-24361

Advanced electronic displays and their potential
in future transport aircraft
N82-25216

Electronic flight instrument systems /EFIS/, the
instrumentation of the 1980s
N82-25324

The role of simulation in the design process
N82-18154

Integration of inertial sensors in helicopters
N82-18173

Impact of technology on avionics cost trends
[AD-A108494] N82-18219

Trends in airline avionics
[NLR-MP-80013-U] N82-18220

Integration of complex systems in current and
future aircraft projects for the example of
avionics
[HBB-UH-18-80-0] N82-18221

A-7E software module guide
[AD-A108649] N82-18920

Assessment of Avionic Equipment Field Reliability
and Maintainability as Functions of Unit Cost
[AD-A109373] N82-19218

AXIAL FLOW TURBINES

An experimental study of the effects of an inlet
flow conditioner on the noise of a low speed
axial flow fan --- in an aircraft engine
[TT-8101] N82-19956

AXIAL LOADS

Fracture and fatigue characterization of aircraft
structural materials under biaxial loading
[AD-A109054] N82-19587

AXIAL STRAIN

Investigation of compaction criteria for airport
pavement subgrade soils
[AD-A108518] N82-18230

B

BASE PRESSURE

A method of predicting fuselage loads in hover
N82-18164

BEACON COLLISION AVOIDANCE SYSTEM

Analysis of a nonlinear altitude tracking method
[AD-A108878] N82-19197

Active Beacon Collision Avoidance System (BCAS)
logic performance during operational flight tests
[AD-A108893] N82-19203

BEAUFORT SEA (NORTH AMERICA)

United States Coast Pilot 9. Pacific and Arctic
Coasts Alaska: Cape Spencer to Beaufort Sea
[PB82-109562] N82-18201

BENDING MOMENTS

A method for applying linear optimal control
theory to the design of a regulator for a
flexible aircraft --- improving riding quality
in fighter aircraft
[NLR-TR-80032-U] N82-19212

BIBLIOGRAPHIES

Bibliography of NASA published reports on general
aviation, 1975 to 1981
[NASA-TM-83307] N82-19132

BILLETS

Lucas stretched acrylic
N82-24318

BIRD-AIRCRAFT COLLISIONS

Transparencies - What an aircraft designer should
know
N82-24305

An analytical methodology to predict potential
aircraft losses due to canopy birdstrikes
N82-24313

BLADE TIPS

- The role of finite element analysis in the design of birdstrike resistant transparencies
A82-24314
- Aircraft transparency bird impact analysis using the MAGNA computer program
A82-24315
- The effects of bird orientation on load profile and damage level
A82-24316
- ## BLADE TIPS
- Prediction of blade vortex interaction noise from measured blade pressure
N82-18147
- The problem of calculation of the flow around helicopter rotor blade tips
N82-18160
- An analytical investigation of the free-tip rotor for helicopters
[NASA-TM-81345]
N82-18179
- On the calculation of transonic blade tip flow for helicopter rotors
[MBB-UD-320-81-0]
N82-18187
- ## BLOWDOWN WIND TUNNELS
- Induction driven transonic wind tunnel T2: Operation at room temperature and cryogenic adaptation
N82-19158
- ## BODY-WING CONFIGURATIONS
- Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts
[NASA-CR-165852]
N82-19167
- ## BOEING 727 AIRCRAFT
- Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072]
A82-24406
- ## BOEING 737 AIRCRAFT
- Boeing's big, quiet 737-300
A82-23369
- Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072]
A82-24406
- ## BOEING 747 AIRCRAFT
- Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072]
A82-24406
- ## BOEING 757 AIRCRAFT
- The development of high strength light-weight windshields for the new generation of Boeing 757 and 767 airliners
A82-24323
- ## BOLTS
- D.C.9 windshield - Effect of attachment retorquer
A82-24324
- ## BOMBS (ORDNANCE)
- Bomb crater repair techniques for permanent airfields. Report 1: Series 1 tests
[AD-A108716]
N82-18229
- ## BOUNDARY LAYER CONTROL
- Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LFC test
[AIAA 82-0568]
A82-24656
- ## BOUNDARY LAYER SEPARATION
- Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory
[MBB-FE-122/S/PUB/37]
N82-18189
- ## BRAKING
- Dynamics of aircraft antiskid braking systems --- conducted at the Langley aircraft landing loads and traction facility
[NASA-TP-1959]
N82-18204
- ## BROADCASTING
- FM broadcast interference related to airborne ILS, VOR and VHF communications
[RTCA/DO-176]
N82-19419
- Investigation of technical requirements
N82-19420
- ## C
- ## C-160 AIRCRAFT
- Importance of a tactical cargo aircraft in emergency relief
A82-25499
- ## CABIN ATMOSPHERES
- Environmental Control Systems
N82-19141
- ## CALIBRATING
- Pressure transducer calibration process
[SAE PAPER 811076]
A82-24408

SUBJECT INDEX

- ## CANOPIES
- Aircraft transparency design guide
A82-24307
- Windshield system structural enhancement
A82-24312
- An analytical methodology to predict potential aircraft losses due to canopy birdstrikes
A82-24313
- Aircraft transparency bird impact analysis using the MAGNA computer program
A82-24315
- ## CAPACITANCE
- Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency
N82-19453
- ## CARBON FIBER REINFORCED PLASTICS
- Characterization of the Airbus horizontal stabilizers of CFRP construction and structural analysis with the finite element method
[MBB-UT-13-81-0]
N82-18213
- ## CARBON FIBERS
- Carbon-fiber composites - A fiber composite material for highly stressed light-construction components
A82-24805
- ## CARGO AIRCRAFT
- The cargo helicopter - A logistical vehicle
A82-24717
- ## CATAPULTS
- Investigation of crossdeck pendant catapult slot interaction; proposed corrective measures
[AD-A108149]
N82-18232
- ## CATHODE RAY TUBES
- Reducing reflections on the front surface of air traffic control displays
A82-23314
- Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s
A82-25324
- ## CEMENTS
- Investigation into the utility of some quick setting cements for runway repair
[B-80-157/60.7.0157]
N82-18225
- ## CENTER OF GRAVITY
- Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning
A82-23470
- A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491]
N82-19226
- ## CERAMIC COATINGS
- Novel metal-ceramics-composite sealing coatings in aircraft engines
A82-24803
- ## CERMENTS
- Novel metal-ceramics-composite sealing coatings in aircraft engines
A82-24803
- ## CERTIFICATION
- Application of damage tolerance technology to type certification
[SAE PAPER 811062]
A82-24388
- Certification of civil composite aircraft structure
[SAE PAPER 811061]
A82-24389
- Collection and evaluation of propeller aircraft noise certification data
[DFVLR-MITT-81-20]
N82-19958
- ## CH-46 HELICOPTER
- Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft
A82-24705
- ## CHARGE COUPLED DEVICES
- A new angular deviation measurement device for aircraft transparencies
A82-24308
- ## CIVIL AVIATION
- International plans for civil and military co-ordination
A82-23317
- Air transportation of handicapped persons
A82-24338
- Airline flight planning - The weather connection
[SAE PAPER 811067]
A82-24386
- Certification of civil composite aircraft structure
[SAE PAPER 811061]
A82-24389

SUBJECT INDEX

COMPUTATIONAL FLUID DYNAMICS

- The application of NAVSTAR differential GPS in the civilian community A82-24645
- Analysis of loran-C system reliability for civil aviation A82-24650
- The toll of ILS-preventable aviation accidents A82-25325
- Impact of technology on avionics cost trends [AD-A108494] N82-18219
- Trends in airline avionics [NLR-AP-80013-0] N82-18220
- Bibliography of NASA published reports on general aviation, 1975 to 1981 [NASA-TM-83307] N82-19132
- FAA statistical handbook of aviation [AD-A109289] N82-19198
- CLEAR AIR TURBULENCE**
- Development of a clear air radar to detect meteorological hazards at airports [AD-A108236] N82-18835
- CLOCKS**
- Global positioning system timing receivers in the DSN N82-20126
- COASTS**
- United States Coast Pilot 9. Pacific and Arctic Coasts Alaska: Cape Spencer to Beaufort Sea [PB82-109562] N82-18201
- COBALT**
- Where is cobalt irreplaceable A82-25538
- COCKPIT SIMULATORS**
- The role of simulation in the design process N82-18154
- COCKPITS**
- F/A-18 weapon system development A82-23774
- Deficiencies and constraints that affect the design of cockpit enclosures and transparencies A82-24303
- B.A.C. One-Eleven flight deck glazing product improvement A82-24325
- Integration of energy management concepts into the flight deck [SAE PAPER 811066] A82-24387
- The multi mode matrix flat panel display: Technology and applications N82-18169
- New developments in cockpit-human interfaces [RAE-TM-PS-412] N82-18215
- Analytical study of cockpit information requirements [AD-A108524] N82-18218
- Transport aircraft cockpit standardization (Federal Aviation regulations part 25) [AD-A108924] N82-19207
- COLLISION AVOIDANCE**
- Discrete Address Beacon System /DABS/ A82-23322
- Conflicts between random flights in a given area A82-25213
- Midair and near midair collisions on two- and three-dimensional curvilinear flight paths [ESA-TT-685] N82-18200
- Aircraft collision avoidance systems [GPO-79-431] N82-19201
- COMBAT**
- Evolution of the Aeroscout A82-24706
- The cargo helicopter - A logistical vehicle A82-24717
- COMBUSTION CHAMBERS**
- Fuel-rich plume combustion [AD-A108136] N82-18349
- Dilution jet behavior in the turn section of a reverse flow combustor [NASA-TM-82776] N82-19220
- COMMAND AND CONTROL**
- A redundancy concept for a digital CSAS N82-18170
- COMMERCIAL AIRCRAFT**
- Airworthiness considerations in the design of commercial transport aircraft [SAE PAPER 811039] A82-24396
- Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s A82-25324
- Naval versions of the Dauphin and the AS 15 TT weapon system N82-18142
- Impact of technology on avionics cost trends [AD-A108494] N82-18219
- Bibliography of NASA published reports on general aviation, 1975 to 1981 [NASA-TM-83307] N82-19132
- FAA statistical handbook of aviation [AD-A109289] N82-19198
- Simulator study of vortex encounters by a twin-engine, commercial, jet transport airplane [NASA-TP-1966] N82-19225
- COMMUNICATION EQUIPMENT**
- Selection of telecommunication equipment - A new approach to the equivalent cost concept A82-25510
- COMMUNICATION NETWORKS**
- Beyond the horizon coverage for air navigation/traffic control A82-24647
- Selection of telecommunication equipment - A new approach to the equivalent cost concept A82-25510
- National Airspace Data Interchange Network (NADIN) support of Remote Maintenance Monitoring System (RMMS) [AD-A109125] N82-19160
- COMMUNITIES**
- Direct comparison of community response to road traffic noise and to aircraft noise A82-22974
- COMPACTING**
- Investigation of compaction criteria for airport pavement subgrade soils [AD-A108518] N82-18230
- COMPATIBILITY**
- Aircraft/airport compatibility - A constant challenge for aircraft designers A82-25119
- COMPONENT RELIABILITY**
- Material/structure degradation due to fretting and fretting-initiated fatigue A82-23771
- The inter-relation between design, construction and maintenance A82-24010
- Standardization of helicopter fatigue methodology - A manufacturer's view A82-24704
- A method of determining safe service life for helicopter components A82-24709
- Advanced attack helicopter fatigue testing - Overview A82-24720
- COMPOSITE STRUCTURES**
- Structural testing of composites with known defects A82-24708
- NDE of composite rotor blades during fatigue testing A82-24713
- COMPRESSOR BLADES**
- Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82 [NASA-TP-1974] N82-19222
- COMPRESSOR ROTORS**
- Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82 [NASA-TP-1974] N82-19222
- COMPRESSORS**
- Open-cycle vapor compression heat pump [PB82-110503] N82-18553
- Foundations for computer simulation of a low pressure oil flooded single screw air compressor [AD-A108230] N82-19391
- COMPUTATION**
- A complete method for computation of blade mode characteristics and responses in forward flight N82-18126
- COMPUTATIONAL FLUID DYNAMICS**
- Design of supercritical swept wings A82-23826
- Annual review of fluid mechanics. Volume 14 --- Book A82-24416

COMPUTER GRAPHICS

SUBJECT INDEX

- International Conference on Numerical Methods in Fluid Dynamics, 7th, Stanford University, Stanford and Moffett Field, CA, June 23-27, 1980, Proceedings
A82-24426
- Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles
A82-25347
- COMPUTER GRAPHICS**
Computer-generated images for simulators - The cost of technology
A82-22881
- Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371
- Integrated control design techniques
[AD-A108223]
N82-18224
- COMPUTER PROGRAMMING**
A program testing assistant
[AD-A108147]
N82-18922
- COMPUTER PROGRAMS**
A Microwave Landing System simulation
A82-23323
- Aircraft transparency bird impact analysis using the MAGNA computer program
A82-24315
- Modal characteristics of rotor blades: Finite element approach and measurement by ground vibration test
N82-18127
- A-7E software module guide
[AD-A108649]
N82-18920
- Transport aircraft cockpit standardization (Federal Aviation regulations part 25)
[AD-A108924]
N82-19207
- COMPUTER SYSTEMS DESIGN**
Air Traffic Control computer replacement - Specification issues and problems
A82-23313
- NAS system load - Utilization of the DARC system
A82-23315
- ATC automation - A look forward: Technology/architecture
A82-23320
- Lightweight ATC systems
A82-23321
- CAD/CAM in British Aerospace - Aircraft Group
A82-24373
- COMPUTER SYSTEMS PERFORMANCE**
NAS system load - Utilization of the DARC system
A82-23315
- Distributed data processing modeling for future ATC systems
A82-23319
- COMPUTERIZED DESIGN**
Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371
- CAD/CAM in British Aerospace - Aircraft Group
A82-24373
- High speed VSCF generator design consideration --- computer aided design for Variable Speed Constant Frequency generator
A82-24379
- A marine NAVSTAR GPS receiver
A82-24644
- Integrated control design techniques
[AD-A108223]
N82-18224
- COMPUTERIZED SIMULATION**
GTD terrain reflection model applied to ILS glide slope --- Geometrical Theory of Diffraction
A82-23027
- Aircraft parameter identification in the presence of atmospheric turbulence
A82-23227
- A Microwave Landing System simulation
A82-23323
- Calculation and measurement of electric field strength for airborne antennas in the LP/MF range
A82-25011
- Developments in rotary wing aircraft aerodynamics
A82-18120
- A study of the techniques of dynamic analysis of helicopter type structures
N82-18129
- A method of predicting fuselage loads in hover
N82-18164
- Rotorcraft flight simulation computer program C81 with DATAMAP interface. Volume 2: Programmer's manual
[AD-A108294]
N82-18231
- Workshop on Mathematical Fire Modeling
[AD-A108876]
N82-19343
- Foundations for computer simulation of a low pressure oil flooded single screw air compressor
[AD-A108230]
N82-19391
- CONCORDE AIRCRAFT**
Navigational aids on-board the Concorde
A82-24065
- Concorde glazings - 5 years of Mach 2 service
A82-24326
- CONCRETES**
Investigation into the utility of some quick setting cements for runway repair
[B-80-157/60.7.0157]
N82-18225
- CONFERENCES**
Air Traffic Control Association, Annual Fall Conference, 25th, Arlington, VA, October 19-24, 1980, Proceedings
A82-23309
- Israel Annual Conference on Aviation and Astronautics, 23rd, Tel Aviv and Haifa, Israel, February 11, 12, 1981, Collection of Papers
A82-23426
- Welding technology for the aerospace industry; Proceedings of the Conference, Las Vegas, NV, October 7, 8, 1980
A82-23751
- Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings
A82-24301
- Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371
- Aircraft electrical power systems; Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981
[SAE SP-500]
A82-24376
- International Conference on Numerical Methods in Fluid Dynamics, 7th, Stanford University, Stanford and Moffett Field, CA, June 23-27, 1980, Proceedings
A82-24426
- Institute of Navigation, Annual Meeting, 37th, U.S. Naval Academy, Annapolis, MD, June 9-11, 1981, Proceedings
A82-24643
- Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers
A82-24651
- Seventh European Rotorcraft and Powered Lift Aircraft Forum
N82-18119
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 3: Aerodynamics and Structures Session
[NASA-TN-84147]
N82-19172
- CONGRESSIONAL REPORTS**
Review of defense-related vertical and short takeoff and landing (V/STOL) aircraft programs
[GPC-55-278]
N82-18205
- Aircraft collision avoidance systems
[GPO-79-431]
N82-19201
- Air traffic control en route computer system
[GPO-89-008]
N82-19202
- CONSOLES**
Task analytic techniques: Application to the design of a flight simulator instructor/operator console
[AD-A108724]
N82-18227
- CONSTRAINTS**
Aircrew restraint and mobility test fixture
[AD-A108274]
N82-18193
- CONTROL CONFIGURED VEHICLES**
Mission-adaptive wing flight demonstration program
[SAE PAPER 811035]
A82-24399
- A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491]
N82-19226
- CONTROL EQUIPMENT**
Fixed gain controller design for aircraft
A82-23441
- F/A-18 weapon system development
A82-23774

SUBJECT INDEX

DATA MANAGEMENT

Fatigue test of the typical main rotor controls component
A82-24715

APWAL turbine engine controls research and development - Present and future
[AIAA PAPER 82-0321]
A82-25050

Three-engine control system for the prototype EH-101 helicopter
[AEBG-9/81-1568L]
N82-18135

CONTROL STABILITY
A control model for maneuvering flight for application to a computer-flight testing program
N82-18153

Apparatus for damping operator induced oscillations of a controlled system --- flight control
[NASA-CASE-FRC-11041-1]
N82-18493

CONTROL THEORY
Analysis and optimization of control systems in piloted flight vehicles --- Russian book
A82-22398

The influence of sensor and actuator characteristics on overall helicopter AFCS design
N82-18171

CONTROL VALVES
An ejector augmented choking valve for the metering and control of inlet and bleed duct flows
[AIAA 82-0575]
A82-24659

CONTROLLERS
Fixed gain controller design for aircraft
A82-23441

COOLING SYSTEMS
Cost of ownership advantages with a shared oil system
A82-24378

COORDINATION
FAA/FCC coordination procedures for FM broadcast stations
N82-19423

CORROSION PREVENTION
Recent developments in materials and processes for aircraft corrosion control
A82-24825

CORROSION RESISTANCE
A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum
A82-23772

Materials aspects of aircraft EMC design
A82-24358

Aircraft surface coatings for drag reduction/erosion protection
[SAE PAPER 811070]
A82-24401

Where is cobalt irreplaceable
A82-25538

COST ANALYSIS
Quality, quantity, and technology - A perspective on fighter development
[SAE PAPER 811097]
A82-24400

Technology for quality and quantity in a new fighter
[SAE PAPER 811100]
A82-24404

The toll of ILS-preventable aviation accidents
A82-25325

Selection of telecommunication equipment - A new approach to the equivalent cost concept
A82-25510

Impact of technology on avionics cost trends
[AD-A108494]
N82-18219

Assessment of Avionic Equipment Field Reliability and Maintainability as Functions of Unit Cost
[AD-A109373]
N82-19218

COST EFFECTIVENESS
Parametric study of the influence of the engine upon the operating cost of a civil helicopter
N82-18131

COST REDUCTION
Airline fuel saving through JT9D engine refurbishment
[SAE PAPER 811051]
A82-24395

Potential reductions in aircraft operation and maintenance costs by using thrust computing support equipment
[AD-A108463]
N82-18207

COUPLING
A further study of helicopter rotor pitch-flap-phase coupling
[BU-259]
N82-19214

COWLINGS
Engine superficial temperature and infrared signature
N82-18136

CRACK PROPAGATION
Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft
A82-24705

Fracture and fatigue characterization of aircraft structural materials under biaxial loading
[AD-A109054]
N82-19587

CRACKING (FRACTURING)
A compilation of stress intensity factor solutions for flawed fastener holes
[AD-A108753]
N82-18628

CRASH LANDING
Disengagement of safety harness buckles - CT4
[AD-A109048]
N82-19199

CRASHES
Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data
[PB82-111832]
N82-18233

An assessment of the crash fire hazard of liquid hydrogen fueled aircraft
[NASA-CR-165526]
N82-19196

CRATERS
Bomb crater repair techniques for permanent airfields. Report 1: Series 1 tests
[AD-A108716]
N82-18229

CROSS COUPLING
The coupling of electromagnetic interference into aircraft systems
A82-24354

The use of a multi-degree-of-freedom dual balance system to measure cross and cross-coupling derivatives
[AIAA 82-0595]
A82-24669

Cross and cross-coupling derivative measurements on the standard dynamics model at AEDC
[AIAA 82-0596]
A82-24670

CRUISING FLIGHT
Wind tunnel investigation of high speed rotor noise
N82-18146

A numerical approach to co-axial rotor aerodynamics
N82-18157

CRYOGENIC WIND TUNNELS
Induction driven transonic wind tunnel T2: Operation at room temperature and cryogenic adaptation
N82-19158

CUMULATIVE DAMAGE
Flight condition recognition /FCE/ technique --- microprocessor-based recording for helicopter structural component fatigue damage
A82-24712

CYCLIC LOADS
The Agusta's solution of AHS's hypothetical fatigue life problem
A82-24701

The challenge of standardizing fatigue methodology
A82-24703

D

DATA ACQUISITION
Flight test data acquisition and interpretation
A82-24707

Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data
[PB82-111832]
N82-18233

DATA BASES
Analysis of system problems using aviation safety reporting system data
A82-23312

Collection and evaluation of propeller aircraft noise certification data
[DFVLR-MTT-81-20]
N82-19958

DATA LINKS
Discrete Address Beacon System /DABS/
A82-23322

MIL-STD 1553B - Aircraft EM environmental susceptibility effects
A82-24357

DATA MANAGEMENT
Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371

DATA PROCESSING

SUBJECT INDEX

DATA PROCESSING

Distributed data processing modeling for future ATC systems

A82-23319

DATA PROCESSING EQUIPMENT

Air traffic control en route computer system

[GPO-89-008]

N82-19202

DATA RECORDING

A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors

[RAE-TM-RAD-NAV-145]

N82-18503

DATA REDUCTION

Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data

A82-25113

Improvements and extensions of the Geometrical Dilution of Precision (GDOP) concept for selecting navigation measurements

[AD-A108607]

N82-18197

Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data

[PB82-111832]

N82-18233

DC 9 AIRCRAFT

D.C.9 windshield - Effect of attachment retorquer

A82-24324

DC 10 AIRCRAFT

Deficiencies and constraints that affect the design of cockpit enclosures and transparencies

A82-24303

DEAD RECKONING

On the calculation of separated flow on helicopter fuselages

[MBB-UD-321-81-0]

N82-18188

DEFECTS

A compilation of stress intensity factor solutions for flawed fastener holes

[AD-A108753]

N82-18628

DEFENSE PROGRAM

Review of defense-related vertical and short takeoff and landing (V/STOL) aircraft programs

[GPO-55-278]

N82-18205

DEICING

Transparencies - What an aircraft designer should know

A82-24305

DEMAND (ECONOMICS)

Selection of telecommunication equipment - A new approach to the equivalent cost concept

A82-25510

DESCENT

Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type

[AD-A108801]

N82-19206

DESIGN ANALYSIS

YF-16 design concept and philosophy

A82-23444

Aircraft transparency design guide

A82-24307

Design considerations of DC-Link aircraft generation systems

A82-24377

Design technology for improved performance retention in turbofan engines

[SAE PAPER 811055]

A82-24392

Airworthiness considerations in the design of commercial transport aircraft

[SAE PAPER 811039]

A82-24396

Designing for continued airworthiness - General aviation

[SAE PAPER 811038]

A82-24397

Aircraft/airport compatibility - A constant challenge for aircraft designers

A82-25119

Design philosophy of the Hughes model 600 helicopter

[BU-262]

N82-18140

A design study of the Marshal --- lightweight twin-engined aircraft

[BU-262]

N82-19215

Cooled variable-area radial turbine technology program

[NASA-CR-165408]

N82-19221

DESIGN TO COST

Task analytic techniques: Application to the design of a flight simulator instructor/operator console

[AD-A108724]

N82-18227

DETERIORATION

MSG-3 structures --- inspection program for aircraft maintenance

A82-24011

RB 211 powerplant deterioration - Review of current situation and lessons learned

[SAE PAPER 811053]

A82-24393

DIFFUSION WELDING

Diffusion bonding in superplastic forming/diffusion bonding

A82-23754

Metal honeycomb to porous wireform substrate diffusion bond evaluation

[NASA-TM-82793]

N82-18612

Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures

[NASA-CR-165827]

N82-19358

DIGITAL SYSTEMS

Digital flight controls

N82-19143

Digital flight controls

N82-19149

DIGITAL TECHNIQUES

Computer-generated images for simulators - The cost of technology

A82-22881

MIL-STD 1553B - Aircraft EM environmental susceptibility effects

A82-24357

Efficient combinations of numerical techniques applied to aircraft turning performance optimization

A82-24814

DILUTION

Dilution jet behavior in the turn section of a reverse flow combustor

[NASA-TM-82776]

N82-19220

DIPOLE ANTENNAS

Analysis of the crossed dipole antenna as a model for aircraft in an electromagnetic environment

A82-25002

DIRECT CURRENT

Evolution and development of high voltage /270 volt/ dc aircraft electric systems in the United States

A82-24382

DIRECTIONAL STABILITY

Interpretation and construction of a dynamic similarity model of the A 310 wings

[MBB-FE-17/S/PUB/42]

N82-18212

DISASTERS

Importance of a tactical cargo aircraft in emergency relief

A82-25499

DISCRETE ADDRESS BEACON SYSTEM

Discrete Address Beacon System /DABS/

A82-23322

DISPLAY DEVICES

The use of dynamic mock-ups in the design of advanced systems --- USAF's Digital Avionic Information System and NAVI's Advanced Integrated Display System

A82-22902

Combined multisensor displays --- image preprocessing for shape coding to reduce pilot workload

A82-22905

Loran for precise position location - The VIEW-NAV system

A82-24648

Advanced electronic displays and their potential in future transport aircraft

A82-25216

Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s

A82-25324

The multi mode matrix flat panel display: Technology and applications

N82-18169

Analytical study of cockpit information requirements

[AD-A108524]

N82-18218

Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type

[AD-A108801]

N82-19206

Transport aircraft cockpit standardization (Federal Aviation regulations part 25)

[AD-A108924]

N82-19207

DISTANCE MEASURING EQUIPMENT

The birth of precision DME

A82-24066

Loran-C RNAV in mountainous areas

A82-24649

DISTRIBUTED PARAMETER SYSTEMS

Distributed intelligence for air fleet control

[AD-A108611]

N82-18195

DOWNWASH

Angle of downwash behind a wing in unsteady flow

A82-24970

Helicopter rotor downwash: Results of experimental research at the DFVLR-rotor test stand and their comparison with theoretical results

N82-18158

DRAG REDUCTION

Fuel-efficient windshields for transport, commuter and business aircraft

A82-24304

Aircraft surface coatings for drag reduction/erosion protection

[SAE PAPER 811070]

A82-24401

Developments in rotary wing aircraft aerodynamics

N82-18120

Laminar airfoils for transport aircraft

[ESA-TT-680]

N82-18190

On the design of some airfoils for sailplane application --- additions to existing wings for inflight testing

[VTB-LR-326]

N82-19213

DRONE AIRCRAFT

A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors

[RAE-TM-RAD-NAV-145]

N82-18503

DUCT GEOMETRY

Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts

[ASME PAPER 81-WA/NCA-13]

A82-24602

DUCTED FANS

An experimental study of the effects of an inlet flow conditioner on the noise of a low speed axial flow fan --- in an aircraft engine

[TT-8101]

N82-19956

DUCTED FLOW

An ejector augmented choking valve for the metering and control of inlet and bleed duct flows

[AIAA 82-0575]

A82-24659

DUPLEX OPERATION

An on board supervisory system for applications in space missions

[INPE-2097-RPE/327]

N82-18216

DYNAMIC CHARACTERISTICS

A method for the investigation of gyro-stabilization systems

A82-24892

A study of the techniques of dynamic analysis of helicopter type structures

N82-18129

DYNAMIC RESPONSE

Dynamics of aircraft antiskid braking systems --- conducted at the Langley aircraft landing loads and traction facility

[NASA-TP-1959]

N82-18204

A criterion for the prediction of the recovery characteristics of spinning aircraft

[RAE-TM-AERO-2251]

N82-19223

Acoustic fatigue endurance test of USB flap structure models at elevated temperature

[NAL-TR-683]

N82-19570

DYNAMIC STABILITY

Stability of a three-stage dynamic stand

A82-25353

DYNAMIC STRUCTURAL ANALYSIS

Aircraft transparency bird impact analysis using the MAGNA computer program

A82-24315

High speed VSCF generator design consideration --- computer aided design for Variable Speed Constant Frequency generator

A82-24379

DYNAMIC TESTS

Review of support interference in dynamic tests

[AIAA 82-0594]

A82-24668

E

ECONOMETRICS

Selection of telecommunication equipment - A new approach to the equivalent cost concept

A82-25510

EJECTION INJURIES

Physiological acceptability tests of the SJU-5/A ejection seat: Second physiological acceptance demonstration

[AD-A108688]

N82-18194

EJECTION SEATS

Multiple ejection effects analysis

[AD-A108277]

N82-18192

Physiological acceptability tests of the SJU-5/A ejection seat: Second physiological acceptance demonstration

[AD-A108688]

N82-18194

EJECTORS

The effect of ejector augmentation on test-section flow quality in the Calspan 8-ft transonic wind tunnel

[AIAA 82-0571]

A82-24658

ELECTRIC AUTOMOBILES

Vehicle test report: Batronic pickup truck

[NASA-CR-168637]

N82-19205

ELECTRIC CONTROL

On-line control for the regulation of power source in multiple-servo electro-hydraulic systems

[ASME PAPER 81-WA/DSC-3]

A82-24562

ELECTRIC FIELD STRENGTH

Calculation and measurement of electric field strength for airborne antennas in the LP/MF range

A82-25011

ELECTRIC FIELDS

TM/TE polarization ratios in a sample of 30 kHz sferics received at altitudes from 0 to 70 km

[AD-A108182]

N82-18464

ELECTRIC GENERATORS

Aircraft electrical power systems; Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981

[SAE SP-500]

A82-24376

Cost of ownership advantages with a shared oil system

A82-24378

The effect of critical design parameters on the selection of a VSCF system

A82-24381

Packaging the VSCF system for an aircraft engine environment

A82-24383

Aircraft electric system development and test facilities

A82-24384

Electric Flight Systems

[NASA-CP-2209]

N82-19134

A propulsion view of the all-electric airplane

N82-19136

Potential propulsion considerations and study areas for all-electric aircraft

N82-19137

A look into the future: The potential of the all-electric secondary power system for the energy efficient transport

N82-19138

The 400-Hertz constant-speed electrical generation systems

N82-19139

ELECTRIC MOTORS

Electric Flight Systems

[NASA-CP-2209]

N82-19134

Electric flight systems, overview

N82-19135

A propulsion view of the all-electric airplane

N82-19136

Potential propulsion considerations and study areas for all-electric aircraft

N82-19137

A look into the future: The potential of the all-electric secondary power system for the energy efficient transport

N82-19138

Electric ECS

N82-19140

Environmental Control Systems

N82-19141

ELECTRIC POWER SUPPLIES

SUBJECT INDEX

- Overview of Honeywell electromechanical actuation programs
N82-19142
- Digital flight controls
N82-19143
- Electric flight systems
N82-19144
- Engine technology
N82-19145
- Power systems
N82-19146
- Electromechanical actuators
N82-19148
- Digital flight controls
N82-19149
- Electric flight systems integration
N82-19150
- ELECTRIC POWER SUPPLIES**
- Recent improvements in aircraft Ni-Cd cells
A82-24245
- Aircraft electrical power systems; Proceedings of the Aerospace Congress and Exposition, Anaheim, CA, October 5-8, 1981
[SAE SP-500]
A82-24376
- Design considerations of DC-link aircraft generation systems
A82-24377
- The effect of critical design parameters on the selection of a VSCF system
A82-24381
- Evolution and development of high voltage /270 volt/ dc aircraft electric systems in the United States
A82-24382
- Aircraft electric system development and test facilities
A82-24384
- ELECTRIC WIRE**
- The use of 'Kapton' polyimide film in aerospace applications
[SAE PAPER 811091]
A82-24413
- ELECTRICAL INSULATION**
- The use of 'Kapton' polyimide film in aerospace applications
[SAE PAPER 811091]
A82-24413
- Electrical ground testing of aircraft antistatic protection
N82-19156
- ELECTRICAL RESISTIVITY**
- A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum
A82-23772
- Electrical ground testing of aircraft antistatic protection
N82-19156
- ELECTRO-OPTICS**
- A new angular deviation measurement device for aircraft transparencies
A82-24308
- ELECTRODEPOSITION**
- Electroforming of space and aircraft structures
[MBB-BB-491-0]
N82-18419
- ELECTROFORMING**
- Electroforming of space and aircraft structures
[MBB-BB-491-0]
N82-18419
- ELECTROMAGNETIC COMPATIBILITY**
- Materials aspects of aircraft EMC design
A82-24358
- EMC clearance of modern military aircraft
A82-24359
- The testing of aircraft under near field conditions
A82-24361
- ELECTROMAGNETIC INTERFERENCE**
- The coupling of electromagnetic interference into aircraft systems
A82-24354
- The variation of induced currents in aircraft wiring
A82-24355
- MIL-STD 1553B - Aircraft EM environmental susceptibility effects
A82-24357
- ELECTROMAGNETIC MEASUREMENT**
- The testing of aircraft under near field conditions
A82-24361
- Calculation and measurement of electric field strength for airborne antennas in the LF/MF range
A82-25011
- ELECTROMAGNETIC NOISE MEASUREMENT**
- Aircraft electric system development and test facilities
A82-24384
- ELECTROMAGNETIC WAVE TRANSMISSION**
- Analysis of the crossed dipole antenna as a model for aircraft in an electromagnetic environment
A82-25002
- A possible way of specifically correcting location and navigational errors caused by reflection and other propagation anomalies
[ESA-TT-667]
N82-18198
- ELECTROMECHANICAL DEVICES**
- Overview of Honeywell electromechanical actuation programs
N82-19142
- Electric flight systems
N82-19144
- Electromechanical actuators
N82-19148
- ELECTRON BEAM WELDING**
- Novel approaches to electron beam welding machine utilization
A82-23753
- ELECTRONIC CONTROL**
- Advanced generating system technology
A82-24380
- The effect of critical design parameters on the selection of a VSCF system
A82-24381
- Packaging the VSCF system for an aircraft engine environment
A82-24383
- High temperature engine control electronics
[SAE PAPER 811074]
A82-24407
- ELECTRONIC COUNTERMEASURES**
- AN/ALQ-135 tail warning system follow-on operational test and evaluation
[AD-A108348]
N82-18471
- ELECTRONIC EQUIPMENT**
- Analysis of Built-In-Test (BIT) false alarm conditions
[AD-A108752]
N82-18217
- ELECTRONIC EQUIPMENT TESTS**
- The variation of induced currents in aircraft wiring
A82-24355
- EMC clearance of modern military aircraft
A82-24359
- The testing of aircraft under near field conditions
A82-24361
- Aircraft electric system development and test facilities
A82-24384
- AN/ALQ-135 tail warning system follow-on operational test and evaluation
[AD-A108348]
N82-18471
- Investigation of airborne VHF communication and navigation equipment
N82-19421
- ELECTROSTATIC CHARGE**
- Electrical ground testing of aircraft antistatic protection
N82-19156
- EMERGENCIES**
- Importance of a tactical cargo aircraft in emergency relief
A82-25499
- EMITTERS**
- Antenna (selected articles)
[AD-A108174]
N82-19448
- ENERGY CONSERVATION**
- Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning
A82-23470
- Wind and temperature database for flight planning
[SAE PAPER 811068]
A82-24385
- Integration of energy management concepts into the flight deck
[SAE PAPER 811066]
A82-24387
- Management of powerplant maintenance and restoration programs for fuel conservation
[SAE PAPER 811052]
A82-24394
- Airline fuel saving through JT9D engine refurbishment
[SAE PAPER 811051]
A82-24395
- ENERGY CONSUMPTION**
- Air transport in the 21st century
A82-24025

- ENERGY CONVERSION**
Open-cycle vapor compression heat pump
[PB82-110503] N82-18553
- ENGINE AIRFRAME INTEGRATION**
The design of a wind tunnel VSTOL fighter model
incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154
- ENGINE CONTROL**
High temperature engine control electronics
[SAE PAPER 811074] A82-24407
Reliability analysis of a dual-redundant engine
controller
[SAE PAPER 811077] A82-24410
APWAL turbine engine controls research and
development - Present and future
[AIAA PAPER 82-0321] A82-25050
A redundancy concept for a digital CSAS
N82-18170
- ENGINE DESIGN**
Lineup of the IM-series aircraft-derivative gas
turbines
A82-22896
Low grade fuels for turbo and jet engines
A82-23439
Reliable power --- Rolls-Royce aircraft engine
designs
A82-24007
RB 211 powerplant deterioration - Review of
current situation and lessons learned
[SAE PAPER 811053] A82-24393
Management of powerplant maintenance and
restoration programs for fuel conservation
[SAE PAPER 811052] A82-24394
Airline fuel saving through JT9D engine
refurbishment
[SAE PAPER 811051] A82-24395
Performance retention features of the PW2037
[SAE PAPER 811054] A82-24409
Prediction of off-design performance of
turbo-shaft engines a simplified method
N82-18132
Component design and development for future
helicopter engines
N82-18134
Three-engine control system for the prototype
EH-101 helicopter
[AEBG-9/81-1568L] N82-18135
Cooled variable-area radial turbine technology
program
[NASA-CR-165408] N82-19221
- ENGINE FAILURE**
Monitoring engine wear by oil analysis
A82-24012
A digital simulation program describing the motion
of an aircraft undergoing engine failure during
its takeoff ground roll
[AD-A108420] N82-18210
- ENGINE INLETS**
Effects of fan inlet temperature disturbances on
the stability of a turbocfan engine
[NASA-TM-82699] N82-18222
- ENGINE MONITORING INSTRUMENTS**
Monitoring engine wear by oil analysis
A82-24012
Propulsion multiplexer /FMUX/ system - The missing
link
[SAE PAPER 811078] A82-24411
- ENGINE NOISE**
Preliminary thoughts on helicopter cabin noise
prediction methods
N82-18148
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using PJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945
- ENGINE TESTS**
Air cooled engine test facilities
A82-24004
Measurement techniques used to assess the
installed power of a helicopter engine
N82-18133
- ENVIRONMENT SIMULATION**
Helicopter Icing Spray System (HISS) nozzle
improvement evaluation
[AD-A109405] N82-19208
- ENVIRONMENTAL CONTROL**
Electric Flight Systems
[NASA-CP-2209] N82-19134
- Electric ECS
N82-19140
Environmental Control Systems
N82-19141
Electric flight systems integration
N82-19150
- ENVIRONMENTAL TESTS**
The coupling of electromagnetic interference into
aircraft systems
A82-24354
The variation of induced currents in aircraft wiring
A82-24355
EMC clearance of modern military aircraft
A82-24359
- EPOXY MATRIX COMPOSITES**
Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding
[AD-A109377] N82-19209
- ERROR ANALYSIS**
Analysis of system problems using aviation safety
reporting system data
A82-23312
- EUROPEAN AIRBUS**
A310 - Design for maintenance
A82-24002
Active gust and maneuver load control concepts
with the example of the Airbus A300. Part 1:
Explanation of a regular in the time zone of
wind gust load decrease and examination of its
effectiveness in stochastic gusts
[MBB-FB-172/S/PUB/39-PT-1] N82-19228
- EVOLUTION (DEVELOPMENT)**
Evolution and development of high voltage /270
volt/ dc aircraft electric systems in the United
States
A82-24382
- EXHAUST GASES**
Fuel-rich plume combustion
[AD-A108136] N82-18349
- EXHAUST NOZZLES**
Prediction of off-design performance of
turbo-shaft engines a simplified method
N82-18132
Effects of installation of F101 DFE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TM-83250] N82-19181
- EXHAUST SYSTEMS**
Measurement techniques used to assess the
installed power of a helicopter engine
N82-18133
Engine superficial temperature and infrared
signature
N82-18136
- EXPOSURE**
A study of the effects of long-term exposure to
fuels and fluids on the behavior of advanced
composite materials
[NASA-CR-165763] N82-18327
- EXTERNALLY BLOWN FLAPS**
Acoustic fatigue endurance test of USB flap
structure models at elevated temperature
[NAL-TR-683] N82-19570

F

- F-14 AIRCRAFT**
Welding for low-cost advanced titanium airframe
structures
A82-23757
Investigation of crossdeck pendant catapult slot
interaction; proposed corrective measures
[AD-A108149] N82-18232
Effects of installation of F101 DFE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TM-83250] N82-19181
- F-16 AIRCRAFT**
YF-16 design concept and philosophy
A82-23444
A new angular deviation measurement device for
aircraft transparencies
A82-24308
- F-18 AIRCRAFT**
F/A-18 weapon system development
A82-23774

F-100 AIRCRAFT

SUBJECT INDEX

F-100 AIRCRAFT

Acoustic measurements of F100-PW-100 engine
operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952

F-111 AIRCRAFT

Mission-adaptive wing flight demonstration program
[SAE PAPER 811035] A82-24399

FABRICATION

Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding
[AD-A109377] N82-19209

FAILURE ANALYSIS

Fatigue test of the typical main rotor controls
component
A82-24715

Investigation of crossdeck pendant catapult slot
interaction; proposed corrective measures
[AD-A108149] N82-18232

Disengagement of safety harness buckles - CT4
[AD-A109048] N82-19199

FASTENERS

A compilation of stress intensity factor solutions
for flawed fastener holes
[AD-A108753] N82-18628

Disengagement of safety harness buckles - CT4
[AD-A109048] N82-19199

FATIGUE (MATERIALS)

Material/structure degradation due to fretting and
fretting-initiated fatigue
A82-23771

Standardization of helicopter fatigue methodology
- A manufacturer's view
A82-24704

Fatigue test of the typical main rotor controls
component
A82-24715

Helicopter rotor load prediction
A82-24719

Fracture and fatigue characterization of aircraft
structural materials under biaxial loading
[AD-A109054] N82-19587

FATIGUE LIFE

On the sonic fatigue life estimation of skin
structures at room and elevated temperatures
A82-23678

Application of damage tolerance technology to type
certification
[SAE PAPER 811062] A82-24388

The Agusta's solution of AHS's hypothetical
fatigue life problem
A82-24701

The challenge of standardizing fatigue methodology
A82-24703

Application of fatigue, crack propagation and
strain survey testing to the CH-46 aft rotor
drive shaft
A82-24705

A method of determining safe service life for
helicopter components
A82-24709

Hughes helicopters - Fatigue life methodology
A82-24710

Fundamentals of helicopter fatigue life
determination
A82-24714

Hypothetical fatigue life problem - Application of
Aerospatiale method
A82-24716

Boeing Vertol fatigue life methodology
A82-24718

Acoustic fatigue endurance test of USB flap
structure models at elevated temperature
[NAL-TR-683] N82-19570

FATIGUE TESTS

The challenge of standardizing fatigue methodology
A82-24703

NDE of composite rotor blades during fatigue testing
A82-24713

Fundamentals of helicopter fatigue life
determination
A82-24714

Fatigue test of the typical main rotor controls
component
A82-24715

Advanced attack helicopter fatigue testing -
Overview
A82-24720

FEEDBACK CONTROL

Sensitivity reduction by double perfect model
following --- with application to aircraft control
A82-23029

FERROGRAPHY

Monitoring engine wear by oil analysis
A82-24012

FIBER COMPOSITES

Carbon-fiber composites - A fiber composite
material for highly stressed light-construction
components
A82-24805

FIBER REINFORCED COMPOSITES

Certification of civil composite aircraft structure
[SAE PAPER 811061] A82-24389
NDE of composite rotor blades during fatigue testing
A82-24713

FIGHTER AIRCRAFT

Fighters - Tomorrow's terminology
A82-23368

An analytical methodology to predict potential
aircraft losses due to canopy birdstrikes
A82-24313

The anatomy of a technology test bed - Integrated
Flight/Fire Control-I /IFFC I/
[SAE PAPER 811036] A82-24398

Quality, quantity, and technology - A perspective
on fighter development
[SAE PAPER 811097] A82-24400

Future strike fighter options - Concepts and
technologies
[SAE PAPER 811099] A82-24403

Technology for quality and quantity in a new fighter
[SAE PAPER 811100] A82-24404

Fighter issues - 2000
[SAE PAPER 811096] A82-24415

The design of a wind tunnel VSTOL fighter model
incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154

Theoretical investigations on the influence of
different strake, tail unit, and conventional
HLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36] N82-18211

FILAMENT WINDING

Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding
[AD-A109377] N82-19209

FINITE DIFFERENCE THEORY

Influence of exit impedance on finite difference
solutions of transient acoustic mode propagation
in ducts
[ASME PAPER 81-WA/NCA-13] A82-24602

FINITE ELEMENT METHOD

The role of finite element analysis in the design
of birdstrike resistant transparencies
A82-24314

High speed VSCF generator design consideration ---
computer aided design for Variable Speed
Constant Frequency generator
A82-24379

Modal characteristics of rotor blades: Finite
element approach and measurement by ground
vibration test
N82-18127

A study of the techniques of dynamic analysis of
helicopter type structures
N82-18129

Interpretation and construction of a dynamic
similarity model of the A 310 wings
[MBB-FE-17/S/PUB/42] N82-18212

Characterization of the Airbus horizontal
stabilizers of CFRP construction and structural
analysis with the finite element method
[MBB-UT-13-81-0] N82-18213

FIRE CONTROL

The anatomy of a technology test bed - Integrated
Flight/Fire Control-I /IFFC I/
[SAE PAPER 811036] A82-24398

Multivariable aircraft control by maneuver
commands: An application to air to surface
gunnery
N82-19154

FIRE DAMAGE

Workshop on Mathematical Fire Modeling
[AD-A108876] N82-19343

SUBJECT INDEX

FLIGHT SIMULATION

FIRE FIGHTING

Evaluation of the North Island A/C crash/rescue training facility
[AD-A108740] N82-18228

FIRE PREVENTION

An assessment of the crash fire hazard of liquid hydrogen fueled aircraft
[NASA-CR-165526] N82-19196
Workshop on Mathematical Fire Modeling
[AD-A108876] N82-19343

FIRST AID

Importance of a tactical cargo aircraft in emergency relief
A82-25499

FLAPPING

A simplified method for predicting rotor blade airloads
N82-18124
A further study of helicopter rotor pitch-flap-phase coupling
[BU-259] N82-19214

FLAPS (CONTROL SURFACES)

Spoilers or auxiliary flaps
A82-24973

FLEXIBLE WINGS

Development of a self-optimizing flexible technology /SOFT/ transonic wing wind tunnel model
[AIAA 82-0601] A82-24673
A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft --- improving riding quality in fighter aircraft
[NLR-TR-80032-U] N82-19212

FLIGHT CHARACTERISTICS

Aircraft parameter identification in the presence of atmospheric turbulence
A82-23227
A complete method for computation of blade mode characteristics and responses in forward flight
N82-18126
Flight characteristics design and development of the MBB/KHI BK117 helicopter
N82-18150
An analytical investigation of the free-tip rotor for helicopters
[NASA-TN-81345] N82-18179

FLIGHT CONDITIONS

Flight condition recognition /FCR/ technique --- microprocessor-based recording for helicopter structural component fatigue damage
A82-24712

FLIGHT CONTROL

The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFC I/
[SAE PAPER 811036] A82-24398
A redundancy concept for a digital CSAS
N82-18170
The influence of sensor and actuator characteristics on overall helicopter APCs design
N82-18171
Integration of inertial sensors in helicopters
N82-18173
Integrated control design techniques
[AD-A108223] N82-18224
Apparatus for damping operator induced oscillations of a controlled system --- flight control
[NASA-CASE-PBC-11041-1] N82-18493
Electric Flight Systems
[NASA-CP-2209] N82-19134
Overview of Honeywell electromechanical actuation programs
N82-19142
Digital flight controls
N82-19143
Digital flight controls
N82-19149
Electric flight systems integration
N82-19150
Multivariable aircraft control by maneuver commands: An application to air to surface gunnery
N82-19154
A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491] N82-19226

FLIGHT CREWS

Aircrew restraint and mobility test fixture
[AD-A108274] N82-18193

FLIGHT HAZARDS

The requirements for reduced IFR separations on final approach
A82-23311

FLIGHT INSTRUMENTS

Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s
A82-25324

FLIGHT LOAD RECORDERS

Operating flight loads and their effect on engine performance
[SAE PAPER 811071] A82-24405
Flight test data acquisition and interpretation
A82-24707
Flight condition recognition /FCR/ technique --- microprocessor-based recording for helicopter structural component fatigue damage
A82-24712

FLIGHT MECHANICS

Efficient combinations of numerical techniques applied to aircraft turning performance optimization
A82-24814

FLIGHT OPERATIONS

Operational air traffic in the Federal Republic of Germany
A82-23318
Operating flight loads and their effect on engine performance
[SAE PAPER 811071] A82-24405
FLIGHT OPTIMIZATION
Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning
A82-23470
Efficient combinations of numerical techniques applied to aircraft turning performance optimization
A82-24814

FLIGHT PATHS

Midair and near midair collisions on two- and three-dimensional curvilinear flight paths
[ESA-TT-685] N82-18200
Optimal aircraft landing patterns for minimal noise impact
N82-19200
A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533] N82-19217

FLIGHT PLANS

Wind and temperature database for flight planning
[SAE PAPER 811068] A82-24385
Airline flight planning - The weather connection
[SAE PAPER 811067] A82-24386
A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533] N82-19217

FLIGHT SAFETY

Analysis of system problems using aviation safety reporting system data
A82-23312
Operational air traffic in the Federal Republic of Germany
A82-23318
Voice communications - The vital link
A82-23324

Active Beacon Collision Avoidance System (BCAS) logic performance during operational flight tests
[AD-A108893] N82-19203

FLIGHT SIMULATION

Mission-adaptive wing flight demonstration program
[SAE PAPER 811035] A82-24399
The role of simulation in the design process
N82-18154
Rotorcraft flight simulation computer program C81 with DATAMAP interface. Volume 2: Programmer's manual
[AD-A108294] N82-18231
A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors
[RAE-TM-RAD-NAV-145] N82-18503
Simulator study of vortex encounters by a twin-engine, commercial, jet transport airplane
[NASA-TP-1966] N82-19225

FLIGHT SIMULATORS

SUBJECT INDEX

FLIGHT SIMULATORS

Task analytic techniques: Application to the design of a flight simulator instructor/operator console
[AD-A108724] N82-18227

Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR
[ESA-TT-675] N82-19219

FLIGHT TESTS

F/A-18 weapon system development
A82-23774

LAMPs III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System
[SAE PAPER 811080] A82-24412

Loran-C RNAV in mountainous areas
A82-24649

Flight test data acquisition and interpretation
A82-24707

Measurement techniques used to assess the installed power of a helicopter engine
N82-18133

SH-608 test program
N82-18141

Evaluation of the helicopter low airspeed system LASSIE
N82-18172

A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors
[RAE-TM-8AD-NAV-145] N82-18503

Active Beacon Collision Avoidance System (BCAS) logic performance during operational flight tests
[AD-A108893] N82-19203

FLIGHT TRAINING

Computer-generated images for simulators - The cost of technology
A82-22881

Task analytic techniques: Application to the design of a flight simulator instructor/operator console
[AD-A108724] N82-18227

FLIGHT VEHICLES

Analysis and optimization of control systems in piloted flight vehicles --- Russian book
A82-22398

FLOW DISTRIBUTION

The problem of calculation of the flow around helicopter rotor blade tips
N82-18160

Separated flow around helicopter bodies
N82-18163

A method of predicting fuselage loads in hover
N82-18164

On the calculation of separated flow on helicopter fuselages
[MBB-UD-321-81-0] N82-18188

Simulator study of vortex encounters by a twin-engine, commercial, jet transport airplane
[NASA-TP-1966] N82-19225

The pressure signature method for blockage corrections, and its applications to the industrial wind tunnel
[BU-263] N82-19231

FLOW EQUATIONS

A complete method for computation of blade mode characteristics and responses in forward flight
N82-18126

FLOW MEASUREMENT

Evaluation of the helicopter low airspeed system LASSIE
N82-18172

FLOW REGULATORS

An ejector augmented choking valve for the metering and control of inlet and bleed duct flows
[AIAA 82-0575] A82-24659

FLOW VELOCITY

Complete velocity profile and 'optimum' skin friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3] A82-24566

FLUID MECHANICS

Annual review of fluid mechanics. Volume 14 --- Book
A82-24416

FLUTTER

Flutter and time response analyses of three degree of freedom airfoils in transonic flow
[AD-A108987] N82-19227

Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts
[MBB-FE-172/S/PUB/39-PT-1] N82-19228

FLUTTER ANALYSIS

Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance
[AIAA PAPER 80-0724] A82-24022

Recent developments in wing with stores flutter suppression
[ONERA, TP NO. 1981-145] A82-24077

FORCED VIBRATION

Cross and cross-coupling derivative measurements on the standard dynamics model at AEDC
[AIAA 82-0596] A82-24670

FORECASTING

Report of the Air Traffic Forecasting Working Party, 1981
N82-19195

FORGING

Practical applications of fracture mechanics
[AGARD-AG-257] N82-19571

FORMING TECHNIQUES

Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures
[NASA-CR-165827] N82-19358

FRACTURE MECHANICS

Practical applications of fracture mechanics
[AGARD-AG-257] N82-19571

Fracture and fatigue characterization of aircraft structural materials under biaxial loading
[AD-A109054] N82-19587

FRACTURE STRENGTH

The effects of absorbed moisture upon the physical properties of stretched acrylic materials
A82-24320

Application of damage tolerance technology to type certification
[SAE PAPER 811062] A82-24388

FREE FLOW

Static pressure in the slipstream of a propeller
A82-24023

FREQUENCY STABILITY

Advanced generating system technology
A82-24380

The effect of critical design parameters on the selection of a VSCF system
A82-24381

Packaging the VSCF system for an aircraft engine environment
A82-24383

FREQUENCY STANDARDS

Global positioning system timing receivers in the DSN
N82-20126

FRESHEN LENSES

Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type
[AD-A108801] N82-19206

FRETTING CORROSION

Material/structure degradation due to fretting and fretting-initiated fatigue
A82-23771

FUEL COMBUSTION

Fuel-rich plume combustion
[AD-A108136] N82-18349

FUEL CONSUMPTION

Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning
A82-23470

Fuel-efficient windshields for transport, commuter and business aircraft
A82-24304

Integration of energy management concepts into the flight deck
[SAE PAPER 811066] A82-24387

Management of powerplant maintenance and restoration programs for fuel conservation
[SAE PAPER 811052] A82-24394

Airline fuel saving through JT9D engine refurbishment
[SAE PAPER 811051] A82-24395

Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072] A82-24406

Developments in rotary wing aircraft aerodynamics
N82-18120

SUBJECT INDEX

GROUND STATIONS

Parametric study of the influence of the engine upon the operating cost of a civil helicopter
N82-18131

Component design and development for future helicopter engines
N82-18134

A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533]
N82-19217

FUEL CORROSION
Improving the accuracy of the estimates of surfactant content in jet fuels
A82-23250

FUELS
A study of the effects of long-term exposure to fuels and fluids on the behavior of advanced composite materials
[NASA-CR-165763]
N82-18327

FULL SCALE TESTS
Slotted wall test section for automotive aerodynamic test facilities
[AIAA 82-0585]
A82-24661

Status and capabilities of the National Full Scale Facility 40- by 80-foot wind tunnel modification
[AIAA 82-0607]
A82-24676

FUSELAGES
Flight characteristics design and development of the MBB/KHI BK117 helicopter
N82-18150

Separated flow around helicopter bodies
N82-18163

A method of predicting fuselage loads in hover
N82-18164

On the calculation of separated flow on helicopter fuselages
[MBB-UD-321-81-0]
N82-18188

Structural system identification technology verification
[AD-A109181]
N82-19583

FUSION WELDING
Aluminum and its alloys - Weldability
A82-23755

G

GAS STREAMS
Dilution jet behavior in the turn section of a reverse flow combustor
[NASA-TN-82776]
N82-19220

GAS TURBINE ENGINES
Lineup of the IM-series aircraft-derivative gas turbines
A82-22896

Reliable power --- Rolls-Royce aircraft engine designs
A82-24007

AFWAL turbine engine controls research and development - Present and future
[AIAA PAPER 82-0321]
A82-25050

Component design and development for future helicopter engines
N82-18134

Dilution jet behavior in the turn section of a reverse flow combustor
[NASA-TN-82776]
N82-19220

Cooled variable-area radial turbine technology program
[NASA-CR-165408]
N82-19221

GEAR TEETH
The measurement of the mobility of structures at acoustic frequencies
N82-18149

GEARS
Cost of ownership advantages with a shared oil system
A82-24378

GENERAL AVIATION AIRCRAFT
Designing for continued airworthiness - General aviation
[SAE PAPER 811038]
A82-24397

Study of cabin noise control for twin engine general aviation aircraft
[NASA-CR-165833]
N82-18995

Bibliography of NASA published reports on general aviation, 1975 to 1981
[NASA-TN-83307]
N82-19132

A design study of the Marshal --- lightweight twin-engined aircraft
[BU-262]
N82-19215

A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533]
N82-19217

An experimental study of the effect of tail configuration on the spinning characteristics of general aviation aircraft --- static wind tunnel force measurements
[NASA-CR-168578]
N82-19224

GEOMETRIC DILUTION OF PRECISION
Improvements and extensions of the Geometrical Dilution of Precision (GDOP) concept for selecting navigation measurements
[AD-A108607]
N82-18197

GEOMETRICAL THEORY OF DIFFRACTION
GTD terrain reflection model applied to ILS glide slope --- Geometrical Theory of Diffraction
A82-23027

Volumetric pattern prediction of antennas on aircraft using the geometrical theory of diffraction
[ESA-TT-677]
N82-18483

GEOPOTENTIAL HEIGHT
Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data
A82-25113

GLAZES
B.A.C. One-Eleven flight deck glazing product improvement
A82-24325

Concorde glazings - 5 years of Mach 2 service
A82-24326

GLIDE PATHS
GTD terrain reflection model applied to ILS glide slope --- Geometrical Theory of Diffraction
A82-23027

GLIDERS
On the design of some airfoils for sailplane application --- additions to existing wings for in-flight testing
[VTH-LB-326]
N82-19213

GLOBAL POSITIONING SYSTEM
Institute of Navigation, Annual Meeting, 37th, U.S. Naval Academy, Annapolis, MD, June 9-11, 1981, Proceedings
A82-24643

A marine NAVSTAR GPS receiver
A82-24644

The application of NAVSTAR differential GPS in the civilian community
A82-24645

Improvements and extensions of the Geometrical Dilution of Precision (GDOP) concept for selecting navigation measurements
[AD-A108607]
N82-18197

Global positioning system timing receivers in the DSN
N82-20126

GOGGLES
Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility
N82-18168

GOVERNMENT/INDUSTRY RELATIONS
International plans for civil and military co-ordination
A82-23317

GRAPHITE-EPOXY COMPOSITES
A study of the effects of long-term exposure to fuels and fluids on the behavior of advanced composite materials
[NASA-CR-165763]
N82-18327

GROUND BASED CONTROL
Stereographic projection in the National Airspace System
A82-23031

GROUND EFFECT (COMMUNICATIONS)
Loran-C RNAV in mountainous areas
A82-24649

GROUND SPEED
A digital simulation program describing the motion of an aircraft undergoing engine failure during its takeoff ground roll
[AD-A108420]
N82-18210

GROUND STATIONS
Analysis of loran-C system reliability for civil aviation
A82-24650

GROUND SUPPORT EQUIPMENT

GROUND SUPPORT EQUIPMENT

- Analysis of Built-In-Test (BIT) false alarm conditions
[AD-A108752] N82-18217
- Further development of the test concept of the ALPHA JET engine LARZAC 04 N82-18223
- GROUND TESTS**
- SH-608 test program N82-18141
- Electrical ground testing of aircraft antistatic protection N82-19156
- GROUND WIND**
- Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts [MBB-FE-172/S/PUB/39-PT-1] N82-19228
- GUST ALLEVIATORS**
- A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft --- improving riding quality in fighter aircraft [NLR-TR-80032-U] N82-19212
- GYROSCOPIC STABILITY**
- Stability of a three-stage dynamic stand A82-25353
- GYROSTABILIZERS**
- A method for the investigation of gyro-stabilization systems A82-24892

H

- HARMONIC MOTION**
- A simplified method for predicting rotor blade airloads N82-18124
- HARNESSES**
- Disengagement of safety harness buckles - CT4 [AD-A109048] N82-19199
- HEAD-UP DISPLAYS**
- A new angular deviation measurement device for aircraft transparencies A82-24308
- HEAT PUMPS**
- Open-cycle vapor compression heat pump [PB82-110503] N82-18553
- HEAT RESISTANT ALLOYS**
- Where is cobalt irreplaceable A82-25538
- HEAT TRANSFER**
- Engine superficial temperature and infrared signature N82-18136
- HEAT TREATMENT**
- Aluminum and its alloys - Weldability A82-23755
- A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum A82-23772
- HELICOPTER CONTROL**
- A control model for maneuvering flight for application to a computer-flight testing program N82-18153
- A redundancy concept for a digital CSAS N82-18170
- The influence of sensor and actuator characteristics on overall helicopter AFCS design N82-18171
- HELICOPTER DESIGN**
- LAMPSS III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System [SAE PAPER 811080] A82-24412
- Standardization of helicopter fatigue methodology - A manufacturer's view A82-24704
- Evolution of the Aeroscout A82-24706
- Flight condition recognition /FCR/ technique --- microprocessor-based recording for helicopter structural component fatigue damage A82-24712
- Fatigue test of the typical main rotor controls component A82-24715

SUBJECT INDEX

- Helicopter rotor load prediction A82-24719
- A study of the techniques of dynamic analysis of helicopter type structures N82-18129
- The effects of slight non-linearities on modal testing of helicopter-like structures N82-18130
- Point of view of a helicopter manufacturer on airworthiness regulations N82-18137
- Military requirements: Too little or too much N82-18138
- Parametric criteria and impact on design trends N82-18139
- Design philosophy of the Hughes model 600 helicopter N82-18140
- SH-608 test program N82-18141
- Naval versions of the Dauphin and the AS 15 TT weapon system N82-18142
- Army Lynx: Product development matched to military combat development N82-18143
- A light helicopter for night firing N82-18144
- Flight characteristics design and development of the MBB/KHI BK117 helicopter N82-18150
- The role of simulation in the design process N82-18154
- Impact of systems technology and integration on helicopter design N82-18165
- The multi mode matrix flat panel display: Technology and applications N82-18169
- Integration of inertial sensors in helicopters N82-18173
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary [NASA-TM-84149] N82-19170
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views [NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors [NASA-TM-84146] N82-19173
- Experience during the development of the German-Japanese helicopter BK 117 [MBB-UD-318-81-0] N82-19210
- Design study into a high endurance mini-rotorcraft [BU-265] N82-19216
- HELICOPTER ENGINES**
- Parametric study of the influence of the engine upon the operating cost of a civil helicopter N82-18131
- Measurement techniques used to assess the installed power of a helicopter engine N82-18133
- Component design and development for future helicopter engines N82-18134
- Three-engine control system for the prototype EH-101 helicopter [AEBG-9/81-1568L] N82-18135
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary [NASA-TM-84149] N82-19170
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views [NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors [NASA-TM-84146] N82-19173
- HELICOPTER PERFORMANCE**
- Utilizing the helicopter's versatility to improve the ATC system A82-23316
- The Agusta's solution of AHS's hypothetical fatigue life problem A82-24701
- Hughes helicopters - Fatigue life methodology A82-24710

SUBJECT INDEX

HUMAN FACTORS ENGINEERING

- Fundamentals of helicopter fatigue life determination
 - A82-24714
- Hypothetical fatigue life problem - Application of aerospace method
 - A82-24716
- The cargo helicopter - A logistical vehicle
 - A82-24717
- An analytical investigation of the free-tip rotor for helicopters
 - [NASA-TM-81345] N82-18179
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary
 - [NASA-TM-84149] N82-19170
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views
 - [NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors
 - [NASA-TM-84146] N82-19173
- HELICOPTER PROPELLER DRIVE
 - Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft
 - A82-24705
- HELICOPTER TAIL ROTORS
 - Wind tunnel investigation of high speed rotor noise
 - N82-18146
- HELICOPTER WAKES
 - Seventh European Rotorcraft and Powered Lift Aircraft Forum
 - N82-18119
 - A simplified approach to the free wake analysis of a hovering rotor
 - N82-18121
 - An experimental analysis of the shape of a rotor wake
 - N82-18122
 - Optimum performance and wake geometry of co-axial rotor in hover
 - N82-18156
 - A numerical approach to co-axial rotor aerodynamics
 - N82-18157
- HELICOPTERS
 - The challenge of standardizing fatigue methodology
 - A82-24703
 - A method of determining safe service life for helicopter components
 - A82-24709
 - Boeing Vertol fatigue life methodology
 - A82-24718
 - The effects of slight non-linearities on modal testing of helicopter-like structures
 - N82-18130
 - Preliminary thoughts on helicopter cabin noise prediction methods
 - N82-18148
 - The measurement of the mobility of structures at acoustic frequencies
 - N82-18149
 - Separated flow around helicopter bodies
 - N82-18163
 - Mast mounted visual aids
 - N82-18167
 - Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility
 - N82-18168
 - Evaluation of the helicopter low airspeed system LASSIE
 - N82-18172
 - An analytical investigation of the free-tip rotor for helicopters
 - [NASA-TM-81345] N82-18179
 - On the calculation of separated flow on helicopter fuselages
 - [MBB-UD-321-81-0] N82-18188
 - A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors.
 - [RAE-TM-RAD-NAV-145] N82-18503
 - NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary
 - [NASA-TM-84149] N82-19170
 - NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views
 - [NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 3: Aerodynamics and Structures Session
 - [NASA-TM-84147] N82-19172
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors
 - [NASA-TM-84146] N82-19173
- Structural system identification technology verification
 - [AD-A109181] N82-19583
- Effects of repetition rate and impulsiveness of simulated helicopter rotor noise on annoyance
 - [NASA-TP-1969] N82-19707
- Noise measurements on the helicopter BK 117 design. Weighted noise levels and influence of airspeed
 - [DFVLR-MITT-81-18] N82-19957
- HELMET MOUNTED DISPLAYS
 - Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility
 - N82-18168
 - Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR
 - [ESA-TT-675] N82-19219
- HIGH FREQUENCIES
 - The testing of aircraft under near field conditions
 - A82-24361
- HIGH SPEED
 - High speed VSCF generator design consideration --- computer aided design for Variable Speed Constant Frequency generator
 - A82-24379
- HIGH STRENGTH
 - The development of high strength light-weight windshields for the new generation of Boeing 757 and 767 airliners
 - A82-24323
- HIGH TEMPERATURE
 - High temperature engine control electronics
 - [SAE PAPER 811074] A82-24407
- HIGH VOLTAGES
 - Evolution and development of high voltage /270 volt/ dc aircraft electric systems in the United States
 - A82-24382
- HISTORIES
 - History of the sweptback wing
 - [DGLR PAPER 81-070] A82-22898
 - NASA pocket statistics
 - [NASA-TM-84134] N82-19084
- HOLE GEOMETRY (MECHANICS)
 - A compilation of stress intensity factor solutions for flawed fastener holes
 - [AD-A108753] N82-18628
- HONEYCOMB STRUCTURES
 - Metal honeycomb to porous wireform substrate diffusion bond evaluation
 - [NASA-TM-82793] N82-18612
- HOT-WIRE FLOWMETERS
 - An experimental analysis of the shape of a rotor wake
 - N82-18122
- HOVERING
 - A simplified approach to the free wake analysis of a hovering rotor
 - N82-18121
 - Optimum performance and wake geometry of co-axial rotor in hover
 - N82-18156
 - A numerical approach to co-axial rotor aerodynamics
 - N82-18157
 - A method of predicting fuselage loads in hover
 - N82-18164
- HOVERING STABILITY
 - Hover tests of a model H-force rotor
 - N82-18159
- HUGHES AIRCRAFT
 - Hughes helicopters - Fatigue life methodology
 - A82-24710
- HUMAN FACTORS ENGINEERING
 - Combined multisensor displays --- image preprocessing for shape coding to reduce pilot workload
 - A82-22905

HUMAN PERFORMANCE

Point of view of a helicopter manufacturer on airworthiness regulations N82-18137

Multiple ejection effects analysis [AD-A108277] N82-18192

HUMAN PERFORMANCE

Analysis of system problems using aviation safety reporting system data A82-23312

HUMAN REACTIONS

Direct comparison of community response to road traffic noise and to aircraft noise A82-22974

HUMIDITY MEASUREMENT

Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data A82-25113

HYDRAULIC CONTROL

On-line control for the regulation of power source in multiple-servo electro-hydraulic systems [ASME PAPER 81-WA/DSC-3] A82-24562

Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20] A82-24565

HYPERSONIC FLOW

Oscillating supersonic/hypersonic wings at high incidence A82-23828

HYPERSONIC WIND TUNNELS

Technical innovations in testing and analysis of heat and pressure models in hypersonic wind tunnels [AIAA 82-0578] A82-24660

HYPOTHESES

A complete method for computation of blade mode characteristics and responses in forward flight N82-18126

ICE FORMATION

Helicopter Icing Spray System (HISS) nozzle improvement evaluation [AD-A109405] N82-19208

IMAGE PROCESSING

Combined multisensor displays --- image preprocessing for shape coding to reduce pilot workload A82-22905

IMAGING TECHNIQUES

Computer-generated images for simulators - The cost of technology A82-22881

IMPACT DAMAGE

The effects of bird orientation on load profile and damage level A82-24316

IMPACT PREDICTION

An analytical methodology to predict potential aircraft losses due to canopy birdstrikes A82-24313

IMPACT RESISTANCE

The role of finite element analysis in the design of birdstrike resistant transparencies A82-24314

IMPEDANCE MEASUREMENT

Antenna (selected articles) [AD-A108174] N82-19448

IN-FLIGHT MONITORING

Propulsion multiplexer /PMUX/ system - The missing link [SAE PAPER 811078] A82-24411

Flight test data acquisition and interpretation A82-24707

Flight condition recognition /PCR/ technique --- microprocessor-based recording for helicopter structural component fatigue damage A82-24712

INDUSTRIES

Experience during the development of the German-Japanese helicopter BK 117 [MBB-UD-318-81-0] N82-19210

INERTIAL PLATFORMS

Integration of inertial sensors in helicopters N82-18173

Software features applicable to inertial measurement unit self alignment [AD-A108511] N82-18196

SUBJECT INDEX

INFORMATION DISSEMINATION

Experience during the development of the German-Japanese helicopter BK 117 [MBB-UD-318-81-0] N82-19210

INFORMATION FLOW

Integration of complex systems in current and future aircraft projects for the example of avionics [MBB-UH-18-80-0] N82-18221

INFORMATION MANAGEMENT

Integration of complex systems in current and future aircraft projects for the example of avionics [MBB-UH-18-80-0] N82-18221

INFORMATION SYSTEMS

The use of dynamic mock-ups in the design of advanced systems --- USAF's Digital Avionic Information System and NAVY's Advanced Integrated Display System A82-22902

Analytical study of cockpit information requirements [AD-A108524] N82-18218

INFRARED RADIATION

Engine superficial temperature and infrared signature N82-18136

INLET FLOW

An ejector augmented choking valve for the metering and control of inlet and bleed duct flows [AIAA 82-0575] A82-24659

An experimental study of the effects of an inlet flow conditioner on the noise of a low speed axial flow fan --- in an aircraft engine [TT-8101] N82-19956

INSPECTION

MSG-3 structures --- inspection program for aircraft maintenance A82-24011

MSG-3 overview --- aircraft maintenance program development A82-24014

Analysis of Built-In-Test (BIT) false alarm conditions [AD-A108752] N82-18217

INSTRUCTORS

Task analytic techniques: Application to the design of a flight simulator instructor/operator console [AD-A108724] N82-18227

INSTRUMENT APPROACH

The requirements for reduced IFR separations on final approach A82-23311

A Microwave Landing System simulation A82-23323

INSTRUMENT FLIGHT RULES

The requirements for reduced IFR separations on final approach A82-23311

Utilizing the helicopter's versatility to improve the ATC system A82-23316

INSTRUMENT LANDING SYSTEMS

GTD terrain reflection model applied to ILS glide slope --- Geometrical Theory of Diffraction A82-23027

The toll of ILS-preventable aviation accidents A82-25325

Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type [AD-A108801] N82-19206

FM broadcast interference related to airborne ILS, VOR and VHF communications [RTCA/DO-176] N82-19419

Investigation of technical requirements N82-19420

Investigation of airborne VHF communication and navigation equipment N82-19421

INTAKE SYSTEMS

Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82 [NASA-TF-1974] N82-19222

INTERACTIVE CONTROL

CAD/CAM in British Aerospace - Aircraft Group A82-24373

INTERFACES

New developments in cockpit-human interfaces
[HAB-TM-PS-412] N82-18215

INTERMODULATION

Investigation of the effects of airborne
installation factors on receiver interference
N82-19422

INTERNATIONAL COOPERATION

Airworthiness regulation: What is our strategy -
What are the issues
A82-24006
What the operator wants --- airline cooperation in
aircraft maintenance
A82-24008
Experience during the development of the
German-Japanese helicopter BK 117
[MBB-UD-318-81-0] N82-19210

INTERPRETATION

Flight test data acquisition and interpretation
A82-24707

INTERPROCESSOR COMMUNICATION

Distributed intelligence for air fleet control
[AD-A108611] N82-18195
An on board supervisory system for applications in
space missions
[INPE-2097-RPE/327] N82-18216

J**JET AIRCRAFT**

Transparencies - What an aircraft designer should
know
A82-24305
Further development of the test concept of the
ALPHA JET engine LARZAC 04
N82-18223

JET AIRCRAFT NOISE

Effect of facility variation on the acoustic
characteristics of three single stream nozzles
[NASA-TM-81635] N82-19944
Acoustic measurements of F100-PW-100 engine
operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952

JET CONTROL

Potential reductions in aircraft operation and
maintenance costs by using thrust computing
support equipment
[AD-A108463] N82-18207

JET ENGINE FUELS

Improving the accuracy of the estimates of
surfactant content in jet fuels
A82-23250
Low grade fuels for turbo and jet engines
A82-23439
Airline fuel saving through JT9D engine
refurbishment
[SAE PAPER 811051] A82-24395
An assessment of the crash fire hazard of liquid
hydrogen fueled aircraft
[NASA-CR-165526] N82-19196

JET ENGINES

Low grade fuels for turbo and jet engines
A82-23439
Air cooled engine test facilities
A82-24004
Airline fuel saving through JT9D engine
refurbishment
[SAE PAPER 811051] A82-24395
Acoustic measurements of F100-PW-100 engine
operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952

JET FLOW

Complete velocity profile and 'optimum' skin
friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3] A82-24566
Dilution jet behavior in the turn section of a
reverse flow combustor
[NASA-TM-82776] N82-19220

JET PROPULSION

Further development of the test concept of the
ALPHA JET engine LARZAC 04
N82-18223

JOINTS (JUNCTIONS)

Practical applications of fracture mechanics
[AGARD-AG-257] N82-19571

K**KALMAN FILTERS**

Fixed gain controller design for aircraft
A82-23441
Extension of proportional navigation by the use of
optimal filtering and control methods
[ESA-TT-683] N82-18199

KAPTON (TRADEMARK)

The use of 'Kapton' polyimide film in aerospace
applications
[SAE PAPER 811091] A82-24413

KEVLAR (TRADEMARK)

Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding
[AD-A109377] N82-19209

L**LAGRANGE COORDINATES**

Modal characteristics of rotor blades: Finite
element approach and measurement by ground
vibration test
N82-18127

LAMINAR BOUNDARY LAYER

Numerical design of the contoured wind-tunnel
liner for the NASA swept-wing LFC test
[AIAA 82-0568] A82-24656

LAMINAR FLOW AIRFOILS

Laminar airfoils for transport aircraft
[ESA-TT-680] N82-18190

LANDING AIDS

The birth of precision DME
A82-24066
Development of a clear air radar to detect
meteorological hazards at airports
[AD-A108236] N82-18835

LANDING GEAR

Describing function analysis of nonlinear nose
gear shimmy
[ASME PAPER 81-WA/DSC-20] A82-24565
Oscillations and vibrations of aircraft on runways
A82-24974

LANDMARKS

United States Coast Pilot 9. Pacific and Arctic
Coasts Alaska: Cape Spencer to Beaufort Sea
[PB82-109562] N82-18201

LASER RANGE/TRACKER

Wide field of view laser beacon system for
three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9] A82-24563

LEAD ACID BATTERIES

Vehicle test report: Battronic pickup truck
[NASA-CR-168637] N82-19205

LEADING EDGES

History of the sweptback wing
[DGLR PAPER 81-070] A82-22898

LEGAL LIABILITY

Air transportation of handicapped persons
A82-24338

LIFE CYCLE COSTS

Cost of ownership advantages with a shared oil
system
A82-24378

LIFT

A three-dimensional approach to lift and moment
coefficients of rotating blades
N82-18125

Slotted variable camber flap
[NASA-CASE-LAR-12541-1] N82-18203

Theoretical investigations on the influence of
different strake, tail unit, and conventional
HLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36] N82-18211

LIFT AUGMENTATION

XPV-12A diagnostic and development programs
[AD-A108354] N82-18206

LIFT FANS

Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

LIFTING ROTORS

SUBJECT INDEX

LIFTING ROTORS

A further study of helicopter rotor pitch-flap-phase coupling
[BU-259] N82-19214

LIGHT AIRBORNE MULTIPURPOSE SYSTEM
LAMPS III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System
[SAE PAPER 811080] A82-24412

LIGHT AIRCRAFT
Complete guide to Rutan homebuilt aircraft --- Book
A82-22880
The reliability and safety of small passenger aircraft
A82-24972

LIGHT EMITTING DIODES
The multi mode matrix flat panel display: Technology and applications
N82-18169

LIQUID HYDROGEN
An assessment of the crash fire hazard of liquid hydrogen fueled aircraft
[NASA-CR-165526] N82-19196

LIQUIDS
A study of the effects of long-term exposure to fuels and fluids on the behavior of advanced composite materials
[NASA-CR-165763] N82-18327

LOAD TESTS
The effects of bird orientation on load profile and damage level
A82-24316
Operating flight loads and their effect on engine performance
[SAE PAPER 811071] A82-24405
Fundamentals of helicopter fatigue life determination
A82-24714

LOADING MOMENTS
Some unsteady aerodynamic effects on helicopter rotors
N82-18162

LOGIC DESIGN
The influence of sensor and actuator characteristics on overall helicopter AFCS design
N82-18171

LONG TERM EFFECTS
Design technology for improved performance retention in turboprop engines
[SAE PAPER 811055] A82-24392

LONGITUDINAL CONTROL
Preliminary investigation into the addition of auxiliary longitudinal thrust on helicopter agility
N82-18155

LOOP ANTENNAS
Calculation and measurement of electric field strength for airborne antennas in the LF/MF range
A82-25011

LORAN
Institute of Navigation, Annual Meeting, 37th, U.S. Naval Academy, Annapolis, MD, June 9-11, 1981, Proceedings
A82-24643
Loran for precise position location - The VIEW-NAV system
A82-24648

LORAN C
Loran-C RNAV in mountainous areas
A82-24649
Analysis of loran-C system reliability for civil aviation
A82-24650

LOW ASPECT RATIO
Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance
[AIAA PAPER 80-0724] A82-24022

LOW COST
Welding for low-cost advanced titanium airframe structures
A82-23757

LUBRICATING OILS
Monitoring engine wear by oil analysis
A82-24012
Cost of ownership advantages with a shared oil system
A82-24378

M

MACH NUMBER
History of the sweptback wing
[DGLR PAPER 81-070] A82-22898

MAGNETIC FIELDS
TM/TE polarization ratios in a sample of 30 kHz sferics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464

MAINTAINABILITY
Integrated control design techniques
[AD-A108223] N82-18224
Assessment of Avionic Equipment Field Reliability and Maintainability as Functions of Unit Cost
[AD-A109373] N82-19218

MAINTENANCE
Investigation into the utility of some quick setting cements for runway repair
[B-80-157/60.7.0157] N82-18225
Bomb crater repair techniques for permanent airfields. Report 1: Series 1 tests
[AD-A108716] N82-18229

MAN MACHINE SYSTEMS
Analysis and optimization of control systems in piloted flight vehicles --- Russian book
A82-22398
New developments in cockpit-human interfaces
[RAE-TN-PS-412] N82-18215

MANAGEMENT INFORMATION SYSTEMS
National Airspace Data Interchange Network (NADIN) support of Remote Maintenance Monitoring System (RMMS)
[AD-A109125] N82-19160

MANEUVERABILITY
A control model for maneuvering flight for application to a computer-flight testing program
N82-18153
Preliminary investigation into the addition of auxiliary longitudinal thrust on helicopter agility
N82-18155

MANUFACTURING
CAD/CAM in British Aerospace - Aircraft Group
A82-24373
Point of view of a helicopter manufacturer on airworthiness regulations
N82-18137

MARINE ENVIRONMENTS
LAMPS III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System
[SAE PAPER 811080] A82-24412

MARINE TRANSPORTATION
A marine NAVSTAR GPS receiver
A82-24644

MARKET RESEARCH
Where is cobalt irreplaceable
A82-25538

MASS
Modal characteristics of rotor blades: Finite element approach and measurement by ground vibration test
N82-18127

MATERIAL ABSORPTION
The effects of absorbed moisture upon the physical properties of stretched acrylic materials
A82-24320

MATHEMATICAL MODELS
Sensitivity reduction by double perfect model following --- with application to aircraft control
A82-23029
An analytical methodology to predict potential aircraft losses due to canopy birdstrikes
A82-24313
Parametric criteria and impact on design trends
N82-18139
Volumetric pattern prediction of antennas on aircraft using the geometrical theory of diffraction
[ESA-TT-677] N82-18483
Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts
[NASA-CR-165852] N82-19167
Workshop on Mathematical Fire Modeling
[AD-A108876] N82-19343

SUBJECT INDEX

MOMENTS

Aircraft noise prediction program theoretical manual, part 1 [NASA-TM-83199-PT-1]	N82-19946	EMC clearance of modern military aircraft	A82-24359
Aircraft noise prediction program theoretical manual, part 2 [NASA-TM-83199-PT-2]	N82-19947	Naval versions of the Dauphin and the AS 15 TT weapon system	N82-18142
MEASURING INSTRUMENTS		Army Lynx: Product development matched to military combat development	N82-18143
Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels [AIAA 82-0603]	A82-24675	A light helicopter for night firing	N82-18144
MECHANICAL ENGINEERING		MILITARY HELICOPTERS	
Lineup of the IM-series aircraft-derivative gas turbines	A82-22896	The way ahead for helicopter maintenance	A82-24009
Design technology for improved performance retention in turbofan engines [SAE PAPER 811055]	A82-24392	Structural testing of composites with known defects	A82-24708
MECHANICAL PROPERTIES		The cargo helicopter - A logistical vehicle	A82-24717
Carbon-fiber composites - A fiber composite material for highly stressed light-construction components	A82-24805	Preliminary investigation into the addition of auxiliary longitudinal thrust on helicopter agility	N82-18155
MEDICAL SERVICES		Review of helicopter Mast Mounted Sight (MMS) base motion isolation and Line-of-Sight (LOS) stabilization concepts	N82-18166
Importance of a tactical cargo aircraft in emergency relief	A82-25499	Vibration levels in Army helicopters: Measurement recommendations and data [AD-A108131]	N82-18209
METAL COATINGS		MILITARY OPERATIONS	
Electroforming of space and aircraft structures [MBB-BB-491-0]	N82-18419	Military requirements: Too little or too much	N82-18138
METAL FILMS		Naval versions of the Dauphin and the AS 15 TT weapon system	N82-18142
High-frequency monitoring of surface layers of metals	A82-23603	Army Lynx: Product development matched to military combat development	N82-18143
METAL FOILS		MILITARY TECHNOLOGY	
Metal honeycomb to porous wireform substrate diffusion bond evaluation [NASA-TM-82793]	N82-18612	YP-16 design concept and philosophy	A82-23444
METAL PARTICLES		Quality, quantity, and technology - A perspective on fighter development [SAE PAPER 811097]	A82-24400
Monitoring engine wear by oil analysis	A82-24012	Future strike fighter options - Concepts and technologies [SAE PAPER 811099]	A82-24403
METEOROLOGICAL PARAMETERS		Technology for quality and quantity in a new fighter [SAE PAPER 811100]	A82-24404
Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data	A82-25113	Evolution of the Aeroscout	A82-24706
METEOROLOGICAL RADAR		Military requirements: Too little or too much	N82-18138
Scanning strategies for air traffic control radars	A82-24646	Tethered rotorplatforms and their mission potential	N82-18145
Development of a clear air radar to detect meteorological hazards at airports [AD-A108236]	N82-18835	MISSILE CONTROL	
METEOROLOGICAL SERVICES		Extension of proportional navigation by the use of optimal filtering and control methods [ESA-TT-683]	N82-18199
Wind and temperature database for flight planning [SAE PAPER 811068]	A82-24385	MISSILE DEFENSE	
Airline flight planning - The weather connection [SAE PAPER 811067]	A82-24386	Perspectives for Controlled Weapons Technology: Report of the 90th Helicopter Forum [MBB-UA-532-80-0]	N82-19211
MICROCRACKS		MISSILE SYSTEMS	
High-frequency monitoring of surface layers of metals	A82-23603	Perspectives for Controlled Weapons Technology: Report of the 90th Helicopter Forum [MBB-UA-532-80-0]	N82-19211
MICROPROCESSORS		MISSION PLANNING	
Lightweight ATC systems	A82-23321	LAMPS III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System [SAE PAPER 811080]	A82-24412
Packaging the VSCF system for an aircraft engine environment	A82-24383	MODAL RESPONSE	
MICROWAVE LANDING SYSTEMS		The effects of slight non-linearities on modal testing of helicopter-like structures	N82-18130
A Microwave Landing System simulation	A82-23323	MOISTURE CONTENT	
MIDAIR COLLISIONS		Improving the accuracy of the estimates of surfactant content in jet fuels	A82-23250
Midair and near midair collisions on two- and three-dimensional curvilinear flight paths [ESA-TT-685]	N82-18200	The effects of absorbed moisture upon the physical properties of stretched acrylic materials	A82-24320
Aircraft collision avoidance systems [GPO-79-431]	N82-19201	MOMENTS	
MILITARY AIR FACILITIES		A three-dimensional approach to lift and moment coefficients of rotating blades	N82-18125
International plans for civil and military co-ordination	A82-23317		
MILITARY AIRCRAFT			
Fixed gain controller design for aircraft	A82-23441		
Transparency development needs for military aircraft in the 1980's	A82-24302		
Aircraft transparency bird impact analysis using the MAGMA computer program	A82-24315		

MOMENTUM THEORY

MOMENTUM THEORY

An extension of the local momentum theory to the rotors operating in twisted flow field N82-18123

MONOCHROMATORS

Engine superficial temperature and infrared signature N82-18136

MOTION STABILITY

Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20] A82-24565

MOUNTAINS

Loran-C RNAV in mountainous areas A82-24649

MULTIPLEXING

Propulsion multiplexer /PMUX/ system - The missing link [SAE PAPER 811078] A82-24411

MX MISSILE

Technical innovations in testing and analysis of heat and pressure models in hypersonic wind tunnels [AIAA 82-0578] A82-24660

N

NACELLES

RB 211 powerplant deterioration - Review of current situation and lessons learned [SAE PAPER 811053] A82-24393

NASA PROGRAMS

Integration of energy management concepts into the flight deck [SAE PAPER 811066] A82-24387
NASA pocket statistics [NASA-TM-84134] N82-19084

NATIONAL AIRSPACE UTILIZATION SYSTEM

Stereographic projection in the National Airspace System A82-23031

NAVIGATION

Integrated control design techniques [AD-A108223] N82-18224

NAVIGATION AIDS

Navigational aids on-board the Concorde A82-24065
United States Coast Pilot 9. Pacific and Arctic Coasts Alaska: Cape Spencer to Beaufort Sea [PB82-109562] N82-18201

NAVIGATION INSTRUMENTS

A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors [RAE-TH-RAD-NAV-145] N82-18503

NAVSTAR SATELLITES

Institute of Navigation, Annual Meeting, 37th, U.S. Naval Academy, Annapolis, MD, June 9-11, 1981, Proceedings A82-24643
A marine NAVSTAR GPS receiver A82-24644
The application of NAVSTAR differential GPS in the civilian community A82-24645

NEAR FIELDS

The testing of aircraft under near field conditions A82-24361

NETWORK SYNTHESIS

A marine NAVSTAR GPS receiver A82-24644

NICKEL CADMIUM BATTERIES

Recent improvements in aircraft Ni-Cd cells A82-24245

NIGHT FLIGHTS (AIRCRAFT)

A light helicopter for night firing N82-18144
Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility N82-18168

NOISE INTENSITY

Preliminary thoughts on helicopter cabin noise prediction methods N82-18148

NOISE MEASUREMENT

Mean flow and noise measurements in a Mach 3.5 pilot quiet tunnel [AIAA 82-0569] A82-24657

SUBJECT INDEX

Effect of facility variation on the acoustic characteristics of three single stream nozzles [NASA-TM-81635] N82-19944

NOISE POLLUTION

Direct comparison of community response to road traffic noise and to aircraft noise A82-22974

NOISE PREDICTION (AIRCRAFT)

Methodology for multiaircraft minimum noise impact landing trajectories A82-23037

Study of cabin noise control for twin engine general aviation aircraft [NASA-CR-165833] N82-18995

Annoyance caused by propeller airplane flyover noise: Preliminary results [NASA-TM-83244] N82-18996

Aircraft noise prediction program theoretical manual, part 1 [NASA-TM-83199-PT-1] N82-19946

Aircraft noise prediction program theoretical manual, part 2 [NASA-TM-83199-PT-2] N82-19947

NOISE PROPAGATION

Study of cabin noise control for twin engine general aviation aircraft [NASA-CR-165833] N82-18995

NOISE REDUCTION

Methodology for multiaircraft minimum noise impact landing trajectories A82-23037

Transparency development needs for military aircraft in the 1980's A82-24302

The measurement of the mobility of structures at acoustic frequencies N82-18149

Study of cabin noise control for twin engine general aviation aircraft [NASA-CR-165833] N82-18995

Optimal aircraft landing patterns for minimal noise impact N82-19200

Acoustic measurements of F100-PW-100 engine operating in hush house NSN 4920-02-070-2721 [AD-A108814] N82-19952

An experimental study of the effects of an inlet flow conditioner on the noise of a low speed axial flow fan --- in an aircraft engine [TT-8101] N82-19956

NOISE SPECTRA

The measurement of the mobility of structures at acoustic frequencies N82-18149

NOISE TOLERANCE

Effects of repetition rate and impulsiveness of simulated helicopter rotor noise on annoyance [NASA-TP-1969] N82-19707

NONDESTRUCTIVE TESTS

High-frequency monitoring of surface layers of metals A82-23603

NDE of composite rotor blades during fatigue testing A82-24713

NONLINEAR FILTERS

Apparatus for damping operator induced oscillations of a controlled system --- flight control [NASA-CASE-FRC-11041-1] N82-18493

NONLINEAR SYSTEMS

Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20] A82-24565

Analysis of a nonlinear altitude tracking method [AD-A108878] N82-19197

NONLINEARITY

The effects of slight non-linearities on modal testing of helicopter-like structures N82-18130

NOSE WHEELS

Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20] A82-24565

NOZZLE FLOW

Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles A82-25347

SUBJECT INDEX

PERFORMANCE PREDICTION

Effects of installation of F101 DPE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TM-83250] N82-19181

NOZZLE GEOMETRY
Effect of facility variation on the acoustic
characteristics of three single stream nozzles
[NASA-TM-81635] N82-19944

NUMERICAL ANALYSIS
A complete method for computation of blade mode
characteristics and responses in forward flight
N82-18126

NUMERICAL CONTROL
Distributed intelligence for air fleet control
[AD-A108611] N82-18195
Software features applicable to inertial
measurement unit self alignment
[AD-A108511] N82-18196

NUMERICAL FLOW VISUALIZATION
Problems of numerical simulation of unsteady
three-dimensional viscous-gas flows in nozzles
N82-25347
The problem of calculation of the flow around
helicopter rotor blade tips
N82-18160
Separated flow around helicopter bodies
N82-18163

O

OBLIQUE WINGS
Spin-tunnel investigation of a 1/13-scale model of
the NASA AD-1 oblique-wing research aircraft
[NASA-TM-83236] N82-18183

OCEANOGRAPHIC PARAMETERS
United States Coast Pilot 9. Pacific and Arctic
Coasts Alaska: Cape Spencer to Beaufort Sea
[PB82-109562] N82-18201

OH-13 HELICOPTER
Evolution of the Aeroscout
N82-24706

ONBOARD DATA PROCESSING
Propulsion multiplexer /FMUI/ system - The missing
link
[SAE PAPER 811078] N82-24411
Flight test data acquisition and interpretation
N82-24707
An on board supervisory system for applications in
space missions
[INPE-2097-RPE/327] N82-18216

ONBOARD EQUIPMENT
Navigational aids on-board the Concorde
N82-24065
The anatomy of a technology test bed - Integrated
Flight/Fire Control-I /IFFC I/
[SAE PAPER 811036] N82-24398

OPERATING COSTS
Management of powerplant maintenance and
restoration programs for fuel conservation
[SAE PAPER 811052] N82-24394
Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072] N82-24406
Aircraft/airport compatibility - A constant
challenge for aircraft designers
N82-25119
Parametric study of the influence of the engine
upon the operating cost of a civil helicopter
N82-18131
Parametric criteria and impact on design trends
N82-18139
Potential reductions in aircraft operation and
maintenance costs by using thrust computing
support equipment
[AD-A108463] N82-18207

OPERATING SYSTEMS (COMPUTERS)
Air traffic control en route computer system
[GPO-89-008] N82-19202

OPERATOR PERFORMANCE
Reducing reflections on the front surface of air
traffic control displays
N82-23314

OPERATORS (PERSONNEL)
Task analytic techniques: Application to the
design of a flight simulator instructor/operator
console
[AD-A108724] N82-18227

OPTICAL MEASUREMENT
A new angular deviation measurement device for
aircraft transparencies
N82-24308

OPTICAL PATHS
GTD terrain reflection model applied to ILS glide
scope --- Geometrical Theory of Diffraction
N82-23027

OPTICAL REFLECTION
Reducing reflections on the front surface of air
traffic control displays
N82-23314

OPTIMAL CONTROL
Analysis and optimization of control systems in
piloted flight vehicles --- Russian book
N82-22398
Sensitivity reduction by double perfect model
following --- with application to aircraft control
N82-23029
Extension of proportional navigation by the use of
optimal filtering and control methods
[ESA-TT-683] N82-18199
Multivariable aircraft control by maneuver
commands: An application to air to surface
gunnery
N82-19154
A method for applying linear optimal control
theory to the design of a regulator for a
flexible aircraft --- improving riding quality
in fighter aircraft
[NLR-TR-80032-U] N82-19212

OPTIMIZATION
Parametric criteria and impact on design trends
N82-18139
A concept for a fuel efficient flight planning aid
for general aviation
[NASA-CR-3533] N82-19217

OSCILLATING FLOW
Developments in rotary wing aircraft aerodynamics
N82-18120
Interpretation and construction of a dynamic
similarity model of the A 310 wings
[NBB-PE-17/S/PUB/42] N82-18212

OSCILLATION DAMPERS
Apparatus for damping operator induced
oscillations of a controlled system --- flight
control
[NASA-CASE-FRC-11041-1] N82-18493

P

PARAMETER IDENTIFICATION
Sensitivity reduction by double perfect model
following --- with application to aircraft control
N82-23029
Aircraft parameter identification in the presence
of atmospheric turbulence
N82-23227

PARAMETERIZATION
Parametric criteria and impact on design trends
N82-18139

PASSENGER AIRCRAFT
Improvement of fuel economy by flying with maximum
rearward center-of-gravity positioning
N82-23470
Development of maintenance programmes through the
functional, structural and flight test phases
N82-24003
Fuel-efficient windshields for transport, commuter
and business aircraft
N82-24304
The reliability and safety of small passenger
aircraft
N82-24972
A study to define the research and technology
requirements for advanced turbo/propfan
transport aircraft
[NASA-CR-166138] N82-18202

PASSENGERS
Air transportation of handicapped persons
N82-24338

PAVEMENTS
Investigation of compaction criteria for airport
pavement subgrade soils
[AD-A108518] N82-18230

PERFORMANCE PREDICTION
Design technology for improved performance
retention in turbofan engines
[SAE PAPER 811055] N82-24392

PERFORMANCE TESTS

SUBJECT INDEX

Performance retention features of the PW2037
[SAE PAPER 811054] A82-24409

Reliability analysis of a dual-redundant engine
controller
[SAE PAPER 811077] A82-24410

Helicopter rotor load prediction A82-24719

Foundations for computer simulation of a low
pressure oil flooded single screw air compressor
[AD-A108230] N82-19391

PERFORMANCE TESTS
A new facility and technique for two-dimensional
aerodynamic testing
[AIAA 82-0608] A82-24677

PERIODIC VARIATIONS
Application of the ONER dynamic stall model to a
helicopter blade in forward flight N82-18161

PHASE ERROR
Antenna (selected articles)
[AD-A108174] N82-19448

PHASE RULE
A further study of helicopter rotor
pitch-flap-phase coupling
[BU-259] N82-19214

PHASE VELOCITY
Antenna (selected articles)
[AD-A108174] N82-19448

PHYSICAL FITNESS
Air transportation of handicapped persons A82-24338

PHYSICAL PROPERTIES
The effects of absorbed moisture upon the physical
properties of stretched acrylic materials A82-24320

PHYSIOLOGICAL EFFECTS
Physiological acceptability tests of the SJU-5/A
ejection seat: Second physiological acceptance
demonstration
[AD-A108688] N82-18194

PILOT PERFORMANCE
Analysis and optimization of control systems in
piloted flight vehicles --- Russian book A82-22398

Combined multisensor displays --- image
preprocessing for shape coding to reduce pilot
workload A82-22905

Transparency design decisions - Assessing their
impact on visual performance A82-24306

PIPES (TUBES)
Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding
[AD-A109377] N82-19209

PITCHING MOMENTS
A further study of helicopter rotor
pitch-flap-phase coupling
[BU-259] N82-19214

PLASMA DISPLAY DEVICES
Lightweight ATC systems A82-23321

PLASTIC AIRCRAFT STRUCTURES
Conference on Aerospace Transparencies, London,
England, September 8-10, 1980, Proceedings A82-24301

Abrasion resistant coated plastic products for
aircraft A82-24310

Proposed method for abrasion testing transparent
plastics and coatings A82-24311

Acrylic - A timely review A82-24317

Problems associated with the quality assurance of
stretched acrylic sheet A82-24319

The effects of absorbed moisture upon the physical
properties of stretched acrylic materials A82-24320

PLASTIC COATINGS
Abrasion resistant coated plastic products for
aircraft A82-24310

Proposed method for abrasion testing transparent
plastics and coatings A82-24311

Aircraft surface coatings for drag
reduction/erosion protection
[SAE PAPER 811070] A82-24401

PLUMES
Fuel-rich plume combustion
[AD-A108136] N82-18349

POLARIMETERS
TH/TE polarization ratios in a sample of 30 kHz
spherics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464

POLLUTION CONTROL
Evaluation of the North Island A/C crash/rescue
training facility
[AD-A108740] N82-18228

POLYMERIC FILMS
Problems associated with the quality assurance of
stretched acrylic sheet A82-24319

The use of 'Kapton' polyimide film in aerospace
applications
[SAE PAPER 811091] A82-24413

PORTABLE EQUIPMENT
Portable transparency optical test system /P-TOTS/
A82-24309

POSITION (LOCATION)
Loran for precise position location - The VIEW-NAV
system A82-24648

A possible way of specifically correcting location
and navigational errors caused by reflection and
other propagation anomalies
[ESA-TT-667] N82-18198

POSITION ERRORS
The application of NAVSTAR differential GPS in the
civilian community A82-24645

Loran-C RNAV in mountainous areas A82-24649

A possible way of specifically correcting location
and navigational errors caused by reflection and
other propagation anomalies
[ESA-TT-667] N82-18198

POSITION INDICATORS
Wide field of view laser beacon system for
three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9] A82-24563

POTENTIAL FLOW
The problem of calculation of the flow around
helicopter rotor blade tips N82-18160

POTENTIAL THEORY
On the calculation of transonic blade tip flow for
helicopter rotors
[MBB-UD-320-81-0] N82-18187

POWER CONDITIONING
Advanced generating system technology A82-24380

Power systems N82-19146

POWER EFFICIENCY
Recent improvements in aircraft Ni-Cd cells A82-24245

PRECIPITATION (METEOROLOGY)
Aircraft measurements and analysis of severe
storms: 1976 field experiment
[NASA-CR-168519] N82-18803

PRESSING (FORMING)
Lucas stretched acrylic A82-24318

PRESSURE DISTRIBUTION
Separated flow around helicopter bodies N82-18163

Transonic perturbation analysis of
wing-fuselage-nacelle-pylon configurations with
powered jet exhausts
[NASA-CR-165852] N82-19167

The effect of a well on the aerodynamics of a
spoiler --- wind tunnel flow visualization and
pressure measurement
[BU-268] N82-19194

PRESSURE GRADIENTS
The pressure signature method for blockage
corrections, and its applications to the
industrial wind tunnel
[BU-263] N82-19231

PRESSURE PULSES
Effects of repetition rate and impulsiveness of
simulated helicopter rotor noise on annoyance
[NASA-TF-1969] N82-19707

SUBJECT INDEX

RADIO FREQUENCY INTERFERENCE

PRESSURE RATIO
Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82
[NASA-TP-1974] N82-19222

PRESSURE SENSORS
Pressure transducer calibration process
[SAE PAPER 811076] A82-24408

PROCESS CONTROL (INDUSTRY)
Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371

PROCESS HEAT
Open-cycle vapor compression heat pump
[PB82-110503] N82-18553

PRODUCT DEVELOPMENT
Evolution of the Aeroscout
A82-24706

SH-608 test program
N82-18141

Army Lynx: Product development matched to military combat development
N82-18143

A design study of the Marshal --- lightweight twin-engined aircraft
[BU-262] N82-19215

Cooled variable-area radial turbine technology program
[NASA-CR-165408] N82-19221

PRODUCTION ENGINEERING
Managing computer aided design; Proceedings of the Conference, London, England, November 19, 1980
A82-24371

PROGRAM VERIFICATION (COMPUTERS)
A program testing assistant
[AD-A108147] N82-18922

PROJECT MANAGEMENT
A310 - Design for maintenance
A82-24002

PROPAGATION MODES
Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts
[ASME PAPER 81-WA/NCA-13] A82-24602

PROPELLER BLADES
Preliminary thoughts on helicopter cabin noise prediction methods
N82-18148

Study of cabin noise control for twin engine general aviation aircraft
[NASA-CR-165833] N82-18995

PROPELLER FANS
A study to define the research and technology requirements for advanced turbo/propfan transport aircraft
[NASA-CR-166138] N82-18202

PROPELLER SLIPSTREAMS
Static pressure in the slipstream of a propeller
A82-24023

PROPELLERS
An extension of the local momentum theory to the rotors operating in twisted flow field
N82-18123

Annoyance caused by propeller airplane flyover noise: Preliminary results
[NASA-TM-83244] N82-18996

Collection and evaluation of propeller aircraft noise certification data
[DFVLR-MITT-81-29] N82-19958

PROPORTIONAL CONTROL
Extension of proportional navigation by the use of optimal filtering and control methods
[ESA-TT-683] N82-18199

PROPULSION SYSTEM CONFIGURATIONS
A propulsion view of the all-electric airplane
N82-19136

PROPULSION SYSTEM PERFORMANCE
Propulsion multiplexer /PNUX/ system - The missing link
[SAE PAPER 811078] A82-24411

Prediction of off-design performance of turbo-shaft engines a simplified method
N82-18132

Three-engine control system for the prototype EH-101 helicopter
[AEBG-9/81-1568L] N82-18135

PROTECTION
Electrical ground testing of aircraft antistatic protection
N82-19156

PROTECTIVE COATINGS
Abrasion resistant coated plastic products for aircraft
A82-24310

PROTOTYPES
Three-engine control system for the prototype EH-101 helicopter
[AEBG-9/81-1568L] N82-18135

PSYCHOACOUSTICS
Annoyance caused by propeller airplane flyover noise: Preliminary results
[NASA-TM-83244] N82-18996

PULSE DOPPLER RADAR
Scanning strategies for air traffic control radars
A82-24646

PULSE RATE
Effects of repetition rate and impulsiveness of simulated helicopter rotor noise on annoyance
[NASA-TP-1969] N82-19707

PYLONS
Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts
[NASA-CR-165852] N82-19167

Q

QUALITY CONTROL
Problems associated with the quality assurance of stretched acrylic sheet
A82-24319

Technology for quality and quantity in a new fighter
[SAE PAPER 811100] A82-24404

QUARTZ TRANSDUCERS
Pressure transducer calibration process
[SAE PAPER 811076] A82-24408

R

RADAR ANTENNAS
Secondary radar problems - The presence of false echoes
A82-25323

RADAR BEACONS
Discrete Address Beacon System /DABS/
A82-23322

Wide field of view laser beacon system for three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9] A82-24563

Analysis of a nonlinear altitude tracking method
[AD-A108878] N82-19197

RADAR ECHOES
Secondary radar problems - The presence of false echoes
A82-25323

RADAR SCANNING
Scanning strategies for air traffic control radars
A82-24646

RADAR TRACKING
Stereographic projection in the National Airspace System
A82-23031

RADIO ANTENNAS
Calculation and measurement of electric field strength for airborne antennas in the LF/MF range
A82-25011

RADIO ATTENUATION
The coupling of electromagnetic interference into aircraft systems
A82-24354

RADIO COMMUNICATION
Voice communications - The vital link
A82-23324

RADIO EQUIPMENT
Utilization of radio equipment at airports and on airways --- Russian book
A82-22407

RADIO FREQUENCY INTERFERENCE
FM broadcast interference related to airborne ILS, VOR and VHF communications
[RTCA/DO-176] N82-19419

Investigation of technical requirements
N82-19420

RADIO FREQUENCY SHIELDING

SUBJECT INDEX

Investigation of airborne VHF communication and navigation equipment
N82-19421

Investigation of the effects of airborne installation factors on receiver interference-
N82-19422

FAA/FCC coordination procedures for FM broadcast stations
N82-19423

RADIO FREQUENCY SHIELDING

Materials aspects of aircraft EMC design
A82-24358

RADIO RECEIVERS

A marine NAVSTAR GPS receiver
A82-24644

Loran for precise position location - The VIEW-NAV system
A82-24648

A possible way of specifically correcting location and navigational errors caused by reflection and other propagation anomalies
[ESA-TT-667]
N82-18198

TM/TE polarization ratios in a sample of 30 kHz sferics received at altitudes from 0 to 70 km
[AD-A108182]
N82-18464

FM broadcast interference related to airborne ILS, VOR and VHF communications
[ETCA/DO-176]
N82-19419

Investigation of technical requirements
N82-19420

Investigation of the effects of airborne installation factors on receiver interference
N82-19422

RADIO RELAY SYSTEMS

Beyond the horizon coverage for air navigation/traffic control
A82-24647

RADIO SCATTERING

A possible way of specifically correcting location and navigational errors caused by reflection and other propagation anomalies
[ESA-TT-667]
N82-18198

RADIO TRANSMITTERS

The variation of induced currents in aircraft wiring
A82-24355

RADIOGRAPHY

High-frequency monitoring of surface layers of metals
A82-23603

RAIN

C-5A austere airfield operational utility evaluation. Phase 2: Operation on unpaved soil surfaces following rainfall
[AD-A108597]
N82-18208

RAMJET ENGINES

Fuel-rich plume combustion
[AD-A108136]
N82-18349

RANGE ERRORS

Stereographic projection in the National Airspace System
A82-23031

REAL TIME OPERATION

NAS system load - Utilization of the DARC system
A82-23315

A Microwave Landing System simulation
A82-23323

RECEIVERS

Global positioning system timing receivers in the DSN
N82-20126

REDUNDANCY

A redundancy concept for a digital CSAS
N82-18170

REDUNDANT COMPONENTS

Reliability analysis of a dual-redundant engine controller
[SAE PAPER 811077]
A82-24410

REGULATIONS

Designing for continued airworthiness - General aviation
[SAE PAPER 811038]
A82-24397

Point of view of a helicopter manufacturer on airworthiness regulations
N82-18137

RELIABILITY

Assessment of Avionic Equipment Field Reliability and Maintainability as Functions of Unit Cost
[AD-A109373]
N82-19218

RELIABILITY ANALYSIS

Reliability centered maintenance /RCM/
A82-24001

Reliability analysis of a dual-redundant engine controller
[SAE PAPER 811077]
A82-24410

Analysis of loran-C system reliability for civil aviation
A82-24650

RELIABILITY ENGINEERING

The inter-relation between design, construction and maintenance
A82-24010

Recent improvements in aircraft Ni-Cd cells
A82-24245

High temperature engine control electronics
[SAE PAPER 811074]
A82-24407

REMOTE SENSING

Wide field of view laser beacon system for three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9]
A82-24563

REMOTE SENSORS

Combined multisensor displays --- image preprocessing for shape coding to reduce pilot workload
A82-22905

REQUIREMENTS

Analytical study of cockpit information requirements
[AD-A108524]
N82-18218

RESCUE OPERATIONS

LAMPS III recovery assist, securing and traversing /RAST/ system --- Light Airborne Multi-Purpose System
[SAE PAPER 811080]
A82-24412

RESEARCH AND DEVELOPMENT

Windshield system structural enhancement
A82-24312

APWAL turbine engine controls research and development - Present and future
[AIAA PAPER 82-0321]
A82-25050

RESEARCH FACILITIES

Aeronautical Research Laboratories Structures Division
[AD-A109049]
N82-19161

RESPONSE BIAS

Flutter and time response analyses of three degree of freedom airfoils in transonic flow
[AD-A108987]
N82-19227

REVERSED FLOW

Dilution jet behavior in the turn section of a reverse flow combustor
[NASA-TN-82776]
N82-19220

REVISIONS

Naval versions of the Dauphin and the AS 15 TT weapon system
N82-18142

REYNOLDS NUMBER

A new facility and technique for two-dimensional aerodynamic testing
[AIAA 82-0608]
A82-24677

RIDING QUALITY

A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft --- improving riding quality in fighter aircraft
[NLR-TR-80032-U]
N82-19212

RIGID ROTORS

Flight characteristics design and development of the MBB/KHI BK117 helicopter
N82-18150

A general purpose program for rotor blade dynamics
N82-18151

Helicopter rotor downwash: Results of experimental research at the DFVLR-rotor test stand and their comparison with theoretical results
N82-18158

RIGIDITY

Interpretation and construction of a dynamic similarity model of the A 310 wings
[MBB-FE-17/S/PUB/42]
N82-18212

ROTARY STABILITY

A further study of helicopter rotor pitch-flap-phase coupling
[BU-259]
N82-19214

SUBJECT INDEX

RUNWAYS

ROTARY WING AIRCRAFT

Rotorcraft flight simulation computer program C81
with DATAMAP interface. Volume 2: Programmer's
manual [AD-A108294] N82-18231
Design study into a high endurance mini-rotorcraft
[BU-265] N82-19216

ROTARY WINGS

Structural testing of composites with known defects
A82-24708
Fatigue test of the typical main rotor controls
component A82-24715

Helicopter rotor load prediction A82-24719

Seventh European Rotorcraft and Powered Lift
Aircraft Forum N82-18119

Developments in rotary wing aircraft aerodynamics
N82-18120

A simplified approach to the free wake analysis of
a hovering rotor N82-18121

An experimental analysis of the shape of a rotor
wake N82-18122

An extension of the local momentum theory to the
rotors operating in twisted flow field N82-18123

A complete method for computation of blade mode
characteristics and responses in forward flight
N82-18126

Wind tunnel investigation of high speed rotor noise
N82-18146

Prediction of blade vortex interaction noise from
measured blade pressure N82-18147

A general purpose program for rotor blade dynamics
N82-18151

Optimum performance and wake geometry of co-axial
rotor in hover N82-18156

A numerical approach to co-axial rotor aerodynamics
N82-18157

Helicopter rotor downwash: Results of
experimental research at the DFVLR-rotor test
stand and their comparison with theoretical
results N82-18158

Hover tests of a model H-force rotor N82-18159

The problem of calculation of the flow around
helicopter rotor blade tips N82-18160

Application of the ONER dynamic stall model to a
helicopter blade in forward flight N82-18161

Some unsteady aerodynamic effects on helicopter
rotors N82-18162

An analytical investigation of the free-tip rotor
for helicopters [NASA-TM-81345] N82-18179

On the calculation of transonic blade tip flow for
helicopter rotors [NBB-UD-320-81-0] N82-18187

Development of manufacturing technology for
fabrication of a composite helicopter main rotor
spar by tubular braiding [AD-A109377] N82-19209

Effects of repetition rate and impulsiveness of
simulated helicopter rotor noise on annoyance
[NASA-TP-1969] N82-19707

ROTATION

An extension of the local momentum theory to the
rotors operating in twisted flow field N82-18123

ROTOR AERODYNAMICS

Seventh European Rotorcraft and Powered Lift
Aircraft Forum N82-18119

Developments in rotary wing aircraft aerodynamics
N82-18120

A simplified approach to the free wake analysis of
a hovering rotor N82-18121

An extension of the local momentum theory to the
rotors operating in twisted flow field N82-18123

A simplified method for predicting rotor blade
airloads N82-18124

Hover tests of a model H-force rotor N82-18159

The problem of calculation of the flow around
helicopter rotor blade tips N82-18160

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 3: Aerodynamics and
Structures Session [NASA-TM-84147] N82-19172

A further study of helicopter rotor
pitch-flap-phase coupling [BU-259] N82-19214

Design study into a high endurance mini-rotorcraft
[BU-265] N82-19216

ROTOR BLADES (TURBOMACHINERY)

NDE of composite rotor blades during fatigue testing
A82-24713

Seventh European Rotorcraft and Powered Lift
Aircraft Forum N82-18119

Developments in rotary wing aircraft aerodynamics
N82-18120

A simplified approach to the free wake analysis of
a hovering rotor N82-18121

An experimental analysis of the shape of a rotor
wake N82-18122

A simplified method for predicting rotor blade
airloads N82-18124

A three-dimensional approach to lift and moment
coefficients of rotating blades N82-18125

A complete method for computation of blade mode
characteristics and responses in forward flight
N82-18126

Modal characteristics of rotor blades: Finite
element approach and measurement by ground
vibration test N82-18127

ROTOR LIFT

A three-dimensional approach to lift and moment
coefficients of rotating blades N82-18125

ROTOR SPEED

An extension of the local momentum theory to the
rotors operating in twisted flow field N82-18123

A simplified method for predicting rotor blade
airloads N82-18124

Wind tunnel investigation of high speed rotor noise
N82-18146

ROTOR SYSTEMS RESEARCH AIRCRAFT

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 3: Aerodynamics and
Structures Session [NASA-TM-84147] N82-19172

ROTORCRAFT AIRCRAFT

Tethered rotorplatforms and their mission potential
N82-18145

RUNWAY CONDITIONS

Oscillations and vibrations of aircraft on runways
A82-24974

C-5A austere airfield operational utility
evaluation. Phase 2: Operation on unpaved soil
surfaces following rainfall [AD-A108597] N82-18208

Investigation into the utility of some quick
setting cements for runway repair [B-80-157/60.7.0157] N82-18225

Investigation of compaction criteria for airport
pavement subgrade soils [AD-A108518] N82-18230

RUNWAYS

Bomb crater repair techniques for permanent
airfields. Report 1: Series 1 tests [AD-A108716] N82-18229

Investigation of compaction criteria for airport
pavement subgrade soils [AD-A108518] N82-18230

S

S-N DIAGRAMS

Hypothetical fatigue life problem - Application of
Aerospatiale method A82-24716

SAFETY DEVICES
Disengagement of safety harness buckles - CT4
[AD-A109048] N82-19199

SANDWICH STRUCTURES
Evaluation of superplastic forming and
co-diffusion bonding of Ti-6Al-4V titanium alloy
expanded sandwich structures
[NASA-CR-165827] N82-19358

SATELLITE SOUNDING
Rapid extraction of layer relative humidity,
geopotential thickness, and atmospheric
stability from satellite sounding radiometer data
A82-25113

SCALE MODELS
Spin-tunnel investigation of a 1/13-scale model of
the NASA AD-1 oblique-wing research aircraft
[NASA-TM-83236] N82-18183

SCINTILLATION COUNTERS
Linear alpha-ray altimeter
A82-23225

SEALERS
Novel metal-ceramics-composite sealing coatings in
aircraft engines
A82-24803

SEALING
Investigation into the utility of some quick
setting cements for runway repair
[B-80-157/60.7.0157] N82-18225

SECONDARY RADAR
Secondary radar problems - The presence of false
echoes
A82-25323

SELF ADAPTIVE CONTROL SYSTEMS
Active gust and maneuver load control concepts
with the example of the Airbus A300. Part 1:
Explanation of a regular in the time zone of
wind gust load decrease and examination of its
effectiveness in stochastic gusts
[MBB-FE-172/S/POB/39-PT-1] N82-19228

SELF ALIGNMENT
Software features applicable to inertial
measurement unit self alignment
[AD-A108511] N82-18196

SENSITIVITY
Sensitivity reduction by double perfect model
following --- with application to aircraft control
A82-23029

SENSORS
The influence of sensor and actuator
characteristics on overall helicopter AFCS design
N82-18171

SEPARATED FLOW
Separated flow around helicopter bodies
N82-18163
A method of predicting fuselage loads in hover
N82-18164
On the calculation of separated flow on helicopter
fuselages
[MBB-UD-321-81-0] N82-18188

SERVICE LIFE
Boeing's big, quiet 737-300
A82-23369
A method of determining safe service life for
helicopter components
A82-24709
Hughes helicopters - Fatigue life methodology
A82-24710

SERVOCONTROL
On-line control for the regulation of power source
in multiple-servo electro-hydraulic systems
[ASME PAPER 81-WA/DSC-3] A82-24562

SHAFTS (MACHINE ELEMENTS)
Application of fatigue, crack propagation and
strain survey testing to the CH-46 aft rotor
drive shaft
A82-24705

SHIELDING
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

SHORT TAKEOFF AIRCRAFT

Review of defense-related vertical and short
takeoff and landing (V/STOL) aircraft programs
[GPO-55-278] N82-18205

XFV-12A diagnostic and development programs
[AD-A108354] N82-18206

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 1: Executive Summary
[NASA-TM-84149] N82-19170

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 2: Operators' Views
[NASA-TM-84148] N82-19171

NASA/HAA Advanced Rotorcraft Technology and Tilt
Rotor Workshops. Volume 4: Flight Control
Avionics Systems and Human Factors
[NASA-TM-84146] N82-19173

Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

SIDELobe REDUCTION
Secondary radar problems - The presence of false
echoes
A82-25323

SIGNAL PROCESSING
A design for a 32-channel multiplexer --- for
unmanned aircraft navigation sensors
[RAP-TM-RAD-NAV-145] N82-18503

SIGNATURE ANALYSIS
The pressure signature method for blockage
corrections, and its applications to the
industrial wind tunnel
[BU-263] N82-19231

SIZE DETERMINATION
Minimum mass sizing of a large low-aspect ratio
airframe for flutter-free performance
[AIAA PAPER 80-0724] A82-24022

SKIN (STRUCTURAL MEMBER)
On the sonic fatigue life estimation of skin
structures at room and elevated temperatures
A82-23678

SKIN FRICTION
Complete velocity profile and 'optimum' skin
friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3] A82-24566
Laminar airfoils for transport aircraft
[ESA-TT-680] N82-18190

SLEDS
Test site instrumentation study. Volume 2: Crash
1 and crash 2 raw data
[PB82-111832] N82-18233

SLENDER BODIES
Review of support interference in dynamic tests
[AIAA 82-0594] A82-24668

SLOTTED WIND TUNNELS
Slotted wall test section for automotive
aerodynamic test facilities
[AIAA 82-0585] A82-24661

SOIL MECHANICS
Investigation of compaction criteria for airport
pavement subgrade soils
[AD-A108518] N82-18230

SOIL MOISTURE
C-5A austere airfield operational utility
evaluation. Phase 2: Operation on unpaved soil
surfaces following rainfall
[AD-A108597] N82-18208

SOLID-SOLID INTERFACES
Diffusion bonding in superplastic
forming/diffusion bonding
A82-23754

SOUND TRANSMISSION
Preliminary thoughts on helicopter cabin noise
prediction methods
N82-18148

SPACE MISSIONS
NASA pocket statistics
[NASA-TM-84134] N82-19084

SPACE TRANSPORTATION
A study of flight control requirements for
advanced, winged, earth-to-orbit vehicles with
far-aft center-of-gravity locations
[NASA-CR-3491] N82-19226

SPACE TUGS
A study of flight control requirements for
advanced, winged, earth-to-orbit vehicles with
far-aft center-of-gravity locations
[NASA-CR-3491] N82-19226

SUBJECT INDEX

STRETCH FORMING

SPACECRAFT CONTROL			
An on board supervisory system for applications in space missions [INPE-2097-RPE/327]	N82-18216	Review of helicopter Mast Mounted Sight (MMS) base motion isolation and Line-of-Sight (LOS) stabilization concepts	N82-18166
SPACECRAFT PERFORMANCE		Mast mounted visual aids	N82-18167
NASA pocket statistics [NASA-TM-84134]	N82-19084	Software features applicable to inertial measurement unit self alignment [AD-A108511]	N82-18196
SPACECRAFT PROPULSION		STANDARDIZATION	
Electric Flight Systems [NASA-CP-2209]	N82-19134	Airworthiness regulation: What is our strategy - What are the issues	A82-24006
Electric flight systems, overview	N82-19135	The challenge of standardizing fatigue methodology	A82-24703
SPACECRAFT STRUCTURES		STANDARDS	
Electroforming of space and aircraft structures [HBB-BE-491-0]	N82-18419	Standardization of helicopter fatigue methodology - A manufacturer's view	A82-24704
SPEED CONTROL		STATIC AERODYNAMIC CHARACTERISTICS	
High speed VSCF generator design consideration --- computer aided design for Variable Speed Constant Frequency generator	A82-24379	The effect of a well on the aerodynamics of a spoiler --- wind tunnel flow visualization and pressure measurement [BU-268]	N82-19194
The effect of critical design parameters on the selection of a VSCF system	A82-24381	STATIC PRESSURE	
Packaging the VSCF system for an aircraft engine environment	A82-24383	Static pressure in the slipstream of a propeller	A82-24023
SPEED INDICATORS		STATIC TESTS	
Evaluation of the helicopter low airspeed system LASSIE	N82-18172	Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine [NAL-TR-687T-PT-2]	N82-19945
SPEED REGULATORS		STATISTICAL ANALYSIS	
Three-engine control system for the prototype EH-101 helicopter [AEBG-9/81-1568L]	N82-18135	Direct comparison of community response to road traffic noise and to aircraft noise	A82-22974
SPIN REDUCTION		FAA statistical handbook of aviation [AD-A109289]	N82-19198
A criterion for the prediction of the recovery characteristics of spinning aircraft [RAE-TN-AERO-2251]	N82-19223	STATOR BLADES	
SPIN STABILIZATION		Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82 [NASA-TP-1974]	N82-19222
Spin-tunnel investigation of a 1/13-scale model of the NASA AL-1 oblique-wing research aircraft [NASA-TM-83236]	N82-18183	STEERING	
SPOILER SLOT ALLERONS		Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20]	A82-24565
Spoilers or auxiliary flaps	A82-24973	STEREOSCOPY	
SPOILERS		Stereographic projection in the National Airspace System	A82-23031
The effect of a well on the aerodynamics of a spoiler --- wind tunnel flow visualization and pressure measurement [BU-268]	N82-19194	STIFFNESS MATRIX	
SPRAY NOZZLES		Modal characteristics of rotor blades: Finite element approach and measurement by ground vibration test	N82-18127
Helicopter Icing Spray System (HISS) nozzle improvement evaluation [AD-A109405]	N82-19208	STOCKPILING	
SQUALLS		Where is cobalt irreplaceable	A82-25538
Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts [HBB-FE-172/S/PUB/39-PT-1]	N82-19228	STORMS (METEOROLOGY)	
STABILITY		Aircraft measurements and analysis of severe storms: 1976 field experiment [NASA-CR-168519]	N82-18803
Effects of fan inlet temperature disturbances on the stability of a turbofan engine [NASA-TM-82699]	N82-18222	STRESS ANALYSIS	
STABILITY AUGMENTATION		Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft	A82-24705
A redundancy concept for a digital CSAS	N82-18170	A compilation of stress intensity factor solutions for flawed fastener holes [AD-A108753]	N82-18628
STABILITY DERIVATIVES		STRESS CONCENTRATION	
Cross and cross-coupling derivative measurements on the standard dynamics model at AEDC [AIAA 82-0596]	A82-24670	Material/structure degradation due to fretting and fretting-initiated fatigue	A82-23771
An experimental study of the effect of tail configuration on the spinning characteristics of general aviation aircraft --- static wind tunnel force measurements [NASA-CR-168578]	N82-19224	STRESS CORROSION CRACKING	
STABILIZATION		A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum	A82-23772
Review of helicopter Mast Mounted Sight (MMS) base motion isolation and Line-of-Sight (LOS) stabilization concepts	N82-18166	STRESS INTENSITY FACTORS	
Integration of inertial sensors in helicopters	N82-18173	A compilation of stress intensity factor solutions for flawed fastener holes [AD-A108753]	N82-18628
STABILIZED PLATFORMS		STRETCH FORMING	
Stability of a three-stage dynamic stand	A82-25353	Problems associated with the quality assurance of stretched acrylic sheet	A82-24319

STRETCHING

SUBJECT INDEX

STRETCHING

Lucas stretched acrylic
A82-24318

STRUCTURAL ANALYSIS

Development of maintenance programmes through the functional, structural and flight test phases
A82-24003

MSG-3 structures --- inspection program for aircraft maintenance
A82-24011

Application of damage tolerance technology to type certification
[SAE PAPER 811062]
A82-24388

Structural modeling of high Reynolds number wind tunnel models
[AIAA 82-0602]
A82-24674

Structural testing of composites with known defects
A82-24708

STRUCTURAL DESIGN

Impact of systems technology and integration on helicopter design
N82-18165

STRUCTURAL DESIGN CRITERIA

Design philosophy of the Hughes model 600 helicopter
N82-18140

SH-608 test program
N82-18141

STRUCTURAL ENGINEERING

Aeronautical Research Laboratories Structures Division
[AD-A109049]
N82-19161

STRUCTURAL FAILURE

D.C.9 windshield - Effect of attachment retorquer
A82-24324

Application of damage tolerance technology to type certification
[SAE PAPER 811062]
A82-24388

Fundamentals of helicopter fatigue life determination
A82-24714

STRUCTURAL RELIABILITY

Windshield system structural enhancement
A82-24312

STRUCTURAL WEIGHT

Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance
[AIAA PAPER 80-0724]
A82-24022

SUBSONIC AIRCRAFT

Tendencies in the development of subsonic transport aircraft with special consideration of aerodynamics
[ESA-TT-705]
N82-18214

SUBSONIC WIND TUNNELS

Status and capabilities of the National Full Scale Facility 40- by 80-foot wind tunnel modification
[AIAA 82-0607]
A82-24676

A new facility and technique for two-dimensional aerodynamic testing
[AIAA 82-0608]
A82-24677

SUPERCRITICAL FLOW

A new facility and technique for two-dimensional aerodynamic testing
[AIAA 82-0608]
A82-24677

SUPERCRITICAL WINGS

Design of supercritical swept wings
A82-23826

Structural modeling of high Reynolds number wind tunnel models
[AIAA 82-0602]
A82-24674

Flutter and time response analyses of three degree of freedom airfoils in transonic flow
[AD-A108987]
N82-19227

SUPERPLASTICITY

Diffusion bonding in superplastic forming/diffusion bonding
A82-23754

Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures
[NASA-CR-165827]
N82-19358

SUPERSONIC AIRCRAFT

Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance
[AIAA PAPER 80-0724]
A82-24022

SUPERSONIC FLOW

Oscillating supersonic/hypersonic wings at high incidence
A82-23828

SUPERSONIC WIND TUNNELS

Mean flow and noise measurements in a Mach 3.5 pilot quiet tunnel
[AIAA 82-0569]
A82-24657

SUPPORT INTERFERENCE

Review of support interference in dynamic tests
[AIAA 82-0594]
A82-24668

SURFACE LAYERS

High-frequency monitoring of surface layers of metals
A82-23603

Electroforming of space and aircraft structures
[MBB-BB-491-0]
N82-18419

SURFACE REACTIONS

Improving the accuracy of the estimates of surfactant content in jet fuels
A82-23250

SURFACE ROUGHNESS

Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels
[AIAA 82-0603]
A82-24675

SURFACE TEMPERATURE

Engine superficial temperature and infrared signature
N82-18136

SURFACE VEHICLES

Direct comparison of community response to road traffic noise and to aircraft noise
A82-22974

SURFACTANTS

Improving the accuracy of the estimates of surfactant content in jet fuels
A82-23250

SWEEP WINGS

Design of supercritical swept wings
A82-23826

Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LFC test
[AIAA 82-0568]
A82-24656

SWEEPBACK WINGS

History of the sweepback wing
[DGLR PAPER 81-070]
A82-22898

Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory
[MBB-FE-122/S/PUB/37]
N82-18189

SYSTEM EFFECTIVENESS

Prediction of off-design performance of turbo-shaft engines a simplified method
N82-18132

Measurement techniques used to assess the installed power of a helicopter engine
N82-18133

Component design and development for future helicopter engines
N82-18134

Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency
N82-19453

SYSTEMS ANALYSIS

Analysis and optimization of control systems in piloted flight vehicles --- Russian book
A82-22398

Analysis of system problems using aviation safety reporting system data
A82-23312

NAS system load - Utilization of the DARC system
A82-23315

Distributed data processing modeling for future ATC systems
A82-23319

A method for the investigation of gyro-stabilization systems
A82-24892

SH-608 test program
N82-18141

A light helicopter for night firing
N82-18144

Task analytic techniques: Application to the design of a flight simulator instructor/operator console
[AD-A108724]
N82-18227

SYSTEMS ENGINEERING

The use of dynamic mock-ups in the design of advanced systems --- USAF's Digital Avionic Information System and NAVY's Advanced Integrated Display System
A82-22902

SUBJECT INDEX

THERMAL STRESSES

- Design technology for improved performance retention in turbfan engines
[SAE PAPER 811055] A82-24392
- A new facility and technique for two-dimensional aerodynamic testing
[AIAA 82-0608] A82-24677
- The influence of sensor and actuator characteristics on overall helicopter APCS design
[AD-A108924] N82-18171
- Transport aircraft cockpit standardization (Federal Aviation regulations part 25)
[AD-A108924] N82-19207
- SYSTEMS INTEGRATION**
- The use of dynamic mock-ups in the design of advanced systems --- USAF's Digital Avionic Information System and NAVY's Advanced Integrated Display System
A82-22902
- The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFPC I/
[SAE PAPER 811036] A82-24398
- Impact of systems technology and integration on helicopter design
N82-18165
- Integration of inertial sensors in helicopters
N82-18173
- Integrated control design techniques
[AD-A108223] N82-18224
- Electric flight systems integration
N82-19150
- National Airspace Data Interchange Network (NADIN) support of Remote Maintenance Monitoring System (RMMS)
[AD-A109125] N82-19160
- T**
- TAIL ASSEMBLIES**
- An experimental study of the effect of tail configuration on the spinning characteristics of general aviation aircraft --- static wind tunnel force measurements
[NASA-CR-168578] N82-19224
- TAKEOFF RUNS**
- A digital simulation program describing the motion of an aircraft undergoing engine failure during its takeoff ground roll
[AD-A108420] N82-18210
- TARGET ACQUISITION**
- Tethered rotorplatforms and their mission potential
N82-18145
- TARGET RECOGNITION**
- Tethered rotorplatforms and their mission potential
N82-18145
- TECHNOLOGICAL FORECASTING**
- ATC automation - A look forward: Technology/architecture
A82-23320
- Fighters - Tomorrow's terminology
A82-23368
- Air transport in the 21st century
A82-24025
- Fighter issues - 2000
[SAE PAPER 811096] A82-24415
- Perspectives for Controlled Weapons Technology: Report of the 90th Helicopter Forum
[MBB-UA-532-80-0] N82-19211
- TECHNOLOGY ASSESSMENT**
- Computer-generated images for simulators - The cost of technology
A82-22881
- Reliable power --- Rolls-Royce aircraft engine designs
A82-24007
- The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFPC I/
[SAE PAPER 811036] A82-24398
- Boeing Vertol fatigue life methodology
A82-24718
- Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s
A82-25324
- Review of defense-related vertical and short takeoff and landing (V/STOL) aircraft programs
[GPO-55-278] N82-18205
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary
[NASA-TM-84149] N82-19170
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views
[NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors
[NASA-TM-84146] N82-19173
- TECHNOLOGY TRANSFER**
- Impact of systems technology and integration on helicopter design
N82-18165
- TECHNOLOGY UTILIZATION**
- Lightweight ATC systems
A82-23321
- Novel approaches to electron beam welding machine utilization
A82-23753
- TELEVISION CAMERAS**
- Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR
[ESA-TT-675] N82-19219
- TEMPERATURE CONTROL**
- Problems associated with the quality assurance of stretched acrylic sheet
A82-24319
- TEMPERATURE DISTRIBUTION**
- Engine superficial temperature and infrared signature
N82-18136
- TEMPERATURE EFFECTS**
- Effects of fan inlet temperature disturbances on the stability of a turbfan engine
[NASA-TM-82699] N82-18222
- TERRAIN ANALYSIS**
- GTD terrain reflection model applied to ILS glide slope --- Geometrical Theory of Diffraction
A82-23027
- TEST FACILITIES**
- Air cooled engine test facilities
A82-24004
- Aerodynamic Testing Conference, 12th, Williamsburg, VA, March 22-24, 1982, Collection of Technical Papers
A82-24651
- Slotted wall test section for automotive aerodynamic test facilities
[AIAA 82-0585] A82-24661
- Evaluation of the North Island A/C crash/rescue training facility
[AD-A108740] N82-18228
- Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data
[PB82-111832] N82-18233
- Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR
[ESA-TT-675] N82-19219
- Acoustic measurements of F100-PW-100 engine operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952
- TEST STANDS**
- Stability of a three-stage dynamic stand
A82-25353
- Further development of the test concept of the ALPHA JET engine LARZAC 04
N82-18223
- TETHERLINES**
- Tethered rotorplatforms and their mission potential
N82-18145
- THEOREMS**
- A study of the techniques of dynamic analysis of helicopter type structures
N82-18129
- THERMAL EXPANSION**
- Operating flight loads and their effect on engine performance
[SAE PAPER 811071] A82-24405
- THERMAL INSULATION**
- The use of 'Kapton' polyimide film in aerospace applications
[SAE PAPER 811091] A82-24413
- THERMAL STRESSES**
- Acoustic fatigue endurance test of USB flap structure models at elevated temperature
[NAL-TR-683] N82-19570

THERMODYNAMIC EFFICIENCY

Lineup of the IM-series aircraft-derivative gas turbines A82-22896

THIN FILMS
High-frequency monitoring of surface layers of metals A82-23603

THREE DIMENSIONAL BOUNDARY LAYER
Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory [MBB-FE-122/S/PUB/37] N82-18189

THREE DIMENSIONAL FLOW
Transonic wind tunnel wall interference corrections for three-dimensional models [AIAA 82-0588] A82-24663
Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles A82-25347
A three-dimensional approach to lift and moment coefficients of rotating blades N82-18125
On the calculation of transonic blade tip flow for helicopter rotors [MBB-UD-320-81-0] N82-18187

THREE DIMENSIONAL MOTION
Wide field of view laser beacon system for three-dimensional aircraft position measurement [ASME PAPER 81-WA/DSC-9] A82-24563

THRUST AUGMENTATION
XFV-12A diagnostic and development programs [AD-A108354] N82-18206

THRUST CONTROL
Potential reductions in aircraft operation and maintenance costs by using thrust computing support equipment [AD-A108463] N82-18207

THRUST MEASUREMENT
Potential reductions in aircraft operation and maintenance costs by using thrust computing support equipment [AD-A108463] N82-18207

THRUST VECTOR CONTROL
Fighters - Tomorrow's terminology A82-23368

TILT ROTOR AIRCRAFT
NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 3: Aerodynamics and Structures Session [NASA-TM-84147] N82-19172

TIME DIVISION MULTIPLEXING
A design for a 32-channel multiplexer --- for unmanned aircraft navigation sensors [RAE-TM-R&D-NAV-145] N82-18503

TIMING DEVICES
Global positioning system timing receivers in the DSN N82-20126

TITANIUM ALLOYS
Welding for low-cost advanced titanium airframe structures A82-23757
Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures [NASA-CR-165827] N82-19358

TOPOGRAPHY
Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels [AIAA 82-0603] A82-24675

TORQUE
D.C.9 windshield - Effect of attachment retorque A82-24324
Dynamics of aircraft antiskid braking systems --- conducted at the Langley aircraft landing loads and traction facility [NASA-TP-1959] N82-18204

TRACKED VEHICLES
The Link-Hiles driver training simulator for tracked vehicles: The effect of method and duration of training on the transfer of training [IZF-1980-28] N82-18226

TRACKING (POSITION)
Analysis of a nonlinear altitude tracking method [AD-A108878] N82-19197

TRACKING NETWORKS

On the calculation of separated flow on helicopter fuselages [MBB-UD-321-81-0] N82-18188

TRAILING-EDGE FLAPS
Slotted variable camber flap [NASA-CASE-LAR-12541-1] N82-18203

TRAINING AIRCRAFT
Disengagement of safety harness buckles - CT4 [AD-A109048] N82-19199

TRAINING DEVICES
Task analytic techniques: Application to the design of a flight simulator instructor/operator console [AD-A108724] N82-18227

TRAINING EVALUATION
Evaluation of the North Island A/C crash/rescue training facility [AD-A108740] N82-18228

TRAINING SIMULATORS
Computer-generated images for simulators - The cost of technology A82-22881
The Link-Hiles driver training simulator for tracked vehicles: The effect of method and duration of training on the transfer of training [IZF-1980-28] N82-18226

TRAJECTORY OPTIMIZATION
Methodology for multi-aircraft minimum noise impact landing trajectories A82-23037
Optimal aircraft landing patterns for minimal noise impact N82-19200

TRANSFER OF TRAINING
The Link-Hiles driver training simulator for tracked vehicles: The effect of method and duration of training on the transfer of training [IZF-1980-28] N82-18226

TRANSHORIZON RADIO PROPAGATION
Beyond the horizon coverage for air navigation/traffic control A82-24647

TRANSONIC COMPRESSORS
Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82 [NASA-TP-1974] N82-19222

TRANSONIC FLOW
Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LFC test [AIAA 82-0568] A82-24656
On the calculation of transonic blade tip flow for helicopter rotors [MBB-UD-320-81-0] N82-18187
Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts [NASA-CR-165852] N82-19167
Flutter and time response analyses of three degree of freedom airfoils in transonic flow [AD-A108987] N82-19227

TRANSONIC FLUTTER
Recent developments in wing with stores flutter suppression [ONERA, TP NO. 1981-145] A82-24077

TRANSONIC WIND TUNNELS
The effect of ejector augmentation on test-section flow quality in the Calspan 8-ft transonic wind tunnel [AIAA 82-0571] A82-24658
Transonic wind tunnel wall interference corrections for three-dimensional models [AIAA 82-0588] A82-24663
Development of a self-optimizing flexible technology /SOFT/ transonic wind tunnel model [AIAA 82-0601] A82-24673
Structural modeling of high Reynolds number wind tunnel models [AIAA 82-0602] A82-24674
Induction driven transonic wind tunnel T2: Operation at room temperature and cryogenic adaptation N82-19158

TRANSPARENCY
Conference on Aerospace Transparencies, London, England, September 8-10, 1980, Proceedings A82-24301

SUBJECT INDEX

UPPER SURFACE BLOWING

- Transparency development needs for military aircraft in the 1980's A82-24302
- Deficiencies and constraints that affect the design of cockpit enclosures and transparencies A82-24303
- Transparencies - What an aircraft designer should know A82-24305
- Transparency design decisions - Assessing their impact on visual performance A82-24306
- Aircraft transparency design guide A82-24307
- A new angular deviation measurement device for aircraft transparencies A82-24308
- Portable transparency optical test system /P-TOTS/ A82-24309
- Abrasion resistant coated plastic products for aircraft A82-24310
- Proposed method for abrasion testing transparent plastics and coatings A82-24311
- Windshield system structural enhancement A82-24312
- The role of finite element analysis in the design of birdstrike resistant transparencies A82-24314
- Aircraft transparency bird impact analysis using the MAGNA computer program A82-24315
- Acrylic - A timely review A82-24317
- Lucas stretched acrylic A82-24318
- The effects of absorbed moisture upon the physical properties of stretched acrylic materials A82-24320
- TRANSPORT AIRCRAFT**
- Reliability centered maintenance /RCM/ A82-24001
- Fuel-efficient windshields for transport, commuter and business aircraft A82-24304
- Airworthiness considerations in the design of commercial transport aircraft [SAE PAPER 811039] A82-24396
- Aircraft surface coatings for drag reduction/erosion protection [SAE PAPER 811070] A82-24401
- The cargo helicopter - A logistical vehicle A82-24717
- Advanced electronic displays and their potential in future transport aircraft A82-25216
- Laminar airfoils for transport aircraft [ESA-TT-680] N82-18190
- C-5A austere airfield operational utility evaluation. Phase 2: Operation on unpaved soil surfaces following rainfall [AD-A108597] N82-18208
- Tendencies in the development of subsonic transport aircraft with special consideration of aerodynamics [ESA-TT-705] N82-18214
- Transport aircraft cockpit standardization (Federal Aviation regulations part 25) [AD-A108924] N82-19207
- Simulator study of vortex encounters by a twin-engine, commercial, jet transport airplane [NASA-TP-1966] N82-19225
- TRAVELING WAVES**
- Antenna (selected articles) [AD-A108174] N82-19448
- Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency N82-19453
- TRENDS**
- Trends in airline avionics [NLR-MP-80013-U] N82-18220
- TRUCKS**
- Vehicle test report: Patronic pickup truck [NASA-CR-168637] N82-19205
- TURBINE BLADES**
- Seventh European Rotorcraft and Powered Lift Aircraft Forum N82-18119
- TURBINE ENGINES**
- Cooled variable-area radial turbine technology program [NASA-CR-165408] N82-19221
- TURBINE EXHAUST NOZZLES**
- Prediction of off-design performance of turbo-shaft engines a simplified method N82-18132
- TURBOFAN AIRCRAFT**
- A study to define the research and technology requirements for advanced turbo/propfan transport aircraft [NASA-CR-166138] N82-18202
- TURBOFAN ENGINES**
- Design technology for improved performance retention in turbofan engines [SAE PAPER 811055] A82-24392
- Management of powerplant maintenance and restoration programs for fuel conservation [SAE PAPER 811052] A82-24394
- Operating flight loads and their effect on engine performance [SAE PAPER 811071] A82-24405
- Performance retention features of the PW2037 [SAE PAPER 811054] A82-24409
- A study to define the research and technology requirements for advanced turbo/propfan transport aircraft [NASA-CR-166138] N82-18202
- Effects of fan inlet temperature disturbances on the stability of a turbofan engine [NASA-TN-82699] N82-18222
- Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine [NAL-TR-687T-PT-2] N82-19945
- TURBOJET ENGINES**
- Low grade fuels for turbo and jet engines A82-23439
- TURBOPROP AIRCRAFT**
- Engine superficial temperature and infrared signature N82-18136
- A study to define the research and technology requirements for advanced turbo/propfan transport aircraft [NASA-CR-166138] N82-18202
- TURBOPROP ENGINES**
- Engine superficial temperature and infrared signature N82-18136
- A study to define the research and technology requirements for advanced turbo/propfan transport aircraft [NASA-CR-166138] N82-18202
- TURBOSHAFTS**
- Prediction of off-design performance of turbo-shaft engines a simplified method N82-18132
- Measurement techniques used to assess the installed power of a helicopter engine N82-18133
- TURBULENT JETS**
- Complete velocity profile and 'optimum' skin friction formulas for the plane wall-jet [ASME PAPER 81-WA/FE-3] A82-24566
- TURNING FLIGHT**
- Efficient combinations of numerical techniques applied to aircraft turning performance optimization A82-24814
- Midair and near midair collisions on two- and three-dimensional curvilinear flight paths [ESA-TT-685] N82-18200
- U**
- UNSTEADY FLOW**
- Angle of downwash behind a wing in unsteady flow A82-24970
- Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles A82-25347
- UPPER SURFACE BLOWING**
- Acoustic fatigue endurance test of USB flap structure models at elevated temperature [NAL-TR-683] N82-19570

USER MANUALS (COMPUTER PROGRAMS)

- Rotorcraft flight simulation computer program C81 with DATAMAP interface. Volume 2: Programmer's manual
[AD-A108294] N82-18231
- USER REQUIREMENTS**
Military requirements: Too little or too much
N82-18138
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 1: Executive Summary
[NASA-TM-84149] N82-19170
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 2: Operators' Views
[NASA-TM-84148] N82-19171
- NASA/HAA Advanced Rotorcraft Technology and Tilt Rotor Workshops. Volume 4: Flight Control Avionics Systems and Human Factors
[NASA-TM-84146] N82-19173

V

V/STOL AIRCRAFT

- The design of a wind tunnel VSTOL fighter model incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154

VANES

- Hover tests of a model H-force rotor
N82-18159

VARIABLE SWEEP WINGS

- Mission-adaptive wing flight demonstration program
[SAE PAPER 811035] A82-24399

VELOCITY DISTRIBUTION

- Complete velocity profile and 'optimum' skin friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3] A82-24566

VELOCITY ERRORS

- The application of NAVSTAR differential GPS in the civilian community
A82-24645

VERTICAL AIR CURRENTS

- Aircraft measurements and analysis of severe storms: 1976 field experiment
[NASA-CR-168519] N82-18803

VERTICAL FLIGHT

- Prediction of blade vortex interaction noise from measured blade pressure
N82-18147

VERTICAL TAKEOFF

- A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491] N82-19226

VERTICAL TAKEOFF AIRCRAFT

- Review of defense-related vertical and short takeoff and landing (V/STOL) aircraft programs
[GPO-55-278] N82-18205

VERY HIGH FREQUENCY RADIO EQUIPMENT

- FM broadcast interference related to airborne ILS, VOR and VHF communications
[RTCA/DO-176] N82-19419
- Investigation of the effects of airborne installation factors on receiver interference
N82-19422

VHF OMNIRANGE NAVIGATION

- FM broadcast interference related to airborne ILS, VOR and VHF communications
[RTCA/DO-176] N82-19419
- Investigation of technical requirements
N82-19420
- Investigation of airborne VHF communication and navigation equipment
N82-19421

VIBRATION

- Vibration levels in Army helicopters: Measurement recommendations and data
[AD-A108131] N82-18209

VIBRATION DAMPING

- Oscillations and vibrations of aircraft on runways
A82-24974
- Review of helicopter Mast Mounted Sight (MMS) base motion isolation and Line-of-Sight (LOS) stabilization concepts
N82-18166

VIBRATION EFFECTS

- Hypothetical fatigue life problem - Application of Aerospace method
A82-24716

VIBRATION ISOLATORS

- The measurement of the mobility of structures at acoustic frequencies
N82-18149

VIBRATION MEASUREMENT

- Vibration levels in Army helicopters: Measurement recommendations and data
[AD-A108131] N82-18209

- Structural system identification technology verification
[AD-A109181] N82-19583

VIBRATION TESTS

- Lineup of the IM-series aircraft-derivative gas turbines
A82-22896
- Modal characteristics of rotor blades: Finite element approach and measurement by ground vibration test
N82-18127

- Vibration levels in Army helicopters: Measurement recommendations and data
[AD-A108131] N82-18209

VIBRATORY LOADS

- Mast mounted visual aids
N82-18167

VIDEO EQUIPMENT

- Mast mounted visual aids
N82-18167

VISCOUS FLOW

- Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles
A82-25347

VISIBILITY

- Deficiencies and constraints that affect the design of cockpit enclosures and transparencies
A82-24303
- Transparency design decisions - Assessing their impact on visual performance
A82-24306

VISORS

- Concorde glazings - 5 years of Mach 2 service
A82-24326

VISUAL AIDS

- Mast mounted visual aids
N82-18167
- Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility
N82-18168

VISUAL FLIGHT

- Midair and near midair collisions on two- and three-dimensional curvilinear flight paths
[ESA-TT-685] N82-18200

VISUAL PERCEPTION

- Transparency design decisions - Assessing their impact on visual performance
A82-24306

VOICE COMMUNICATION

- Voice communications - The vital link
A82-23324

VOLTAGE GENERATORS

- Design considerations of DC-Link aircraft generation systems
A82-24377
- Evolution and development of high voltage /270 volt/ dc aircraft electric systems in the United States
A82-24382

VORTEX SHEETS

- A method of predicting fuselage loads in hover
N82-18164

VORTICES

- The requirements for reduced IFR separations on final approach
A82-23311
- Prediction of blade vortex interaction noise from measured blade pressure
N82-18147
- Optimum performance and wake geometry of co-axial rotor in hover
N82-18156
- A numerical approach to co-axial rotor aerodynamics
N82-18157
- Helicopter rotor downwash: Results of experimental research at the DFVLR-rotor test stand and their comparison with theoretical results
N82-18158

Simulator study of vortex encounters by a
twin-engine, commercial, jet transport airplane
[NASA-TP-1966] N82-19225

W

WALL FLOW

Transonic wind tunnel wall interference
corrections for three-dimensional models
[AIAA 82-0588] A82-24663

WALL JETS

Complete velocity profile and 'optimum' skin
friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3] A82-24566

WALL PRESSURE

The pressure signature method for blockage
corrections, and its applications to the
industrial wind tunnel
[BU-263] N82-19231

WARNING SYSTEMS

AN/ALQ-135 tail warning system follow-on
operational test and evaluation
[AD-A108348] N82-18471

WASTE ENERGY UTILIZATION

Open-cycle vapor compression heat pump
[PB82-110503] N82-18553

WATER

Improving the accuracy of the estimates of
surfactant content in jet fuels
A82-23250

WEAPON SYSTEMS

F/A-18 weapon system development
A82-23774

Future strike fighter options - Concepts and
technologies
[SAE PAPER 811099] A82-24403

Fighter issues - 2000
[SAE PAPER 811096] A82-24415

Naval versions of the Dauphin and the AS 15 TT
weapon system
N82-18142

A light helicopter for night firing
N82-18144

WEAPONS DEVELOPMENT

F/A-18 weapon system development
A82-23774

WEAR TESTS

Monitoring engine wear by oil analysis
A82-24012

Proposed method for abrasion testing transparent
plastics and coatings
A82-24311

WEIGHT REDUCTION

Minimum mass sizing of a large low-aspect ratio
airframe for flutter-free performance
[AIAA PAPER 80-0724] A82-24022

Fuel-efficient windshields for transport, commuter
and business aircraft
A82-24304

The development of high strength light-weight
windshields for the new generation of Boeing 757
and 767 airliners
A82-24323

Advanced generating system technology
A82-24380

WEIGHTING FUNCTIONS

Noise measurements on the helicopter BK 117
design. Weighted noise levels and influence of
airspeed
[DFVLR-MITT-81-18] N82-19957

WELDABILITY

Aluminum and its alloys - Weldability
A82-23755

WELDED STRUCTURES

Welding for low-cost advanced titanium airframe
structures
A82-23757

WELDING

Welding technology for the aerospace industry;
Proceedings of the Conference, Las Vegas, NV,
October 7, 8, 1980
A82-23751

WELDING MACHINES

Novel approaches to electron beam welding machine
utilization
A82-23753

WHEEL BRAKES

Dynamics of aircraft antiskid braking systems ---
conducted at the Langley aircraft landing loads
and traction facility
[NASA-TP-1959] N82-18204

WIND MEASUREMENT

Wind and temperature database for flight planning
[SAE PAPER 811068] A82-24385

WIND SHEAR

Development of a clear air radar to detect
meteorological hazards at airports
[AD-A108236] N82-18835

WIND TUNNEL APPARATUS

The effect of ejector augmentation on test-section
flow quality in the Calspan 8-ft transonic wind
tunnel
[AIAA 82-0571] A82-24658

An ejector augmented choking valve for the
metering and control of inlet and bleed duct flows
[AIAA 82-0575] A82-24659

Status and capabilities of the National Full Scale
Facility 40- by 80-foot wind tunnel modification
[AIAA 82-0607] A82-24676

WIND TUNNEL CALIBRATION

The pressure signature method for blockage
corrections, and its applications to the
industrial wind tunnel
[BU-263] N82-19231

WIND TUNNEL MODELS

Cross and cross-coupling derivative measurements
on the standard dynamics model at AEDC
[AIAA 82-0596] A82-24670

Development of a self-optimizing flexible
technology /SOFT/ transonic wing wind tunnel model
[AIAA 82-0601] A82-24673

Structural modeling of high Reynolds number wind
tunnel models
[AIAA 82-0602] A82-24674

Evaluation of methods for characterizing surface
topography of models for high Reynolds number
wind-tunnels
[AIAA 82-0603] A82-24675

The design of a wind tunnel VSTOL fighter model
incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154

Effects of installation of F101 DPE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TN-83250] N82-19181

WIND TUNNEL NOZZLES

Mean flow and noise measurements in a Mach 3.5
pilot quiet tunnel
[AIAA 82-0569] A82-24657

WIND TUNNEL STABILITY TESTS

Review of support interference in dynamic tests
[AIAA 82-0594] A82-24668

WIND TUNNEL TESTS

History of the sweptback wing
[DGLR PAPER 81-070] A82-22898

Recent developments in wing with stores flutter
suppression
[ONERA, TP NO. 1981-145] A82-24077

Aerodynamic Testing Conference, 12th,
Williamsburg, VA, March 22-24, 1982, Collection
of Technical Papers
A82-24651

Numerical design of the contoured wind-tunnel
liner for the NASA swept-wing LPC test
[AIAA 82-0568] A82-24656

Technical innovations in testing and analysis of
heat and pressure models in hypersonic wind
tunnels
[AIAA 82-0578] A82-24660

Slotted wall test section for automotive
aerodynamic test facilities
[AIAA 82-0585] A82-24661

The use of a multi-degree-of-freedom dual balance
system to measure cross and cross-coupling
derivatives
[AIAA 82-0595] A82-24669

Separated flow around helicopter bodies
N82-18163

Evaluation of the helicopter low airspeed system
LASSIE
N82-18172

Spin-tunnel investigation of a 1/13-scale model of
the NASA AD-1 oblique-wing research aircraft
[NASA-TN-83236] N82-18183


- Multiple ejection effects analysis
[AD-A108277] N82-18192
- Effects of installation of F101 DFE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TM-83250] N82-19181
- On the design of some airfoils for sailplane
application --- additions to existing wings for
inflight testing
[VTH-LR-326] N82-19213
- An experimental study of the effect of tail
configuration on the spinning characteristics of
general aviation aircraft --- static wind tunnel
force measurements
[NASA-CR-168578] N82-19224
- A study of flight control requirements for
advanced, winged, earth-to-orbit vehicles with
far-aft center-of-gravity locations
[NASA-CR-34911] N82-19226
- WIND TUNNEL WALLS**
- Transonic wind tunnel wall interference
corrections for three-dimensional models
[AIAA 82-0588] A82-24663
- The pressure signature method for blockage
corrections, and its applications to the
industrial wind tunnel
[BU-263] N82-19231
- WINDMILLS (WINDPOWERED MACHINES)**
- An extension of the local momentum theory to the
rotors operating in twisted flow field
N82-18123
- Modal characteristics of rotor blades: Finite
element approach and measurement by ground
vibration test
N82-18127
- WINDSHIELDS**
- Conference on Aerospace Transparencies, London,
England, September 8-10, 1980, Proceedings
A82-24301
- Transparency development needs for military
aircraft in the 1980's
A82-24302
- Deficiencies and constraints that affect the
design of cockpit enclosures and transparencies
A82-24303
- Fuel-efficient windshields for transport, commuter
and business aircraft
A82-24304
- Transparencies - What an aircraft designer should
know
A82-24305
- Aircraft transparency design guide
A82-24307
- A new angular deviation measurement device for
aircraft transparencies
A82-24308
- Proposed method for abrasion testing transparent
plastics and coatings
A82-24311
- Windshield system structural enhancement
A82-24312
- The role of finite element analysis in the design
of birdstrike resistant transparencies
A82-24314
- The development of high strength light-weight
windshields for the new generation of Boeing 757
and 767 airliners
A82-24323
- D.C.9 windshield - Effect of attachment retorquer
A82-24324
- B.A.C. One-Eleven flight deck glazing product
improvement
A82-24325
- Concorde glazings - 5 years of Mach 2 service
A82-24326
- WING CAMBER**
- Slotted variable camber flap
[NASA-CASE-LAR-12541-1] N82-18203
- WING FLAPS**
- Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945
- WING LOADING**
- Structural modeling of high Reynolds number wind
tunnel models
[AIAA 82-0602] A82-24674
- Some unsteady aerodynamic effects on helicopter
rotors
N82-18162
- WING NACELLE CONFIGURATIONS**
- Transonic perturbation analysis of
wing-fuselage-nacelle-pylon configurations with
powered jet exhausts
[NASA-CR-165852] N82-19167
- WING OSCILLATIONS**
- Oscillating supersonic/hypersonic wings at high
incidence
A82-23828
- Recent developments in wing with stores flutter
suppression
[ONERA, TP NO. 1981-145] A82-24077
- Application of the ONERA dynamic stall model to a
helicopter blade in forward flight
N82-18161
- WING PLANFORMS**
- YF-16 design concept and philosophy
A82-23444
- WING PROFILES**
- Mission-adaptive wing flight demonstration program
[SAE PAPER 811035] A82-24399
- Transonic wind tunnel wall interference
corrections for three-dimensional models
[AIAA 82-0588] A82-24663
- Development of a self-optimizing flexible
technology /SOFT/ transonic wing wind tunnel model
[AIAA 82-0601] A82-24673
- Structural modeling of high Reynolds number wind
tunnel models
[AIAA 82-0602] A82-24674
- WING SLOTS**
- Slotted variable camber flap
[NASA-CASE-LAR-12541-1] N82-18203
- WING TIPS**
- Hover tests of a model H-force rotor
N82-18159
- An analytical investigation of the free-tip rotor
for helicopters
[NASA-TM-81345] N82-18179
- On the design of some airfoils for sailplane
application --- additions to existing wings for
inflight testing
[VTH-LR-326] N82-19213
- WINGS**
- Angle of downwash behind a wing in unsteady flow
A82-24970
- XFV-12A diagnostic and development programs
[AD-A108354] N82-18206
- WIRE CLOTH**
- Metal honeycomb to porous wireform substrate
diffusion bond evaluation
[NASA-TM-82793] N82-18612
- WIRING**
- The variation of induced currents in aircraft wiring
A82-24355
- WORKLOADS (PSYCHOPHYSIOLOGY)**
- Combined multisensor displays --- image
preprocessing for shape coding to reduce pilot
workload
A82-22905
- Utilizing the helicopter's versatility to improve
the ATC system
A82-23316

PERSONAL AUTHOR INDEX

AERONAUTICAL ENGINEERING/A Continuing Bibliography (Suppl 149)

JUNE 1982

Typical Personal Author Index Listing



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document cited (e.g., NASA report, translation, NASA contractor report). The accession number is located beneath and to the right of the title, e.g., N82-11514. Under any one author's name the accession numbers are arranged in sequence with the /AA accession numbers appearing first.

A

- ABBINK, P. J.**
Trends in airline avionics
[NLR-MP-80013-U] N82-18220
- ABDELWAHAB, M.**
Effects of fan inlet temperature disturbances on the stability of a turbofan engine
[NASA-TM-82699] N82-18222
- ABELLA, E. L.**
The toll of ILS-preventable aviation accidents
A82-25325
- AGARWAL, J. C.**
Where is cobalt irreplaceable
A82-25538
- AHLSTEDT, M.**
Collection and evaluation of propeller aircraft noise certification data
[DPVLR-MITT-81-20] N82-19958
- ALDINIO, G.**
The Agusta's solution of AHS's hypothetical fatigue life problem
A82-24701
- ALGER, R. S.**
Evaluation of the North Island A/C crash/rescue training facility
[AD-A108740] N82-18228
- ALLAVEHA, A. M.**
Engine superficial temperature and infrared signature
N82-18136
- ALLI, P.**
The Agusta's solution of AHS's hypothetical fatigue life problem
A82-24701
- ALLISON, J. W.**
Airline fuel saving through JT9D engine refurbishment
[SAE PAPER 811051] A82-24395
- ALTMAN, B.**
The challenge of standardizing fatigue methodology
A82-24703
- ANDERS, K. P.**
Noise measurements on the helicopter BK 117 design. Weighted noise levels and influence of airspeed
[DPVLR-MITT-81-18] N82-19957
- Collection and evaluation of propeller aircraft noise certification data
[DPVLR-MITT-81-20] N82-19958

- ANDERSON, E. C.**
Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LFC test
[AIAA 82-0568] A82-24656
- ANDREWS, D. G.**
Slotted variable camber flap
[NASA-CASE-LAR-12541-1] N82-18203
- ANTONAZZI, P., SR.**
Pressure transducer calibration process
[SAE PAPER 811076] A82-24408
- ARENDT, R. H.**
Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data
[PB82-111832] N82-18233
- ARVIN, G. H.**
Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures
[NASA-CR-165827] N82-19358
- ASCHENBACH, J. W.**
Reducing reflections on the front surface of air traffic control displays
A82-23314
- AZUMA, A.**
An extension of the local momentum theory to the rotors operating in twisted flow field
N82-18123
- A numerical approach to co-axial rotor aerodynamics
N82-18157

B

- BAER, J. C.**
Restoration of performance, Models 727, 737, and 747
[SAE PAPER 811072] A82-24406
- BAILEY, R. O.**
The design of a wind tunnel VSTOL fighter model incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154
- BAKER, S. M.**
Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels
[AIAA 82-0603] A82-24675
- BALLIN, M. G.**
An experimental study of the effect of tail configuration on the spinning characteristics of general aviation aircraft
[NASA-CR-168578] N82-19224
- BARAN, Y.**
Fixed gain controller design for aircraft
A82-23441
- BASH, J.**
Calculation and measurement of electric field strength for airborne antennas in the LF/MF range
A82-25011
- BASKERVILLE, M. W.**
Materials aspects of aircraft EMC design
A82-24358
- BAUMEISTER, K. J.**
Influence of exit impedance on finite difference solutions of transient acoustic mode propagation in ducts
[ASME PAPER 81-WA/NCA-13] A82-24602
- BAVITZ, P. C.**
Future strike fighter options - Concepts and technologies
[SAE PAPER 811099] A82-24403
- BEARD, M. C.**
Airworthiness regulation: What is our strategy - What are the issues
A82-24006
- BECKER, P. E.**
Open-cycle vapor compression heat pump
[PB82-110503] N82-18553

- BECKER, J.**
Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts
[MBB-PE-172/S/PUB/39-PT-1] N82-19228
- BECKWITH, I. E.**
Mean flow and noise measurements in a Mach 3.5 pilot quiet tunnel
[AIAA 82-0569] A82-24657
- BEDDOES, J. C.**
A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum A82-23772
- BREDELL, D. A. E.**
Design study into a high endurance mini-rotorcraft [BU-265] N82-19216
- BEIN, T. W.**
Foundations for computer simulation of a low pressure oil flooded single screw air compressor [AD-A108230] N82-19391
- BELL, D. B.**
Lucas stretched acrylic A82-24318
- BELTE, D.**
Helicopter Icing Spray System (HISS) nozzle improvement evaluation [AD-A109405] N82-19208
- BERKEBILE, D. H.**
The use of 'Kapton' polyimide film in aerospace applications [SAE PAPER 811091] A82-24413
- BERMAN, A.**
Structural system identification technology verification [AD-A109181] N82-19583
- BESER, J.**
The application of NAVSTAR differential GPS in the civilian community A82-24645
- BEVILAKUA, P. M.**
XFV-12A diagnostic and development programs [AD-A108354] N82-18206
- BEYER, R.**
Experimental investigation of visual aids for helicopters: Low level flight at night and poor visibility N82-18168
- BEZIAC, G.**
Parametric study of the influence of the engine upon the operating cost of a civil helicopter N82-18131
- BIERTUENPEL, E.**
Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR [ESA-TT-675] N82-19219
- BIGHAM, J.**
Electromechanical actuators N82-19148
- BILLMANN, B. E.**
Analysis of a nonlinear altitude tracking method [AD-A108878] N82-19197
- BIRNIE, S. E.**
Direct comparison of community response to road traffic noise and to aircraft noise A82-22974
- BLANK, D.**
Efficient combinations of numerical techniques applied to aircraft turning performance optimization A82-24814
- BOCCADORO, C. B.**
An ejector augmented choking valve for the metering and control of inlet and bleed duct flows [AIAA 82-0575] A82-24659
- BOERNHANS, L. M. H.**
On the design of some airfoils for sailplane application [VTH-LR-326] N82-19213
- BONITCH, R.**
Lightweight ATC systems A82-23321
- BONNATERRE, R.**
Recent improvements in aircraft N₁-Cd cells A82-24245
- BOON, D. J.**
A study of the techniques of dynamic analysis of helicopter type structures N82-18129
- BORGER, J. G.**
Maintenance objectives for future aircraft A82-24005
- BORRI, M.**
A general purpose program for rotor blade dynamics N82-18151
- BOULET, J.**
Point of view of a helicopter manufacturer on airworthiness regulations N82-18137
- BOWMAN, J. S., JR.**
Spin-tunnel investigation of a 1/13-scale model of the NASA AD-1 oblique-wing research aircraft [NASA-TN-83236] N82-18183
- BRABSTON, W. H.**
Investigation of compaction criteria for airport pavement subgrade soils [AD-A108518] N82-18230
- BRETTLE, J.**
Materials aspects of aircraft EMC design A82-24358
- BREUHAUS, W. O.**
C-5A austere airfield operational utility evaluation. Phase 2: Operation on unpaved soil surfaces following rainfall [AD-A108597] N82-18208
- BRITTON, K. H.**
A-7E software module guide [AD-A108649] N82-18920
- BROGAN, W. L.**
Improvements and extensions of the Geometrical Dilution of Precision (GDOP) concept for selecting navigation measurements [AD-A108607] N82-18197
- BROWN, R. A.**
Concorde glazings - 5 years of Mach 2 service A82-24326
- BRUDNYY, E. O.**
Assessment of aircraft capacitive circuit medium wave antennas according to their efficiency N82-19453
- BRUERE, A.**
Electrical ground testing of aircraft antistatic protection N82-19156
- BUNJE, A. J.**
Proposed method for abrasion testing transparent plastics and coatings A82-24311
- BURCAT, A.**
Low grade fuels for turbo and jet engines A82-23439
- BURTON, R. W.**
Analysis of the crossed dipole antenna as a model for aircraft in an electromagnetic environment A82-25002
- BURTON, T. D.**
Describing function analysis of nonlinear nose gear shimmy [ASME PAPER 81-WA/DSC-20] A82-24565

C

- CABREIT, P.**
Parametric study of the influence of the engine upon the operating cost of a civil helicopter N82-18131
- CALDWELL, J. D.**
Analytical study of cockpit information requirements [AD-A108524] N82-18218
- CANNARATA, S.**
Distributed intelligence for air fleet control [AD-A108611] N82-18195
- CAMPBELL, W. C.**
Development of a clear air radar to detect meteorological hazards at airports [AD-A108236] N82-18835
- CANDA, J. P.**
A light helicopter for night firing N82-18144
- CANTRELL, W. G.**
Software features applicable to inertial measurement unit self alignment [AD-A108511] N82-18196

- CABEL, O.
The birth of precision DME
N82-24066
- CARLSON, J. R.
Effects of installation of F101 DFE exhaust
nozzles on the afterbody-nozzle characteristics
of the F-14 airplane
[NASA-TN-83250] N82-19181
- CARMINE, W. A.
Cost of ownership advantages with a shared oil
system
N82-24378
- CARRIERE, J. K.
Performance retention features of the PW2037
[SAE PAPER 811054] N82-24409
- CARROLL, H. R.
Technical innovations in testing and analysis of
heat and pressure models in hypersonic wind
tunnels
[AIAA 82-0578] N82-24660
- CASPARI, M.
Improvement of fuel economy by flying with maximum
rearward center-of-gravity positioning
N82-23470
- CASTERL, G. R.
Multiple ejection effects analysis
[AD-A108277] N82-18192
- CEHN, H. A.
The effect of a well on the aerodynamics of a
spoiler
[BU-268] N82-19194
- CERNOSEK, J.
Fatigue test of the typical main rotor controls
component
N82-24715
- CHABANNE, J. P.
Importance of a tactical cargo aircraft in
emergency relief
N82-25499
- CHADWICK, R. B.
Development of a clear air radar to detect
meteorological hazards at airports
[AD-A108236] N82-18835
- CHALLITA, A.
The effects of bird orientation on load profile
and damage level
N82-24316
- CHANG, R.
Methodology for multi-aircraft minimum noise impact
landing trajectories
N82-23037
- CHANG, R. C. T.
Optimal aircraft landing patterns for minimal
noise impact
N82-19200
- CHAPMAN, D.
A program testing assistant
[AD-A108147] N82-18922
- CHEESEMAN, I. C.
Developments in rotary wing aircraft aerodynamics
N82-18120
Wind tunnel investigation of high speed rotor noise
N82-18146
- CHEN, C. H.
Flutter and time response analyses of three degree
of freedom airfoils in transonic flow
[AD-A108987] N82-19227
- CHINN, J. H.
Acoustic measurements of F100-PW-100 engine
operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952
- CHIUCHIOLO, E. A.
Three-engine control system for the prototype
EH-101 helicopter
[AEBG-9/81-1568L] N82-18135
- CHRISTENSEN, J.
D.C.9 windshield - Effect of attachment retorque
N82-24324
- CHUDYK, D. W.
The effect of ejector augmentation on test-section
flow quality in the Calspan 8-ft transonic wind
tunnel
[AIAA 82-0571] N82-24658
- CLARK, P. J. P.
Slotted wall test section for automotive
aerodynamic test facilities
[AIAA 82-0585] N82-24661
- CLAY, C. W.
Electric flight systems
N82-19144
- CLEMENTS, P. A.
Global positioning system timing receivers in the
DSN
N82-20126
- CLOUD, W. W.
Evolution and development of high voltage /270
volt/ dc aircraft electric systems in the United
States
N82-24382
- COLLINGS, W. Z.
Review of defense-related vertical and short
takeoff and landing (V/STOL) aircraft programs
[GPO-55-278] N82-18205
- COLLINS, A. G.
BB 211 powerplant deterioration - Review of
current situation and lessons learned
[SAE PAPER 811053] N82-24393
- COLLINS, B. P.
A concept for a fuel efficient flight planning aid
for general aviation
[NASA-CR-3533] N82-19217
- COMBS, C. P.
XFV-12A diagnostic and development programs
[AD-A108354] N82-18206
- COOK, G.
Methodology for multi-aircraft minimum noise impact
landing trajectories
N82-23037
- COOKSEY, D. L.
Bomb crater repair techniques for permanent
airfields. Report 1: Series 1 tests
[AD-A108716] N82-18229
- COULTER, S. M.
Cross and cross-coupling derivative measurements
on the standard dynamics model at AEDC
[AIAA 82-0596] N82-24670
- COUSINS, D.
Aircraft electric system development and test
facilities
N82-24384
- CRACKNELL, F.
LAMP III recovery assist, securing and traversing
/RAST/ system
[SAE PAPER 811080] N82-24412
- CRONIN, M. J.
Electric flight systems, overview
N82-19135
- CURRAN, J. J.
Three-engine control system for the prototype
EH-101 helicopter
[AEBG-9/81-1568L] N82-18135
- CUTLER, R.
A310 - Design for maintenance
N82-24002

D

- DANMS, S. M.
The measurement of the mobility of structures at
acoustic frequencies
N82-18149
- DANGVU, B.
Multivariable aircraft control by maneuver
commands: An application to air to surface
gunnery
N82-19154
- DANNENBERG, E.
Experimental investigation of visual aids for
helicopters: Low level flight at night and poor
visibility
N82-18168
- DAVIES, E. B.
New developments in cockpit-human interfaces
[RAE-TN-PS-412] N82-18215
- DAWSON, G. P.
Air cooled engine test facilities
N82-24004
- DE LUCCIA, J. J.
Recent developments in materials and processes for
aircraft corrosion control
N82-24825
- DE HALHERBE, M. C.
A new approach to the problem of stress corrosion
cracking in 7075-T6 aluminum
N82-23772

DEDIEU, J. P.
Parametric study of the influence of the engine upon the operating cost of a civil helicopter
N82-18131

DELUCIEN, A. G. B.
Utilizing the helicopter's versatility to improve the ATC system
A82-23316

DENING, D. C.
High temperature engine control electronics [SAE PAPER 811074]
A82-24407

DEPOMPEIS, R.
Parametric criteria and impact on design trends
N82-18139

DEPONTE, S.
An experimental analysis of the shape of a rotor wake
N82-18122

DESTUYNDER, R.
Recent developments in wing with stores flutter suppression [ONERA, TP NO. 1981-145]
A82-24077

DETMAN, T. R.
Development of a clear air radar to detect meteorological hazards at airports [AD-A108236]
N82-18835

DEVEAUX, G. D.
Advanced attack helicopter fatigue testing - Overview
A82-24720

DIERKE, R.
Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR [ESA-TT-675]
N82-19219

DONOHUE, J. B.
TM/TE polarization ratios in a sample of 30 kHz sferics received at altitudes from 0 to 70 km [AD-A108182]
N82-18464

DOROFEEV, A. L.
High-frequency monitoring of surface layers of metals
A82-23603

DOVE, B.
Digital flight controls
N82-19149

DOWNIE, D.
Complete guide to Rutan homebuilt aircraft
A82-22880

DOWNIE, J.
Complete guide to Rutan homebuilt aircraft
A82-22880

DREES, J. M.
Standardization of helicopter fatigue methodology - A manufacturer's view
A82-24704

DREHER, R. C.
Dynamics of aircraft antiskid braking systems [NASA-TP-1959]
N82-18204

DUBREUIL, J. P.
Naval versions of the Dauphin and the AS 15 TT weapon system
N82-18142

DUBROVSKII, V. I.
Utilization of radio equipment at airports and on airways
A82-22407

DURAN, M. G.
Secondary radar problems - The presence of false echoes
A82-25323

DUSTERBERRY, J. C.
Status and capabilities of the National Full Scale Facility 40- by 80-foot wind tunnel modification [AIAA 82-0607]
A82-24676

E

EARNshaw, K. B.
Development of a clear air radar to detect meteorological hazards at airports [AD-A108236]
N82-18835

EAST, A.
A further study of helicopter rotor pitch-flap-phase coupling [BU-259]
N82-19214

EDWARDS, J. W.
Apparatus for damping operator induced oscillations of a controlled system [NASA-CASE-FRC-11041-1]
N82-18493

EFTIS, J.
Fracture and fatigue characterization of aircraft structural materials under biaxial loading [AD-A109054]
N82-19587

EGAWA, K.
Acoustic fatigue endurance test of USB flap structure models at elevated temperature [NAL-TR-683]
N82-19570

EGGLESTON, B. G.
Transparency design decisions - Assessing their impact on visual performance
A82-24306

A new angular deviation measurement device for aircraft transparencies
A82-24308

Portable transparency optical test system /P-TOTS/
A82-24309

EHLERS, R.
Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR [ESA-TT-675]
N82-19219

EIDELMAN, D.
Fixed gain controller design for aircraft
A82-23441

ELLIOTT, M.
The testing of aircraft under near field conditions
A82-24361

ENGELBERT, D. F.
Status and capabilities of the National Full Scale Facility 40- by 80-foot wind tunnel modification [AIAA 82-0607]
A82-24676

ERDMANN, F.
Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR [ESA-TT-675]
N82-19219

ERICSSON, L. E.
Review of support interference in dynamic tests [AIAA 82-0594]
A82-24668

ERKELENS, L. J. J.
A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft [NLR-TR-80032-U]
N82-19212

ESPOSTI, W.
Engine superficial temperature and infrared signature
N82-18136

EWINS, D. J.
The effects of slight non-linearities on modal testing of helicopter-like structures
N82-18130

F

FABIAN, H.
Experience during the development of the German-Japanese helicopter BK 117 [MBB-UD-318-81-0]
N82-19210

FALCHERO, D.
Application of the ONER dynamic stall model to a helicopter blade in forward flight
N82-18161

FAULHANN, D.
Induction driven transonic wind tunnel T2: Operation at room temperature and cryogenic adaptation
N82-19158

FAUST, H. S.
Application of fatigue, crack propagation and strain survey testing to the CH-46 aft rotor drive shaft
A82-24705

FEDORCHENKO, A. T.
Problems of numerical simulation of unsteady three-dimensional viscous-gas flows in nozzles
A82-25347

FINKE, R.
Power systems
N82-19146

FISCHER, W. P.
Abrasion resistant coated plastic products for aircraft
A82-24310

FLANNELLY, W. G.
Structural system identification technology verification
[AD-A109181]
N82-19583

FORD, R. L.
Conflicts between random flights in a given area
A82-25213

FORESTCUE, P. W.
Preliminary investigation into the addition of auxiliary longitudinal thrust on helicopter agility
N82-18155

FOSSUM, G., II
Evolution of the Aeroscout
A82-24706

FRANCO, B. G.
An ejector augmented choking valve for the metering and control of inlet and bleed duct flows
[AIAA 82-0575]
A82-24659

FREEMAN, G. A.
Multiple ejection effects analysis
[AD-A108277]
N82-18192

FREEMAN, R. J.
Vehicle test report: Battronic pickup truck
[NASA-CR-168637]
N82-19205

FUKIMORI, Y.
Acoustic fatigue endurance test of USB flap structure models at elevated temperature
[NAL-TR-683]
N82-19570

G

GAGLIARDI, P.
Parametric criteria and impact on design trends
N82-18139

GAI, E.
Reliability analysis of a dual-redundant engine controller
[SAE PAPER 811077]
A82-24410

GAL-OR, E.
Low grade fuels for turbo and jet engines
A82-23439

GALENTE, J. B.
Electronic flight instrument systems /EFIS/, the instrumentation of the 1980s
A82-25324

GARABEDIAN, P.
Design of supercritical swept wings
A82-23826

GEMCO, L. V.
Transparency design decisions - Assessing their impact on visual performance
A82-24306

A new angular deviation measurement device for aircraft transparencies
A82-24308

Portable transparency optical test system /P-TOTS/
A82-24309

GERBI, G.
MIL-STD 1553B - Aircraft EM environmental susceptibility effects
A82-24357

GIANSANTE, M.
Structural system identification technology verification
[AD-A109181]
N82-19583

GLOSS, B. B.
Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels
[AIAA 82-0603]
A82-24675

GOELLER, W.
Tethered rotorplatforms and their mission potential
N82-18145

GOLDSMITH, I. M.
A study to define the research and technology requirements for advanced turbo/propfan transport aircraft
[NASA-CR-166138]
N82-18202

GORENKOV, A. P.
Improving the accuracy of the estimates of surfactant content in jet fuels
A82-23250

GOULD, D. K.
Mission-adaptive wing flight demonstration program
[SAE PAPER 811035]
A82-24399

GRAHAM, K. D.
Integrated control design techniques
[AD-A108223]
N82-18224

GRANDT, A. P., JR.
A compilation of stress intensity factor solutions for flawed fastener holes
[AD-A108753]
N82-18628

GRANGER, K. G.
Acrylic - A timely review
A82-24317

GRAVELY, M. L.
The use of dynamic mock-ups in the design of advanced systems
A82-22902

GRAY, P. J.
International plans for civil and military co-ordination
A82-23317

GRAYSON, R. L.
Analysis of system problems using aviation safety reporting system data
A82-23312

GREBER, I.
Dilation jet behavior in the turn section of a reverse flow combustor
[NASA-TN-82776]
N82-19220

GREEN, W. L.
On-line control for the regulation of power source in multiple-servo electro-hydraulic systems
[ASME PAPER 81-WA/DSC-3]
A82-24562

GREENE, W. H.
Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance
[AIAA PAPER 80-0724]
A82-24022

GREGG, O.
The reliability and safety of small passenger aircraft
A82-24972

GRIFFIN, J. M.
An analytical methodology to predict potential aircraft losses due to canopy birdstrikes
A82-24313

GRIGG, R. E.
Development of maintenance programmes through the functional, structural and flight test phases
A82-24003

GROOM, N. J.
Electric Flight Systems
[NASA-CF-2209]
N82-19134

GUERARD, A.
Selection of telecommunication equipment - A new approach to the equivalent cost concept
A82-25510

GUTIERREZ, O. A.
Effect of facility variation on the acoustic characteristics of three single stream nozzles
[NASA-TN-81635]
N82-19944

H

HABERMAN, D. R.
The use of a multi-degree-of-freedom dual balance system to measure cross and cross-coupling derivatives
[AIAA 82-0595]
A82-24669

HAERDTL, K. H.
Investigations of the separation behavior on airfoils at high angles of attack, using linear lift theory
[MBB-FR-122/S/PUB/37]
N82-18189

HAUSER, H.
Integration of complex systems in current and future aircraft projects for the example of avionics
[MBB-UH-18-80-0]
N82-18221

HAPEZ, M.
Transonic wind tunnel wall interference corrections for three-dimensional models
[AIAA 82-0588]
A82-24663

HAINES, A. L.
A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533]
N82-19217

HALL, P. L.

PERSONAL AUTHOR INDEX

- HALL, P. L.
Direct comparison of community response to road
traffic noise and to aircraft noise
A82-22974
- HALL, J. C.
Digital flight controls
N82-19143
- HALPIN, J. C.
An analytical methodology to predict potential
aircraft losses due to canopy birdstrikes
A82-24313
- HAMMOND, G. P.
Complete velocity profile and 'optimum' skin
friction formulas for the plane wall-jet
[ASME PAPER 81-WA/FE-3]
A82-24566
- HAND, L. A.
A new facility and technique for two-dimensional
aerodynamic testing
[AIAA 82-0608]
A82-24677
- HANLY, R. D.
The effect of ejector augmentation on test-section
flow quality in the Calspan 8-ft transonic wind
tunnel
[AIAA 82-0571]
A82-24658
- HANNAH, T. L.
Air Traffic Control computer replacement -
Specification issues and problems
A82-23313
- HARRISON, W. C.
Abrasion resistant coated plastic products for
aircraft
A82-24310
- HARRISON, J. V.
Reliability analysis of a dual-redundant engine
controller
[SAE PAPER 811077]
A82-24410
- HARRISON, R. P.
TM/TE polarization ratios in a sample of 30 kHz
spherics received at altitudes from 0 to 70 km
[AD-A108182]
N82-18464
- HASTINGS, E. C., JR.
Simulator study of vortex encounters by a
twin-engine, commercial, jet transport airplane
[NASA-TP-1966]
N82-19225
- HATFIELD, J. J.
Advanced electronic displays and their potential
in future transport aircraft
A82-25216
- HAVERIDINGS, H.
A control model for maneuvering flight for
application to a computer-flight testing program
N82-18153
- HAYASHI, T.
An extension of the local momentum theory to the
rotors operating in twisted flow field
N82-18123
- HAYES-ROTH, P. A.
Distributed intelligence for air fleet control
[AD-A108611]
N82-18195
- HEEHN, R. C.
The cargo helicopter - A logistical vehicle
A82-24717
- HEITKANO, L. F.
Airport related residential acoustical insulation
demonstration project: Report 1720
[PB82-100777]
N82-19396
- HELD, V.
Integration of inertial sensors in helicopters
N82-18173
- HENDY, J. C.
Design study into a high endurance mini-rotorcraft
[BU-265]
N82-19216
- HEPLER, A. K.
A study of flight control requirements for
advanced, winged, earth-to-orbit vehicles with
far-aft center-of-gravity locations
[NASA-CR-3491]
N82-19226
- HIGHLAND, R. W.
Analysis of Built-In-Test (BIT) false alarm
conditions
[AD-A108752]
N82-18217
- HILEY, P. E.
The design of a wind tunnel VSTOL fighter model
incorporating turbine powered engine simulators
[AIAA PAPER 82-2635]
A82-25154
- HILLAKER, H. J.
YF-16 design concept and philosophy
A82-23444
- HITCHCOCK, L.
The use of dynamic mock-ups in the design of
advanced systems
A82-22902
- HITTNER, A.
Investigation of crossdeck pendant catapult slot
interaction; proposed corrective measures
[AD-A108149]
N82-18232
- HIKSON, W. W.
Propulsion multiplexer /PMUX/ system - The missing
link
[SAE PAPER 811078]
A82-24411
- HO, T. L.
High speed VSCP generator design consideration
A82-24379
- HODGKINS, P. D.
Discrete Address Beacon System /DABS/
A82-23322
- HOENLINGER, H.
Interpretation and construction of a dynamic
similarity model of the A 310 wings
[NBB-FE-17/S/PUB/42]
N82-18212
- HOEPPNER, D. W.
Material/structure degradation due to fretting and
fretting-initiated fatigue
A82-23771
- HOFFMAN, A. C.
Engine technology
N82-19145
- HOOD, R. V.
Electric Flight Systems
[NASA-CP-2209]
N82-19134
- HOOD, R. V.
Electric flight systems integration
N82-19150
- HOOKER, P. H.
Aeronautical Research Laboratories Structures
Division
[AD-A109049]
N82-19161
- HOUGHTON, W.
NDE of composite rotor blades during fatigue testing
A82-24713
- HOUMMOUZIADIS, J.
Component design and development for future
helicopter engines
N82-18134
- HOWELL, D. A. S.
Army Lynx: Product development matched to
military combat development
N82-18143
- HSIEH, P. Y.
Rotorcraft flight simulation computer program C81
with DATAMAP interface. Volume 2: Programmer's
manual
[AD-A108294]
N82-18231
- HUBER, H.
Flight characteristics design and development of
the NBB/KHI BK117 helicopter
N82-18150
- HUI, W. H.
Oscillating supersonic/hypersonic wings at high
incidence
A82-23828
- HULL, D. R.
Metal honeycomb to porous wireform substrate
diffusion bond evaluation
[NASA-TM-82793]
N82-18612
- HUNG, J. C.
Software features applicable to inertial
measurement unit self alignment
[AD-A108511]
N82-18196
- HUSTEAD, R. E.
Voice communications - The vital link
A82-23324
- HUTCHINSON, C.
Flight test data acquisition and interpretation
A82-24707
- HYVARINEN, W. E.
The effect of critical design parameters on the
selection of a VSCP system
A82-24381
- IIDA, S.
Acoustic fatigue endurance test of USB flap
structure models at elevated temperature
[NAL-TR-683]
N82-19570

ILNITSKIY, I. Y.
Assessment of aircraft capacitive circuit medium
wave antennas according to their efficiency
N82-19453

ISRAELI, I.
Evaluation of superplastic forming and
co-diffusion bonding of Ti-6Al-4V titanium alloy
expanded sandwich structures
[NASA-CR-165827] N82-19358

J

JACKSON, K. T., JR.
An analytical methodology to predict potential
aircraft losses due to canopy birdstrikes
A82-24313

JACKSON, S. K., JR.
Quality, quantity, and technology - A perspective
on fighter development
[SAE PAPER 811097] A82-24400

JACOB, G.
Importance of a tactical cargo aircraft in
emergency relief
A82-25499

JACOBSON, I. D.
Methodology for multiaircraft minimum noise impact
landing trajectories
A82-23037

JANK, T.
Volumetric pattern prediction of antennas on
aircraft using the geometrical theory of
diffraction
[ESA-TT-677] N82-18483

JENKINS, V. B.
AN/ALQ-135 tail warning system follow-on
operational test and evaluation
[AD-A108348] N82-18471

JENSEN, S. W.
Evaluation of methods for characterizing surface
topography of models for high Reynolds number
wind-tunnels
[AIAA 82-0603] A82-24675

JOHNSON, J. C.
Vibration levels in Army helicopters: Measurement
recommendations and data
[AD-A108131] N82-18209

JONES, A. L.
Integrated control design techniques
[AD-A108223] N82-18224

JONES, D. L.
Fracture and fatigue characterization of aircraft
structural materials under biaxial loading
[AD-A109054] N82-19587

JONES, R. B.
Distributed data processing modeling for future
ATC systems
A82-23319

JONES, T. G.
Analytical study of cockpit information requirements
[AD-A108524] N82-18218

JOOS, H. D.
Extension of proportional navigation by the use of
optimal filtering and control methods
[ESA-TT-683] N82-18199

JOSEFOWITZ, A. J.
Combined multisensor displays
A82-22905

JUNKER, B.
Helicopter rotor downwash: Results of
experimental research at the DFVLR-rotor test
stand and their comparison with theoretical
results
N82-18158

K

KAHANEK, V.
The reliability and safety of small passenger
aircraft
A82-24972

KALETKA, J.
Evaluation of the helicopter low airspeed system
LASSIE
N82-18172

KALININ, M. P.
High-frequency monitoring of surface layers of
metals
A82-23603

KANEHOV, P. S.
Linear alpha-ray altimeter
A82-23225

KANOU, T.
Aircraft parameter identification in the presence
of atmospheric turbulence
A82-23227

KAUL, C. B.
Descent-rate cuing for carrier landings: Effects
of display gain, display noise and aircraft type
[AD-A108801] N82-19206

KEEN, J. M. S.
Reliable power
A82-24007

KELLER, M.
A redundancy concept for a digital CSAS
N82-18170

KENNETT, R. J.
Advanced generating system technology
A82-24380

KERR, T. H.
A criterion for the prediction of the recovery
characteristics of spinning aircraft
[RAE-TN-AERO-2251] N82-19223

KETCHAM, S. J.
Recent developments in materials and processes for
aircraft corrosion control
A82-24825

KEYSER, G. L., JR.
Simulator study of vortex encounters by a
twin-engine, commercial, jet transport airplane
[NASA-TP-1966] N82-19225

KIHARA, M.
Sensitivity reduction by double perfect model
following
A82-23029

KING, A. E.
A look into the future: The potential of the
all-electric secondary power system for the
energy efficient transport
N82-19138

KING, R. W. P.
Analysis of the crossed dipole antenna as a model
for aircraft in an electromagnetic environment
A82-25002

KLINT, H.
Theoretical investigations on the influence of
different strake, tail unit, and conventional
BLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FR-122/S/PUB/36] N82-18211

KNAPP, M. I.
Assessment of Avionic Equipment Field Reliability
and Maintainability as Functions of Unit Cost
[AD-A109373] N82-19218

KOBAYAKAWA, M.
Aircraft parameter identification in the presence
of atmospheric turbulence
A82-23227

KOCH, J. B.
Airworthiness considerations in the design of
commercial transport aircraft
[SAE PAPER 811039] A82-24396

KOERNER, H.
Tendencies in the development of subsonic
transport aircraft with special consideration of
aerodynamics
[ESA-TT-705] N82-18214

KOHNEN, E.
Experimental investigation of visual aids for
helicopters: Low level flight at night and poor
visibility
N82-18168

KOLLODGE, M. A.
Integrated control design techniques
[AD-A108223] N82-18224

KONATSU, K.
Acoustic fatigue endurance test of USB flap
structure models at elevated temperature
[NAL-TR-683] N82-19570

KONDO, H.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

KOZLOWSKI, D. R.
Fighter issues - 2000
[SAE PAPER 811096] A82-24415

KRAJCI, G. E.
Packaging the VSCF system for an aircraft engine environment A82-24383

KREINER, H. B.
Component design and development for future helicopter engines N82-18134

KREITINGER, R. L.
Aircraft surface coatings for drag reduction/erosion protection
[SAE PAPER 811070] A82-24401

KRICKE, D.
Improvement of fuel economy by flying with maximum rearward center-of-gravity positioning A82-23470

KROPAC, O.
Oscillations and vibrations of aircraft on runways A82-24974

KULLGREEN, T. E.
A compilation of stress intensity factor solutions for flawed fastener holes
[AD-A108753] N82-18628

KUZHINA, L. K.
A method for the investigation of gyro-stabilization systems A82-24892

KUZNETSOV, A. A.
Utilization of radio equipment at airports and on airways A82-22407

L

LANGER, H. J.
Helicopter rotor downwash: Results of experimental research at the DFVLR-rotor test stand and their comparison with theoretical results N82-18158

LANZ, M.
A general purpose program for rotor blade dynamics N82-18151

LARGE, G. D.
Cooled variable-area radial turbine technology program
[NASA-CR-165408] N82-19221

LARSON, G. C.
Computer-generated images for simulators - The cost of technology A82-22881

LATINA, M. S.
Propulsion multiplexer /PMUX/ system - The missing link
[SAE PAPER 811078] A82-24411

LAWRENCE, J. E., JR.
Deficiencies and constraints that affect the design of cockpit enclosures and transparencies A82-24303

Aircraft transparency design guide A82-24307

LEE, H. J.
Fuel-rich plume combustion
[AD-A108136] N82-18349

LEFRANCQ, J. P.
A complete method for computation of blade mode characteristics and responses in forward flight N82-18126

LEGG, P. J.
Preliminary investigation into the addition of auxiliary longitudinal thrust on helicopter agility N82-18155

LENOX, T. G.
Potential propulsion considerations and study areas for all-electric aircraft N82-19137

LEONARDI, J.
Recent improvements in aircraft N1-Cd cells A82-24245

LERCHE, E.
Further development of the test concept of the ALPHA JET engine LAZAC 04 N82-18223

LEWIS, E. A.
TM/TE polarization ratios in a sample of 30 kHz spherics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464

LIEBOWITZ, H.
Practical applications of fracture mechanics
[AGARD-AG-257] N82-19571

LINTEN, G.
Descent-rate cuing for carrier landings: Effects of display gain, display noise and aircraft type
[AD-A108801] N82-19206

LIPSHITZ, A.
Dilution jet behavior in the turn section of a reverse flow combustor
[NASA-TN-82776] N82-19220

LOEHR, R.
Equipment for testing and measuring a "helmet mounted sight and display" system with a coupled movable TV camera in the flight simulator for research of the DFVLR
[ESA-TT-675] N82-19219

LOVELACE, W.
Impact of technology on avionics cost trends
[AD-A108494] N82-18219

LOVELL, D.
Transonic wind tunnel wall interference corrections for three-dimensional models
[AIAA 82-0588] A82-24663

LUDWIG, R.
History of the sweptback wing
[DGLR PAPER 81-070] A82-22898

LUDWIG, D.
Modal characteristics of rotor blades: Finite element approach and measurement by ground vibration test N82-18127

LUEBBERS, R.
GTD terrain reflection model applied to ILS glide slope A82-23027

LUEBBERS, R. J.
Calculation and measurement of electric field strength for airborne antennas in the LP/MF range A82-25011

LUMLEY, J. L.
Annual review of fluid mechanics. Volume 14 A82-24416

LUPPOLD, R. H.
Reliability analysis of a dual-redundant engine controller
[SAE PAPER 811077] A82-24410

M

MACCORMACK, R. W.
International Conference on Numerical Methods in Fluid Dynamics, 7th, Stanford University, Stanford and Moffett Field, CA, June 23-27, 1980, Proceedings A82-24426

MACDIARMID, I. P.
EMC clearance of modern military aircraft A82-24359

MAEKAWA, S.
On the sonic fatigue life estimation of skin structures at room and elevated temperatures A82-23678

MAHAPATRA, P. R.
Scanning strategies for air traffic control radars A82-24646

MAHESH, J. K.
Integrated control design techniques
[AD-A108223] N82-18224

MAILLARD, W. E.
Technology for quality and quantity in a new fighter
[SAE PAPER 811100] A82-24404

MAINE, R. E.
A marine NAVSTAR GPS receiver A82-24644

MAITA, M.
Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

MACCOLM, J. G.
Analysis of Built-In-Test (BIT) false alarm conditions
[AD-A108752] N82-18217

- MALDONADO, J. C.**
An on board supervisory system for applications in space missions
[INPE-2097-RPE/327] N82-18216
- MALONEY, P. F.**
Structural testing of composites with known defects
A82-24708
- MANTEGAZZA, P.**
A general purpose program for rotor blade dynamics
N82-18151
- MAPELLI, R.**
Air transportation of handicapped persons
A82-24338
- MARAZ, M. R.**
The design of a wind tunnel VSTOL fighter model incorporating turbine powered engine simulators
[AIAA PAPER 82-2635] A82-25154
- MARIN, K.**
Impact of technology on avionics cost trends
[AD-A108494] N82-18219
- MARQUART, E. J.**
Cross and cross-coupling derivative measurements on the standard dynamics model at AEDC
[AIAA 82-0596] A82-24670
- MARTI, V. M.**
The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFFC I/
[SAE PAPER 811036] A82-24398
- MARTIN, R. L.**
Operating flight loads and their effect on engine performance
[SAE PAPER 811071] A82-24405
- MARTINSON, P. F.**
A design for a 32-channel multiplexer
[RAE-TM-RAD-NAV-145] N82-18503
- MASON, A. J.**
The effects of absorbed moisture upon the physical properties of stretched acrylic materials
A82-24320
- MASUE, T.**
Flight characteristics design and development of the MBB/KHI BK117 helicopter
N82-18150
- MASURE, B.**
A complete method for computation of blade mode characteristics and responses in forward flight
N82-18126
- MATSUMI, M.**
Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945
- MCBRYAN, J. C.**
Airport related residential acoustical insulation demonstration project: Report 1720
[PB82-100777] N82-19396
- MCCARTY, R. E.**
Aircraft transparency bird impact analysis using the MAGNA computer program
A82-24315
- MCCLAIR, A. A.**
Development of a self-optimizing flexible technology /SOFT/ transonic wing wind tunnel model
[AIAA 82-0601] A82-24673
- MCCLOUD, G. W.**
A method of determining safe service life for helicopter components
A82-24709
- MCCLUNG, R.**
The 400-Hertz constant-speed electrical generation systems
N82-19139
- MCCURDY, D. A.**
Annoyance caused by propeller airplane flyover noise: Preliminary results
[NASA-TM-83244] N82-18996
Effects of repetition rate and impulsiveness of simulated helicopter rotor noise on annoyance
[NASA-TP-1969] N82-19707
- MCDERMOTT, J.**
Hughes helicopters - Fatigue life methodology
A82-24710
- MCDONALD, A. B.**
Aircrew restraint and mobility test fixture
[AD-A108274] N82-18193
- MCPADDER, G.**
Design of supercritical swept wings
A82-23826
- MCPARLAND, A. L.**
Active Beacon Collision Avoidance System (BCAS) logic performance during operational flight tests
[AD-A108893] N82-19203
- MEHROTRA, S. C.**
Structural modeling of high Reynolds number wind tunnel models
[AIAA 82-0602] A82-24674
- MELINE, J.**
What the operator wants
A82-24008
- MELTON, R.**
Methodology for multi-aircraft minimum noise impact landing trajectories
A82-23037
- MENDES, R. D.**
An on board supervisory system for applications in space missions
[INPE-2097-RPE/327] N82-18216
- MESSLER, R. W., JR.**
Welding for low-cost advanced titanium airframe structures
A82-23757
- MEYER, L. J.**
Cooled variable-area radial turbine technology program
[NASA-CR-165408] N82-19221
- MIDDLETON, D. B.**
Aircraft surface coatings for drag reduction/erosion protection
[SAE PAPER 811070] A82-24401
- MIEDLAR, M. J.**
A digital simulation program describing the motion of an aircraft undergoing engine failure during its takeoff ground roll
[AD-A108420] N82-18210
- MIGNOSI, A.**
Induction driven transonic wind tunnel T2: Operation at room temperature and cryogenic adaptation
N82-19158
- MIKULLA, V.**
On the calculation of transonic blade tip flow for helicopter rotors
[MBB-UD-320-81-0] N82-18187
- MILES, R. B.**
Wide field of view laser beacon system for three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9] A82-24563
- MILLER, J.**
Some unsteady aerodynamic effects on helicopter rotors
N82-18162
- MILLER, K. L.**
Physiological acceptability tests of the SJU-5/A ejection seat: Second physiological acceptance demonstration
[AD-A108688] N82-18194
- MILLER, P. M.**
Test site instrumentation study. Volume 2: Crash 1 and crash 2 raw data
[PB82-111832] N82-18233
- MILLER, R. E.**
A simplified approach to the free wake analysis of a hovering rotor
N82-18121
- MILLER, V. E.**
Acoustic measurements of F100-PW-100 engine operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952
- MINOUE, M.**
Selection of telecommunication equipment - A new approach to the equivalent cost concept
A82-25510
- MITCHELL, J. R.**
NDE of composite rotor blades during fatigue testing
A82-24713
- MITCHELL, L.**
GTD terrain reflection model applied to ILS glide slope
A82-23027

MOELLER, D. O.
Electric ECS
N82-19140

MOFFAT, A.
The multi mode matrix flat panel display:
Technology and applications
N82-18169

MONTGOMERIE, I. F.
The role of simulation in the design process
N82-18154

MOORE, M. C.
Transparency development needs for military
aircraft in the 1980's
A82-24302

MOORE, R. D.
Performance of single-stage axial-flow transonic
compressor with rotor and stator aspect ratios
of 1.63 and 1.78, respectively, and with design
pressure ratio of 1.82
[NASA-TP-1974]
N82-19222

MOORE, W. O., III
Mean flow and noise measurements in a Mach 3.5
pilot quiet tunnel
[AIAA 82-0569]
A82-24657

MOOREHEAD, P. E.
Metal honeycomb to porous wireform substrate
diffusion bond evaluation
[NASA-TM-82793]
N82-18612

MOOSHAN, L.
Aircraft transparency design guide
A82-24307

MORAN, K. P.
Development of a clear air radar to detect
meteorological hazards at airports
[AD-A108236]
N82-18835

MORBELLO, S. A.
Integration of energy management concepts into the
flight deck
[SAE PAPER 811066]
A82-24387

MORITA, M.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2]
N82-19945

MORRIS, W. E.
The way ahead for helicopter maintenance
A82-24009

MORT, K. W.
Status and capabilities of the National Full Scale
Facility 40- by 80-foot wind tunnel modification
[AIAA 82-0607]
A82-24676

MORTON, T. G.
Measurement techniques used to assess the
installed power of a helicopter engine
N82-18133

MOTOYAMA, K.
Sensitivity reduction by double perfect model
following
A82-23029

MULHOLLAND, B. G.
Stereographic projection in the National Airspace
System
A82-23031

MURMAN, E. M.
Transonic wind tunnel wall interference
corrections for three-dimensional models
[AIAA 82-0588]
A82-24663

N

NAGASHIMA, T.
Optimum performance and wake geometry of co-axial
rotor in hover
N82-18156

NAGY, E. J.
Structural system identification technology
verification
[AD-A109181]
N82-19583

NAKABURA, Y.
Prediction of blade vortex interaction noise from
measured blade pressure
N82-18147

NAKANISHI, K.
Optimum performance and wake geometry of co-axial
rotor in hover
N82-18156

NAKAYAMA, S.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2]
N82-19945

NASU, K. I.
An extension of the local momentum theory to the
rotors operating in twisted flow field
N82-18123

NEWMAN, P. A.
Numerical design of the contoured wind-tunnel
liner for the NASA swept-wing LFC test
[AIAA 82-0568]
A82-24656

NEWTON, P. H.
The variation of induced currents in aircraft wiring
A82-24355

NORTH, R. A.
Combined multisensor displays
A82-22905

NOWLAN, P. S.
Reliability centered maintenance /RCM/
A82-24001

O

OBERST, D.
Theoretical investigations on the influence of
different strake, tail unit, and conventional
HLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36]
N82-18211

OKADA, T.
Sensitivity reduction by double perfect model
following
A82-23029

OKUBO, H.
Aircraft parameter identification in the presence
of atmospheric turbulence
A82-23227

OLIVA, P.
Recent improvements in aircraft Ni-Cd cells
A82-24245

OLLERHEAD, J. B.
An experimental study of the effects of an inlet
flow conditioner on the noise of a low speed
axial flow fan
[TT-8101]
N82-19956

OLSSON, W. J.
Operating flight loads and their effect on engine
performance
[SAE PAPER 811071]
A82-24405

OSADCHENKO, M. V.
Stability of a three-stage dynamic stand
A82-25353

OSTAPENKO, V. D.
High-frequency monitoring of surface layers of
metals
A82-23603

OVENS, J. J.
The effect of a well on the aerodynamics of a
spoiler
[BU-268]
N82-19194

P

PAEZ, C. A.
Welding for low-cost advanced titanium airframe
structures
A82-23757

PALMER, J. E.
Direct comparison of community response to road
traffic noise and to aircraft noise
A82-22974

PANKHURST, R. V.
The coupling of electromagnetic interference into
aircraft systems
A82-24354

PARKINSON, B. W.
The application of NAVSTAR differential GPS in the
civilian community
A82-24645

PARNAS, D. L.
A-7E software module guide
[AD-A108649]
N82-18920

- PARSONS, W. E.
Aircraft/airport compatibility - A constant challenge for aircraft designers
A82-25119
- PECKHAM, J. B.
New developments in cockpit-human interfaces
[RAE-TM-FS-412] N82-18215
- PERIE, M. E.
Air Traffic Control computer replacement - Specification issues and problems
A82-23313
- PETERSON, J. B., JR.
Numerical design of the contoured wind-tunnel liner for the NASA swept-wing LPC test
[AIAA 82-0568] A82-24656
- PETERSON, R. L.
Windshield system structural enhancement
A82-24312
- PLATZER, M. P.
Oscillating supersonic/hypersonic wings at high incidence
A82-23828
- PLEDGER, D. P.
Integrated control design techniques
[AD-A108223] N82-18224
- PLZAK, G. A.
Acoustic measurements of F100-PW-100 engine operating in hush house NSN 4920-02-070-2721
[AD-A108814] N82-19952
- POGOBZELSKI, P. S.
Novel approaches to electron beam welding machine utilization
A82-23753
- POKORNY, V.
Spoilers or auxiliary flaps
A82-24973
- POLACK, A.
A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491] N82-19226
- POLER, T. E.
A new facility and technique for two-dimensional aerodynamic testing
[AIAA 82-0608] A82-24677
- POLL, K. J.
The Link-Hiles driver training simulator for tracked vehicles: The effect of method and duration of training on the transfer of training
[IZF-1980-28] N82-18226
- POLLARD, D. D.
Packaging the VSCP system for an aircraft engine environment
A82-24383
- POLLARD, J. S.
Preliminary thoughts on helicopter cabin noise prediction methods
N82-18148
- POLZ, G.
Separated flow around helicopter bodies
N82-18163
On the calculation of separated flow on helicopter fuselages
[NBB-UD-321-81-0] N82-18188
- POMPA, M. P.
Vehicle test report: Batttronic pickup truck
[NASA-CR-168637] N82-19205
- POUNTNEY, S.
Development of a self-optimizing flexible technology /SOFT/ transonic wing wind tunnel model
[AIAA 82-0601] A82-24673
- POWERLL, C. A.
Annoyance caused by propeller airplane flyover noise: Preliminary results
[NASA-TM-83244] N82-18996
Effects of repetition rate and impulsiveness of simulated helicopter rotor noise on annoyance
[NASA-TP-1969] N82-19707
- PRATT, J.
The challenge of standardizing fatigue methodology
A82-24703
- PRICE, T. W.
Vehicle test report: Batttronic pickup truck
[NASA-CR-168637] N82-19205
- PRISER, D. B.
Vibration levels in Army helicopters: Measurement recommendations and data
[AD-A108131] N82-18209
- PROCHAZKA, M.
Oscillations and vibrations of aircraft on runways
A82-24974
- ## Q
- QUAST, A.
Laminar airfoils for transport aircraft
[ESA-TT-680] N82-18190
- QUENTIN, J.
Separated flow around helicopter bodies
N82-18163
- ## R
- RAIMONDO, S.
Slotted wall test section for automotive aerodynamic test facilities
[AIAA 82-0585] A82-24661
- RAMSDEN, J. M.
The inter-relation between design, construction and maintenance
A82-24010
- RANG, E. R.
Integrated control design techniques
[AD-A108223] N82-18224
- RASMUSSEN, J. E.
TM/TE polarization ratios in a sample of 30 MHz sferics received at altitudes from 0 to 70 km
[AD-A108182] N82-18464
- RATCLIFFE, S.
Conflicts between random flights in a given area
A82-25213
- RAWLINS, J. S.
CAD/CAM in British Aerospace - Aircraft Group
A82-24373
- REDING, J. P.
Review of support interference in dynamic tests
[AIAA 82-0594] A82-24668
- REID, C.
Management of powerplant maintenance and restoration programs for fuel conservation
[SAE PAPER 811052] A82-24394
- REID, L.
Performance of single-stage axial-flow transonic compressor with rotor and stator aspect ratios of 1.63 and 1.78, respectively, and with design pressure ratio of 1.82
[NASA-TP-1974] N82-19222
- REMBLESKE, C. A.
Designing for continued airworthiness - General aviation
[SAE PAPER 811038] A82-24397
- REPPERT, L. M.
ATC automation - A look forward: Technology/architecture
A82-23320
- REUBUSH, D. E.
Effects of installation of F101 DPE exhaust nozzles on the afterbody-nozzle characteristics of the F-14 airplane
[NASA-TM-83250] N82-19181
- REYNOLDS, W. C.
International Conference on Numerical Methods in Fluid Dynamics, 7th, Stanford University, Stanford and Moffett Field, CA, June 23-27, 1980, Proceedings
A82-24426
- RICCI, A. M.
Engine superficial temperature and infrared signature
N82-18136
- RIDDLEBAUGH, S. M.
Dilution jet behavior in the turn section of a reverse flow combustor
[NASA-TM-82776] N82-19220
- RILEY, M. J.
Some unsteady aerodynamic effects on helicopter rotors
N82-18162
- RIZK, M. H.
Transonic wind tunnel wall interference corrections for three-dimensional models
[AIAA 82-0588] A82-24663
- ROBINSON, I. B.
Aluminum and its alloys - Weldability
A82-23755

ROBINSON, J. C.
Structural modeling of high Reynolds number wind
tunnel models
[AIAA 82-0602] A82-24674

ROGOFF, M.
Loran for precise position location - The VIEW-NAV
system A82-24648

ROSE, W. C.
The effect of ejector augmentation on test-section
flow quality in the Calspan 8-ft transonic wind
tunnel
[AIAA 82-0571] A82-24658

ROSENBUSH, F. M.
Environmental Control Systems N82-19141

ROSSWURM, M. A.
Design considerations of EC-Link aircraft
generation systems A82-24377

RUSSELL, J. P.
B.A.C. One-Eleven flight deck glazing product
improvement A82-24325

RYLSKII, G. I.
Analysis and optimization of control systems in
piloted flight vehicles A82-22398

RZONCA, L.
Loran-C RNAV in mountainous areas A82-24649

S

SAITO, S.
A numerical approach to co-axial rotor aerodynamics
N82-18157

SAKHUJA, R.
Open-cycle vapor compression heat pump
[PB82-110503] N82-18553

SALEEV, V. A.
Improving the accuracy of the estimates of
surfactant content in jet fuels A82-23250

SANDERS, C. D.
Task analytic techniques: Application to the
design of a flight simulator instructor/operator
console
[AD-A108724] N82-18227

SANGER, D. J.
On-line control for the regulation of power source
in multiple-servo electro-hydraulic systems
[ASME PAPER 81-WA/DSC-3] A82-24562

SANO, M.
Acoustic fatigue endurance test of USB flap
structure models at elevated temperature
[NAL-TR-683] N82-19570

SARRAILLE, S. R.
Disengagement of safety harness buckles - CT4
[AD-A109048] N82-19199

SAYLOR, D. M.
Flight condition recognition /FCR/ technique
A82-24712

SCHADOW, K. C.
Fuel-rich plume combustion
[AD-A108136] N82-18349

SCHERR, W.
Carbon-fiber composites - A fiber composite
material for highly stressed light-construction
components A82-24805

SCHMALHOFFER, W.
Theoretical investigations on the influence of
different strake, tail unit, and conventional
BLW arrangement as well as of CCV on the
aerodynamic characteristics of fighter aircraft
configurations
[MBB-FE-122/S/PUB/36] N82-18211

SCHMIDT, E. P.
NAS system load - Utilization of the DARC system
A82-23315

SCHOFIELD, S.
MSG-3 structures A82-24011

SCHOUTEN, G.
Static pressure in the slipstream of a propeller
A82-24023

SCHRAGE, D. P.
Fundamentals of helicopter fatigue life
determination A82-24714

Review of helicopter Mast Mounted Sight (MMS) base
motion isolation and Line-of-Sight (LOS)
stabilization concepts N82-18166

SCHYMANIETZ, K.
Impact of systems technology and integration on
helicopter design N82-18165

SCIRE, P. E.
Evaluation of methods for characterizing surface
topography of models for high Reynolds number
wind-tunnels
[AIAA 82-0603] A82-24675

SCOLES, J.
An experimental study of the effects of an inlet
flow conditioner on the noise of a low speed
axial flow fan
[TT-8101] N82-19956

SEGREST, J. D.
Evolution and development of high voltage /270
volt/ dc aircraft electric systems in the United
States A82-24382

SEHMI, N. S.
A further study of helicopter rotor
pitch-flap-phase coupling
[BU-259] N82-19214

SEIWERT, D. L.
Design technology for improved performance
retention in turbofan engines
[SAE PAPER 811055] A82-24392

SEKINE, S.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

SELEN, H. J. W.
On the design of some airfoils for sailplane
application
[VTH-LR-326] N82-19213

SEND, M.
A three-dimensional approach to lift and moment
coefficients of rotating blades N82-18125

SENSBURG, O.
Active gust and maneuver load control concepts
with the example of the Airbus A300. Part 1:
Explanation of a regular in the time zone of
wind gust load decrease and examination of its
effectiveness in stochastic gusts
[MBB-FE-172/S/PUB/39-PT-1] N82-19228

SERAUDIE, A.
Induction driven transonic wind tunnel T2:
Operation at room temperature and cryogenic
adaptation N82-19158

SERMIN, D. P.
Monitoring engine wear by oil analysis A82-24012

SHAIN, T. W.
Vehicle test report: Batttronix pickup truck
[NASA-CR-168637] N82-19205

SHARP, P. J.
Transparencies - What an aircraft designer should
know A82-24305

SHEPPARD, D. J.
Descent-rate cuing for carrier landings: Effects
of display gain, display noise and aircraft type
[AD-A108801] N82-19206

SHI-CUN, W.
A simplified method for predicting rotor blade
airloads N82-18124

SHINAR, J.
Efficient combinations of numerical techniques
applied to aircraft turning performance
optimization A82-24814

- SHINDO, S.
Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine [NAL-TR-687T-PT-2] N82-19945
- SHUFORD, R.
NDE of composite rotor blades during fatigue testing A82-24713
- SICKINGER, A.
Novel metal-ceramics-composite sealing coatings in aircraft engines A82-24803
- SILVERIO, P. J.
SH-608 test program N82-18141
- SIMONS, J. L.
A method for applying linear optimal control theory to the design of a regulator for a flexible aircraft [NLR-TR-80032-U] N82-19212
- SINCLAIR, P. C.
Aircraft measurements and analysis of severe storms: 1976 field experiment [NASA-CR-168519] N82-18803
- SLACK, J.
Fatigue test of the typical main rotor controls component A82-24715
- SLAZAK, M.
Study of cabin noise control for twin engine general aviation aircraft [NASA-CR-165833] N82-18995
- SMALL, L. L.
AFWAL turbine engine controls research and development - Present and future [AIAA PAPER 82-0321] A82-25050
- SMITH, E. G.
Dynamics of aircraft antiskid braking systems [NASA-TP-1959] N82-18204
- SMITH, P. D.
Utilizing the helicopter's versatility to improve the ATC system A82-23316
- SMITH, J. W.
Apparatus for damping operator induced oscillations of a controlled system [NASA-CASE-FRC-11041-1] N82-18493
- SMITH, W. L.
Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data A82-25113
- SOBCZAK, J. W.
NDE of composite rotor blades during fatigue testing A82-24713
- SOBIESZCZANSKI-SOBIESKI, J.
Minimum mass sizing of a large low-aspect ratio airframe for flutter-free performance [AIAA PAPER 80-0724] A82-24022
- SODERQUIST, J. R.
Certification of civil composite aircraft structure [SAE PAPER 811061] A82-24389
- SOPER, W. P. C.
Concorde glazings - 5 years of Mach 2 service A82-24326
- SPEELMAN, R. J.
Windshield system structural enhancement A82-24312
- SPENGLER, R. P.
A Microwave Landing System simulation A82-23323
- SPIEGEL, K. H.
Noise measurements on the helicopter BK 117 design. Weighted noise levels and influence of airspeed [DFVLR-MIT-81-18] N82-19957
- SPLETTSTORSEN, W. R.
Noise measurements on the helicopter BK 117 design. Weighted noise levels and influence of airspeed [DFVLR-MIT-81-18] N82-19957
- SPREEDBOROUGH, S. G.
The influence of sensor and actuator characteristics on overall helicopter AFCS design N82-18171
- SPRINC, J.
Oscillations and vibrations of aircraft on runways A82-24974
- STAAB, W. M.
Restoration of performance, Models 727, 737, and 747 [SAE PAPER 811072] A82-24406
- STACHER, G. W.
Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures [NASA-CR-165827] N82-19358
- STAHL, H.
The problem of calculation of the flow around helicopter rotor blade tips N82-18160
- On the calculation of transonic blade tip flow for helicopter rotors [MBB-UD-320-81-0] N82-18187
- STAHL, J. W.
Assessment of Avionic Equipment Field Reliability and Maintainability as Functions of Unit Cost [AD-A109373] N82-19218
- STEEB, R.
Distributed intelligence for air fleet control [AD-A108611] N82-18195
- STEIN, R.
Experimental investigation of visual aids for helicopters: low level flight at night and poor visibility N82-18168
- STEINBERG, R.
Airline flight planning - The weather connection [SAE PAPER 811067] A82-24386
- STEINLE, P. W., JR.
The effect of ejector augmentation on test-section flow quality in the Calspan 8-ft transonic wind tunnel [AIAA 82-0571] A82-24658
- STEINMANN, H.
Flight test data acquisition and interpretation A82-24707
- STELZEL, P.
A possible way of specifically correcting location and navigational errors caused by reflection and other propagation anomalies [ESA-TT-667] N82-18198
- STEPANENKO, V. S.
Improving the accuracy of the estimates of surfactant content in jet fuels A82-23250
- STEVENSON, D. L.
The use of 'Kapton' polyimide film in aerospace applications [SAE PAPER 811091] A82-24413
- STIEVENARD, G.
Hypothetical fatigue life problem - Application of Aerospace method A82-24716
- STOEFLER, G.
Carbon-fiber composites - A fiber composite material for highly stressed light-construction components A82-24805
- STOESSNER, R. L.
The cargo helicopter - A logistical vehicle A82-24717
- STOLPESTAD, J. H.
Evaluation of superplastic forming and co-diffusion bonding of Ti-6Al-4V titanium alloy expanded sandwich structures [NASA-CR-165827] N82-19358
- STOUT, D. W.
Stereographic projection in the National Airspace System A82-23031
- STROUB, R. H.
An analytical investigation of the free-tip rotor for helicopters [NASA-TN-81345] N82-18179
- STUBBS, S. M.
Dynamics of aircraft antiskid braking systems [NASA-TP-1959] N82-18204
- SUCHETTRUNK, R.
Electroforming of space and aircraft structures [MBB-BE-491-0] N82-18419
- SUEN, D.
A design study of the Marshal [BU-262] N82-19215
- SULZER, R.
Transport aircraft cockpit standardization (Federal Aviation regulations part 25) [AD-A108924] N82-19207

SUN, C. C.
Transonic perturbation analysis of
wing-fuselage-nacelle-pylon configurations with
powered jet exhausts
[NASA-CR-165852] N82-19167

SURESH, B. M.
On-line control for the regulation of power source
in multiple-servo electro-hydraulic systems
[ASME PAPER 81-WA/DSC-3] A82-24562

SWARTZ, W. P.
The anatomy of a technology test bed - Integrated
Flight/Fire Control-I /IFFC I/
[SAE PAPER 811036] A82-24398

SWEDISH, W. J.
The requirements for reduced IFR separations on
final approach A82-23311

SWEET, L. M.
Wide field of view laser beacon system for
three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9] A82-24563

SWEETMAN, B.
Boeing's big, quiet 737-300 A82-23369

SWIFT, T.
Application of damage tolerance technology to type
certification
[SAE PAPER 811062] A82-24388

SZCZEPONIK, K.
Experience during the development of the
German-Japanese helicopter BK 117
[MBB-UD-318-81-0] N82-19210

T

TADGHIGHI, H.
Wind tunnel investigation of high speed rotor noise
N82-18146

TAKEDA, K.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

TAKEO, K.
Lineup of the IM-series aircraft-derivative gas
turbines A82-22896

TAN, G. H.
A design study of the Marshal
[BU-262] N82-19215

TANIMOTO, R. Y.
A study of the effects of long-term exposure to
fuels and fluids on the behavior of advanced
composite materials
[NASA-CR-165763] N82-18327

TANNER, J. A.
Dynamics of aircraft antiskid braking systems
[NASA-TP-1959] N82-18204

TASK, H. L.
A new angular deviation measurement device for
aircraft transparencies A82-24308
Portable transparency optical test system /P-TOTS/
A82-24309

TAYLOR, P.
Preliminary investigation into the addition of
auxiliary longitudinal thrust on helicopter
agility N82-18155
A method of predicting fuselage loads in hover
N82-18164

TAYLOR, R. S.
Design philosophy of the Hughes model 600 helicopter
N82-18140

TAYLOR, S. M.
Direct comparison of community response to road
traffic noise and to aircraft noise A82-22974

TEAGUE, E. C.
Evaluation of methods for characterizing surface
topography of models for high Reynolds number
wind-tunnels
[AIAA 82-0603] A82-24675

THOMAS, G. A.
Disengagement of safety harness buckles - CT4
[AD-A109048] N82-19199

THOMPSON, G. H.
Boeing Vertol fatigue life methodology A82-24718

THORNDYKE, P. W.
Distributed intelligence for air fleet control
[AD-A108611] N82-18195

TKACH, M. J.
F/A-18 weapon system development A82-23774

TORISAKI, T.
Aerodynamic noise generated by jet wing/flap
interactions of the external USB configuration
of STOL aircraft. Part 2: Full scale model
experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2] N82-19945

TORNESE, R. A.
Active Beacon Collision Avoidance System (BCAS)
logic performance during operational flight tests
[AD-A108893] N82-19203

TOTH, S.
Impact of technology on avionics cost trends
[AD-A108494] N82-18219

TOTTO, R. R.
MIL-STD 1553B - Aircraft EM environmental
susceptibility effects A82-24357

TRAHAN, C.
Evaluation of methods for characterizing surface
topography of models for high Reynolds number
wind-tunnels
[AIAA 82-0603] A82-24675

TRAN, C. T.
Application of the ONER dynamic stall model to a
helicopter blade in forward flight N82-18161

TRIMBLE, J.
Combined multisensor displays A82-22905

TRUE, H. C.
Wind and temperature database for flight planning
[SAE PAPER 811068] A82-24385

U

UNGVIICHIAN, V.
GTD terrain reflection model applied to ILS glide
scope A82-23027

V

VAICAITIS, R.
Study of cabin noise control for twin engine
general aviation aircraft
[NASA-CR-165833] N82-18995

VALEIKA, R.
MSG-3 overview A82-24014

VALENTE, E.
Military requirements: Too little or too much
N82-18138

VAN DYKE, M.
Annual review of fluid mechanics. Volume 14
A82-24416

VANNOCKER, R. C.
Cost of ownership advantages with a shared oil
system A82-24378

VAPIREV, E. N.
Linear alpha-ray altimeter A82-23225

VARY, A.
Metal honeycomb to porous wireform substrate
diffusion bond evaluation
[NASA-TM-82793] N82-18612

VASILIEV, D. N.
Linear alpha-ray altimeter A82-23225

VELKOFF, H. R.
Hover tests of a model H-force rotor
N82-18159

VENN, G. M.
A study of the techniques of dynamic analysis of
helicopter type structures N82-18129

VICENS, P.
Navigational aids on-board the Concorde
A82-24065

- VIGEVANO, L.
An experimental analysis of the shape of a rotor wake
N82-18122
- VON SCHLICHTKRULL, P.-W.
Operational air traffic in the Federal Republic of Germany
A82-23318
- VONRETH, R. D.
Hast mounted visual aids
N82-18167
- VORBURGER, T. V.
Evaluation of methods for characterizing surface topography of models for high Reynolds number wind-tunnels
[AIAA 82-0603]
A82-24675
- ## W
- WAGNER, R. P.
A propulsion view of the all-electric airplane
N82-19136
- WAI, J. C.
Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts
[NASA-CR-165852]
N82-19167
- WALES, C. J.
A concept for a fuel efficient flight planning aid for general aviation
[NASA-CR-3533]
N82-19217
- WALKER, A. S.
The pressure signature method for blockage corrections, and its applications to the industrial wind tunnel
[BU-263]
N82-19231
- WALKER, R. H.
Windshield system structural enhancement
A82-24312
- WALKER, W. H.
A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491]
N82-19226
- WALLACE, W.
A new approach to the problem of stress corrosion cracking in 7075-T6 aluminum
A82-23772
- WARD, W. C., JR.
Physiological acceptability tests of the SJU-5/A ejection seat: Second physiological acceptance demonstration
[AD-A108688]
N82-18194
- WARWICK, G.
Fighters - Tomorrow's terminology
A82-23368
- WEBB, S. G.
Wide field of view laser beacon system for three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9]
A82-24563
- WEBER, O.
Midair and near midair collisions on two- and three-dimensional curvilinear flight paths
[ESA-TT-685]
N82-18200
- WEHAUSEN, J. V.
Annual review of fluid mechanics. Volume 14
A82-24416
- WEIHE, V. I.
Beyond the horizon coverage for air navigation/traffic control
A82-24647
- WEIS, D.
Perspectives for Controlled Weapons Technology: Report of the 90th Helicopter Forum
[HBB-UA-532-80-0]
N82-19211
- WEISEL, D. R.
Airline fuel saving through JT9D engine refurbishment
[SAE PAPER 811051]
A82-24395
- WEISS, P.
Active gust and maneuver load control concepts with the example of the Airbus A300. Part 1: Explanation of a regular in the time zone of wind gust load decrease and examination of its effectiveness in stochastic gusts
[HBB-FE-172/S/PUB/39-PT-1]
N82-19228
- WEISSENBURGER, J. T.
Airport related residential acoustical insulation demonstration project: Report 1720
[PB82-100777]
N82-19396
- WESSON, B. E.
Distributed intelligence for air fleet control
[AD-A108611]
N82-18195
- WEST, B. S.
The role of finite element analysis in the design of birdstrike resistant transparencies
A82-24314
- The effects of bird orientation on load profile and damage level
A82-24316
- WHITE, H. V.
Software features applicable to inertial measurement unit self alignment
[AD-A108511]
N82-18196
- WHITE, M. L.
Development of manufacturing technology for fabrication of a composite helicopter main rotor spar by tubular braiding
[AD-A109377]
N82-19209
- WHITE, W. L.
Spin-tunnel investigation of a 1/13-scale model of the NASA AD-1 oblique-wing research aircraft
[NASA-TN-83236]
N82-18183
- WILBY, P. G.
Some unsteady aerodynamic effects on helicopter rotors
N82-18162
- WILPERT, M. E.
Aircraft/airport compatibility - A constant challenge for aircraft designers
A82-25119
- WILKINSON, K. G.
Air transport in the 21st century
A82-24025
- WILLIAMSON, J. R.
Diffusion bonding in superplastic forming/diffusion bonding
A82-23754
- WILMS, V.
Novel metal-ceramics-composite sealing coatings in aircraft engines
A82-24803
- WILSON, K. C.
Fuel-rich plume combustion
[AD-A108136]
N82-18349
- WINDER, D. E.
Wind and temperature database for flight planning
[SAE PAPER 811068]
A82-24385
- WINKLER, E.
Characterization of the Airbus horizontal stabilizers of CFRP construction and structural analysis with the finite element method
[HBB-UT-13-81-0]
N82-18213
- WINKLER, P. M.
Loran for precise position location - The VIEW-NAV system
A82-24648
- WISEMAN, M. P.
The pressure signature method for blockage corrections, and its applications to the industrial wind tunnel
[BU-263]
N82-19231
- WISER, G. L.
Fuel-efficient windshields for transport, commuter and business aircraft
A82-24304
- WITTENBERG, H.
Prediction of off-design performance of turbo-shaft engines a simplified method
N82-18132
- WONG, E. Y.
Wide field of view laser beacon system for three-dimensional aircraft position measurement
[ASME PAPER 81-WA/DSC-9]
A82-24563
- WONG, G. A.
Analysis of loran-C system reliability for civil aviation
A82-24650
- WOODS, J., JR.
The anatomy of a technology test bed - Integrated Flight/Fire Control-I /IFPC I/
[SAE PAPER 811036]
A82-24398
- WORMSTONE, D. M.
EMC clearance of modern military aircraft
A82-24359

- WORSDALL, R. L.
Problems associated with the quality assurance of stretched acrylic sheet
A82-24319
- WRIGHT, P.
The multi mode matrix flat panel display: Technology and applications
N82-18169
- WRIGHT, R. W.
The development of high strength light-weight windshields for the new generation of Boeing 757 and 767 airliners
A82-24323
- WUEST, P.
A redundancy concept for a digital CSAS
N82-18170
- WURTINGER, H.
Carbon-fiber composites - A fiber composite material for highly stressed light-construction components
A82-24805
- WYATT, G. C. F.
The role of simulation in the design process
N82-18154
- WYLLIE, C.
Overview of Honeywell electromechanical actuation programs
N82-19142

Y

- YANG, T. Y.
Flutter and time response analyses of three degree of freedom airfoils in transonic flow
[AD-A108987]
N82-19227
- YEN, J. G.
Helicopter rotor load prediction
A82-24719
- YORKSIE, D. S.
The effect of critical design parameters on the selection of a VSCF system
A82-24381
- YOSHIDA, A.
Aerodynamic noise generated by jet wing/flap interactions of the external USB configuration of STOL aircraft. Part 2: Full scale model experiment using FJR710 turbofan engine
[NAL-TR-687T-PT-2]
N82-19945
- YOSHIHARA, H.
Transonic perturbation analysis of wing-fuselage-nacelle-pylon configurations with powered jet exhausts
[NASA-CR-165852]
N82-19167
- YOUNGKOS, E.
Oscillating supersonic/hypersonic wings at high incidence
A82-23828

Z

- ZADNIK, M.
Angle of downwash behind a wing in unsteady flow
A82-24970
- ZAHAVI, E.
Low grade fuels for turbo and jet engines
A82-23439
- ZECK, H.
A study of flight control requirements for advanced, winged, earth-to-orbit vehicles with far-aft center-of-gravity locations
[NASA-CR-3491]
N82-19226
- ZHI, X.
A simplified method for predicting rotor blade airloads
N82-18124
- ZHOU, F. X.
Rapid extraction of layer relative humidity, geopotential thickness, and atmospheric stability from satellite sounding radiometer data
A82-25113
- ZOLADZ, E. W.
A Microwave Landing System simulation
A82-23323
- ZORUMSKI, W. E.
Aircraft noise prediction program theoretical manual, part 1
[NASA-TN-83199-PT-1]
N82-19946


- Aircraft noise prediction program theoretical manual, part 2
[NASA-TN-83199-PT-2]
N82-19947
- ZEMIC, D. S.
Scanning strategies for air traffic control radars
A82-24646

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Suppl. 149)

JUNE 1982

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number, the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the IAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in either the IAA or STAR section.

AF PROJ. 2307
N82-18628
N82-19227
N82-19587
AF PROJ. 2338
N82-18217
AF PROJ. 2403
N82-18224
AF PROJ. 2418
N82-18628
AF PROJ. 4600
N82-18464
AF PROJ. 6095
N82-18197
AF PROJ. 6670
N82-18835
AF PROJ. 7231
N82-18192
N82-18193
AF PROJ. 9983
N82-18227
AF-AFOSR-80-0178
A82-23441
AF-AFOSR-3096-76
N82-19587
AF-AFOSR-3523-78
N82-19227
ARPA ORDER 3640
N82-18195
AT/2170/049/XR
N82-19956
A76/KL/148
N82-18226
DA PROJ. 1L1-62209-AH-76
N82-18231
N82-19583
DA PROJ. 3E1-6277-A-878
N82-18209
DAAG46-78-C-0070
N82-19209
DAAK51-78-C-0017
N82-19583
DAAK51-79-C-0015
N82-18231
DE-AI01-78CS-54209
N82-19205
DOT-FA7WA-3549
A82-23027
DOT-FA01-80-1-Y-10524
A82-24646
DOT-FA78WAI-876
N82-18230
DOT-FA79WA-4335
N82-19160
DOT-FA79WA-4368
N82-18218
DOT-FA80WA-4370
A82-23311
DOT-HS-8-01936
N82-18233
DTFA-01-80-C-10030
N82-18219
DTFA01-81-C-10001
N82-19203
ESD-0-0630
N82-18835
FAA PROJ. 052-242-320
N82-19197

FAA PROJ. 161-200-130
N82-19207
F30602-80-C-0074
N82-18217
F33615-75-C-3134
A82-24314
F33615-76-C-3103
A82-24314
F33615-77-C-2097
A82-25154
F33615-78-C-3402
A82-24316
F33615-79-C-0522
N82-18193
F33615-79-C-3609
N82-18224
F33615-80-C-0519
N82-18192
F33615-80-C-1092
N82-18197
F33615-80-C-3401
A82-24314
F49620-79-C-0038
N82-18227
GRI-5011-342-0094
N82-18553
MDA903-78-C-0029
N82-18195
MDA903-79-C-0018
N82-18208
NAG1-73
N82-19224
NASA ORDER L-4718-B
A82-24675
NAS1-12428
N82-18327
NAS1-15788
N82-19358
NAS1-15887
N82-19167
NAS1-16114
A82-24674
NAS1-16117
N82-18995
NAS1-16128
N82-19226
NAS1-16262
A82-24663
NAS1-16430
N82-19217
NAS2-10078
N82-18202
NAS3-22004
N82-19221
NAS3-22482
N82-19196
NAS7-100
N82-19205
NCA2-08565-001
N82-18159
NCC2-94
A82-24563
NGR-33-015-201
A82-23826
NSG-1509
A82-23037
NSG-1579
A82-23826
NSG-5105
N82-18803
N00014-76-C-0742
A82-24673
N00014-77-C-0684
A82-22905
N00014-80-C-0505
N82-18922
N00014-80-C-0696
N82-18228
N00019-73-C-0053
N82-18206
N00173-79-C-0010
A82-24407

N61339-78-C-0060
N82-19206
SRC-B/BG/98590
A82-24566
SRC-GR/A/44312
A82-24566
SRI PROJ. PYU-1943
N82-18228
505-06-63-03
N82-18183
505-15-22
N82-19220
505-31-43-04
N82-19181
505-32-2A
N82-19222
505-32-6A
N82-18222
505-32-03-01
N82-19946
N82-19947
505-33-32
N82-18612
505-35-13-01
N82-18996
N82-19707
505-44-33-01
N82-18204
532-03-11
N82-18179
534-02-13-01
N82-19134
534-04-13-80
N82-19217
778-36-05
N82-19205

1 Report No NASA SP-7037(149)		2. Government Accession No.		3. Recipient's Catalog No	
4 Title and Subtitle Aeronautical Engineering A Continuing Bibliography (Supplement 149)				5 Report Date June 1982	
				6 Performing Organization Code	
7 Author(s)				8 Performing Organization Report No	
9 Performing Organization Name and Address National Aeronautics and Space Administration Washington, D.C. 20546				10 Work Unit No	
				11 Contract or Grant No	
				13 Type of Report and Period Covered	
12. Sponsoring Agency Name and Address				14 Sponsoring Agency Code	
15 Supplementary Notes					
16. Abstract <p style="text-align: center;">This bibliography lists 418 reports, articles and other documents introduced into the NASA scientific and technical information system in May 1982.</p>					
17 Key Words (Suggested by Author(s)) Aerodynamics Aeronautical Engineering Aeronautics Bibliographies			18. Distribution Statement Unclassified - Unlimited		
19 Security Classif (of this report) Unclassified		20 Security Classif (of this page) Unclassified		21 No of Pages 176	
				22. Price* \$5.00 HC-	

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC

NASA distributes its technical documents and bibliographic tools to eleven special libraries located in the organizations listed below. Each library is prepared to furnish the public such services as reference assistance, interlibrary loans, photocopy service, and assistance in obtaining copies of NASA documents for retention.

CALIFORNIA

University of California, Berkeley

COLORADO

University of Colorado, Boulder

DISTRICT OF COLUMBIA

Library of Congress

GEORGIA

Georgia Institute of Technology, Atlanta

ILLINOIS

The John Crerar Library, Chicago

MASSACHUSETTS

Massachusetts Institute of Technology, Cambridge

MISSOURI

Linda Hall Library, Kansas City

NEW YORK

Columbia University, New York

OKLAHOMA

University of Oklahoma, Bizzell Library

PENNSYLVANIA

Carnegie Library of Pittsburgh

WASHINGTON

University of Washington, Seattle

NASA publications (those indicated by an "*" following the accession number) are also received by the following public and free libraries:

CALIFORNIA

Los Angeles Public Library

San Diego Public Library

COLORADO

Denver Public Library

CONNECTICUT

Hartford Public Library

MARYLAND

Enoch Pratt Free Library, Baltimore

MASSACHUSETTS

Boston Public Library

MICHIGAN

Detroit Public Library

MINNESOTA

Minneapolis Public Library and Information Center

NEW JERSEY

Trenton Public Library

NEW YORK

Brooklyn Public Library

Buffalo and Erie County Public Library

Rochester Public Library

New York Public Library

OHIO

Akron Public Library

Cincinnati and Hamilton County Public Library

Cleveland Public Library

Dayton Public Library

Toledo and Lucas County Public Library

TEXAS

Dallas Public Library

Fort Worth Public Library

WASHINGTON

Seattle Public Library

WISCONSIN

Milwaukee Public Library

An extensive collection of NASA and NASA-sponsored documents and aerospace publications available to the public for reference purposes is maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 555 West 57th Street, 12th Floor, New York, New York 10019.

EUROPEAN

An extensive collection of NASA and NASA-sponsored publications is maintained by the British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England. By virtue of arrangements other than with NASA, the British Library Lending Division also has available many of the non-NASA publications cited in *STAR*. European requesters may purchase facsimile copy of microfiche of NASA and NASA-sponsored documents, those identified by both the symbols "*" and "**", from ESA - Information Retrieval Service, European Space Agency, 8-10 rue Mario-Nikis, 75738 Paris CEDEX 15, France.

National Aeronautics and
Space Administration

Washington, D.C.
20546

Official Business

Penalty for Private Use, \$300

THIRD-CLASS BULK RATE

Postage and Fees Paid
National Aeronautics and
Space Administration
NASA-451



NASA

POSTMASTER

If Undeliverable (Section 158
Postal Manual) Do Not Return
